



HDMI, DVI		
	#03337 Net Price: 0.976 USD Unit: pcs	
Cable HDMI(M)/HDMI(M), HQ, 5.0 m		
AV adaptors		
	#00360 Net Price: 0.280 USD Unit: pcs	
Adaptor; BNC male to F female		Adaptor; FME male to SMA male
	#00366 Net Price: 1.85 USD Unit: pcs	
Adaptor; N male to UHF female		
AV connections		
	#00292 Net Price: 1.64 USD Unit: pcs	
DC cable 2x0.22 mm, 1.5 m + connector 2.1/5.5 male, 90°		DC cable 2x0.22 mm, 1.5 m + connector 2.5/5.5 male, 90°
Cables coaxial type		
	#08999 Net Price: 194.00 USD Unit: roll 100m	
Coaxial cable RG213, stranded wire, black, 100 m Internal wire: 7x0.75 copper/stranded wire Insulation: 7.2 mm, PE External coating: 10.3mm/PVC/black Impedance: 50Ω capacitance: 98 +/- 2 pF/m attenuation: 10 MHz - 1.7 dB/100m, 50 MHz - 4.6 dB/100m, 100 MHz - 6.7 dB/100m, 230 MHz - 9.8 dB/100m, 470 MHz - 15.3 dB/100m, 860 MHz - 22.3 dB/100m, 1000 MHz - 24.5 dB/100m, 1500 MHz - 31.3 dB/100m, 2000 MHz - 36.5 dB/100m		Coaxial cable Wave Cables RG174, stranded wire, black, 100 m Internal wire: 7x0.16 copper/stranded wire Insulation: 1.6 mm, PE Shield: 96x0.1 copper External coating: 2.90mm/PVC/black Impedance: 50Ω capacitance: 100 +/- 2 pF/m attenuation: 50 MHz - 18.0 dB/100m, 200 MHz - 37.2 dB/100m, 400 MHz - 53.2 dB/100m, 600 MHz - 64.3 dB/100m, 800 MHz - 79.2 dB/100m
	#07208 Net Price: 24.60 USD Unit: roll 100m	
Coaxial cable Wave Cables RG58, stranded wire, black, 100 m Internal wire: 19x0.18 copper/stranded wire Insulation: 3.0 mm, PE Shield: 112x0.1 copper External coating: 5.0mm/PVC/black Impedance: 50Ω capacitance: 100 +/- 2 pF/m attenuation: 50 MHz - 10.9 dB/100m, 200 MHz - 23.0 dB/100m, 400 MHz - 33.8 dB/100m, 600 MHz - 42.5 dB/100m, 800 MHz - 47.8 dB/100m, 1000 MHz - 51.9 dB/100m		Coaxial cable Wave Cables RG58, stranded wire, black, 100 m Internal wire: 19x0.18 copper/stranded wire Insulation: 3.0 mm, PE Shield: 112x0.1 copper External coating: 5.0mm/PVC/black Impedance: 50Ω capacitance: 100 +/- 2 pF/m attenuation: 50 MHz - 10.9 dB/100m, 200 MHz - 23.0 dB/100m, 400 MHz - 33.8 dB/100m, 600 MHz - 42.5 dB/100m, 800 MHz - 47.8 dB/100m, 1000 MHz - 51.9 dB/100m
	#07103 Net Price: 45.50 USD Unit: roll 100m	
Coaxial cable, RG58 R-ALL, stranded wire, 100 m, black High performance, professional outdoor coaxial cable for video installation. Internal wire: 1.10mm/cooper (Cu) Insulation: 2.90mm Shield: Cu-Al-PET + 94% CuCa External coating: 4.95mm/PVC/black		Coaxial cable CTF 113 Tri-shield, 100 m CFT 113 Tri-shield is a high quality 75Ω coaxial cable designed for perfect signal transmission of digital and analog in a very difficult external environment. internal vein: 1.13 mm / copper wire (Cu) dielectric: 4.8 mm Screen: Al foil + braid 90% + Al-Pet braid: 90% outer shell: 7mm/PVC/white Attenuation: 50 MHz - 4.1 dB/100m, 100 MHz - 5.5 dB/100m, 200 MHz - 8.1 dB/100m, 450 MHz - 11.9 dB/100m, 860 MHz - 17.1 dB/100m, 1000 MHz - 18.5 dB/100m, 1350 MHz - 21.9 dB/100m, 1750 MHz - 25.3 dB/100m, 2150 MHz - 27.9 dB/100m, 3000 MHz - 34.7 dB/100m
	#07098 Net Price: 47.80 USD Unit: roll 100m	
Coaxial cable, RG58 R-ALL, stranded wire, 100 m, black High performance, professional outdoor coaxial cable for video installation. Internal wire: 1.10mm/cooper (Cu) Insulation: 2.90mm Shield: Cu-Al-PET + 94% CuCa External coating: 4.95mm/PVC/black		Coaxial cable RG-11/U Tri-shield, gel, 100 m RG-11/U Tri-shield is a high quality 75Ω coaxial cable designed for perfect signal transmission of digital and analog in a very difficult external environment. internal vein: 1.63 mm / copper wire (Cu) dielectric: 7.11 mm Screen: Al foil + braid 60% + Al-Pet outer shell: 10.1 mm/PE/black + gel Attenuation: 50 MHz - 3.1 dB/100m, 100 MHz - 4.3 dB/100m, 200 MHz - 6.1 dB/100m, 450 MHz - 9.1 dB/100m, 860 MHz - 12.9 dB/100m, 1000 MHz - 14.3 dB/100m, 1350 MHz - 17.1 dB/100m, 1750 MHz - 20.1 dB/100m, 2150 MHz - 23.0 dB/100m, 2400MHz - 24.5 dB/100m, 3000 MHz - 37.3 dB/100m



 #07206 Net Price: 23.90 USD Unit: roll 100m Coaxial cable Wave Cables RG6 Cu, black, 100 m center conductor: 1.02 mm / copper wire (Cu) dielectric: 4.7 mm screen: Al-PES foil braid: 64x0.12 Al outer shell: 6.8mm/PVC impedance: 75Ω capacitance: 52 +/- 2 pF/m return loss: 1-1000 MHz - >23dB, 1000-3000 MHz - >20dB screening attenuation: 1-1000MHz - >90dB attenuation: 5 MHz - 5 MHz - 1.7 dB/100m, 50 MHz - 5.0 dB/100m, 200 MHz - 8.7 dB/100m, 400 MHz - 12.8 dB/100m, 800 MHz - 18.0 dB/100m, 1000 MHz - 19.8 dB/100m, 1350 MHz - 23.8 dB/100m, 1750 MHz - 28.0 dB/100m, 2150 MHz - 31.4 dB/100m, 3000 MHz - 38.0 dB/100m	 #07212 Net Price: 23.90 USD Unit: roll 100m Coaxial cable Wave Cables RG6 Cu, white, 100 m center conductor: 1.02 mm / copper wire (Cu) dielectric: 4.7 mm screen: Al-PES foil braid: 64x0.12 Al outer shell: 6.8mm/PVC impedance: 75Ω capacitance: 52 +/- 2 pF/m return loss: 1-1000 MHz - >23dB, 1000-3000 MHz - >20dB screening attenuation: 1-1000MHz - >90dB attenuation: 5 MHz - 5 MHz - 1.7 dB/100m, 50 MHz - 5.0 dB/100m, 200 MHz - 8.7 dB/100m, 400 MHz - 12.8 dB/100m, 800 MHz - 18.0 dB/100m, 1000 MHz - 19.8 dB/100m, 1350 MHz - 23.8 dB/100m, 1750 MHz - 28.0 dB/100m, 2150 MHz - 31.4 dB/100m, 3000 MHz - 38.0 dB/100m	 #07291 Net Price: 26.30 USD Unit: roll 100m Coaxial cable Wave Cables RG6 Cu, white, LSOH, 100 m center conductor: 1.02 mm / copper wire (Cu) dielectric: 4.7 mm screen: Al-PES foil braid: 64x0.12 Al outer shell: 6.8mm/LSOH impedance: 75Ω capacitance: 52 +/- 2 pF/m return loss: 1-1000 MHz - >23dB, 1000-3000 MHz - >20dB screening attenuation: 1-1000MHz - >90dB attenuation: 5 MHz - 5 MHz - 1.7 dB/100m, 50 MHz - 5.0 dB/100m, 200 MHz - 8.7 dB/100m, 400 MHz - 12.8 dB/100m, 800 MHz - 18.0 dB/100m, 1000 MHz - 19.8 dB/100m, 1350 MHz - 23.8 dB/100m, 1750 MHz - 28.0 dB/100m, 2150 MHz - 31.4 dB/100m, 3000 MHz - 38.0 dB/100m
 #08002 Net Price: 54.80 USD Unit: roll 100m Coaxial cable XAp RG59 + 2 x power cable, white, 100m XAP RG59 + 2x0.75mm2 is 75Ω coaxial cable with the wires supplying integrated / octal construction controls, designed primarily for use in CCTV installations. The parameters of the coaxial Inner conductor: 0.59 mm / copper wire (Cu) Dielectric: 3.70 mm / EP Display: braided copper (Cu) 90% Outer sheath: PE 6mm/black Impedance: 75 Ω +/- 3 Unit Capacity: 67 +/- 3 pF / m Screening efficiency:> 65dB (100-900MHz) Internal conductor resistance: 46 Ω / km Minimum bending radius in the internal installations:> 5x cable diameter Damping [dB/100m]: 7.6 (50MHz), 10.9 (100MHz), 15.5 (200MHz), 23.1 (450MHz), 25.9 (500MHz), 32.6 (800MHz), 36 , 5 (1000MHz), 42.0 (1300MHz)	 #08000 Net Price: 78.20 USD Unit: roll 100m Coaxial cable YAp RG59 + 2 x power cable 0.75mm2, white, 100m YAp 75-0,59/3,7 + 2x0.75mm2 coaxial outdoor cable for industrial tv installation. The parameters of the coaxial Inner conductor: 0.59 mm / copper wire (Cu) Dielectric: 3.70 mm / EP Display: braided copper (Cu) 90% Outer sheath: 6mm/PVC/biala Impedance: 75 Ω +/- 3 Unit Capacity: 67 +/- 3 pF / m Screening efficiency:> 65dB (100-900MHz) Internal conductor resistance: 46 Ω / km Minimum bending radius in the internal installations:> 5x cable diameter Damping [dB/100m]: 7.6 (50MHz), 10.9 (100MHz), 15.5 (200MHz), 23.1 (450MHz), 25.9 (500MHz), 32.6 (800MHz), 36 , 5 (1000MHz), 42.0 (1300MHz)	 #07290 Net Price: 77.60 USD Unit: roll 100m H155 (WC-55) coaxial cable Wave Cables, 50 Ohm (LSOH), 100 m High performance outdoor coaxial cable for WLAN communication (2,4 GHz). Internal wire:7x0.45 / cooper (Cu) Insulation: 3.60mm Shield: Double Al foil, 96x0.12Cu External coating:5.4mm/LSOH Attenuation 20°C [dB/100m] 5 MHz: 1,8 50 MHz: 6,8 200 MHz: 12,5 400 MHz: 17,8 800 MHz: 26 1000 MHz: 29,6 1350 MHz: 34,7 1750 MHz: 40 2150 MHz: 44,5 3000 MHz: 53,2 Return loss [dB] 5-30 MHz: >22 30-470 MHz: >20 470-1000 MHz: >18
 #07211 Net Price: 70.50 USD Unit: roll 100m H155 (WC-55) coaxial cable Wave Cables, 50 Ohm (PE), 100 m High performance outdoor coaxial cable for WLAN communication (2,4 GHz). Internal wire:7x0.45 / cooper (Cu) Insulation: 3.60mm Shield: Double Al foil, 96x0.12Cu External coating:5.4mm/PE Attenuation 20°C [dB/100m] 5 MHz: 1,8 50 MHz: 6,8 200 MHz: 12,5 400 MHz: 17,8 800 MHz: 26 1000 MHz: 29,6 1350 MHz: 34,7 1750 MHz: 40 2150 MHz: 44,5 3000 MHz: 53,2 Return loss [dB] 5-30 MHz: >22 30-470 MHz: >20 470-1000 MHz: >18	 #07253 Net Price: 352.00 USD Unit: roll 500m H155 (WC-55) coaxial cable Wave Cables, 50 Ohm (PE), 500 m 50Ω, 5,4mm (H155) High performance outdoor coaxial cable for WLAN communication (2,4 GHz). Internal wire:7x0.45 / cooper (Cu) Insulation: 3.60mm Shield: Double Al foil, 96x0.12Cu External coating:5.4mm/PE Attenuation 20°C [dB/100m] 5 MHz: 1,8 50 MHz: 6,8 200 MHz: 12,5 400 MHz: 17,8 800 MHz: 26 1000 MHz: 29,6 1350 MHz: 34,7 1750 MHz: 40 2150 MHz: 44,5 3000 MHz: 53,2 Return loss [dB] 5-30 MHz: >22 30-470 MHz: >20 470-1000 MHz: >18	 #02058 Net Price: 262.00 USD Unit: roll 100m RF-10F (H1000) coaxial cable, 50 Ohm (PE), wire, 100 m Internal wire: 2.71/Cu/solid Insulation: 7.25/Foam-PE Shield: 10.3 mm Cu-PET-Cu-foil+cooper braid External coating: 5.4/PE/black Wave loss [100/1000/2500MHz]: 1.0/3.6/20.6

 #02051 Net Price: 53.80 USD Unit: roll 100m RF-5X (H155) coaxial cable, 50 Ohm (PE), 100m High performance outdoor coaxial cable for WLAN communication (2,4 GHz). Internal wire:1.35mm(7x0,45)/cooper (Cu) Insulation: 3.60mm Shield: Cu-Al-PET + 60% cooper (CuCA) External coating:5.4mm/PE/black	 #02050 Net Price: 270.00 USD Unit: roll 500m RF-5X (H155) coaxial cable, 50 Ohm (PE), 500m High performance outdoor coaxial cable for WLAN communication (2,4 GHz) Internal wire:1.35mm(7x0,45)/cooper (Cu) Insulation: 3.60mm Shield: Cu-Al-PET + 60% cooper (CuCA) External coating:5.4mm/PE/black	 #08259 Net Price: 128.00 USD Unit: roll 100m MRC 400 ECO coaxial cable, Draka, 50 Ohm (PE), 100 m High performance, professional outdoor coaxial cable for WLAN communication (2,4 GHz, WiMAX, 5 GHz) with a CCA inner conductor (Copper Clad Aluminium). Draka Comteq. Internal wire: 2.74 mm/CCA Insulation: Ø7.24 mm Shield: AL-PET Foil, bonded to the dielectric + Aluminium braid External coating:10.3 mm/PE/black Attenuation table 30 MHz: 2.2 dB/100m 150 MHz: 5 dB/100m 220 MHz: 6.1 dB/100m 450 MHz: 8.9 dB/100m 900 MHz: 12.8 dB/100m 1800 MHz: 18.6 dB/100m 2500 MHz: 22.3 dB/100m 5200 MHz: 33.6 dB/100m
 #05299 Net Price: 102.00 USD Unit: roll 100m Tri-lan 240 (RF-240) coaxial cable, 50 Ohm, 100 m Copper core diameter: 1.4 mm+/-0.02 mm Outer diameter: 3.8 mm +/- 0.05 mm Shield: Al/Poliester Foil/Al Foil 12/15/12 um Foil coverage rate: 100 % CuSn braid: 16x7x0.12 Braid coverage rate: 80 % Outer diameter: 4.45 mm Sheath Material: PE Outer diameter: 6.10 mm +/-0.10 mm Colour: black Electrical parameters Impedance: 50 Ohm +/-2 Capacitance: 83 pF/m Wave reduction factor: 81% Screening efficiency: >90 dB Core resistance: 11.2 Ohm/km Braid resistance: 12.4 Ohm/km Other parameters		
Connectors SMA type		
 #02023 Net Price: 0.790 USD Unit: pcs SMA male connector, crimp type, H155	 #00378 Net Price: 0.847 USD Unit: pcs SMA male connector, crimp type, RG174	 #01561 Net Price: 0.847 USD Unit: pcs SMA male connector, crimp type, RG58
 #02025 Net Price: 0.956 USD Unit: pcs SMA male reverse pin connector (RP), crimp type, H155	 #02789 Net Price: 0.956 USD Unit: pcs SMA male reverse pin connector (RP), crimp type, RG174	 #02791 Net Price: 0.956 USD Unit: pcs SMA male reverse pin connector (RP), crimp type, RG58
 #00374 Net Price: 1.38 USD Unit: pcs Adaptor, SMA female to SMA female	 #00372 Net Price: 1.25 USD Unit: pcs SMA female connector, bulkhead	 #02024 Net Price: 1.07 USD Unit: pcs SMA female connector, crimp type, H155

 #00375 Net Price: 0.922 USD Unit: pcs SMA female connector, crimp type, RG174	 #01560 Net Price: 0.888 USD Unit: pcs SMA female connector, crimp type, RG58	 #02039 Net Price: 0.341 USD Unit: pcs SMA female reverse pin connector (RP), bulkhead receptacle, 11.6 mm
 #02041 Net Price: 1.13 USD Unit: pcs SMA female reverse pin connector (RP), bulkhead receptacle, 13.15 mm	 #02026 Net Price: 1.03 USD Unit: pcs SMA female reverse pin connector (RP), crimp type, H155	 #02792 Net Price: 1.03 USD Unit: pcs SMA female reverse pin connector (RP), crimp type, RG174
 #02790 Net Price: 1.03 USD Unit: pcs SMA female reverse pin connector (RP), crimp type, RG58		
Connectors N type		
 #00723 Net Price: 1.86 USD Unit: pcs N male connector, clamp type, RG213	 #02017 Net Price: 2.04 USD Unit: pcs N male connector, crimp type, H1000	 #02021 Net Price: 1.61 USD Unit: pcs N male connector, crimp type, H155
 #00347 Net Price: 1.61 USD Unit: pcs N male connector, crimp type, RG58	 #00342 Net Price: 0.585 USD Unit: pcs N female connector, bulkhead crimp type, RG58	 #02019 Net Price: 1.41 USD Unit: pcs N female connector, crimp type, H1000
 #02022 Net Price: 1.45 USD Unit: pcs N female connector, crimp type, H155	 #00344 Net Price: 1.61 USD Unit: pcs N female connector, crimp type, RG58	 #02020 Net Price: 1.26 USD Unit: pcs N female connector, receptacle chassis mount, RG58
 #00346 Net Price: 2.02 USD Unit: pcs Adaptor, N male to N male		
Connectors TNC type		
 #02483 Net Price: 0.529 USD Unit: pcs TNC male connector, crimp type, H155	 #00386 Net Price: 0.507 USD Unit: pcs TNC male connector, crimp type, RG58	 #04727 Net Price: 1.01 USD Unit: pcs TNC male RP connector (Reverse Pin), crimp type, H155



#00380
Net Price:
0.727 USD
Unit: pcs

TNC female connector, bulkhead receptacle

Connectors FME type



#02481
Net Price:
0.599 USD
Unit: pcs

FME male connector, crimp type, H155



FME male connector, crimp type, RG174

#01503
Net Price:
0.599 USD
Unit: pcs



FME female connector, crimp type, H155

#02480
Net Price:
0.380 USD
Unit: pcs



FME female connector, crimp type, RG174



FME female connector, crimp type, RG58

#00755
Net Price:
0.307 USD
Unit: pcs

MCX, MC CARD, TS9, CRC9 Connectors



#07133
Net Price:
1.07 USD
Unit: pcs

TS9 male connector, 90°, crimp type, RG174

TS9 is mainly used in 3G and LTE modems manufactured by ZTE, Sierra Wireless, Novatel and others.

Connectors BNC type



Adaptor, BNC(M) - BNC(M)

#00314
Net Price:
0.757 USD
Unit: pcs



BNC male connector, clamp type, RG58

#00716
Net Price:
0.561 USD
Unit: pcs



BNC male connector, clamp type, RG6

#00718
Net Price:
0.561 USD
Unit: pcs



BNC male connector, crimp type, H155

#07186
Net Price:
0.465 USD
Unit: pcs



BNC male connector, crimp type, RG174

#01635
Net Price:
0.536 USD
Unit: pcs



BNC male connector, crimp type, RG58

#00317
Net Price:
0.443 USD
Unit: pcs



BNC male connector, crimp type, RG59

#00318
Net Price:
0.443 USD
Unit: pcs



Adaptor, BNC(F) - BNC(F)

#00311
Net Price:
0.334 USD
Unit: pcs



BNC female connector, bulkhead receptacle nut 12.7 mm 50ohm

#00310
Net Price:
0.376 USD
Unit: pcs



BNC female connector, crimp type, RG174

#01634
Net Price:
0.575 USD
Unit: pcs



BNC female connector, crimp type, RG58

#00312
Net Price:
0.536 USD
Unit: pcs



BNC female connector, crimp type, RG59

#01633
Net Price:
0.507 USD
Unit: pcs



#00714
Net Price:
0.654 USD
Unit: pcs

BNC female connector, isolated ground



#00715
Net Price:
0.727 USD
Unit: pcs

BNC female connector, PCB, 90°



#02408
Net Price:
0.061 USD
Unit: pcs

BNC boot, RG58
Length: 44,5mm
Diameters: 8.5mm; 5.5mm



#02409
Net Price:
0.061 USD
Unit: pcs

BNC boot, RG59
Length: 44,5mm
Diameters: 8,5mm; 6,5mm

Connectors F type



#01796
Net Price:
6.00 USD
Unit: 100pcs

F male connector, TWIST-ON, RG59, brass



#02059
Net Price:
7.00 USD
Unit: 100pcs

F male connector, TWIST-ON, RG6



#01550
Net Price:
8.00 USD
Unit: 100pcs

F male connector, TWIST-ON, RG6, Thickness 7.2 mm



#00575
Net Price:
6.38 USD
Unit: 100pcs

F double female connector + Nut/Washer, diecast



#00574
Net Price:
16.00 USD
Unit: 100pcs

F female connector, bulkhead receptacle, O.D.:11 mm, brass, with Nut/Washer

Connectors UHF type



#03387
Net Price:
0.656 USD
Unit: pcs

UHF male connector, crimp type, RG58



#01558
Net Price:
0.678 USD
Unit: pcs

UHF male connector, twist type, RG11



#00699
Net Price:
0.685 USD
Unit: pcs

UHF male connector, twist type, RG58



#00700
Net Price:
0.685 USD
Unit: pcs

UHF male connector, twist type, RG59



#00696
Net Price:
0.746 USD
Unit: pcs

UHF female connector, bulkhead, 16 teeth

Connectors PAL type



#00539
Net Price:
0.244 USD
Unit: 100pcs

TV antenna male connector, chassis mount



#00529
Net Price:
0.244 USD
Unit: 100pcs

TV antenna female connector, metal, PCB

Index

HDMI, DVI	1
AV adaptors	1
AV connections	1
Cables coaxial type	1
Connectors SMA type	3
Connectors N type	4
Connectors TNC type	4
Connectors FME type	5
MCX, MC CARD, TS9, CRC9 Connectors	5
Connectors BNC type	5
Connectors F type	6
Connectors UHF type	6
Connectors PAL type	6