Fiber Optic Patch Cords

#06835
Net Price:
3.13 USD
Unit: pcs

Patchcord SC/UPC-SC/UPC, MM, 50/125 duplex, OM4 fiber, 1 m

#06836
Net Price:
3.66 USD
Unit: pcs

Patchcord SC/UPC-SC/UPC, MM, 50/125 duplex, OM4 fiber, 2 m

#06837
Net Price:
4.19 USD
Unit: pcs

Patchcord SC/UPC-SC/UPC, MM, 50/125 duplex, OM4 fiber, 3 m

#06839
Net Price:
5.54 USD
Unit: pcs

Patchcord SC/UPC-SC/UPC, MM, 50/125 duplex, OM4 fiber, 5 m

#06840
Net Price:
8.34 USD
Unit: pcs

Patchcord SC/UPC-SC/UPC, MM, 50/125 duplex, OM4 fiber, 10 m

#06944
Net Price:
12.30 USD
Unit: pcs

Patchcord SC/UPC-SC/UPC, MM, 50/125 duplex, OM4 fiber, 15 m

#08604
Net Price:
2.92 USD
Unit: pcs

Patchcord SC/APC-SC/APC, SM, 9/125 duplex, G652D fiber, 1 m

Patchcord duplex L=1m

Insertion Loss: <=0.20dB
Return Loss: >=60dB
Repeatability: <=0.1dB
Durability: <=0.1 dB typical change, 500 matings
Interchangeability: <=0.2dB
Tensile Strength: >10kg
Operating Temperature: -40 ÷ 80°C

#08605
Net Price:
3.06 USD
Unit: pcs

Patchcord SC/APC-SC/APC, SM, 9/125 duplex, G652D fiber, 2 m

Patchcord duplex L=2m

Insertion Loss: <=0.20dB
Return Loss: >=60dB
Repeatability: <=0.1dB
Durability: <=0.1 dB typical change, 500 matings
Interchangeability: <=0.2dB
Tensile Strength: >10kg
Operating Temperature: -40 ÷ 80°C

#08606
Net Price:
3.20 USD
Unit: pcs

Patchcord SC/APC-SC/APC, SM, 9/125 duplex, G652D fiber, 3 m

Patchcord duplex L=3m

Insertion Loss: <=0.20dB
Return Loss: >=60dB
Repeatability: <=0.1dB
Durability: <=0.1 dB typical change, 500 matings
Interchangeability: <=0.2dB
Tensile Strength: >10kg
Operating Temperature: -40 ÷ 80°C

#08607
Net Price:
3.66 USD
Unit: pcs

Patchcord SC/APC-SC/APC, SM, 9/125 duplex, G652D fiber, 5 m

Patchcord duplex L=5m

Insertion Loss: <=0.20dB
Return Loss: >=60dB
Repeatability: <=0.1dB
Durability: <=0.1 dB typical change, 500 matings
Interchangeability: <=0.2dB
Tensile Strength: >10kg
Operating Temperature: -40 ÷ 80°C

#04500
Net Price:
4.39 USD
Unit: pcs

Patchcord SC/APC-SC/APC, SM, 9/125 duplex, G652D fiber, 10 m

Patchcord duplex L=10m

Insertion Loss: <=0.20dB
Return Loss: >=60dB
Repeatability: <=0.1dB
Durability: <=0.1 dB typical change, 500 matings
Interchangeability: <=0.2dB
Tensile Strength: >10kg
Operating Temperature: -40 ÷ 80°C

#04520
Net Price:
5.63 USD
Unit: pcs

Patchcord SC/APC-SC/APC, SM, 9/125 duplex, G652D fiber, 15 m

Patchcord duplex L=15m

Insertion Loss: <=0.20dB
Return Loss: >=60dB
Repeatability: <=0.1dB
Durability: <=0.1 dB typical change, 500 matings
Interchangeability: <=0.2dB
Tensile Strength: >10kg
Operating Temperature: -40 ÷ 80°C

#08894
Net Price:
2.93 USD
Unit: pcs

Patchcord SC/APC-SC/APC, SM, 9/125 duplex, G657A1 fiber, 1 m

Patchcord duplex L=1m

#08594
Net Price:
3.08 USD
Unit: pcs

Patchcord SC/APC-SC/APC, SM, 9/125 duplex, G657A1 fiber, 2 m

Patchcord duplex L=2m

#08595
Net Price:
3.23 USD
Unit: pcs

Patchcord SC/APC-SC/APC, SM, 9/125 duplex, G657A1 fiber, 3 m

Patchcord duplex L=3m

#08896
Net Price:
3.72 USD
Unit: pcs

Patchcord SC/APC-SC/APC, SM, 9/125 duplex, G657A1 fiber, 5 m

Patchcord duplex L=5m

#08834
Net Price:
2.87 USD
Unit: pcs

Patchcord SC/APC-SC/UPC, SM, 9/125 duplex, G652D fiber, 1 m

Patchcord duplex L=1m

#08835
Net Price:
3.01 USD
Unit: pcs

Patchcord SC/APC-SC/UPC, SM, 9/125 duplex, G652D fiber, 2 m

Patchcord duplex L=2m

#08836
Net Price:
3.15 USD
Unit: pcs

Patchcord SC/APC-SC/UPC, SM, 9/125 duplex, G652D fiber, 3 m

Patchcord duplex L=3m

#08837
Net Price:
3.61 USD
Unit: pcs

Patchcord SC/APC-SC/UPC, SM, 9/125 duplex, G652D fiber, 5 m

Patchcord duplex L=5m

#04501
Net Price:
4.34 USD
Unit: pcs

Patchcord SC/APC-SC/UPC, SM, 9/125 duplex, G652D fiber, 10 m

Patchcord duplex L=10m

Insertion Loss: <=0.20dB
Return Loss: >=60dB
Repeatability: <=0.1dB
Durability: <=0.1 dB typical change, 500 matings
Interchangeability: <=0.2dB
Tensile Strength: >10kg
Operating Temperature: -40 ÷ 80°C

#04521
Net Price:
5.58 USD
Unit: pcs

Patchcord SC/APC-SC/UPC, SM, 9/125 duplex, G652D fiber, 15 m

Patchcord duplex L=15m

Insertion Loss: <=0.20dB
Return Loss: >=60dB
Repeatability: <=0.1dB
Durability: <=0.1 dB typical change, 500 matings
Interchangeability: <=0.2dB
Tensile Strength: >10kg
Operating Temperature: -40 ÷ 80°C

#08597
Net Price:
2.88 USD
Unit: pcs

Patchcord SC/APC-SC/UPC, SM, 9/125 duplex, G657A1 fiber, 1 m

Patchcord duplex L=1m

#08892
Net Price:
3.04 USD
Unit: pcs

Patchcord SC/APC-SC/UPC, SM, 9/125 duplex, G657A1 fiber, 2 m

Patchcord duplex L=2m

#08599
Net Price:
3.19 USD
Unit: pcs

Patchcord SC/APC-SC/UPC, SM, 9/125 duplex, G657A1 fiber, 3 m

Patchcord duplex L=3m

#08596
Net Price:
3.67 USD
Unit: pcs

Patchcord SC/APC-SC/UPC, SM, 9/125 duplex, G657A1 fiber, 5 m

Patchcord duplex L=5m

#08608
Net Price:
2.78 USD
Unit: pcs

Patchcord SC/UPC-SC/UPC, MM, 50/125 duplex, OM2 fiber, 1 m

Patchcord duplex L=1m

Insertion Loss: <=0.30dB
Return Loss: >=30dB
Operating Temperature: -40 ÷ 80°C

#08609
Net Price:
2.97 USD
Unit: pcs

Patchcord SC/UPC-SC/UPC, MM, 50/125 duplex, OM2 fiber, 2 m

Patchcord duplex L=2m

Insertion Loss: <=0.30dB
Return Loss: >=30dB
Operating Temperature: -40 ÷ 80°C

#08610
Net Price:
3.15 USD
Unit: pcs

Patchcord SC/UPC-SC/UPC, MM, 50/125 duplex, OM2 fiber, 3 m

Patchcord duplex L=3m

Insertion Loss: <=0.30dB
Return Loss: >=30dB
Operating Temperature: -40 ÷ 80°C

#08611
Net Price:
3.71 USD
Unit: pcs

Patchcord SC/UPC-SC/UPC, MM, 50/125 duplex, OM2 fiber, 5 m

Patchcord duplex L=5m

Insertion Loss: <=0.30dB
Return Loss: >=30dB
Operating Temperature: -40 ÷ 80°C

#04502
Net Price:
4.68 USD
Unit: pcs

Patchcord SC/UPC-SC/UPC, MM, 50/125 duplex, OM2 fiber, 10 m

Patchcord duplex L=10m

Insertion Loss: <=0.30dB
Return Loss: >=30dB
Operating Temperature: -40 ÷ 80°C

#04522
Net Price:
6.22 USD
Unit: pcs

Patchcord SC/UPC-SC/UPC, MM, 50/125 duplex, OM2 fiber, 15 m

Patchcord duplex L=15m

Insertion Loss: <=0.30dB
Return Loss: >=30dB
Operating Temperature: -40 ÷ 80°C

#08867
Net Price:
2.85 USD
Unit: pcs

Patchcord SC/UPC-SC/UPC, MM, 50/125 duplex, OM3 fiber, 1 m

#08210
Net Price:
3.10 USD
Unit: pcs

Patchcord SC/UPC-SC/UPC, MM, 50/125 duplex, OM3 fiber, 2 m

#08211
Net Price:
3.36 USD
Unit: pcs

Patchcord SC/UPC-SC/UPC, MM, 50/125 duplex, OM3 fiber, 3 m

#08212
Net Price:
4.07 USD
Unit: pcs

Patchcord SC/UPC-SC/UPC, MM, 50/125 duplex, OM3 fiber, 5 m

#08877
Net Price:
3.99 USD
Unit: pcs

Patchcord SC/UPC-SC/UPC, MM, 62.5/125 duplex, OM1 fiber, 1 m

Patchcord duplex L=1m

Insertion Loss: <=0.30dB
Return Loss: >=30dB
Operating Temperature: -40 ÷ 80°C

#08878
Net Price:
3.15 USD
Unit: pcs

Patchcord SC/UPC-SC/UPC, MM, 62.5/125 duplex, OM1 fiber, 2 m

Patchcord duplex L=2m

Insertion Loss: <=0.30dB
Return Loss: >=30dB
Operating Temperature: -40 ÷ 80°C

#08879
Net Price:
3.43 USD
Unit: pcs

Patchcord SC/UPC-SC/UPC, MM, 62.5/125 duplex, OM1 fiber, 3 m

Patchcord duplex L=3m

Insertion Loss: <=0.30dB
Return Loss: >=30dB
Operating Temperature: -40 ÷ 80°C

#08880
Net Price:
4.20 USD
Unit: pcs

Patchcord SC/UPC-SC/UPC, MM, 62.5/125 duplex, OM1 fiber, 5 m

Patchcord duplex L=5m

Insertion Loss: <=0.30dB
Return Loss: >=30dB
Operating Temperature: -40 ÷ 80°C

#08881
Net Price:
5.66 USD
Unit: pcs

Patchcord SC/UPC-SC/UPC, MM, 62.5/125 duplex, OM1 fiber, 10 m

Patchcord duplex L=10m

Insertion Loss: <=0.30dB
Return Loss: >=30dB
Operating Temperature: -40 ÷ 80°C

#08882
Net Price:
7.83 USD
Unit: pcs

Patchcord SC/UPC-SC/UPC, MM, 62.5/125 duplex, OM1 fiber, 15 m

Patchcord duplex L=15m

Insertion Loss: <=0.30dB
Return Loss: >=30dB
Operating Temperature: -40 ÷ 80°C

#08600
Net Price:
2.83 USD
Unit: pcs

Patchcord SC/UPC-SC/UPC, SM, 9/125 duplex, G652D fiber, 1 m

Patchcord duplex L=1m

Insertion Loss: <=0.20dB
Return Loss: >=50dB
Repeatability: <=0.2dB
Durability: <=0.1 dB typical change, 500 matings
Interchangeability: <=0.2dB
Tensile Strength: >10kg
Operating Temperature: -40 ÷ 80°C

#08601
Net Price:
2.97 USD
Unit: pcs

Patchcord SC/UPC-SC/UPC, SM, 9/125 duplex, G652D fiber, 2 m

Patchcord duplex L=2m

Insertion Loss: <=0.20dB
Return Loss: >=50dB
Repeatability: <=0.2dB
Durability: <=0.1 dB typical change, 500 matings
Interchangeability: <=0.2dB
Tensile Strength: >10kg
Operating Temperature: -40 ÷ 80°C

#08602
Net Price:
3.10 USD
Unit: pcs

Patchcord SC/UPC-SC/UPC, SM, 9/125 duplex, G652D fiber, 3 m

Patchcord duplex L=3m

Insertion Loss: <=0.20dB
Return Loss: >=50dB
Repeatability: <=0.2dB
Durability: <=0.1 dB typical change, 500 matings
Interchangeability: <=0.2dB
Tensile Strength: >10kg
Operating Temperature: -40 ÷ 80°C

#08603
Net Price:
3.56 USD
Unit: pcs

Patchcord SC/UPC-SC/UPC, SM, 9/125 duplex, G652D fiber, 5 m

Patchcord duplex L=5m

Insertion Loss: <=0.20dB
Return Loss: >=50dB
Repeatability: <=0.2dB
Durability: <=0.1 dB typical change, 500 matings
Interchangeability: <=0.2dB
Tensile Strength: >10kg
Operating Temperature: -40 ÷ 80°C

#04503
Net Price:
4.29 USD
Unit: pcs

Patchcord SC/UPC-SC/UPC, SM, 9/125 duplex, G652D fiber, 10 m

Patchcord duplex L=10m

Insertion Loss: <=0.20dB
Return Loss: >=50dB
Repeatability: <=0.2dB
Durability: <=0.1 dB typical change, 500 matings
Interchangeability: <=0.2dB
Tensile Strength: >10kg
Operating Temperature: -40 ÷ 80°C

#04523
Net Price:
5.53 USD
Unit: pcs

Patchcord SC/UPC-SC/UPC, SM, 9/125 duplex, G652D fiber, 15 m

Patchcord duplex L=15m

Insertion Loss: <=0.20dB
Return Loss: >=50dB
Repeatability: <=0.2dB
Durability: <=0.1 dB typical change, 500 matings
Interchangeability: <=0.2dB
Tensile Strength: >10kg
Operating Temperature: -40 ÷ 80°C

#08199
Net Price:
2.83 USD
Unit: pcs

Patchcord SC/UPC-LC/APC, SM, 9/125 duplex, G652D fiber, 1 m

Patchcord duplex L=1m

Insertion Loss: <=0.20dB
Return Loss: >=60dB
Repeatability: <=0.1dB
Durability: <=0.1 dB typical change, 500 matings
Interchangeability: <=0.2dB
Tensile Strength: >10kg
Operating Temperature: -40 ÷ 80°C

#04491
Net Price:
5.41 USD
Unit: pcs

Patchcord SC/UPC-LC/UPC, MM, 50/125 duplex, OM3 fiber, 10 m

#04492
Net Price:
7.43 USD
Unit: pcs

Patchcord SC/UPC-LC/UPC, MM, 50/125 duplex, OM3 fiber, 15 m

#07398
Net Price:
3.10 USD
Unit: pcs

Patchcord SC/UPC-LC/UPC, MM, 50/125 duplex, OM3 fiber, 2 m

#08213
Net Price:
3.36 USD
Unit: pcs

Patchcord SC/UPC-LC/UPC, MM, 50/125 duplex, OM3 fiber, 3 m

#07397
Net Price:
4.07 USD
Unit: pcs

Patchcord SC/UPC-LC/UPC, MM, 50/125 duplex, OM3 fiber, 5 m

#07495
Net Price:
3.13 USD
Unit: pcs

Patchcord SC/UPC-LC/UPC, MM, 50/125 duplex, OM4 fiber, 1 m

#07499
Net Price:
8.34 USD
Unit: pcs

Patchcord SC/UPC-LC/UPC, MM, 50/125 duplex, OM4 fiber, 10 m

#06834
Net Price:
12.30 USD
Unit: pcs

Patchcord SC/UPC-LC/UPC, MM, 50/125 duplex, OM4 fiber, 15 m

#07496
Net Price:
3.66 USD
Unit: pcs

Patchcord SC/UPC-LC/UPC, MM, 50/125 duplex, OM4 fiber, 2 m

#07497
Net Price:
4.19 USD
Unit: pcs

Patchcord SC/UPC-LC/UPC, MM, 50/125 duplex, OM4 fiber, 3 m

#07498
Net Price:
5.54 USD
Unit: pcs

Patchcord SC/UPC-LC/UPC, MM, 50/125 duplex, OM4 fiber, 5 m

#08628
Net Price:
2.87 USD
Unit: pcs

Patchcord SC/APC-LC/APC, SM, 9/125 duplex, G652D fiber, 1 m

Patchcord duplex L=1m

Insertion Loss: <=0.20dB
Return Loss: >=60dB
Repeatability: <=0.1dB
Durability: <=0.1 dB typical change, 500 matings
Interchangeability: <=0.2dB
Tensile Strength: >10kg
Operating Temperature: -40 ÷ 80°C

#08629
Net Price:
3.01 USD
Unit: pcs

Patchcord SC/APC-LC/APC, SM, 9/125 duplex, G652D fiber, 2 m

Patchcord duplex L=2m

Insertion Loss: <=0.20dB
Return Loss: >=60dB
Repeatability: <=0.1dB
Durability: <=0.1 dB typical change, 500 matings
Interchangeability: <=0.2dB
Tensile Strength: >10kg
Operating Temperature: -40 ÷ 80°C

#08630
Net Price:
3.15 USD
Unit: pcs

Patchcord SC/APC-LC/APC, SM, 9/125 duplex, G652D fiber, 3 m

Patchcord duplex L=3m

Insertion Loss: <=0.20dB
Return Loss: >=60dB
Repeatability: <=0.1dB
Durability: <=0.1 dB typical change, 500 matings
Interchangeability: <=0.2dB
Tensile Strength: >10kg
Operating Temperature: -40 ÷ 80°C

#08631
Net Price:
3.61 USD
Unit: pcs

Patchcord SC/APC-LC/APC, SM, 9/125 duplex, G652D fiber, 5 m

Patchcord duplex L=5m

Insertion Loss: <=0.20dB
Return Loss: >=60dB
Repeatability: <=0.1dB
Durability: <=0.1 dB typical change, 500 matings
Interchangeability: <=0.2dB
Tensile Strength: >10kg
Operating Temperature: -40 ÷ 80°C

#04507
Net Price:
4.34 USD
Unit: pcs

Patchcord SC/APC-LC/APC, SM, 9/125 duplex, G652D fiber, 10 m

Patchcord duplex L=10m

Insertion Loss: <=0.20dB
Return Loss: >=60dB
Repeatability: <=0.1dB
Durability: <=0.1 dB typical change, 500 matings
Interchangeability: <=0.2dB
Tensile Strength: >10kg
Operating Temperature: -40 ÷ 80°C

#04527
Net Price:
5.58 USD
Unit: pcs

Patchcord SC/APC-LC/APC, SM, 9/125 duplex, G652D fiber, 15 m

Patchcord duplex L=15m

Insertion Loss: <=0.20dB
Return Loss: >=60dB
Repeatability: <=0.1dB
Durability: <=0.1 dB typical change, 500 matings
Interchangeability: <=0.2dB
Tensile Strength: >10kg
Operating Temperature: -40 ÷ 80°C

#08830
Net Price:
2.87 USD
Unit: pcs

Patchcord SC/APC-LC/UPC, SM, 9/125 duplex, G652D fiber, 1 m

Patchcord duplex L=1m

#08831
Net Price:
3.01 USD
Unit: pcs

Patchcord SC/APC-LC/UPC, SM, 9/125 duplex, G652D fiber, 2 m

Patchcord duplex L=2m

#08832
Net Price:
3.15 USD
Unit: pcs

Patchcord SC/APC-LC/UPC, SM, 9/125 duplex, G652D fiber, 3 m

Patchcord duplex L=3m

#08833
Net Price:
3.61 USD
Unit: pcs

Patchcord SC/APC-LC/UPC, SM, 9/125 duplex, G652D fiber, 5 m

Patchcord duplex L=5m

#04506
Net Price:
4.34 USD
Unit: pcs

Patchcord SC/APC-LC/UPC, SM, 9/125 duplex, G652D fiber, 10 m

Patchcord duplex L=10m

Insertion Loss: <=0.20dB
Return Loss: >=60dB
Repeatability: <=0.1dB
Durability: <=0.1 dB typical change, 500 matings
Interchangeability: <=0.2dB
Tensile Strength: >10kg
Operating Temperature: -40 ÷ 80°C

#04526
Net Price:
5.58 USD
Unit: pcs

Patchcord SC/APC-LC/UPC, SM, 9/125 duplex, G652D fiber, 15 m

Patchcord duplex L=15m

Insertion Loss: <=0.20dB
Return Loss: >=60dB
Repeatability: <=0.1dB
Durability: <=0.1 dB typical change, 500 matings
Interchangeability: <=0.2dB
Tensile Strength: >10kg
Operating Temperature: -40 ÷ 80°C

#08632
Net Price:
2.78 USD
Unit: pcs

Patchcord SC/UPC-LC/UPC, MM, 50/125 duplex, OM2 fiber, 1 m

Patchcord duplex L=1m

Insertion Loss: <=0.30dB
Return Loss: >=30dB
Operating Temperature: -40 ÷ 80°C

#08866
Net Price:
2.85 USD
Unit: pcs

Patchcord SC/UPC-LC/UPC, MM, 50/125 duplex, OM3 fiber, 1 m

#08633
Net Price:
2.97 USD
Unit: pcs

Patchcord SC/UPC-LC/UPC, MM, 50/125 duplex, OM2 fiber, 2 m

Patchcord duplex L=2m

Insertion Loss: <=0.30dB
Return Loss: >=30dB
Operating Temperature: -40 ÷ 80°C

#08634
Net Price:
3.15 USD
Unit: pcs

Patchcord SC/UPC-LC/UPC, MM, 50/125 duplex OM2 fiber, 3 m

Patchcord duplex L=3m

Insertion Loss: <=0.30dB
Return Loss: >=30dB
Operating Temperature: -40 ÷ 80°C

#08635
Net Price:
3.71 USD
Unit: pcs

Patchcord SC/UPC-LC/UPC, MM, 50/125 duplex, OM2 fiber, 5 m

Patchcord duplex L=5m

Insertion Loss: <=0.30dB
Return Loss: >=30dB
Operating Temperature: -40 ÷ 80°C

#04505
Net Price:
4.68 USD
Unit: pcs

Patchcord SC/UPC-LC/UPC, MM, 50/125 duplex, OM2 fiber, 10 m

Patchcord duplex L=10m

Insertion Loss: <=0.30dB
Return Loss: >=30dB
Operating Temperature: -40 ÷ 80°C

#04525
Net Price:
6.22 USD
Unit: pcs

Patchcord SC/UPC-LC/UPC, MM, 50/125 duplex, OM2 fiber, 15 m

Patchcord duplex L=15m

Insertion Loss: <=0.30dB
Return Loss: >=30dB
Operating Temperature: -40 ÷ 80°C

#08883
Net Price:
2.87 USD
Unit: pcs

Patchcord SC/UPC-LC/UPC, MM, 62.5/125 duplex, OM1 fiber, 1 m

Patchcord duplex L=1m

Insertion Loss: <=0.30dB
Return Loss: >=30dB
Operating Temperature: -40 ÷ 80°C

#08884
Net Price:
3.15 USD
Unit: pcs

Patchcord SC/UPC-LC/UPC, MM, 62.5/125 duplex, OM1 fiber, 2 m

Patchcord duplex L=2m

Insertion Loss: <=0.30dB
Return Loss: >=30dB
Operating Temperature: -40 ÷ 80°C

#08885
Net Price:
3.43 USD
Unit: pcs

Patchcord SC/UPC-LC/UPC, MM, 62.5/125 duplex, OM1 fiber, 3 m

Patchcord duplex L=3m

Insertion Loss: <=0.30dB
Return Loss: >=30dB
Operating Temperature: -40 ÷ 80°C

#08886
Net Price:
4.20 USD
Unit: pcs

Patchcord SC/UPC-LC/UPC, MM, 62.5/125 duplex, OM1 fiber, 5 m

Patchcord duplex L=5m

Insertion Loss: <=0.30dB
Return Loss: >=30dB
Operating Temperature: -40 ÷ 80°C

#08887
Net Price:
5.66 USD
Unit: pcs

Patchcord SC/UPC-LC/UPC, MM, 62.5/125 duplex, OM1 fiber, 10 m

Patchcord duplex L=10m

Insertion Loss: <=0.30dB
Return Loss: >=30dB
Operating Temperature: -40 ÷ 80°C

#08888
Net Price:
7.83 USD
Unit: pcs

Patchcord SC/UPC-LC/UPC, MM, 62.5/125 duplex, OM1 fiber, 15 m

Patchcord duplex L=15m

Insertion Loss: <=0.30dB
Return Loss: >=30dB
Operating Temperature: -40 ÷ 80°C

#08624

Net Price:
2.83 USD
Unit: pcs

Patchcord SC/UPC-LC/UPC, SM, 9/125 duplex, G652D fiber, 1 m

Patchcord duplex L=1m

Insertion Loss: <=0.20dB
Return Loss: >=50dB
Repeatability: <=0.2dB
Durability: <=0.1 dB typical change, 500 matings
Interchangeability: <=0.2dB
Tensile Strength: >10kg
Operating Temperature: -40 ÷ 80°C

#08625

Net Price:
2.97 USD
Unit: pcs

Patchcord SC/UPC-LC/UPC, SM, 9/125 duplex, G652D fiber, 2 m

Patchcord duplex L=2m

Insertion Loss: <=0.20dB
Return Loss: >=50dB
Repeatability: <=0.2dB
Durability: <=0.1 dB typical change, 500 matings
Interchangeability: <=0.2dB
Tensile Strength: >10kg
Operating Temperature: -40 ÷ 80°C

#08626

Net Price:
3.10 USD
Unit: pcs

Patchcord SC/UPC-LC/UPC, SM, 9/125 duplex, G652D fiber, 3 m

Patchcord duplex L=3m

Insertion Loss: <=0.20dB
Return Loss: >=50dB
Repeatability: <=0.2dB
Durability: <=0.1 dB typical change, 500 matings
Interchangeability: <=0.2dB
Tensile Strength: >10kg
Operating Temperature: -40 ÷ 80°C

#08627

Net Price:
3.56 USD
Unit: pcs

Patchcord SC/UPC-LC/UPC, SM, 9/125 duplex, G652D fiber, 5 m

Patchcord duplex L=5m

Insertion Loss: <=0.20dB
Return Loss: >=50dB
Repeatability: <=0.2dB
Durability: <=0.1 dB typical change, 500 matings
Interchangeability: <=0.2dB
Tensile Strength: >10kg
Operating Temperature: -40 ÷ 80°C

#04504

Net Price:
4.29 USD
Unit: pcs

Patchcord SC/UPC-LC/UPC, SM, 9/125 duplex, G652D fiber, 10 m

Patchcord duplex L=10m

Insertion Loss: <=0.20dB
Return Loss: >=50dB
Repeatability: <=0.2dB
Durability: <=0.1 dB typical change, 500 matings
Interchangeability: <=0.2dB
Tensile Strength: >10kg
Operating Temperature: -40 ÷ 80°C

#04524

Net Price:
5.53 USD
Unit: pcs

Patchcord SC/UPC-LC/UPC, SM, 9/125 duplex, G652D fiber, 15 m

Patchcord duplex L=15m

Insertion Loss: <=0.20dB
Return Loss: >=50dB
Repeatability: <=0.2dB
Durability: <=0.1 dB typical change, 500 matings
Interchangeability: <=0.2dB
Tensile Strength: >10kg
Operating Temperature: -40 ÷ 80°C

#08640

Net Price:
2.87 USD
Unit: pcs

Patchcord SC/UPC-FC/UPC, MM, 50/125 duplex, OM2 fiber, 1 m

Patchcord duplex L=1m

Insertion Loss: <=0.30dB
Return Loss: >=30dB
Operating Temperature: -40 ÷ 80°C

#08641

Net Price:
3.06 USD
Unit: pcs

Patchcord SC/UPC-FC/UPC, MM, 50/125 duplex, OM2 fiber, 2 m

Patchcord duplex L=2m

Insertion Loss: <=0.30dB
Return Loss: >=30dB
Operating Temperature: -40 ÷ 80°C

#08642

Net Price:
3.24 USD
Unit: pcs

Patchcord SC/UPC-FC/UPC, MM, 50/125 duplex, OM2 fiber, 3 m

Patchcord duplex L=3m

Insertion Loss: <=0.30dB
Return Loss: >=30dB
Operating Temperature: -40 ÷ 80°C

#08643

Net Price:
3.80 USD
Unit: pcs

Patchcord SC/UPC-FC/UPC, MM, 50/125 duplex, OM2 fiber, 5 m

Patchcord duplex L=5m

Insertion Loss: <=0.30dB
Return Loss: >=30dB
Operating Temperature: -40 ÷ 80°C

#08636

Net Price:
2.87 USD
Unit: pcs

Patchcord SC/UPC-FC/UPC, SM, 9/125 duplex, G652D fiber, 1 m

Patchcord duplex L=1m

Insertion Loss: <=0.20dB
Return Loss: >=50dB
Repeatability: <=0.2dB
Durability: <=0.1 dB typical change, 500 matings
Interchangeability: <=0.2dB
Tensile Strength: >10kg
Operating Temperature: -40 ÷ 80°C

#08637

Net Price:
3.01 USD
Unit: pcs

Patchcord SC/UPC-FC/UPC, SM, 9/125 duplex, G652D fiber, 2 m

Patchcord duplex L=2m

Insertion Loss: <=0.20dB
Return Loss: >=50dB
Repeatability: <=0.2dB
Durability: <=0.1 dB typical change, 500 matings
Interchangeability: <=0.2dB
Tensile Strength: >10kg
Operating Temperature: -40 ÷ 80°C

#08638

Net Price:
3.15 USD
Unit: pcs

Patchcord SC/UPC-FC/UPC, SM, 9/125 duplex, G652D fiber, 3 m

Patchcord duplex L=3m

Insertion Loss: <=0.20dB
Return Loss: >=50dB
Repeatability: <=0.2dB
Durability: <=0.1 dB typical change, 500 matings
Interchangeability: <=0.2dB
Tensile Strength: >10kg
Operating Temperature: -40 ÷ 80°C

#08639

Net Price:
3.61 USD
Unit: pcs

Patchcord SC/UPC-FC/UPC, SM, 9/125 duplex, G652D fiber, 5 m

Patchcord duplex L=5m

Insertion Loss: <=0.20dB
Return Loss: >=50dB
Repeatability: <=0.2dB
Durability: <=0.1 dB typical change, 500 matings
Interchangeability: <=0.2dB
Tensile Strength: >10kg
Operating Temperature: -40 ÷ 80°C

#04515

Net Price:
2.97 USD
Unit: pcs

Patchcord ST/UPC-ST/UPC, MM, 50/125 duplex, OM2 fiber, 1 m

Patchcord duplex L=1m

Insertion Loss: <=0.30dB
Return Loss: >=30dB
Operating Temperature: -40 ÷ 80°C

#04516
Net Price:
3.15 USD
Unit: pcs

Patchcord ST/UPC-ST/UPC, MM, 50/125 duplex, OM2 fiber, 2 m

Patchcord duplex L=2m

Insertion Loss: <=0.30dB
Return Loss: >=30dB
Operating Temperature: -40 ÷ 80°C

#04517
Net Price:
3.34 USD
Unit: pcs

Patchcord ST/UPC-ST/UPC, MM, 50/125 duplex, OM2 fiber, 3 m

Patchcord duplex L=3m

Insertion Loss: <=0.30dB
Return Loss: >=30dB
Operating Temperature: -40 ÷ 80°C

#04518
Net Price:
3.90 USD
Unit: pcs

Patchcord ST/UPC-ST/UPC, MM, 50/125 duplex, OM2 fiber, 5 m

Patchcord duplex L=5m

Insertion Loss: <=0.30dB
Return Loss: >=30dB
Operating Temperature: -40 ÷ 80°C

#04519
Net Price:
4.88 USD
Unit: pcs

Patchcord ST/UPC-ST/UPC, MM, 50/125 duplex, OM2 fiber, 10 m

Patchcord duplex L=10m

Insertion Loss: <=0.30dB
Return Loss: >=30dB
Operating Temperature: -40 ÷ 80°C

#04535
Net Price:
6.44 USD
Unit: pcs

Patchcord ST/UPC-ST/UPC, MM, 50/125 duplex, OM2 fiber, 15 m

Patchcord duplex L=15m

Insertion Loss: <=0.30dB
Return Loss: >=30dB
Operating Temperature: -40 ÷ 80°C

#08656
Net Price:
2.87 USD
Unit: pcs

Patchcord SC/UPC-ST/UPC, MM, 50/125 duplex, OM2 fiber, 1 m

Patchcord duplex L=1m

Insertion Loss: <=0.30dB
Return Loss: >=30dB
Operating Temperature: -40 ÷ 80°C

#08657
Net Price:
3.06 USD
Unit: pcs

Patchcord SC/UPC-ST/UPC, MM, 50/125 duplex, OM2 fiber, 2 m

Patchcord duplex L=2m

Insertion Loss: <=0.30dB
Return Loss: >=30dB
Operating Temperature: -40 ÷ 80°C

#08658
Net Price:
3.24 USD
Unit: pcs

Patchcord SC/UPC-ST/UPC, MM, 50/125 duplex, OM2 fiber, 3 m

Patchcord duplex L=3m

Insertion Loss: <=0.30dB
Return Loss: >=30dB
Operating Temperature: -40 ÷ 80°C

#08659
Net Price:
3.80 USD
Unit: pcs

Patchcord SC/UPC-ST/UPC, MM, 50/125 duplex, OM2 fiber, 5 m

Patchcord duplex L=5m

Insertion Loss: <=0.30dB
Return Loss: >=30dB
Operating Temperature: -40 ÷ 80°C

#04512
Net Price:
4.78 USD
Unit: pcs

Patchcord SC/UPC-ST/UPC, MM, 50/125 duplex, OM2 fiber, 10 m

Patchcord duplex L=10m

Insertion Loss: <=0.30dB
Return Loss: >=30dB
Operating Temperature: -40 ÷ 80°C

#04532
Net Price:
6.33 USD
Unit: pcs

Patchcord SC/UPC-ST/UPC, MM, 50/125 duplex, OM2 fiber, 15 m

Patchcord duplex L=15m

Insertion Loss: <=0.30dB
Return Loss: >=30dB
Operating Temperature: -40 ÷ 80°C

#04224
Net Price:
3.20 USD
Unit: pcs

Patchcord SC/UPC-ST/UPC, MM, 50/125 duplex, OM3 fiber, 2 m

Patchcord duplex L=2m

Insertion Loss: <=0.30dB
Return Loss: >=30dB
Operating Temperature: -40 ÷ 80°C

#08652
Net Price:
2.87 USD
Unit: pcs

Patchcord SC/UPC-ST/UPC, SM, 9/125 duplex, G652D fiber, 1 m

Patchcord duplex L=1m

Insertion Loss: <=0.20dB
Return Loss: >=50dB
Repeatability: <=0.2dB
Durability: <=0.1 dB typical change, 500 matings
Interchangeability: <=0.2dB
Tensile Strength: >10kg
Operating Temperature: -40 ÷ 80°C

#08653
Net Price:
3.01 USD
Unit: pcs

Patchcord SC/UPC-ST/UPC, SM, 9/125 duplex, G652D fiber, 2 m

Patchcord duplex L=2m

Insertion Loss: <=0.20dB
Return Loss: >=50dB
Repeatability: <=0.2dB
Durability: <=0.1 dB typical change, 500 matings
Interchangeability: <=0.2dB
Tensile Strength: >10kg
Operating Temperature: -40 ÷ 80°C

#08654
Net Price:
3.15 USD
Unit: pcs

Patchcord SC/UPC-ST/UPC, SM, 9/125 duplex, G652D fiber, 3 m

Patchcord duplex L=3m

Insertion Loss: <=0.20dB
Return Loss: >=50dB
Repeatability: <=0.2dB
Durability: <=0.1 dB typical change, 500 matings
Interchangeability: <=0.2dB
Tensile Strength: >10kg
Operating Temperature: -40 ÷ 80°C

#08655
Net Price:
3.61 USD
Unit: pcs

Patchcord SC/UPC-ST/UPC, SM, 9/125 duplex, G652D fiber, 5 m

Patchcord duplex L=5m

Insertion Loss: <=0.20dB
Return Loss: >=50dB
Repeatability: <=0.2dB
Durability: <=0.1 dB typical change, 500 matings
Interchangeability: <=0.2dB
Tensile Strength: >10kg
Operating Temperature: -40 ÷ 80°C

#04511
Net Price:
4.34 USD
Unit: pcs

Patchcord SC/UPC-ST/UPC, SM, 9/125 duplex, G652D fiber, 10 m

Patchcord duplex L=10m

Insertion Loss: <=0.20dB
Return Loss: >=50dB
Repeatability: <=0.2dB
Durability: <=0.1 dB typical change, 500 matings
Interchangeability: <=0.2dB
Tensile Strength: >10kg
Operating Temperature: -40 ÷ 80°C

#04531
Net Price:
5.58 USD
Unit: pcs

Patchcord SC/UPC-ST/UPC, SM, 9/125 duplex, G652D fiber, 15 m

Patchcord duplex L=15m

Insertion Loss: <=0.20dB
Return Loss: >=50dB
Repeatability: <=0.2dB
Durability: <=0.1 dB typical change, 500 matings
Interchangeability: <=0.2dB
Tensile Strength: >10kg
Operating Temperature: -40 ÷ 80°C

#08648
Net Price:
2.87 USD
Unit: pcs

Patchcord LC/UPC-FC/UPC, MM, 50/125 duplex, OM2 fiber, 1 m

Patchcord duplex L=1m

Insertion Loss: <=0.30dB
Return Loss: >=30dB
Operating Temperature: -40 ÷ 80°C

#08649
Net Price:
3.06 USD
Unit: pcs

Patchcord LC/UPC-FC/UPC, MM, 50/125 duplex, OM2 fiber, 2 m

Patchcord duplex L=2m

Insertion Loss: <=0.30dB
Return Loss: >=30dB
Operating Temperature: -40 ÷ 80°C

#08650
Net Price:
3.24 USD
Unit: pcs

Patchcord LC/UPC-FC/UPC, MM, 50/125 duplex, OM2 fiber, 3 m

Patchcord duplex L=3m

Insertion Loss: <=0.30dB
Return Loss: >=30dB
Operating Temperature: -40 ÷ 80°C

#08651
Net Price:
3.80 USD
Unit: pcs

Patchcord LC/UPC-FC/UPC, MM, 50/125 duplex, OM2 fiber, 5 m

Patchcord duplex L=5m

Insertion Loss: <=0.30dB
Return Loss: >=30dB
Operating Temperature: -40 ÷ 80°C

#08644
Net Price:
2.87 USD
Unit: pcs

Patchcord LC/UPC-FC/UPC, SM, 9/125 duplex, G652D fiber, 1 m

Patchcord duplex L=1m

Insertion Loss: <=0.20dB
Return Loss: >=50dB
Repeatability: <=0.2dB
Durability: <=0.1 dB typical change, 500 matings
Interchangeability: <=0.2dB
Tensile Strength: >10kg
Operating Temperature: -40 ÷ 80°C

#08645
Net Price:
3.01 USD
Unit: pcs

Patchcord LC/UPC-FC/UPC, SM, 9/125 duplex, G652D fiber, 2 m

Patchcord duplex L=2m

Insertion Loss: <=0.20dB
Return Loss: >=50dB
Repeatability: <=0.2dB
Durability: <=0.1 dB typical change, 500 matings
Interchangeability: <=0.2dB
Tensile Strength: >10kg
Operating Temperature: -40 ÷ 80°C

#08646
Net Price:
3.15 USD
Unit: pcs

Patchcord LC/UPC-FC/UPC, SM, 9/125 duplex, G652D fiber, 3 m

Patchcord duplex L=3m

Insertion Loss: <=0.20dB
Return Loss: >=50dB
Repeatability: <=0.2dB
Durability: <=0.1 dB typical change, 500 matings
Interchangeability: <=0.2dB
Tensile Strength: >10kg
Operating Temperature: -40 ÷ 80°C

#08647
Net Price:
3.61 USD
Unit: pcs

Patchcord LC/UPC-FC/UPC, SM, 9/125 duplex, G652D fiber, 5 m

Patchcord duplex L=5m

Insertion Loss: <=0.20dB
Return Loss: >=50dB
Repeatability: <=0.2dB
Durability: <=0.1 dB typical change, 500 matings
Interchangeability: <=0.2dB
Tensile Strength: >10kg
Operating Temperature: -40 ÷ 80°C

#07489
Net Price:
3.13 USD
Unit: pcs

Patchcord LC/UPC-LC/UPC, MM, 50/125 duplex, OM4 fiber, 1 m

#07493
Net Price:
8.34 USD
Unit: pcs

Patchcord LC/UPC-LC/UPC, MM, 50/125 duplex, OM4 fiber, 10 m

#07494
Net Price:
12.30 USD
Unit: pcs

Patchcord LC/UPC-LC/UPC, MM, 50/125 duplex, OM4 fiber, 15 m

#07490
Net Price:
3.66 USD
Unit: pcs

Patchcord LC/UPC-LC/UPC, MM, 50/125 duplex, OM4 fiber, 2 m

#07491
Net Price:
4.19 USD
Unit: pcs

Patchcord LC/UPC-LC/UPC, MM, 50/125 duplex, OM4 fiber, 3 m

#07492
Net Price:
5.54 USD
Unit: pcs

Patchcord LC/UPC-LC/UPC, MM, 50/125 duplex, OM4 fiber, 5 m

#04545
Net Price:
3.15 USD
Unit: pcs

Patchcord LC/UPC-LC/UPC, MM, 62,5/125 duplex, OM1 fiber, 1 m

#08193
Net Price:
3.10 USD
Unit: pcs

Patchcord LC/UPC-LC/UPC, MM, 50/125 duplex, OM3 fiber, 2 m

#08196
Net Price:
3.36 USD
Unit: pcs

Patchcord LC/UPC-LC/UPC, MM, 50/125 duplex, OM3 fiber, 3 m

#08616
Net Price:
2.83 USD
Unit: pcs

Patchcord LC/APC-LC/APC, SM, 9/125 duplex, G652D fiber, 1 m

Patchcord duplex L=1m

Insertion Loss: <=0.20dB
Return Loss: >=60dB
Repeatability: <=0.1dB
Durability: <=0.1 dB typical change, 500 matings
Interchangeability: <=0.2dB
Tensile Strength: >10kg
Operating Temperature: -40 ÷ 80°C

#08617
Net Price:
2.97 USD
Unit: pcs

Patchcord LC/APC-LC/APC, SM, 9/125 duplex, G652D fiber, 2 m

Patchcord duplex L=2m

Insertion Loss: <=0.20dB
Return Loss: >=60dB
Repeatability: <=0.1dB
Durability: <=0.1 dB typical change, 500 matings
Interchangeability: <=0.2dB
Tensile Strength: >10kg
Operating Temperature: -40 ÷ 80°C

#08618
Net Price:
3.10 USD
Unit: pcs

Patchcord LC/APC-LC/APC, SM, 9/125 duplex, G652D fiber, 3 m

Patchcord duplex L=3m

Insertion Loss: <=0.20dB
Return Loss: >=60dB
Repeatability: <=0.1dB
Durability: <=0.1 dB typical change, 500 matings
Interchangeability: <=0.2dB
Tensile Strength: >10kg
Operating Temperature: -40 ÷ 80°C

#08619
Net Price:
3.56 USD
Unit: pcs

Patchcord LC/APC-LC/APC, SM, 9/125 duplex, G652D fiber, 5 m

Patchcord duplex L=5m

Insertion Loss: <=0.20dB
Return Loss: >=60dB
Repeatability: <=0.1dB
Durability: <=0.1 dB typical change, 500 matings
Interchangeability: <=0.2dB
Tensile Strength: >10kg
Operating Temperature: -40 ÷ 80°C

#04510
Net Price:
4.29 USD
Unit: pcs

Patchcord LC/APC-LC/APC, SM, 9/125 duplex, G652D fiber, 10 m

Patchcord duplex L=10m

Insertion Loss: <=0.20dB
Return Loss: >=60dB
Repeatability: <=0.1dB
Durability: <=0.1 dB typical change, 500 matings
Interchangeability: <=0.2dB
Tensile Strength: >10kg
Operating Temperature: -40 ÷ 80°C

#04530
Net Price:
5.53 USD
Unit: pcs

Patchcord LC/APC-LC/APC, SM, 9/125 duplex, G652D fiber, 15 m

Patchcord duplex L=15m

Insertion Loss: <=0.20dB
Return Loss: >=60dB
Repeatability: <=0.1dB
Durability: <=0.1 dB typical change, 500 matings
Interchangeability: <=0.2dB
Tensile Strength: >10kg
Operating Temperature: -40 ÷ 80°C

#08620
Net Price:
2.78 USD
Unit: pcs

Patchcord LC/UPC-LC/UPC, MM, 50/125 duplex, OM2 fiber, 1 m

Patchcord duplex L=1m

Insertion Loss: <=0.30dB
Return Loss: >=30dB
Operating Temperature: -40 ÷ 80°C

#08621
Net Price:
2.97 USD
Unit: pcs

Patchcord LC/UPC-LC/UPC, MM, 50/125 duplex, OM2 fiber, 2 m

Patchcord duplex L=2m

Insertion Loss: <=0.30dB
Return Loss: >=30dB
Operating Temperature: -40 ÷ 80°C

#08622
Net Price:
3.15 USD
Unit: pcs

Patchcord LC/UPC-LC/UPC, MM, 50/125 duplex, OM2 fiber, 3 m

Patchcord duplex L=3m

Insertion Loss: <=0.30dB
Return Loss: >=30dB
Operating Temperature: -40 ÷ 80°C

#08623
Net Price:
3.71 USD
Unit: pcs

Patchcord LC/UPC-LC/UPC, MM, 50/125 duplex, OM2 fiber, 5 m

Patchcord duplex L=5m

Insertion Loss: <=0.30dB
Return Loss: >=30dB
Operating Temperature: -40 ÷ 80°C

#04509
Net Price:
4.68 USD
Unit: pcs

Patchcord LC/UPC-LC/UPC, MM, 50/125 duplex, OM2 fiber, 10 m

Patchcord duplex L=10m

Insertion Loss: <=0.30dB
Return Loss: >=30dB
Operating Temperature: -40 ÷ 80°C

#04529
Net Price:
6.22 USD
Unit: pcs

Patchcord LC/UPC-LC/UPC, MM, 50/125 duplex, OM2 fiber, 15 m

Patchcord duplex L=15m

Insertion Loss: <=0.30dB
Return Loss: >=30dB
Operating Temperature: -40 ÷ 80°C

#08865
Net Price:
2.85 USD
Unit: pcs

Patchcord LC/UPC-LC/UPC, MM, 50/125 duplex, OM3 fiber, 1 m

#08613

Net Price:
2.97 USD
Unit: pcs

Patchcord LC/UPC-LC/UPC, SM, 9/125 duplex, G652D fiber, 2 m

Patchcord duplex L=2m

Insertion Loss: <=0.20dB
Return Loss: >=50dB
Repeatability: <=0.2dB
Durability: <=0.1 dB typical change, 500 matings
Interchangeability: <=0.2dB
Tensile Strength: >10kg
Operating Temperature: -40 ÷ 80°C

#08614

Net Price:
3.10 USD
Unit: pcs

Patchcord LC/UPC-LC/UPC, SM, 9/125 duplex, G652D fiber, 3 m

Patchcord duplex L=3m

Insertion Loss: <=0.20dB
Return Loss: >=50dB
Repeatability: <=0.2dB
Durability: <=0.1 dB typical change, 500 matings
Interchangeability: <=0.2dB
Tensile Strength: >10kg
Operating Temperature: -40 ÷ 80°C

#08590

Net Price:
4.07 USD
Unit: pcs

Patchcord LC/UPC-LC/UPC, MM, 50/125 duplex, OM3 fiber, 5 m

#08589

Net Price:
5.41 USD
Unit: pcs

Patchcord LC/UPC-LC/UPC, MM, 50/125 duplex, OM3 fiber, 10 m

#08588

Net Price:
7.43 USD
Unit: pcs

Patchcord LC/UPC-LC/UPC, MM, 50/125 duplex, OM3 fiber, 15 m

#08587

Net Price:
8.91 USD
Unit: pcs

Patchcord LC/UPC-LC/UPC, MM, 50/125 duplex, OM3 fiber, 20 m

#08586

Net Price:
10.40 USD
Unit: pcs

Patchcord LC/UPC-LC/UPC, MM, 50/125 duplex, OM3 fiber, 25 m

#08612

Net Price:
2.83 USD
Unit: pcs

Patchcord LC/UPC-LC/UPC, SM, 9/125 duplex, G652D fiber. 1 m

Patchcord duplex L=1m

Insertion Loss: <=0.20dB
Return Loss: >=50dB
Repeatability: <=0.2dB
Durability: <=0.1 dB typical change, 500 matings
Interchangeability: <=0.2dB
Tensile Strength: >10kg
Operating Temperature: -40 ÷ 80°C

#08615

Net Price:
3.56 USD
Unit: pcs

Patchcord LC/UPC-LC/UPC, SM, 9/125 duplex, G652D fiber, 5 m

Patchcord duplex L=5m

Insertion Loss: <=0.20dB
Return Loss: >=50dB
Repeatability: <=0.2dB
Durability: <=0.1 dB typical change, 500 matings
Interchangeability: <=0.2dB
Tensile Strength: >10kg
Operating Temperature: -40 ÷ 80°C

#04508

Net Price:
4.29 USD
Unit: pcs

Patchcord LC/UPC-LC/UPC, SM, 9/125 duplex, G652D fiber. 10 m

Patchcord duplex L=10m

Insertion Loss: <=0.20dB
Return Loss: >=50dB
Repeatability: <=0.2dB
Durability: <=0.1 dB typical change, 500 matings
Interchangeability: <=0.2dB
Tensile Strength: >10kg
Operating Temperature: -40 ÷ 80°C

#04528

Net Price:
5.53 USD
Unit: pcs

Patchcord LC/UPC-LC/UPC, SM, 9/125 duplex, G652D fiber. 15 m

Patchcord duplex L=15m

Insertion Loss: <=0.20dB
Return Loss: >=50dB
Repeatability: <=0.2dB
Durability: <=0.1 dB typical change, 500 matings
Interchangeability: <=0.2dB
Tensile Strength: >10kg
Operating Temperature: -40 ÷ 80°C

#08664

Net Price:
2.87 USD
Unit: pcs

Patchcord LC/UPC-ST/UPC, MM, 50/125 duplex, OM2 fiber, 1 m

Patchcord duplex L=1m

Insertion Loss: <=0.30dB
Return Loss: >=30dB
Operating Temperature: -40 ÷ 80°C

#08665

Net Price:
3.06 USD
Unit: pcs

Patchcord LC/UPC-ST/UPC, MM, 50/125 duplex, OM2 fiber, 2 m

Patchcord duplex L=2m

Insertion Loss: <=0.30dB
Return Loss: >=30dB
Operating Temperature: -40 ÷ 80°C

#08666

Net Price:
3.24 USD
Unit: pcs

Patchcord LC/UPC-ST/UPC, MM, 50/125 duplex, OM2 fiber, 3 m

Patchcord duplex L=3m

Insertion Loss: <=0.30dB
Return Loss: >=30dB
Operating Temperature: -40 ÷ 80°C

#08667

Net Price:
3.80 USD
Unit: pcs

Patchcord LC/UPC-ST/UPC, MM, 50/125 duplex, OM2 fiber, 5 m

Patchcord duplex L=5m

Insertion Loss: <=0.30dB
Return Loss: >=30dB
Operating Temperature: -40 ÷ 80°C

#04514
Net Price:
4.78 USD
Unit: pcs

Patchcord LC/UPC-ST/UPC, MM, 50/125 duplex, OM2 fiber, 10 m

Patchcord duplex L=10m

Insertion Loss: <=0.30dB
Return Loss: >=30dB
Operating Temperature: -40 ÷ 80°C

#04534
Net Price:
6.33 USD
Unit: pcs

Patchcord LC/UPC-ST/UPC, MM, 50/125 duplex, OM2 fiber, 15 m

Patchcord duplex L=15m

Insertion Loss: <=0.30dB
Return Loss: >=30dB
Operating Temperature: -40 ÷ 80°C

#04223
Net Price:
3.20 USD
Unit: pcs

Patchcord LC/UPC-ST/UPC, MM, 50/125 duplex, OM3 fiber, 2 m

Patchcord duplex L=2m

Insertion Loss: <=0.30dB
Return Loss: >=30dB
Operating Temperature: -40 ÷ 80°C

#08660
Net Price:
2.87 USD
Unit: pcs

Patchcord LC/UPC-ST/UPC, SM, 9/125 duplex, G652D fiber, 1 m

Patchcord duplex L=1m

Insertion Loss: <=0.20dB
Return Loss: >=50dB
Repeatability: <=0.2dB
Durability: <=0.1 dB typical change, 500 matings
Interchangeability: <=0.2dB
Tensile Strength: >10kg
Operating Temperature: -40 ÷ 80°C

#08661
Net Price:
3.01 USD
Unit: pcs

Patchcord LC/UPC-ST/UPC, SM, 9/125 duplex, G652D fiber, 2 m

Patchcord duplex L=2m

Insertion Loss: <=0.20dB
Return Loss: >=50dB
Repeatability: <=0.2dB
Durability: <=0.1 dB typical change, 500 matings
Interchangeability: <=0.2dB
Tensile Strength: >10kg
Operating Temperature: -40 ÷ 80°C

#08662
Net Price:
3.15 USD
Unit: pcs

Patchcord LC/UPC-ST/UPC, SM, 9/125 duplex, G652D fiber, 3 m

Patchcord duplex L=3m

Insertion Loss: <=0.20dB
Return Loss: >=50dB
Repeatability: <=0.2dB
Durability: <=0.1 dB typical change, 500 matings
Interchangeability: <=0.2dB
Tensile Strength: >10kg
Operating Temperature: -40 ÷ 80°C

#08663
Net Price:
3.61 USD
Unit: pcs

Patchcord LC/UPC-ST/UPC, SM, 9/125 duplex, G652D fiber, 5 m

Patchcord duplex L=5m

Insertion Loss: <=0.20dB
Return Loss: >=50dB
Repeatability: <=0.2dB
Durability: <=0.1 dB typical change, 500 matings
Interchangeability: <=0.2dB
Tensile Strength: >10kg
Operating Temperature: -40 ÷ 80°C

#04513
Net Price:
4.34 USD
Unit: pcs

Patchcord LC/UPC-ST/UPC, SM, 9/125 duplex, G652D fiber, 10 m

Patchcord duplex L=10m

Insertion Loss: <=0.20dB
Return Loss: >=50dB
Repeatability: <=0.2dB
Durability: <=0.1 dB typical change, 500 matings
Interchangeability: <=0.2dB
Tensile Strength: >10kg
Operating Temperature: -40 ÷ 80°C

#04533
Net Price:
5.58 USD
Unit: pcs

Patchcord LC/UPC-ST/UPC, SM, 9/125 duplex, G652D fiber, 15 m

Patchcord duplex L=15m

Insertion Loss: <=0.20dB
Return Loss: >=50dB
Repeatability: <=0.2dB
Durability: <=0.1 dB typical change, 500 matings
Interchangeability: <=0.2dB
Tensile Strength: >10kg
Operating Temperature: -40 ÷ 80°C

#08672
Net Price:
18.70 USD
Unit: pcs

Patchcord E2000/APC-E2000/APC, SM, 9/125 simplex, G652D fiber, 1 m

Fiber optic patchcord E2000/APC to E2000/APC, singlemode, 9/125µm, simplex, L=1m.

#08673
Net Price:
19.00 USD
Unit: pcs

Patchcord E2000/APC-E2000/APC, SM, 9/125 simplex, G652D fiber, 2 m

Fiber optic patchcord E2000/APC to E2000/APC, singlemode 9/125µm, simplex, L=2m.

#08674
Net Price:
19.20 USD
Unit: pcs

Patchcord E2000/APC-E2000/APC, SM, 9/125 simplex, G652D fiber, 3 m

Fiber optic patchcord E2000/APC to E2000/APC, singlemode 9/125µm, simplex, L=3m.

#08675
Net Price:
19.70 USD
Unit: pcs

Patchcord E2000/APC-E2000/APC, SM, 9/125 simplex, G652D fiber, 5 m

Fiber optic patchcord E2000/APC to E2000/APC, singlemode 9/125µm, simplex, L=5m.

#08668
Net Price:
18.70 USD
Unit: pcs

Patchcord E2000/UPC-E2000/UPC, SM, 9/125 simplex, G652D fiber, 1 m

Fiber optic patchcord E2000/UPC to E2000/UPC, singlemode 9/125µm, simplex, L=1m.

#08669
Net Price:
19.00 USD
Unit: pcs

Patchcord E2000/UPC-E2000/UPC, SM, 9/125 simplex, G652D fiber, 2 m

Fiber optic patchcord E2000/UPC to E2000/UPC, singlemode 9/125µm, simplex, L=2m.

#08670
Net Price:
19.20 USD
Unit: pcs

Patchcord E2000/UPC-E2000/UPC, SM, 9/125 simplex, G652D fiber, 3 m

Fiber optic patchcord E2000/UPC to E2000/UPC, singlemode 9/125µm, simplex, L=3m.

#08671
Net Price:
19.70 USD
Unit: pcs

Patchcord E2000/UPC-E2000/UPC, SM, 9/125 simplex, G652D fiber, 5 m

Fiber optic patchcord E2000/UPC to E2000/UPC, singlemode 9/125µm, simplex, L=5m.

#07395
Net Price:
21.00 USD
Unit: pcs

Patchcord MPO(F)-LC/UPC, MM, 50/125, 12F, OM3 fiber, 1 m

#07392
Net Price:
30.70 USD
Unit: pcs

Patchcord MPO(F)-LC/UPC, MM, 50/125, 12F, OM3 fiber, 10 m

#07393
Net Price:
36.10 USD
Unit: pcs

Patchcord MPO(F)-LC/UPC, MM, 50/125, 12F, OM3 fiber, 15 m

#07394
Net Price:
41.20 USD
Unit: pcs

Patchcord MPO(F)-LC/UPC, MM, 50/125, 12F, OM3 fiber, 20 m

#07396
Net Price:
23.90 USD
Unit: pcs

Patchcord MPO(F)-LC/UPC, MM, 50/125, 12F, OM4 fiber, 1 m

#08579
Net Price:
29.80 USD
Unit: pcs

Patchcord MPO(F)-MPO(F) type B, MM, 50/125, 12F, OM3 fiber, 10 m

#08580
Net Price:
35.10 USD
Unit: pcs

Patchcord MPO(F)-MPO(F) type B, MM, 50/125, 12F, OM3 fiber, 15 m

#08581
Net Price:
41.00 USD
Unit: pcs

Patchcord MPO(F)-MPO(F) type B, MM, 50/125, 12F, OM3 fiber, 20 m

#08582
Net Price:
48.30 USD
Unit: pcs

Patchcord MPO(F)-MPO(F) type B, MM, 50/125, 12F, OM4 fiber, 10 m

#08583
Net Price:
65.40 USD
Unit: pcs

Patchcord MPO(F)-MPO(F) type B, MM, 50/125, 12F, OM4 fiber, 15 m

#08584
Net Price:
81.00 USD
Unit: pcs

Patchcord MPO(F)-MPO(F) type B, MM, 50/125, 12F, OM4 fiber, 20 m

#04538
Net Price:
3.66 USD
Unit: pcs

Patchcord LC/UPC-FC/UPC, MM, 50/125 duplex, OM3 fiber, 15 m

#04541
Net Price:
4.39 USD
Unit: pcs

Patchcord LC/UPC-FC/UPC, MM, 50/125 duplex, OM3 fiber, 20 m

#04544
Net Price:
2.87 USD
Unit: pcs

Patchcord LC/UPC-LC/UPC, MM, 62,5/125 duplex, OM1 fiber, 1 m

Fiber Optic Pigtails

#08688
Net Price:
0.718 USD
Unit: pcs

Pigtail SC/APC, SM, 9/125, 0,9mm, G652D fiber, 1m

Pigtail L=1m

#08689
Net Price:
0.741 USD
Unit: pcs

Pigtail SC/APC, SM, 9/125, 0,9mm, G652D fiber, 2m

Pigtail L=2m

#08690
Net Price:
0.765 USD
Unit: pcs

Pigtail SC/APC, SM, 9/125, 0,9mm, G652D fiber, 3m

Pigtail L=3m

#08891
Net Price:
0.730 USD
Unit: pcs

Pigtail SC/APC, SM, 9/125, 0,9mm, G657A1 fiber, 1m

Pigtail L=1m

#08598
Net Price:
0.765 USD
Unit: pcs

Pigtail SC/APC, SM, 9/125, 0,9mm, G657A1 fiber, 2m

Pigtail L=2m

#08691
Net Price:
0.695 USD
Unit: pcs

Pigtail SC/UPC, MM, 50/125, 0,9mm, OM2 fiber, 1m

Multimode fiber optic pigtail with SC/UPC connector and OM2 fiber. Length 1m

#08692
Net Price:
0.741 USD
Unit: pcs

Pigtail SC/UPC, MM, 50/125, 0,9mm, OM2 fiber, 2m

Pigtail L=2m

#08693
Net Price:
0.811 USD
Unit: pcs

Pigtail SC/UPC, MM, 50/125, 0,9mm, OM2 fiber, 3m

Pigtail L=3m

#08868
Net Price:
0.741 USD
Unit: pcs

Pigtail SC/UPC, MM, 50/125, 0,9mm, OM3 fiber, 1m

#04487

Net Price:
0.834 USD
Unit: pcs

Pigtail SC/UPC, MM, 50/125, 0,9mm, OM3 fiber, 2m

#04488

Net Price:
0.927 USD
Unit: pcs

Pigtail SC/UPC, MM, 50/125, 0,9mm, OM3 fiber, 3m

#04158

Net Price:
0.880 USD
Unit: pcs

Pigtail SC/UPC, MM, 50/125, 0,9mm, OM4 fiber, 1m

#04160

Net Price:
1.14 USD
Unit: pcs

Pigtail SC/UPC, MM, 50/125, 0,9mm, OM4 fiber, 2m

#08890

Net Price:
0.765 USD
Unit: pcs

Pigtail SC/UPC, MM, 62.5/125, 0,9mm, OM1 fiber, 1m

Multimode fiber optic pigtail with SC/UPC connector and OM2 fiber. Length 1m

#08685

Net Price:
0.695 USD
Unit: pcs

Pigtail SC/UPC, SM, 9/125, 0,9mm, G652D fiber, 1m

Pigtail L=1m

#08686

Net Price:
0.718 USD
Unit: pcs

Pigtail SC/UPC, SM, 9/125, 0,9mm, G652D fiber, 2m

Pigtail L=2m

#08687

Net Price:
0.741 USD
Unit: pcs

Pigtail SC/UPC, SM, 9/125, 0,9mm, G652D fiber, 3m

Singlemode fiber optic pigtail with SC/UPC connector and G652D fiber. Length 3m

#04215

Net Price:
8.43 USD
Unit: pcs

12 colors pigtail set SC/UPC, MM, 50/125, 0,9mm, OM2 fiber, 2m

A set of 12 pigtails in different colors

Length: 2m
Fiber type: MM OM2 50/125
Colors: blue, orange, green, brown, grey, white, red, black, yellow, purple, pink, aqua

#04216

Net Price:
8.47 USD
Unit: pcs

12 colors pigtail set SC/UPC, MM, 50/125, 0,9mm, OM3 fiber, 2m

A set of 12 pigtails in different colors

Length: 2m
Fiber type: MM OM3 50/125
Colors: blue, orange, green, brown, grey, white, red, black, yellow, purple, pink, aqua

#04217

Net Price:
8.78 USD
Unit: pcs

12 colors pigtail set SC/UPC, MM, 50/125, 0,9mm, OM4 fiber, 2m

A set of 12 pigtails in different colors

Length: 2m
Fiber type: MM OM4 50/125
Colors: blue, orange, green, brown, grey, white, red, black, yellow, purple, pink, aqua

#04213

Net Price:
9.13 USD
Unit: pcs

12 colors pigtail set SC/APC, SM, 9/125, 0,9mm, G.652D fiber, 2m

A set of 12 pigtails in different colors

Length: 2m
Fiber type: SM G.652D 9/125
Colors: blue, orange, green, brown, grey, white, red, black, yellow, purple, pink, aqua

#04214

Net Price:
8.91 USD
Unit: pcs

12 colors pigtail set SC/UPC, SM, 9/125, 0,9mm, G.652D fiber, 2m

A set of 12 pigtails in different colors

Length: 2m
Fiber type: SM G.652D 9/125
Colors: blue, orange, green, brown, grey, white, red, black, yellow, purple, pink, aqua

#08679

Net Price:
0.695 USD
Unit: pcs

Pigtail LC/APC, SM, 9/125, 0,9mm, G652D fiber, 1m

Pigtail L=1m

#08680

Net Price:
0.718 USD
Unit: pcs

Pigtail LC/APC, SM, 9/125, 0,9mm, G652D fiber, 2m

Pigtail L=2m

#08681

Net Price:
0.741 USD
Unit: pcs

Pigtail LC/APC, SM, 9/125, 0,9mm, G652D fiber, 3m

Pigtail L=3m

#08682

Net Price:
0.695 USD
Unit: pcs

Pigtail LC/UPC, MM, 50/125, 0,9mm, OM2 fiber, 1m

Pigtail L=1m

#08683

Net Price:
0.741 USD
Unit: pcs

Pigtail LC/UPC, MM, 50/125, 0,9mm, OM2 fiber, 2m

Pigtail L=2m

#08684
Net Price:
0.811 USD
Unit: pcs

Pigtail LC/UPC, MM, 50/125, 0,9mm, OM2 fiber, 3m

Pigtail L=3m

#08870
Net Price:
0.741 USD
Unit: pcs

Pigtail LC/UPC, MM, 50/125, 0,9mm, OM3 fiber, 1m

#04489
Net Price:
0.834 USD
Unit: pcs

Pigtail LC/UPC, MM, 50/125, 0,9mm, OM3 fiber, 2m

#04490
Net Price:
0.927 USD
Unit: pcs

Pigtail LC/UPC, MM, 50/125, 0,9mm, OM3 fiber, 3m

#04157
Net Price:
0.880 USD
Unit: pcs

Pigtail LC/UPC, MM, 50/125, 0,9mm, OM4 fiber, 1m

#04159
Net Price:
1.14 USD
Unit: pcs

Pigtail LC/UPC, MM, 50/125, 0,9mm, OM4 fiber, 2m

#08585
Net Price:
0.834 USD
Unit: pcs

Pigtail LC/UPC, MM, 62.5/125, 0,9mm, OM1 fiber, 2m

Multimode fiber optic pigtail with LC/UPC connector and OM2 fiber. Length 2m

#08676
Net Price:
0.695 USD
Unit: pcs

Pigtail LC/UPC, SM, 9/125, 0,9mm, G652D fiber, 1m

Pigtail L=1m

#08677
Net Price:
0.718 USD
Unit: pcs

Pigtail LC/UPC, SM, 9/125, 0,9mm, G652D fiber, 2m

Pigtail L=2m

#08678
Net Price:
0.741 USD
Unit: pcs

Pigtail LC/UPC, SM, 9/125, 0,9mm, G652D fiber, 3m

Pigtail L=3m

#04219
Net Price:
8.43 USD
Unit: pcs

12 colors pigtail set LC/UPC, MM, 50/125, 0,9mm, OM2 fiber, 2m

A set of 12 pigtails in different colors

Colors: blue, orange, green, brown, grey, white, red, black, yellow, purple, pink, aqua

#04220
Net Price:
8.47 USD
Unit: pcs

12 colors pigtail set LC/UPC, MM, 50/125, 0,9mm, OM3 fiber, 2m

A set of 12 pigtails in different colors

Length: 2m
Fiber type: MM OM3 50/125
Colors: blue, orange, green, brown, grey, white, red, black, yellow, purple, pink, aqua

#04221
Net Price:
8.78 USD
Unit: pcs

12 colors pigtail set LC/UPC, MM, 50/125, 0,9mm, OM4 fiber, 2m

A set of 12 pigtails in different colors

Length: 2m
Fiber type: MM OM4 50/125
Colors: blue, orange, green, brown, grey, white, red, black, yellow, purple, pink, aqua

#04218
Net Price:
8.87 USD
Unit: pcs

12 colors pigtail set LC/UPC, SM, 9/125, 0,9mm, G.652D fiber, 2m

A set of 12 pigtails in different colors

Length: 2m
Fiber type: SM G.652D 9/125
Colors: blue, orange, green, brown, grey, white, red, black, yellow, purple, pink, aqua

#08697
Net Price:
0.741 USD
Unit: pcs

Pigtail FC/UPC, MM, 50/125, 0,9mm, OM2 fiber, 1m

Pigtail L=1m

#08698
Net Price:
0.788 USD
Unit: pcs

Pigtail FC/UPC, MM, 50/125, 0,9mm, OM2 fiber, 2m

Pigtail L=2m

#08699
Net Price:
0.834 USD
Unit: pcs

Pigtail FC/UPC, MM, 50/125, 0,9mm, OM2 fiber, 3m

Pigtail L=3m

#08694
Net Price:
0.765 USD
Unit: pcs

Pigtail FC/UPC, SM, 9/125, 0,9mm, G652D fiber, 1m

Pigtail L=1m

#08695
Net Price:
0.788 USD
Unit: pcs

Pigtail FC/UPC, SM, 9/125, 0,9mm, G652D fiber, 2m

Pigtail L=2m

#08696
Net Price:
0.811 USD
Unit: pcs

Pigtail FC/UPC, SM, 9/125, 0,9mm, G652D fiber, 3m

Pigtail L=3m

#08703
Net Price:
0.741 USD
Unit: pcs

Pigtail ST/UPC, MM, 50/125, 0,9mm, OM2 fiber, 1m

Pigtail L=1m

#08704
Net Price:
0.788 USD
Unit: pcs

Pigtail ST/UPC, MM, 50/125, 0,9mm, OM2 fiber, 2m
Pigtail L=2m

#08705
Net Price:
0.834 USD
Unit: pcs

Pigtail ST/UPC, MM, 50/125, 0,9mm, OM2 fiber, 3m
Pigtail L=3m

#04222
Net Price:
0.788 USD
Unit: pcs

Pigtail ST/UPC, MM, 50/125, 0,9mm, OM3 fiber, 1m
Pigtail L=1m

#08700
Net Price:
0.765 USD
Unit: pcs

Pigtail ST/UPC, SM, 9/125, 0,9mm, G652D fiber, 1m
Pigtail L=1m

#08701
Net Price:
0.788 USD
Unit: pcs

Pigtail ST/UPC, SM, 9/125, 0,9mm, G652D fiber, 2m
Pigtail L=2m

#08702
Net Price:
0.811 USD
Unit: pcs

Pigtail ST/UPC, SM, 9/125, 0,9mm, G652D fiber, 3m
Pigtail L=3m

#08709
Net Price:
8.68 USD
Unit: pcs

Pigtail E2000/APC, SM, 9/125, 0,9mm, G652D fiber, 1m
Fiber optic pigtail E2000/APC, singlemode 9/125µm, simplex, L=1m.

#08710
Net Price:
8.85 USD
Unit: pcs

Pigtail E2000/APC, SM, 9/125, 0,9mm, G652D fiber, 2m
Fiber optic pigtail E2000/APC, singlemode 9/125µm, simplex, L=2m.

#08711
Net Price:
9.02 USD
Unit: pcs

Pigtail E2000/APC, SM, 9/125, 0,9mm, G652D fiber, 3m
Fiber optic pigtail E2000/APC, singlemode 9/125µm, simplex, L=3m.

#08706
Net Price:
8.68 USD
Unit: pcs

Pigtail E2000/UPC, SM, 9/125, 0,9mm, G652D fiber, 1m
Fiber optic pigtail E2000/UPC, singlemode 9/125µm, simplex, L=1m.

#08707
Net Price:
8.85 USD
Unit: pcs

Pigtail E2000/UPC, SM, 9/125, 0,9mm, G652D fiber, 2m
Fiber optic pigtail E2000/UPC, singlemode 9/125µm, simplex, L=2m.

#08708
Net Price:
9.02 USD
Unit: pcs

Pigtail E2000/UPC, SM, 9/125, 0,9mm, G652D fiber, 3m
Fiber optic pigtail E2000/UPC, singlemode 9/125µm, simplex, L=3m.

Fiber Optic Cables

#08003
Net Price:
0.668 USD
Unit: m

Universal cable 4x50/125, OM2 fiber, LSZH
Fiber optic indoor-outdoor cable, central loose tube, fiberglass yarns, LSOH, fully dielectric.

#08005
Net Price:
0.592 USD
Unit: m

Universal cable 4x9/125, G652D fiber, LSZH
Fiber optic indoor-outdoor cable, central loose tube, fiberglass yarns, LSOH, fully dielectric.

#08007
Net Price:
0.820 USD
Unit: m

Universal cable 8x50/125, OM2 fiber, LSZH
Fiber optic indoor-outdoor cable, central loose tube, fiberglass yarns, LSOH, fully dielectric.

#08011
Net Price:
1.04 USD
Unit: m

Universal cable 12x50/125, OM2 fiber, LSZH
Fiber optic indoor-outdoor cable, central loose tube, fiberglass yarns, LSOH, fully dielectric.

#08013
Net Price:
0.642 USD
Unit: m

Universal cable 12x9/125, G652D fiber, LSZH
Fiber optic indoor-outdoor cable, central loose tube, fiberglass yarns, LSOH, fully dielectric.

#08015
Net Price:
2.00 USD
Unit: m

Universal cable 24x50/125, OM2 fiber, LSZH
Fiber optic indoor-outdoor cable, central loose tube, fiberglass yarns, LSOH, fully dielectric.

#08017
Net Price:
1.06 USD
Unit: m

Universal cable 24x9/125, G652D fiber, LSZH
Fiber optic indoor-outdoor cable, central loose tube, fiberglass yarns, LSOH, fully dielectric.

#08033
Net Price:
0.705 USD
Unit: m

Indoor cable mini-breakout, 4x50/125/900, OM2 fiber, LSZH
Fiber optic indoor mini-breakout cable, tight tube 1,8mm, aramid yarns, LSOH, fully dielectric.

#08034
Net Price:
0.672 USD
Unit: m

Indoor cable mini-breakout, 4x9/125/900, G652D fiber, LSZH
Fiber optic indoor mini-breakout cable, tight tube 1,8mm, aramid yarns, LSOH, fully dielectric.

#08035

Net Price:
1.23 USD
Unit: m

Indoor cable mini-breakout, 8x50/125/900, OM2 fiber, LSZH

Fiber optic indoor mini-breakout cable, tight tube 1,8mm, aramid yarns, LSOH, fully dielectric.

#08037

Net Price:
1.76 USD
Unit: m

Indoor cable mini-breakout, 12x50/125/900, OM2 fiber, LSZH

Fiber optic indoor mini-breakout cable, tight tube 1,8mm, aramid yarns, LSOH, fully dielectric.

#08036

Net Price:
1.06 USD
Unit: m

Indoor cable mini-breakout, 12x9/125/900, G652D fiber, LSZH

Fiber optic indoor mini-breakout cable, tight tube 1,8mm, aramid yarns, LSOH, fully dielectric.

#08038

Net Price:
1.63 USD
Unit: m

Indoor cable mini-breakout, 24x9/125/900, G652D fiber, LSZH

Fiber optic indoor mini-breakout cable, tight tube 1,8mm, aramid yarns, LSOH, fully dielectric.

#08004

Net Price:
0.550 USD
Unit: m

Outdoor cable 4x50/125, OM2 fiber, PE

Fiber optic outdoor cable, central loose tube, fiberglass yarns, PE, fully dielectric.

#08006

Net Price:
0.435 USD
Unit: m

Outdoor cable 4x9/125, G652D fiber, PE

Fiber optic outdoor cable, central loose tube, fiberglass yarns, PE, fully dielectric.

#08008

Net Price:
0.788 USD
Unit: m

Outdoor cable 8x50/125, OM2 fiber, PE

Fiber optic outdoor cable, central loose tube, fiberglass yarns, PE, fully dielectric.

#08010

Net Price:
0.512 USD
Unit: m

Outdoor cable 8x9/125, G652D fiber, PE

Fiber optic outdoor cable, central loose tube, fiberglass yarns, PE, fully dielectric.

#08012

Net Price:
1.01 USD
Unit: m

Outdoor cable 12x50/125, OM2 fiber, PE

Fiber optic outdoor cable, central loose tube, fiberglass yarns, PE, fully dielectric.

#08014

Net Price:
0.612 USD
Unit: m

Outdoor cable 12x9/125, G652D fiber, PE

Fiber optic outdoor cable, central loose tube, fiberglass yarns, PE, fully dielectric.

#08018

Net Price:
1.03 USD
Unit: m

Outdoor cable 24x9/125, G652D fiber, PE

Fiber optic outdoor cable, central loose tube, fiberglass yarns, PE, fully dielectric.

#08028

Net Price:
0.792 USD
Unit: m

Outdoor cable for primary ducts, 12x9/125, G652D fiber; PE

Fiber optic outdoor primary duct cable, tubes stranded around central strength member, fiberglass yarns, PE, fully dielectric.

#08029

Net Price:
0.970 USD
Unit: m

Outdoor cable for primary ducts, 24x9/125, G652D fiber; PE

Fiber optic outdoor primary duct cable, tubes stranded around central strength member, fiberglass yarns, PE, fully dielectric.

#08023

Net Price:
0.708 USD
Unit: m

Outdoor cable for secondary ducts, 12x9/125, G652D fiber; PE

Fiber optic outdoor secondary duct cable, tubes stranded around central strength member, PE, fully dielectric.

#08025

Net Price:
1.28 USD
Unit: m

Outdoor cable for secondary ducts, 48x9/125, G652D fiber; PE

Fiber optic outdoor secondary duct cable, tubes stranded around central strength member, PE, fully dielectric.

#08027

Net Price:
2.17 USD
Unit: m

Outdoor cable for secondary ducts, 96x9/125, G652D fiber; PE

Fiber optic outdoor secondary duct cable, tubes stranded around central strength member, PE, fully dielectric.

#08019

Net Price:
0.478 USD
Unit: m

Outdoor cable, self supporting aerial, 4x9/125, G652D fiber, PE, span up to 50 m

Fiber optic selfsupporting outdoor cable, central loose tube with strength members, PE, fully dielectric.

#08020

Net Price:
0.642 USD
Unit: m

Outdoor cable, self supporting aerial, 8x9/125, G652D fiber, PE, span up to 80 m

Fiber optic selfsupporting outdoor cable, central loose tube with strength members, PE, fully dielectric.

#08021

Net Price:
0.755 USD
Unit: m

Outdoor cable, self supporting aerial, 12x9/125, G652D fiber, PE, span up to 50 m

Fiber optic selfsupporting outdoor cable, central loose tube with strength members, PE, fully dielectric.

#08022

Net Price:
1.07 USD
Unit: m

Outdoor cable, self supporting aerial, 24x9/125, G652D fiber, PE, span up to 50 m

Fiber optic selfsupporting outdoor cable, central loose tube with strength members, PE, fully dielectric.

#08042

Net Price:
0.292 USD
Unit: m

Patch cable 1x9/125, G652D fiber, 2.8 mm, LSOH

Fiber optic patch cable with a single fibre 9/125µm, 2.8mm, LSOH

#08889

Net Price:
189.00 USD
Unit: km

Patch cable 2x50/125, OM2, 2.8mm, LSZH

#08043

Net Price:
0.185 USD
Unit: m

Pigtail cable 9/125, G652D fiber, tight tube 0.9 mm

Fiber optic tight tube cable with a single fibre 9/125µm, 0.9mm

#08044

Net Price:
0.180 USD
Unit: m

Pigtail cable 50/125, OM2 fiber, tight tube 0.9 mm

Fiber optic tight tube cable with a single fibre 50/125µm, 0.9mm

Fiber Optic Adaptors

#04104

Net Price:
8.54 USD
Unit: pcs

Adaptor for VFL

Adaptor for visual fault locators, allows to connect patchcords and pigtails with LC connectors (1,25mm ferrule)

#08227

Net Price:
0.073 USD
Unit: pcs

Adaptor MM FC-FC simplex metal, D-hole

#08746

Net Price:
1.22 USD
Unit: pcs

Hybrid adaptor MM FC/UPC - ST/UPC duplex

Insertion Loss: <=0.30dB
Durability: <=0.2 dB typical change, 1000matings
Operating Temperature: -40 ÷ 80°C
Humidity Cycling: 75°C, 95% / 336hr
Vibration: 10~55Hz (2hr)
Impact: 1.5m drop, 8 Times

#08744

Net Price:
0.610 USD
Unit: pcs

Hybrid adaptor MM FC/UPC - ST/UPC simplex

Insertion Loss: <=0.30dB
Durability: <=0.2 dB typical change, 1000matings
Operating Temperature: -40 ÷ 80°C
Humidity Cycling: 75°C, 95% / 336hr
Vibration: 10~55Hz (2hr)
Impact: 1.5m drop, 8 Times

#08732

Net Price:
9.27 USD
Unit: pcs

Hybrid adaptor MM LC/UPC - FC/UPC simplex

Insertion Loss: <=0.30dB
Durability: <=0.2 dB typical change, 1000matings
Operating Temperature: -40 ÷ 80°C
Humidity Cycling: 75°C, 95% / 336hr
Vibration: 10~55Hz (2hr)
Impact: 1.5m drop, 8 Times

#08730

Net Price:
9.27 USD
Unit: pcs

Hybrid adaptor MM LC/UPC - SC/UPC simplex

Insertion Loss: <=0.30dB
Durability: <=0.2 dB typical change, 1000matings
Operating Temperature: -40 ÷ 80°C
Humidity Cycling: 75°C, 95% / 336hr
Vibration: 10~55Hz (2hr)
Impact: 1.5m drop, 8 Times

#08734

Net Price:
9.27 USD
Unit: pcs

Hybrid adaptor MM LC/UPC - ST/UPC simplex

Insertion Loss: <=0.30dB
Durability: <=0.2 dB typical change, 1000matings
Operating Temperature: -40 ÷ 80°C
Humidity Cycling: 75°C, 95% / 336hr
Vibration: 10~55Hz (2hr)
Impact: 1.5m drop, 8 Times

#08738

Net Price:
1.22 USD
Unit: pcs

Hybrid adaptor MM SC/UPC - FC/UPC duplex

Insertion Loss: <=0.30dB
Durability: <=0.2 dB typical change, 1000matings
Operating Temperature: -40 ÷ 80°C
Humidity Cycling: 75°C, 95% / 336hr
Vibration: 10~55Hz (2hr)
Impact: 1.5m drop, 8 Times

#08736

Net Price:
0.610 USD
Unit: pcs

Hybrid adaptor MM SC/UPC - FC/UPC simplex

Insertion Loss: <=0.30dB
Durability: <=0.2 dB typical change, 1000matings
Operating Temperature: -40 ÷ 80°C
Humidity Cycling: 75°C, 95% / 336hr
Vibration: 10~55Hz (2hr)
Impact: 1.5m drop, 8 Times

#08742

Net Price:
1.22 USD
Unit: pcs

Hybrid adaptor MM SC/UPC - ST/UPC duplex

Insertion Loss: <=0.30dB
Durability: <=0.2 dB typical change, 1000matings
Operating Temperature: -40 ÷ 80°C
Humidity Cycling: 75°C, 95% / 336hr
Vibration: 10~55Hz (2hr)
Impact: 1.5m drop, 8 Times

#08740

Net Price:
0.610 USD
Unit: pcs

Hybrid adaptor MM SC/UPC - ST/UPC simplex

Insertion Loss: <=0.30dB
Durability: <=0.2 dB typical change, 1000matings
Operating Temperature: -40 ÷ 80°C
Humidity Cycling: 75°C, 95% / 336hr
Vibration: 10~55Hz (2hr)
Impact: 1.5m drop, 8 Times

#08747

Net Price:
1.22 USD
Unit: pcs

Hybrid adaptor SM FC/UPC - ST/UPC duplex

Insertion Loss: <=0.20dB
Durability: <=0.2 dB typical change, 1000matings
Operating Temperature: -40 ÷ 80°C
Humidity Cycling: 75°C, 95% / 336hr
Vibration: 10~55Hz (2hr)
Impact: 1.5m drop, 8 Times

#08745

Net Price:
0.610 USD
Unit: pcs

Hybrid adaptor SM FC/UPC - ST/UPC simplex

Insertion Loss: <=0.20dB
Durability: <=0.2 dB typical change, 1000matings
Operating Temperature: -40 ÷ 80°C
Humidity Cycling: 75°C, 95% / 336hr
Vibration: 10~55Hz (2hr)
Impact: 1.5m drop, 8 Times

#08733

Net Price:
9.27 USD
Unit: pcs

Hybrid adaptor SM LC/UPC - FC/UPC simplex

Insertion Loss: <=0.20dB
Durability: <=0.2 dB typical change, 1000matings
Operating Temperature: -40 ÷ 80°C
Humidity Cycling: 75°C, 95% / 336hr
Vibration: 10~55Hz (2hr)
Impact: 1.5m drop, 8 Times

#08731

Net Price:
9.27 USD
Unit: pcs

Hybrid adaptor SM LC/UPC - SC/UPC simplex

Insertion Loss: <=0.20dB
Durability: <=0.2 dB typical change, 1000matings
Operating Temperature: -40 ÷ 80°C
Humidity Cycling: 75°C, 95% / 336hr
Vibration: 10~55Hz (2hr)
Impact: 1.5m drop, 8 Times

#08735

Net Price:
9.27 USD
Unit: pcs

Hybrid adaptor SM LC/UPC - ST/UPC simplex

Insertion Loss: <=0.20dB
Durability: <=0.2 dB typical change, 1000matings
Operating Temperature: -40 ÷ 80°C
Humidity Cycling: 75°C, 95% / 336hr
Vibration: 10~55Hz (2hr)
Impact: 1.5m drop, 8 Times

#08739

Net Price:
1.22 USD
Unit: pcs

Hybrid adaptor SM SC/UPC - FC/UPC duplex

Insertion Loss: <=0.20dB
Durability: <=0.2 dB typical change, 1000matings
Operating Temperature: -40 ÷ 80°C
Humidity Cycling: 75°C, 95% / 336hr
Vibration: 10~55Hz (2hr)
Impact: 1.5m drop, 8 Times

#08737

Net Price:
0.610 USD
Unit: pcs

Hybrid adaptor SM SC/UPC - FC/UPC simplex

Insertion Loss: <=0.20dB
Durability: <=0.2 dB typical change, 1000matings
Operating Temperature: -40 ÷ 80°C
Humidity Cycling: 75°C, 95% / 336hr
Vibration: 10~55Hz (2hr)
Impact: 1.5m drop, 8 Times

#08743

Net Price:
1.22 USD
Unit: pcs

Hybrid adaptor SM SC/UPC - ST/UPC duplex

Insertion Loss: <=0.20dB
Durability: <=0.2 dB typical change, 1000matings
Operating Temperature: -40 ÷ 80°C
Humidity Cycling: 75°C, 95% / 336hr
Vibration: 10~55Hz (2hr)
Impact: 1.5m drop, 8 Times

#08741

Net Price:
0.610 USD
Unit: pcs

Hybrid adaptor SM SC/UPC - ST/UPC simplex

Insertion Loss: <=0.20dB
Durability: <=0.2 dB typical change, 1000matings
Operating Temperature: -40 ÷ 80°C
Humidity Cycling: 75°C, 95% / 336hr
Vibration: 10~55Hz (2hr)
Impact: 1.5m drop, 8 Times

#08715

Net Price:
0.488 USD
Unit: pcs

Adaptor MM LC/UPC - LC/UPC duplex, OM2

Insertion Loss: <=0.30dB
Plug and unplug force(g/f): 200-600N
Durability: <=0.2 dB typical change, 1000matings
Operating Temperature: -40 ÷ 80°C
Humidity Cycling: 75°C, 95% / 336hr
Vibration: 10~55Hz (2hr)
Impact: 1.5m drop, 8 Times

#08569

Net Price:
0.488 USD
Unit: pcs

Adaptor MM LC/UPC - LC/UPC duplex, OM3

Insertion Loss: <=0.30dB
Plug and unplug force(g/f): 200-600N
Durability: <=0.2 dB typical change, 1000matings
Operating Temperature: -40 ÷ 80°C
Humidity Cycling: 75°C, 95% / 336hr
Vibration: 10~55Hz (2hr)
Impact: 1.5m drop, 8 Times

#04208

Net Price:
0.488 USD
Unit: pcs

Adaptor MM LC/UPC - LC/UPC duplex, OM4

Insertion Loss: <=0.30dB
Plug and unplug force(g/f): 200-600N
Durability: <=0.2 dB typical change, 1000matings
Operating Temperature: -40 ÷ 80°C
Humidity Cycling: 75°C, 95% / 336hr
Vibration: 10~55Hz (2hr)
Impact: 1.5m drop, 8 Times

#04209

Net Price:
1.22 USD
Unit: pcs

Adaptor MM LC/UPC - LC/UPC quad, OM4

Insertion Loss: <=0.30dB
Plug and unplug force(g/f): 200-600N
Durability: <=0.2 dB typical change, 1000matings
Operating Temperature: -40 ÷ 80°C
Humidity Cycling: 75°C, 95% / 336hr
Vibration: 10~55Hz (2hr)
Impact: 1.5m drop, 8 Times

#08712

Net Price:
0.293 USD
Unit: pcs

Adaptor MM LC/UPC - LC/UPC simplex

Insertion Loss: <=0.30dB
Plug and unplug force(g/f): 200-600N
Durability: <=0.2 dB typical change, 1000matings
Operating Temperature: -40 ÷ 80°C
Humidity Cycling: 75°C, 95% / 336hr
Vibration: 10~55Hz (2hr)
Impact: 1.5m drop, 8 Times

#08723

Net Price:
0.341 USD
Unit: pcs

Adaptor MM SC/UPC - SC/UPC duplex, OM2

Insertion Loss: <=0.30dB
Return Loss: >=30dB
Operating Temperature: -40 ÷ 80°C
Humidity Cycling: 75°C, 95% / 336hr
Vibration: 10~55Hz (2hr)
Impact: 1.5m drop, 8 Times

#08355

Net Price:
0.341 USD
Unit: pcs

Adaptor MM SC/UPC - SC/UPC duplex, OM3

Insertion Loss: <=0.30dB
Plug and unplug force(g/f): 200-600N
Durability: <=0.2 dB typical change, 1000matings
Operating Temperature: -40 ÷ 80°C
Humidity Cycling: 75°C, 95% / 336hr
Vibration: 10~55Hz (2hr)
Impact: 1.5m drop, 8 Times

#04207

Net Price:
0.341 USD
Unit: pcs

Adaptor MM SC/UPC - SC/UPC duplex, OM4

Insertion Loss: <=0.30dB
Plug and unplug force(g/f): 200-600N
Durability: <=0.2 dB typical change, 1000matings
Operating Temperature: -40 ÷ 80°C
Humidity Cycling: 75°C, 95% / 336hr
Vibration: 10~55Hz (2hr)
Impact: 1.5m drop, 8 Times

#08720

Net Price:
0.171 USD
Unit: pcs

Adaptor MM SC/UPC - SC/UPC simplex

Insertion Loss: <=0.30dB
Return Loss: >=30dB
Operating Temperature: -40 ÷ 80°C
Humidity Cycling: 75°C, 95% / 336hr
Vibration: 10~55Hz (2hr)
Impact: 1.5m drop, 8 Times

#04211

Net Price:
0.180 USD
Unit: pcs

Adaptor MM SC/UPC - SC/UPC simplex, OM3

Insertion Loss: <=0.30dB
Plug and unplug force(g/f): 200-600N
Durability: <=0.2 dB typical change, 1000matings
Operating Temperature: -40 ÷ 80°C
Humidity Cycling: 75°C, 95% / 336hr
Vibration: 10~55Hz (2hr)
Impact: 1.5m drop, 8 Times

#04210

Net Price:
0.171 USD
Unit: pcs

Adaptor MM SC/UPC - SC/UPC simplex, OM4

Insertion Loss: <=0.30dB
Plug and unplug force(g/f): 200-600N
Durability: <=0.2 dB typical change, 1000matings
Operating Temperature: -40 ÷ 80°C
Humidity Cycling: 75°C, 95% / 336hr
Vibration: 10~55Hz (2hr)
Impact: 1.5m drop, 8 Times

#08726

Net Price:
0.317 USD
Unit: pcs

Adaptor MM ST/UPC - ST/UPC simplex

Insertion Loss: <=0.30dB
Plug and unplug force(g/f): 200-600N
Durability: <=0.2 dB typical change, 1000matings
Operating Temperature: -40 ÷ 80°C
Humidity Cycling: 75°C, 95% / 336hr
Vibration: 10~55Hz (2hr)
Impact: 1.5m drop, 8 Times

#04194

Net Price:
1.71 USD
Unit: pcs

Adaptor MPO, type A (key-up, key-down)

Fiber optic MPO adaptor.

#08729

Net Price:
5.62 USD
Unit: pcs

Adaptor SM E2000/APC - E2000/APC simplex

Fiber optic adaptor E2000/APC to E2000/APC, singlemode 9/125µm, simplex.

#08728

Net Price:
5.62 USD
Unit: pcs

Adaptor SM E2000/UPC - E2000/UPC simplex

Fiber optic adaptor E2000/UPC to E2000/UPC, singlemode 9/125µm, simplex.

#08718

Net Price:
0.488 USD
Unit: pcs

Adaptor SM LC/APC - LC/APC duplex

Insertion Loss: <=0.20dB
Plug and unplug force(g/f): 200-600N
Durability: <=0.2 dB typical change, 1000matings
Operating Temperature: -40 ÷ 80°C
Humidity Cycling: 75°C, 95% / 336hr
Vibration: 10~55Hz (2hr)
Impact: 1.5m drop, 8 Times

#08719

Net Price:
1.46 USD
Unit: pcs

Adaptor SM LC/APC - LC/APC quad

Insertion Loss: <=0.20dB
Plug and unplug force(g/f): 200-600N
Durability: <=0.2 dB typical change, 1000matings
Operating Temperature: -40 ÷ 80°C
Humidity Cycling: 75°C, 95% / 336hr
Vibration: 10~55Hz (2hr)
Impact: 1.5m drop, 8 Times

#08714

Net Price:
0.293 USD
Unit: pcs

Adaptor SM LC/APC - LC/APC simplex

Insertion Loss: <=0.20dB
Plug and unplug force(g/f): 200-600N
Durability: <=0.2 dB typical change, 1000matings
Operating Temperature: -40 ÷ 80°C
Humidity Cycling: 75°C, 95% / 336hr
Vibration: 10~55Hz (2hr)
Impact: 1.5m drop, 8 Times

#08716

Net Price:
0.488 USD
Unit: pcs

Adaptor SM LC/UPC - LC/UPC duplex

Insertion Loss: <=0.20dB
Plug and unplug force(g/f): 200-600N
Durability: <=0.2 dB typical change, 1000matings
Operating Temperature: -40 ÷ 80°C
Humidity Cycling: 75°C, 95% / 336hr
Vibration: 10~55Hz (2hr)
Impact: 1.5m drop, 8 Times

#08717

Net Price:
1.22 USD
Unit: pcs

Adaptor SM LC/UPC - LC/UPC quad

Insertion Loss: <=0.20dB
Plug and unplug force(g/f): 200-600N
Durability: <=0.2 dB typical change, 1000matings
Operating Temperature: -40 ÷ 80°C
Humidity Cycling: 75°C, 95% / 336hr
Vibration: 10~55Hz (2hr)
Impact: 1.5m drop, 8 Times

#08713

Net Price:
0.293 USD
Unit: pcs

Adaptor SM LC/UPC - LC/UPC simplex

Insertion Loss: <=0.20dB
Plug and unplug force(g/f): 200-600N
Durability: <=0.2 dB typical change, 1000matings
Operating Temperature: -40 ÷ 80°C
Humidity Cycling: 75°C, 95% / 336hr
Vibration: 10~55Hz (2hr)
Impact: 1.5m drop, 8 Times

#08725

Net Price:
0.341 USD
Unit: pcs

Adaptor SM SC/APC - SC/APC duplex

Insertion Loss: <=0.20dB
Return Loss: >=60dB
Repeatability: <=0.1dB
Durability: <=0.1 dB typical change, 500 matings
Interchangeability: <=0.2dB
Tensile Strength: >10kg
Operating Temperature: -40 ÷ 80°C
Humidity Cycling: 75°C, 95% / 336hr
Vibration: 10~55Hz (2hr)
Impact: 1.5m drop, 8 Times

#08722

Net Price:
0.171 USD
Unit: pcs

Adaptor SM SC/APC - SC/APC simplex

Insertion Loss: <=0.20dB
Return Loss: >=60dB
Repeatability: <=0.1dB
Durability: <=0.1 dB typical change, 500 matings
Interchangeability: <=0.2dB
Tensile Strength: >10kg
Operating Temperature: -40 ÷ 80°C
Humidity Cycling: 75°C, 95% / 336hr
Vibration: 10~~55Hz (2hr)
Impact: 1.5m drop, 8 Times

#04101

Net Price:
0.171 USD
Unit: pcs

Adaptor SM SC/APC - SC/APC simplex, flangeless

Insertion Loss: <=0.20dB
Return Loss: >=60dB
Repeatability: <=0.1dB
Durability: <=0.1 dB typical change, 500 matings
Interchangeability: <=0.2dB
Tensile Strength: >10kg
Operating Temperature: -40 ÷ 80°C
Humidity Cycling: 75°C, 95% / 336hr
Vibration: 10~~55Hz (2hr)
Impact: 1.5m drop, 8 Times

#08724

Net Price:
0.341 USD
Unit: pcs

Adaptor SM SC/UPC - SC/UPC duplex

Insertion Loss: <=0.20dB
Return Loss: >=50dB
Repeatability: <=0.2dB
Durability: <=0.1 dB typical change, 500 matings
Interchangeability: <=0.2dB
Tensile Strength: >10kg
Operating Temperature: -40 ÷ 80°C
Humidity Cycling: 75°C, 95% / 336hr
Vibration: 10~55Hz (2hr)
Impact: 1.5m drop, 8 Times

#08721
Net Price:
0.171 USD
Unit: pcs

Adaptor SM SC/UPC - SC/UPC simplex
Insertion Loss: <=0.20dB
Return Loss: >=50dB
Repeatability: <=0.2dB
Durability: <=0.1 dB typical change, 500 matings
Interchangeability: <=0.2dB
Tensile Strength: >10kg
Operating Temperature: -40 ÷ 80°C
Humidity Cycling: 75°C, 95% / 336hr
Vibration: 10~55Hz (2hr)
Impact: 1.5m drop, 8 Times

#04102
Net Price:
0.171 USD
Unit: pcs

Adaptor SM SC/UPC - SC/UPC simplex, flangeless
Insertion Loss: <=0.20dB
Return Loss: >=50dB
Repeatability: <=0.2dB
Durability: <=0.1 dB typical change, 500 matings
Interchangeability: <=0.2dB
Tensile Strength: >10kg
Operating Temperature: -40 ÷ 80°C
Humidity Cycling: 75°C, 95% / 336hr
Vibration: 10~55Hz (2hr)
Impact: 1.5m drop, 8 Times

#08727
Net Price:
0.317 USD
Unit: pcs

Adaptor SM ST/UPC - ST/UPC simplex
Insertion Loss: <=0.20dB
Plug and unplug force(g/f): 200-600N
Durability: <=0.2 dB typical change, 1000matings
Operating Temperature: -40 ÷ 80°C
Humidity Cycling: 75°C, 95% / 336hr
Vibration: 10~55Hz (2hr)
Impact: 1.5m drop, 8 Times

Fiber Optic Connectors

#08801
Net Price:
0.417 USD
Unit: pcs

Connector FC/APC SM, 0.9mm

#08802
Net Price:
0.417 USD
Unit: pcs

Connector FC/APC SM, 3.0 mm

#08803
Net Price:
0.395 USD
Unit: pcs

Connector FC/UPC MM, 0.9mm

#08804
Net Price:
0.395 USD
Unit: pcs

Connector FC/UPC MM, 3.0mm

#08799
Net Price:
0.395 USD
Unit: pcs

Connector FC/UPC SM, 0.9mm

#08800
Net Price:
0.395 USD
Unit: pcs

Connector FC/UPC SM, 3.0 mm

#08789
Net Price:
0.395 USD
Unit: pcs

Connector LC/APC SM, 0.9mm
Insertion Loss: <=0.20dB
Return Loss: >=65dB
Durability: <=0.2 dB typical change, 500 matings
Ferrule Hole Sizes: 125.0+1/-0μm, 125.5+1/-0μm, 126.0+1/-0μm
Concentricity: <=1.0μm
Operating Temperature: -40 ÷ 80°C

#08790
Net Price:
0.395 USD
Unit: pcs

Connector LC/APC SM, 3.0 mm
Insertion Loss: <=0.20dB
Return Loss: >=65dB
Durability: <=0.2 dB typical change, 500 matings
Ferrule Hole Sizes: 125.0+1/-0μm, 125.5+1/-0μm, 126.0+1/-0μm
Concentricity: <=1.0μm
Operating Temperature: -40 ÷ 80°C

#08791
Net Price:
0.329 USD
Unit: pcs

Connector LC/UPC MM, 0.9 mm
Insertion Loss: <=0.25dB
Return Loss: >=30dB
Ferrule Hole Sizes: 127μm
Concentricity: <=3μm
Operating Temperature: -40 ÷ 80°C

#08792
Net Price:
0.329 USD
Unit: pcs

Connector LC/UPC MM, 3.0 mm
Insertion Loss: <=0.25dB
Return Loss: >=30dB
Ferrule Hole Sizes: 127μm
Concentricity: <=3μm
Operating Temperature: -40 ÷ 80°C

#08787
Net Price:
0.395 USD
Unit: pcs

Connector LC/UPC SM, 0.9mm
Insertion Loss: <=0.20dB
Durability: <=0.2 dB typical change, 500 matings
Ferrule Hole Sizes: 125.0+1/-0μm, 125.5+1/-0μm, 126.0+1/-0μm
Concentricity: <=1.0μm
Operating Temperature: -40 ÷ 80°C

#08788
Net Price:
0.395 USD
Unit: pcs

Connector LC/UPC SM, 3.0 mm
Insertion Loss: <=0.20dB
Durability: <=0.2 dB typical change, 500 matings
Ferrule Hole Sizes: 125.0+1/-0μm, 125.5+1/-0μm, 126.0+1/-0μm
Concentricity: <=1.0μm
Operating Temperature: -40 ÷ 80°C

#08795
Net Price:
0.395 USD
Unit: pcs

Connector SC/APC SM, 0.9mm

#08796
Net Price:
0.395 USD
Unit: pcs

Connector SC/APC SM, 3.0 mm

#08797
Net Price:
0.329 USD
Unit: pcs

Connector SC/UPC MM, 0.9 mm

#08798
Net Price:
0.329 USD
Unit: pcs

Connector SC/UPC MM, 3.0 mm

#08793
Net Price:
0.395 USD
Unit: pcs

Connector SC/UPC SM, 0.9mm

#08794
Net Price:
0.395 USD
Unit: pcs

Connector SC/UPC SM, 3.0 mm

#04704

Net Price:
0.805 USD
Unit: pcs

SC/APC Optic Fast Connector

Connector type: SC/APC
Attenuation: 0.25dB

#04705

Net Price:
0.878 USD
Unit: pcs

SC/UPC Optic Fast Connector

Connector type: SC/UPC
Attenuation: 0.25dB

Measuring Instruments

#07792

Net Price:
40.00 USD
Unit: pcs

Optical power meter -50 ÷ +26dBm

Compact and an easy-to-use testing device for optical fiber networks, which can be used for absolute optical power measurements as well as for relative loss measurements in optical fibers. It has wide range of power measurement and high accuracy.

Measurement Range (dBm): -50 ÷ +26dBm
Detector type: InGaAs
Wavelength: 850~1600nm
Calibrated wave depths: 850/1300/1310/1490/1550/1625 nm
Resolution: 0.01dBm (0.1%)
Permissible operating temperature: -10 ° C ÷ 50 ° C
Storage temperature: -20 ° C ÷ 70 ° C
Power: 3x AAA battery
Dimensions: 130x65x32 mm
Weight: 122g (without batteries)
Kit includes: Power meter, case, user manual, additional FC and SC adapter

#07795

Net Price:
56.60 USD
Unit: pcs

Optical power meter -70 ÷ +10dBm

Compact and an easy-to-use testing instrument for optical fiber networks, which can be used for absolute optical power measurements as well as for relative loss measurements in optical fibers. It has a wide range of power measurement and a high accuracy.
Additionally equipped with VFL.

Measurement Range (dBm): -70 ÷ +10dBm
Detector type: InGaAs
Wavelength: 850~1620nm
Calibrated wave depths: 850/1300/1310/1490/1550/1625 nm
Resolution: 0.01dBm (0.1%)
Measurement accuracy: 3%
Permissible operating temperature: -10 ° C ÷ 50 ° C
Storage temperature: -20 ° C ÷ 70 ° C
VFL: Class III, <10mW, continuous or pulsating operation
Power: rechargeable battery (charger included)
Dimensions: 80x43x16mm
Weight: 280g

#07791

Net Price:
40.00 USD
Unit: pcs

Optical power meter -70 ÷ +10dBm

Compact and an easy-to-use testing instrument for optical fiber networks, which can be used for absolute optical power measurements as well as for relative loss measurements in optical fibers. It has a wide range of power measurement and a high accuracy.

Measurement Range (dBm):-70 ÷ +10dBm
Detector type:InGaAs
Wavelength:850~1620nm
Calibrated wave depths:850/1300/1310/1490/1550/1625 nm
Resolution:0.01dBm (0.1%)
Permissible operating temperature:-10 ° C ÷ 50 ° C
Storage temperature:-20 ° C ÷ 70 ° C
Power:3x AAA battery
Dimensions: 130x65x32 mm
Weight: 122g (without batteries)
Kit includes: Power meter, case, user manual, additional FC and SC adapter

#06819

Net Price:
1 730.00 USD
Unit: pcs

Optical power meter SFPOWERMETER (SimpliFiber Pro)

Measurement accuracy: +/-0,25 dB
Connector: removable, SC (standard), LC/ST (optional)
Detector type: InGaAs
Wavelength: 850/1300/1310/1490/1550/1625 nm
Measurement range: 10 dBm ÷ -52 dBm (850 nm), 10 dBm ÷ -60 dBm (1300/1310/1490/1550/1625 nm)
Measurement linearity for 850 nm: +/- 0.2 dB (power from 0 dBm to -45 dBm), +/- 0.25 dB (power < -45 dBm)
Measurement linearity for 1300/1310/1490/1550/1625 nm: +/- 0.1 dB (power from 0 dBm to -55 dBm), +/- 0.2 dB (power > 0 dBm and < -55 dBm)
Resolution: 0.01 dB
Battery life: 50 h
Memory: 1000 records
Dimensions: 165x80x39 mm
Operating temperatures: -10°C ÷ 50°C
Operating humidity: up to 95%, non-condensing
Certificates: CE, CSA, N10140
Weight: 278g
Communication interface: USB
Producer: Fluke Networks

#06820

Net Price:
3 180.00 USD
Unit: pcs

Optical light source SM, 1310/1550 nm (SimpliFiber Pro)

Connector type: SC
Wavelength: 1310/1550 nm
Emitter type: laser
Ouput power: 8 dBm (minimum), -7 dBm (typical)
Source stability: +/-0.25 dB over 8 h
AA battery life: 30 h
Dimensions: 142x81x41 mm
Operating temperatures: -10°C ÷ 50°C
Operating humidity: up to 95%, non-condensing
Certificates: CE, CSA, N10140
Weight: 278g

#07793

Net Price:
101.00 USD
Unit: pcs

Optical light source, 1310/1550 nm

An optical light source with a wavelength of 1310 and 1550 nm for measuring multimode and singlemode fiber optic cables.

Wavelength: 1310/1550nm
Power: -7 dBm
Battery life: 45 h
Power supply: 3x AAA battery
Source stability: 0.04 dBm
Permissible operating temperature: -10 ° C ÷ 50 ° C
Storage temperature: -20 ° C ÷ 70 ° C
Dimensions: 130 x 63 x 29 mm
Weight: 160 g
Kit contents: light source, cover, user manual, case

#07794

Net Price:
113.00 USD
Unit: pcs

Optical light source, 850/1300 nm

An optical light source with a wavelength of 850 and 1300 nm for measuring multimode and singlemode fiber optic cables.

Wavelength: 850/1300nm
Power: -15 dBm
Battery life: 45 h
Power supply: 3x AAA battery
Source stability: 0.04 dBm
Permissible operating temperature: -10 ° C ÷ 50 ° C
Storage temperature: -20 ° C ÷ 70 ° C
Dimensions: 130 x 63 x 29 mm
Weight: 160 g
Kit contents: light source, cover, user manual, case

#03840

Net Price:
84.90 USD
Unit: pcs

Optical multimeter Noyafa NF-911C

The Optical multimeter Noyafa NF-911C is a measurement set in one housing, consisting of a precise source, an optical power meter and a visible light source, designed for bidirectional measurements of attenuation and reflectance in fiber optic systems and networks.

Optical power meter
Detector: InGaAs
Wavelength: 850 ÷ 1700 nm
Power range: +26 dBm ÷ -50 dBm
Resolution: 0.01dBm
Connector: universal 2.5mm

Source of light
Wavelength: 1310 / 1550nm
Modulation frequency: 270Hz, 1kHz, 2kHz
Connector: universal 2.5mm

VFL
Wavelength: 650nm
Power: 20mW
Connector: universal 2.5mm

General parameters
Battery life: 240h
Power supply: 3x AA battery
Permissible operating temperature: -20 ° C ÷ 70 ° C
Dimensions: 160 x 75 x 32 mm
Weight: 205g
Kit contents: Meter, Cover, User manual

Producer: Noyafa

#05721

Net Price:
418.00 USD
Unit: pcs

Visible light source - VISIFAULT (FL-VISIFAULT)

Fiber compatibility: singlemode, multimode
Wavelength: 650 nm
Connector: standard 2,5 mm connector for SC/FC/ST optical connectors, 1,25 mm (LC/MU) with FL-NF380
Laser safety rating: Class II
Max. output power: 1 mW
Output modes: continuous, flashing (2 Hz ÷ 3 Hz)
Range: 3 km (multimode), 4 km (singlemode)
Impact strength: 1m drop
Vibration: random, 2g, 5 Hz ÷ 500 Hz
Altitude: 3000 m
Operating temperature: 0°C ÷ 40°C
Operating humidity: 0% ÷ 95%, non-condensing
Dimensions: 157x52x37 mm
Weight: 0,18 kg
Power: 2x AA battery
Battery life: > 80h in continuous mode
Safety: CSA C22.2 No. 1010.1 1992, EN 61010-1, CE
Warranty period: 12 months
Manufacturer: Fluke Networks

#03827

Net Price:
19.30 USD
Unit: pcs

Visible light source, alluminium alloy, 10mW

The visible light source is very helpful in measurements and identification of fibers of every type.
The compact design and simple operation make it an ideal device in everyday use.

Wavelength: 640-665nm
Output: max. 10mW
Adapter: universal 2,5mm (SC, ST, FC)
Working modes: countinous or pulsation
Power: 2xAA
Dimensions: 170x13mm (length x diameter)
Cover: aluminum

#04177

Net Price:
25.90 USD
Unit: pcs

Wave Optics, WO-VFL-10-AL Visible light source

The visible light source is very helpful in measurements and identification of fibers of every type. Its compact design and ease of use make it an ideal device for everyday use.

Wavelength: 640-665nm
Output: max. 10mW
Adapter: universal 2,5mm (SC, ST, FC)
Working modes: countinous or pulsating
Power: 2xAA
Dimensions: 170x13mm (length x diameter)
Coating: aluminium
Manufacturer: Wave Optics

NEW

#03832

Net Price:
21.00 USD
Unit: pcs

Wave Optics, WO-VFL-10-AL Visible light source with build-in power bank

The visible light source is very helpful in measurements and identification of fibers of every type. Its compact design and ease of use make it an ideal device for everyday use.

Wavelength: 640-665nm
Output: max. 10mW
Adapter: universal 2,5mm (SC, ST, FC)
Working modes: countinous or pulsating
Power: 2xAA
Dimensions: 170x13mm (length x diameter)
Coating: aluminium
Manufacturer: Wave Optics

#04181

Net Price:
33.20 USD
Unit: pcs

Wave Optics, WO-VFL-20-AL Visible light source

The visible light source is very helpful in measurements and identification of fibers of every type. Its compact design and ease of use make it an ideal device for everyday use.

Wavelength: 640-665nm
Output: max. 20mW
Adapter: universal 2,5mm (SC, ST, FC)
Working modes: countinous or pulsation
Power: 2xAA
Dimensions: 170x13mm (length x diameter)
Coating: aluminium
Manufacturer: Wave Optics

Fiber Optic Splice Boxes

#04710

Net Price:
21.30 USD
Unit: pcs

Splice box, 19", w/o front panel

19" Fiber optic splice box without front panel.

Color: RAL9005 (black)

#04717

Net Price:
23.50 USD
Unit: pcs

Splice box, 19", w/o front panel, slide-in

19" Fiber optic splice box without front panel.

Color: RAL9005 (black)

#06622

Net Price:
25.40 USD
Unit: pcs

Splice box, 12x SC duplex, 19", no adaptors

Fiber optic splice box with front panel for 12 adaptors SC duplex, 19", adaptors not included

#06634

Net Price:
23.00 USD
Unit: pcs

Splice box, 24x SC duplex, 19", no adaptors

Fiber optic splice box with front panel for 24 adaptors SC duplex, 19", adaptors not included

#06637

Net Price:
25.40 USD
Unit: pcs

Splice box, 24x SC simplex, 19", no adaptors

Fiber optic splice box with front panel for 24 adaptors SC simplex, LC duplex or E2000, 19", adaptors not included

#07413

Net Price:
17.10 USD
Unit: pcs

Splice box, 24x SC simplex, 19" 3U, no adaptors

Fiber optic splice box for 24 adaptors SC simplex, LC duplex or E2000, 19", adaptors not included

#04722

Net Price:
2.30 USD
Unit: pcs

12x SC duplex front panel

Front panel for 12adaptors SC duplex, 19", adaptors not included. Dedicated for #04717.

#04715

Net Price:
2.30 USD
Unit: pcs

12x SC duplex front panel

Front panel for 12adaptors SC duplex, 19", adaptors not included. Dedicated for #04710.

#04720

Net Price:
2.30 USD
Unit: pcs

12x SC simplex front panel

Front panel for 12 adaptors SC simplex, 19", adaptors not included. Dedicated for #04717.

#04713

Net Price:
2.30 USD
Unit: pcs

12x SC simplex front panel

Front panel for 12 adaptors SC simplex, 19", adaptors not included. Dedicated for #04710.

#04718

Net Price:
0.976 USD
Unit: pcs

12x ST simplex front panel

Front panel for 12 adaptors ST simplex, 19", adaptors not included. Dedicated for #04717.

#04711

Net Price:
1.90 USD
Unit: pcs

12x ST simplex front panel

Front panel for 12 adaptors ST simplex, 19", adaptors not included. Dedicated for #04710.

#04716

Net Price:
2.30 USD
Unit: pcs

24x SC duplex front panel

Front panel for 24 adaptors SC duplex, 19", adaptors not included. Dedicated for #04710.

#04723

Net Price:
2.30 USD
Unit: pcs

24x SC duplex front panel

Front panel for 24adaptors SC duplex, 19", adaptors not included. Dedicated for #04717.

#04714

Net Price:
2.30 USD
Unit: pcs

24x SC simplex front panel

Front panel for 24 adaptors SC simplex, 19", adaptors not included. Dedicated for #04710.

#04721

Net Price:
2.30 USD
Unit: pcs

24x SC simplex front panel

Front panel for 24 adaptors SC simplex, 19", adaptors not included. Dedicated for #04717.

#04712

Net Price:
1.90 USD
Unit: pcs

24x ST simplex front panel

Front panel for 24 adaptors ST simplex, 19", adaptors not included. Dedicated for #04710.

#04719

Net Price:
1.90 USD
Unit: pcs

24x ST simplex front panel

Front panel for 24 adaptors ST simplex, 19", adaptors not included. Dedicated for #04717.



#06702

Net Price:
48.00 USD
Unit: set

Splice box, 12xSC/APC SM duplex, 24x pigtail SC/APC SC 1m

Splice box include:
- 12 adaptors SC/APC SM DX #08725
- 24 pigtails SC/APC SM 1m #08688
- 2 splice trays with cover #04108

#06700

Net Price:
48.00 USD
Unit: set

Splice box, 12xSC/UPC MM duplex, 24x pigtail SC/UPC MM 1m

Splice box include:
- 12 adaptors SC/UPC MM DX #08723
- 24 pigtails SC/UPC MM 1m #08691
- 2 splice trays with cover #04108

#06701

Net Price:
48.00 USD
Unit: set

Splice box, 12xSC/UPC SM duplex, 24x pigtail SC/UPC SM 1m

Splice box include:
- 12 adaptors: SC/UPC SM DX #08724
- 24 pigtails: SC/UPC SM 1m #08685
- 2 splice trays with cover #04108

#06705

Net Price:
48.00 USD
Unit: set

Splice box, 24xSC/APC SM simplex, 24x pigtail SC/APC SM 1m

Splice box include:
- 24 adaptors SC/APC SM SX #08722
- 24 pigtails SC/APC SM 1m #08688
- 2 splice trays with cover #04108

#06703

Net Price:
48.00 USD
Unit: set

Splice box, 24xSC/UPC MM simplex, 24x pigtail SC/UPC MM 1m

Splice box include:
- 24 adaptors SC/UPC MM SX #08720
- 24 pigtails SC/UPC MM 1m #08691
- 2 splice trays with cover #04108

#07500

Net Price:
31.80 USD
Unit: pcs

Splice box, 12 cores FTTH box

Fiber optic splicing box for 12 adaptors SC simplex, LC duplex or E2000 with key. Wall mounting enabled.

Dimensions: 300x300x83 mm

#04708

Net Price:
20.60 USD
Unit: pcs

Splice box, 16 cores outdoor (IP65) FTTH box, PLC

FTTH outdoor box. Wall mounting enabled. Waterproof IP65. PLC not included.

Dimensions: 285x175x103 mm

#07779

Net Price:
31.20 USD
Unit: pcs

Splice box, 24 cores outdoor (IP65) FTTH box, 16x SC simplex, w/o adaptors

FTTH outdoor box for 24 adaptors SC simplex, LC duplex or E2000 with key. Wall mounting enabled. Waterproof IP65. Adaptor not included.

#07399

Net Price:
7.32 USD
Unit: pcs

Splice box, 24 cores outdoor (IP65) FTTH box, for PLC splitters

FTTH outdoor box for PLC splitters. Wall mounting enabled. Waterproof IP65.

Dimensions: 170x290x80 mm

#07437
Net Price:
6.91 USD
Unit: pcs

Splice box, 4 cores FTTH box

Fiber optic splicing metal box for 4 adaptors SC simplex, LC duplex or E2000. Wall mounting enabled.

Dimensions: 200x130x50 mm

#07452
Net Price:
11.20 USD
Unit: pcs

Splice box, 4 cores outdoor (IP65) FTTH box, 2x SC simplex, w/o adaptors

FTTH outdoor box for 2 adaptors SC simplex, LC duplex or E2000 with key. Wall mounting enabled. Waterproof IP65. Adaptor not included.

Dimensions: 220x155x53 mm

#07424
Net Price:
6.80 USD
Unit: pcs

Splice box, 4 cores outdoor (IP65) FTTH box, 4x SC simplex, w/o adaptors

FTTH outdoor box for 4 adaptors SC simplex, LC duplex or E2000 with key. Wall mounting enabled. Waterproof IP65. Adaptor not included.

Dimensions: 187x117x40 mm

#07438
Net Price:
10.30 USD
Unit: pcs

Splice box, 8 cores FTTH box

Fiber optic splicing metal box for 8 adaptors SC simplex, LC duplex or E2000. Wall mounting enabled.

Dimensions: 200x170x45 mm

#07432
Net Price:
14.30 USD
Unit: pcs

Splice box, 8 cores outdoor (IP65) FTTH box, 8x SC simplex, w/o adaptors

FTTH outdoor box for 8 adaptors SC simplex, LC duplex or E2000 with key. Wall mounting enabled. Waterproof IP65. Adaptor not included.

Dimensions: 245x205x65 mm

#07777
Net Price:
10.60 USD
Unit: pcs

Splice box, 8 cores outdoor (IP65) FTTH box, 8x SC simplex, w/o adaptors

FTTH outdoor box for 8 adaptors SC simplex, LC duplex or E2000 with key. Wall mounting enabled. Waterproof IP65. Adaptor not included.

Dimensions: 230x170x55 mm

#07453
Net Price:
18.00 USD
Unit: pcs

Splice box, 12 cores outdoor (IP65) FTTH box, 6x SC duplex, w/o adaptors

FTTH outdoor box for 6 adaptors SC duplex with key. Wall mounting enabled. Waterproof IP65. Adaptor not included.

#07439
Net Price:
13.20 USD
Unit: pcs

Splice box, 16 cores FTTH box

Fiber optic splicing metal box for 16 adaptors SC simplex, LC duplex or E2000. Wall mounting enabled.

Dimensions: 220x200x40 mm
Kit includes: frame for 16 SC simplex adaptors, mounts for 24 splices, 16x splice protectors, cable glands, plastic cable organisers, wall mounting screws

#07778
Net Price:
15.10 USD
Unit: pcs

Splice box, 16 cores outdoor (IP65) FTTH box, 16x SC simplex, w/o adaptors

FTTH outdoor box for 16 adaptors SC simplex, LC duplex or E2000 with key. Wall mounting enabled. Waterproof IP65. Adaptor not included.

Dimensions: 300x260x100 mm

#07780
Net Price:
27.60 USD
Unit: pcs

Splice box, 24 cores outdoor (IP65) FTTH box, 24x SC simplex, w/o adaptors

FTTH outdoor box for 24 adaptors SC simplex, LC duplex or E2000 with key. Wall mounting enabled. Waterproof IP65. Adaptor not included.

Dimensions: 330x270x120 mm

#07451
Net Price:
33.40 USD
Unit: pcs

Splice box, 48 cores FTTH box

Fiber optic splicing box for 24 adaptors SC simplex, LC duplex or E2000 with key. Wall mounting enabled.

Dimensions: 410x450x160 mm

#07771
Net Price:
16.10 USD
Unit: pcs

Splice box, 48 cores FTTH box

FTTH splice box for 48 cores. Wall mounting enabled.

Dimensions: 255x186x80 mm

#06704
Net Price:
13.00 USD
Unit: pcs

Splice box, 16x SC duplex, 10", no adaptors

Fiber optic splice box with front panel for 16 adaptors SC duplex, 10", adaptors not included

Depth: 167mm

#04707
Net Price:
3.59 USD
Unit: pcs

DIN Splice box, 4x SC simplex, no adaptors

Fiber optic splicing plastic box for 4 adaptors SC simplex. DIN-Rail and wall mounting enabled.

Dimensions: 100x80x32mm

#08329
Net Price:
16.10 USD
Unit: pcs

Wall-mount type splice box, 6x SC duplex, no adaptors

Fiber optic splicing metal box for 6 adaptors SC duplex with key. Wall mounting enabled.

#07428
Net Price:
8.68 USD
Unit: pcs

DIN Splice box, 6x SC duplex, no adaptors

Fiber optic splicing plastic box for 6 adaptors SC duplex. DIN-Rail and wall mounting enabled.

Dimmensions: 125x132x35mm
Includes: splice tray, cable glands
Adaptors: not included, suitable for 6x SC duplex

#08858
Net Price:
8.68 USD
Unit: pcs

DIN Splice box, 8x SC simplex, no adaptors

Fiber optic splicing metal box for 8 adaptors SC simplex, LC duplex or E2000. DIN-Rail and wall mounting enabled.

Adaptors: none, 8 slots for SC simplex adaptors
Dimensions: 125x132x35mm

#08334
Net Price:
9.27 USD
Unit: pcs

Mini splice box, 8x SC simplex, no adaptors

Fiber optic splicing plastic box for 8 adaptors SC simplex, LC duplex or E2000. Wall mounting enabled.

#08330

Net Price:
20.30 USD
Unit: pcs

Wall-mount type splice box, 12x SC duplex, no adaptors

Fiber optic splicing metal box for 12 adaptors SC duplex with key. Wall mounting enabled.

#03823

Net Price:
15.70 USD
Unit: pcs

DIN Splice box, 12x SC duplex, no adaptors

Fiber optic splicing metal box for 12 adaptors SC duplex.

Dimmensions: 135x150x63mm
Includes: splice tray, cable glands
Adaptors: not included, suitable for 12x SC duplex

#03829

Net Price:
0.834 USD
Unit: pcs

Mini splice box for optical patchcords

Protector box can be used for joining two simplex 2-3mm fiber patchcords with SC connectors.

#07773

Net Price:
15.10 USD
Unit: pcs

Fiber optic splice closure

Fiber optic splice closure for 12 cores. Mechanical performance comply with IEC10113-1 standards. The splice case and sealing packing can be opened and refused more than 10 times. Using life > 30 years.

#07422

Net Price:
21.70 USD
Unit: pcs

Fiber optic splice closure

Fiber optic splice closure for 24 cores. Mechanical performance comply with IEC10113-1 standards. The splice case and sealing packing can be opened and refused more than 10 times. Using life > 30 years.

Dimensions: 385x180x90 mm
Performance standard: IEC10113-1
Durability: 30 years
Protection: IP67, can be opened and refused more than 10 times

#07774

Net Price:
18.20 USD
Unit: pcs

Splice closure, 2x24 splices

Fiber optic splice closure with 2 splice tray. Each splice tray core capacity is 24.

Dimensions: 345x110mm (height x diameter)

#07410

Net Price:
42.60 USD
Unit: pcs

Splice closure, 2x24 splices

Fiber optic splice closure with 2 splice tray. Each splice tray core capacity is 24.

#07411

Net Price:
44.40 USD
Unit: pcs

Splice closure, 3x24 splices

Fiber optic splice closure with 3 splice tray. Each splice tray core capacity is 24.

#07412

Net Price:
50.70 USD
Unit: pcs

Splice closure, 4x24 splices

Fiber optic splice closure with 4 splice tray. Each splice tray core capacity is 24.

#07450

Net Price:
22.70 USD
Unit: pcs

Fiber optic splice closure 48 cores

Fiber optic splice closure for 48 cores. Mechanical performance comply with IEC10113-1 standards. The splice case and sealing packing can be opened and refused more than 10 times. Using life > 30 years.

#07772

Net Price:
25.90 USD
Unit: pcs

Fiber optic splice closure 96 cores

Fiber optic splice closure for 48 cores. Mechanical performance comply with IEC10113-1 standards. The splice case and sealing packing can be opened and refused more than 10 times. Using life > 30 years.

Attenuators, Couplers, Splitters

#08772

Net Price:
4.06 USD
Unit: pcs

PLC splitter SM 1x2 0.9mm, G657A fiber

Channel Number: 1×2
Operation Wavelength: 1260 ~ 1650 nm
Insertion Loss: <=4.0 dB
Uniformity: <=0.4 dB
PDL: <=0.2 dB
Return Loss: >=50 dB
Directivity: >=55 dB
Fiber Type: G657A
Pigtail Type: Input - tight tube, Output - loose tube
Input Length: >=1.5 m
Output Length: >=1.5 m
Fiber Mark: Input - white, Output - blue/orange
Operation Temperature: -40 ÷ 85 °C
Storage Temperature: -40 ÷ 85 °C

#08773

Net Price:
4.61 USD
Unit: pcs

PLC splitter SM 1x4 0.9mm, G657A fiber

Channel Number: 1×4
Operation Wavelength: 1260 ~ 1650 nm
Insertion Loss: <=7.4 dB
Uniformity: <=0.6 dB
PDL (1310/1550nm): <=0.2 dB
Return Loss (1310/1550nm): >=50 dB
Directivity: >=55 dB
Fiber Type: SMF-28e
Pigtail Type: Input - 0.9mm tight tube, Output - 0.9mm loose tube
Input Length: >=1.5 m
Output Length: >=1.5 m
Fiber Mark: Input - white, Output - Grey, White, Red, Black
Operation Temperature: -40 ÷ 85 °C
Storage Temperature: -40 ÷ 85 °C

#08774

Net Price:
5.05 USD
Unit: pcs

PLC splitter SM 1x8 0.9mm, G657A fiber

Channel Number: 1×8
Operation Wavelength: 1260 ~ 1650 nm
Insertion Loss: <=10.7 dB
Uniformity: <=0.8 dB
PDL: <=0.3 dB
Return Loss: >=50 dB
Directivity: >=55 dB
Fiber Type: G657A
Pigtail Type: 2.0mm loose tube
Length: >=1.5 m
Fiber Mark: Input - Yellow, Output - Yellow
Operation Temperature: -40 ÷ 85 °C
Storage Temperature: -40 ÷ 85 °C

#08775

Net Price:
8.34 USD
Unit: pcs

PLC splitter SM 1x16 0.9mm, G657A fiber

Channel Number: 1×16
Operation Wavelength: 1260 ~ 1650 nm
Insertion Loss: <=13.6 dB
Uniformity: <=1.2 dB
PDL: <=0.3 dB
Return Loss: >=50 dB
Directivity: >=55 dB
Fiber Type: G657A
Pigtail Type: 2.0mm loose tube
Length: >=1.2 m
Fiber Mark: Input - Yellow, Output - Yellow
Operation Temperature: -40 ÷ 85 °C
Storage Temperature: -40 ÷ 85 °C

#08776

Net Price:
18.20 USD
Unit: pcs

PLC splitter SM 1x32 0.9mm, G657A fiber

Channel Number: 1×32
Operation Wavelength: 1260 ~ 1650 nm
Insertion Loss: <=17.3 dB
Uniformity: <=1.7 dB
PDL: <=0.3 dB
Return Loss: >=50 dB
Directivity: >=55 dB
Fiber Type: G657A
Pigtail Type: 2.0mm loose tube
Length: >=1.5 m
Fiber Mark: Input - Yellow, Output - Yellow
Operation Temperature: -40 ÷ 85 °C
Storage Temperature: -40 ÷ 85 °C

#08777

Net Price:
46.10 USD
Unit: pcs

PLC splitter SM 1x64 0.9mm, G657A fiber

Channel Number: 1×16
Operation Wavelength: 1260 ~ 1650 nm
Insertion Loss: <=21.3 dB
Uniformity: <=2.5 dB
PDL: <=0.5 dB
Return Loss: >=50 dB
Directivity: >=55 dB
Fiber Type: G657A
Pigtail Type: 2.0mm loose tube
Length: >=1.5 m
Fiber Mark: Yellow
Operation Temperature: -40 ÷ 85 °C
Storage Temperature: -40 ÷ 85 °C

#08784

Net Price:
3.07 USD
Unit: pcs

Coupler 1x2, 1%/99% 1310+1550 nm

#08785

Net Price:
3.07 USD
Unit: pcs

Coupler 1x2, 2%/98% 1310+1550 nm

#08786

Net Price:
3.07 USD
Unit: pcs

Coupler 1x2, 5%/95% 1310+1550 nm

#08779

Net Price:
3.07 USD
Unit: pcs

Coupler 1x2, 10%/90% 1310+1550 nm

#08780

Net Price:
3.07 USD
Unit: pcs

Coupler 1x2, 20%/80% 1310+1550 nm

#08781

Net Price:
3.07 USD
Unit: pcs

Coupler 1x2, 30%/70% 1310+1550 nm

#08782

Net Price:
3.07 USD
Unit: pcs

Coupler 1x2, 40%/60% 1310+1550 nm

#08783

Net Price:
3.07 USD
Unit: pcs

Coupler 1x2, 50%/50% 1310+1550 nm

#08593

Net Price:
3.07 USD
Unit: pcs

Attenuator 0dB LC/UPC(F) - LC/UPC(M) singlemode

Operating Wavelength: 1200-1600nm or 1310nm, 1550nm
Return Loss: <=55 dB (UPC)
Attenuation Accuracy: +/-0.5
Polarization Dependent Loss: <=0.2dB
Maximum Optical Input Power: 200mW
Operating Temperature: -40 ÷ 80°C

#08592

Net Price:
3.95 USD
Unit: pcs

Attenuator 0dB SC/UPC(F) - SC/UPC(M) singlemode

Operating Wavelength: 1200-1600nm or 1310nm, 1550nm
Return Loss: <=55 dB (UPC)
Attenuation Accuracy: +/-0.5
Polarization Dependent Loss: <=0.2dB
Maximum Optical Input Power: 200mW
Operating Temperature: -40 ÷ 80°C

#08810

Net Price:
1.27 USD
Unit: pcs

Attenuator 1dB LC/UPC(F) - LC/UPC(F) singlemode

Operating Wavelength: 1200-1600nm or 1310nm, 1550nm
Return Loss: <=55 dB (UPC)
Attenuation Accuracy: +/-0.5
Polarization Dependent Loss: <=0.2dB
Maximum Optical Input Power: 200mW
Operating Temperature: -40 ÷ 80°C

#08811

Net Price:
3.07 USD
Unit: pcs

Attenuator 1dB LC/UPC(F) - LC/UPC(M) singlemode

Operating Wavelength: 1200-1600nm or 1310nm, 1550nm
Return Loss: <=55 dB (UPC)
Attenuation Accuracy: +/-0.5
Polarization Dependent Loss: <=0.2dB
Maximum Optical Input Power: 200mW
Operating Temperature: -40 ÷ 80°C

#08812

Net Price:
1.10 USD
Unit: pcs

Attenuator 1dB SC/UPC(F) - SC/UPC(F) singlemode

Operating Wavelength: 1200-1600nm or 1310nm, 1550nm
Return Loss: <=55 dB (UPC)
Attenuation Accuracy: +/-0.5
Polarization Dependent Loss: <=0.2dB
Maximum Optical Input Power: 200mW
Operating Temperature: -40 ÷ 80°C

#08813

Net Price:
3.95 USD
Unit: pcs

Attenuator 1dB SC/UPC(F) - SC/UPC(M) singlemode

Operating Wavelength: 1200-1600nm or 1310nm, 1550nm
Return Loss: <=55 dB (UPC)
Attenuation Accuracy: +/-0.5
Polarization Dependent Loss: <=0.2dB
Maximum Optical Input Power: 200mW
Operating Temperature: -40 ÷ 80°C

#08766

Net Price:
3.95 USD
Unit: pcs

Attenuator 2dB SC/UPC(F) - SC/UPC(M) singlemode

Operating Wavelength: 1200-1600nm or 1310nm, 1550nm
Return Loss: <=55 dB (UPC)
Attenuation Accuracy: +/-0.5
Polarization Dependent Loss: <=0.2dB
Maximum Optical Input Power: 200mW
Operating Temperature: -40 ÷ 80°C

#08748

Net Price:
1.27 USD
Unit: pcs

Attenuator 2dB LC/UPC(F) - LC/UPC(F) singlemode

Operating Wavelength: 1200-1600nm or 1310nm, 1550nm
Return Loss: <=55 dB (UPC)
Attenuation Accuracy: +/-0.5
Polarization Dependent Loss: <=0.2dB
Maximum Optical Input Power: 200mW
Operating Temperature: -40 ÷ 80°C

#08754

Net Price:
3.07 USD
Unit: pcs

Attenuator 2dB LC/UPC(F) - LC/UPC(M) singlemode

Operating Wavelength: 1200-1600nm or 1310nm, 1550nm
Return Loss: <=55 dB (UPC)
Attenuation Accuracy: +/-0.5
Polarization Dependent Loss: <=0.2dB
Maximum Optical Input Power: 200mW
Operating Temperature: -40 ÷ 80°C

#08760

Net Price:
1.10 USD
Unit: pcs

Attenuator 2dB SC/UPC(F) - SC/UPC(F) singlemode

Operating Wavelength: 1200-1600nm or 1310nm, 1550nm
Return Loss: <=55 dB (UPC)
Attenuation Accuracy: +/-0.5
Polarization Dependent Loss: <=0.2dB
Maximum Optical Input Power: 200mW
Operating Temperature: -40 ÷ 80°C

#08767

Net Price:
3.95 USD
Unit: pcs

Attenuator 3dB SC/UPC(F) - SC/UPC(M) singlemode

Operating Wavelength: 1200-1600nm or 1310nm, 1550nm
Return Loss: <=55 dB (UPC)
Attenuation Accuracy: +/-0.5
Polarization Dependent Loss: <=0.2dB
Maximum Optical Input Power: 200mW
Operating Temperature: -40 ÷ 80°C

#08749

Net Price:
1.27 USD
Unit: pcs

Attenuator 3dB LC/UPC(F) - LC/UPC(F) singlemode

Operating Wavelength: 1200-1600nm or 1310nm, 1550nm
Return Loss: <=55 dB (UPC)
Attenuation Accuracy: +/-0.5
Polarization Dependent Loss: <=0.2dB
Maximum Optical Input Power: 200mW
Operating Temperature: -40 ÷ 80°C

#08755

Net Price:
3.07 USD
Unit: pcs

Attenuator 3dB LC/UPC(F) - LC/UPC(M) singlemode

Operating Wavelength: 1200-1600nm or 1310nm, 1550nm
Return Loss: <=55 dB (UPC)
Attenuation Accuracy: +/-0.5
Polarization Dependent Loss: <=0.2dB
Maximum Optical Input Power: 200mW
Operating Temperature: -40 ÷ 80°C

#08761

Net Price:
1.10 USD
Unit: pcs

Attenuator 3dB SC/UPC(F) - SC/UPC(F) singlemode

Operating Wavelength: 1200-1600nm or 1310nm, 1550nm
Return Loss: <=55 dB (UPC)
Attenuation Accuracy: +/-0.5
Polarization Dependent Loss: <=0.2dB
Maximum Optical Input Power: 200mW
Operating Temperature: -40 ÷ 80°C

#08762

Net Price:
1.10 USD
Unit: pcs

Attenuator 5dB SC/UPC(F) - SC/UPC(F) singlemode

Operating Wavelength: 1200-1600nm or 1310nm, 1550nm
Return Loss: <=55 dB (UPC)
Attenuation Accuracy: +/-0.5
Polarization Dependent Loss: <=0.2dB
Maximum Optical Input Power: 200mW
Operating Temperature: -40 ÷ 80°C

#08768

Net Price:
3.95 USD
Unit: pcs

Attenuator 5dB SC/UPC(F) - SC/UPC(M) singlemode

Operating Wavelength: 1200-1600nm or 1310nm, 1550nm
Return Loss: <=55 dB (UPC)
Attenuation Accuracy: +/-0.5
Polarization Dependent Loss: <=0.2dB
Maximum Optical Input Power: 200mW
Operating Temperature: -40 ÷ 80°C

#08750

Net Price:
1.27 USD
Unit: pcs

Attenuator 5dB LC/UPC(F) - LC/UPC(F) singlemode

Operating Wavelength: 1200-1600nm or 1310nm, 1550nm
Return Loss: <=55 dB (UPC)
Attenuation Accuracy: +/-0.5
Polarization Dependent Loss: <=0.2dB
Maximum Optical Input Power: 200mW
Operating Temperature: -40 ÷ 80°C

#08756

Net Price:
3.07 USD
Unit: pcs

Attenuator 5dB LC/UPC(F) - LC/UPC(M) singlemode

Operating Wavelength: 1200-1600nm or 1310nm, 1550nm
Return Loss: <=55 dB (UPC)
Attenuation Accuracy: +/-0.5
Polarization Dependent Loss: <=0.2dB
Maximum Optical Input Power: 200mW
Operating Temperature: -40 ÷ 80°C

#08763

Net Price:
1.10 USD
Unit: pcs

Attenuator 8dB SC/UPC(F) - SC/UPC(F) singlemode

Operating Wavelength: 1200-1600nm or 1310nm, 1550nm
Return Loss: <=55 dB (UPC)
Attenuation Accuracy: +/-0.5
Polarization Dependent Loss: <=0.2dB
Maximum Optical Input Power: 200mW
Operating Temperature: -40 ÷ 80°C

#08769

Net Price:
3.95 USD
Unit: pcs

Attenuator 8dB SC/UPC(F) - SC/UPC(M) singlemode

Operating Wavelength: 1200-1600nm or 1310nm, 1550nm
Return Loss: <=55 dB (UPC)
Attenuation Accuracy: +/-0.5
Polarization Dependent Loss: <=0.2dB
Maximum Optical Input Power: 200mW
Operating Temperature: -40 ÷ 80°C

#08751

Net Price:
1.27 USD
Unit: pcs

Attenuator 8dB LC/UPC(F) - LC/UPC(F) singlemode

Operating Wavelength: 1200-1600nm or 1310nm, 1550nm
Return Loss: <=55 dB (UPC)
Attenuation Accuracy: +/-0.5
Polarization Dependent Loss: <=0.2dB
Maximum Optical Input Power: 200mW
Operating Temperature: -40 ÷ 80°C

#08757

Net Price:
3.07 USD
Unit: pcs

Attenuator 8dB LC/UPC(F) - LC/UPC(M) singlemode

Operating Wavelength: 1200-1600nm or 1310nm, 1550nm
Return Loss: <=55 dB (UPC)
Attenuation Accuracy: +/-0.5
Polarization Dependent Loss: <=0.2dB
Maximum Optical Input Power: 200mW
Operating Temperature: -40 ÷ 80°C

#08752

Net Price:
1.27 USD
Unit: pcs

Attenuator 10dB LC/UPC(F) - LC/UPC(F) singlemode

Operating Wavelength: 1200-1600nm or 1310nm, 1550nm
Return Loss: <=55 dB (UPC)
Attenuation Accuracy: +/-0.5
Polarization Dependent Loss: <=0.2dB
Maximum Optical Input Power: 200mW
Operating Temperature: -40 ÷ 80°C

#08758

Net Price:
3.07 USD
Unit: pcs

Attenuator 10dB LC/UPC(F) - LC/UPC(M) singlemode

Operating Wavelength: 1200-1600nm or 1310nm, 1550nm
Return Loss: <=55 dB (UPC)
Attenuation Accuracy: +/-0.5
Polarization Dependent Loss: <=0.2dB
Maximum Optical Input Power: 200mW
Operating Temperature: -40 ÷ 80°C

#08764

Net Price:
1.10 USD
Unit: pcs

Attenuator 10dB SC/UPC(F) - SC/UPC(F) singlemode

Operating Wavelength: 1200-1600nm or 1310nm, 1550nm
Return Loss: <=55 dB (UPC)
Attenuation Accuracy: +/-0.5
Polarization Dependent Loss: <=0.2dB
Maximum Optical Input Power: 200mW
Operating Temperature: -40 ÷ 80°C

#08770

Net Price:
3.95 USD
Unit: pcs

Attenuator 10dB SC/UPC(F) - SC/UPC(M) singlemode

Operating Wavelength: 1200-1600nm or 1310nm, 1550nm
Return Loss: <=55 dB (UPC)
Attenuation Accuracy: +/-0.5
Polarization Dependent Loss: <=0.2dB
Maximum Optical Input Power: 200mW
Operating Temperature: -40 ÷ 80°C

#08753

Net Price:
1.27 USD
Unit: pcs

Attenuator 15dB LC/UPC(F) - LC/UPC(F) singlemode

Operating Wavelength: 1200-1600nm or 1310nm, 1550nm
Return Loss: <=55 dB (UPC)
Attenuation Accuracy: +/-1.0
Polarization Dependent Loss: <=0.2dB
Maximum Optical Input Power: 200mW
Operating Temperature: -40 ÷ 80°C

#08759

Net Price:
3.07 USD
Unit: pcs

Attenuator 15dB LC/UPC(F) - LC/UPC(M) singlemode

Operating Wavelength: 1200-1600nm or 1310nm, 1550nm
Return Loss: <=55 dB (UPC)
Attenuation Accuracy: +/-1.0
Polarization Dependent Loss: <=0.2dB
Maximum Optical Input Power: 200mW
Operating Temperature: -40 ÷ 80°C

#08765

Net Price:
1.10 USD
Unit: pcs

Attenuator 15dB SC/UPC(F) - SC/UPC(F) singlemode

Operating Wavelength: 1200-1600nm or 1310nm, 1550nm
Return Loss: <=55 dB (UPC)
Attenuation Accuracy: +/-1.0
Polarization Dependent Loss: <=0.2dB
Maximum Optical Input Power: 200mW
Operating Temperature: -40 ÷ 80°C

#08771

Net Price:
3.95 USD
Unit: pcs

Attenuator 15dB SC/UPC(F) - SC/UPC(M) singlemode

Operating Wavelength: 1200-1600nm or 1310nm, 1550nm
Return Loss: <=55 dB (UPC)
Attenuation Accuracy: +/-1.0
Polarization Dependent Loss: <=0.2dB
Maximum Optical Input Power: 200mW
Operating Temperature: -40 ÷ 80°C

#08591

Net Price:
3.95 USD
Unit: pcs

Attenuator 0dB SC/APC(F) - SC/APC(M), singlemode

Operating Wavelength: 1200-1600nm or 1310nm, 1550nm
Return Loss: <=55 dB (APC)
Attenuation Accuracy: +/-0.5
Polarization Dependent Loss: <=0.2dB
Maximum Optical Input Power: 200mW
Operating Temperature: -40 ÷ 80°C

#08814

Net Price:
3.29 USD
Unit: pcs

Attenuator 1dB LC/APC(F) - LC/APC(M) singlemode

Operating Wavelength: 1200-1600nm or 1310nm, 1550nm
Return Loss: <=55 dB (APC)
Attenuation Accuracy: +/-0.5
Polarization Dependent Loss: <=0.2dB
Maximum Optical Input Power: 200mW
Operating Temperature: -40 ÷ 80°C

#08821

Net Price:
3.95 USD
Unit: pcs

Attenuator 1dB SC/APC(F) - SC/APC(M), singlemode

Operating Wavelength: 1200-1600nm or 1310nm, 1550nm
Return Loss: <=55 dB (APC)
Attenuation Accuracy: +/-0.5
Polarization Dependent Loss: <=0.2dB
Maximum Optical Input Power: 200mW
Operating Temperature: -40 ÷ 80°C

#08815

Net Price:
3.29 USD
Unit: pcs

Attenuator 2dB LC/APC(F) - LC/APC(M) singlemode

Operating Wavelength: 1200-1600nm or 1310nm, 1550nm
Return Loss: <=55 dB (APC)
Attenuation Accuracy: +/-0.5
Polarization Dependent Loss: <=0.2dB
Maximum Optical Input Power: 200mW
Operating Temperature: -40 ÷ 80°C

#08822

Net Price:
3.95 USD
Unit: pcs

Attenuator 2dB SC/APC(F) - SC/APC(M), singlemode

Operating Wavelength: 1200-1600nm or 1310nm, 1550nm
Return Loss: <=55 dB (APC)
Attenuation Accuracy: +/-0.5
Polarization Dependent Loss: <=0.2dB
Maximum Optical Input Power: 200mW
Operating Temperature: -40 ÷ 80°C

#08816

Net Price:
3.29 USD
Unit: pcs

Attenuator 3dB LC/APC(F) - LC/APC(M) singlemode

Operating Wavelength: 1200-1600nm or 1310nm, 1550nm
Return Loss: <=55 dB (APC)
Attenuation Accuracy: +/-0.5
Polarization Dependent Loss: <=0.2dB
Maximum Optical Input Power: 200mW
Operating Temperature: -40 ÷ 80°C

#08823

Net Price:
3.95 USD
Unit: pcs

Attenuator 3dB SC/APC(F) - SC/APC(M), singlemode

Operating Wavelength: 1200-1600nm or 1310nm, 1550nm
Return Loss: <=55 dB (APC)
Attenuation Accuracy: +/-0.5
Polarization Dependent Loss: <=0.2dB
Maximum Optical Input Power: 200mW
Operating Temperature: -40 ÷ 80°C

#08817

Net Price:
3.29 USD
Unit: pcs

Attenuator 5dB LC/APC(F) - LC/APC(M) singlemode

Operating Wavelength: 1200-1600nm or 1310nm, 1550nm
Return Loss: <=55 dB (APC)
Attenuation Accuracy: +/-0.5
Polarization Dependent Loss: <=0.2dB
Maximum Optical Input Power: 200mW
Operating Temperature: -40 ÷ 80°C

#08824

Net Price:
3.95 USD
Unit: pcs

Attenuator 5dB SC/APC(F) - SC/APC(M), singlemode

Operating Wavelength: 1200-1600nm or 1310nm, 1550nm
Return Loss: <=55 dB (APC)
Attenuation Accuracy: +/-0.5
Polarization Dependent Loss: <=0.2dB
Maximum Optical Input Power: 200mW
Operating Temperature: -40 ÷ 80°C

#08818

Net Price:
3.29 USD
Unit: pcs

Attenuator 8dB LC/APC(F) - LC/APC(M) singlemode

Operating Wavelength: 1200-1600nm or 1310nm, 1550nm
Return Loss: <=55 dB (APC)
Attenuation Accuracy: +/-0.5
Polarization Dependent Loss: <=0.2dB
Maximum Optical Input Power: 200mW
Operating Temperature: -40 ÷ 80°C

#08825

Net Price:
3.95 USD
Unit: pcs

Attenuator 8dB SC/APC(F) - SC/APC(M), singlemode

Operating Wavelength: 1200-1600nm or 1310nm, 1550nm
Return Loss: <=55 dB (APC)
Attenuation Accuracy: +/-0.5
Polarization Dependent Loss: <=0.2dB
Maximum Optical Input Power: 200mW
Operating Temperature: -40 ÷ 80°C

#08826

Net Price:
3.95 USD
Unit: pcs

Attenuator 10dB SC/APC(F) - SC/APC(M), singlemode

Operating Wavelength: 1200-1600nm or 1310nm, 1550nm
Return Loss: <=55 dB (APC)
Attenuation Accuracy: +/-0.5
Polarization Dependent Loss: <=0.2dB
Maximum Optical Input Power: 200mW
Operating Temperature: -40 ÷ 80°C

#08819

Net Price:
3.29 USD
Unit: pcs

Attenuator 10dB LC/APC(F) - LC/APC(M) singlemode

Operating Wavelength: 1200-1600nm or 1310nm, 1550nm
Return Loss: <=55 dB (APC)
Attenuation Accuracy: +/-0.5
Polarization Dependent Loss: <=0.2dB
Maximum Optical Input Power: 200mW
Operating Temperature: -40 ÷ 80°C

#08820

Net Price:
3.29 USD
Unit: pcs

Attenuator 15dB LC/APC(F) - LC/APC(M) singlemode

Operating Wavelength: 1200-1600nm or 1310nm, 1550nm
Return Loss: <=55 dB (APC)
Attenuation Accuracy: +/-0.5
Polarization Dependent Loss: <=0.2dB
Maximum Optical Input Power: 200mW
Operating Temperature: -40 ÷ 80°C

#08827

Net Price:
3.95 USD
Unit: pcs

Attenuator 15dB SC/APC(F) - SC/APC(M), singlemode

Operating Wavelength: 1200-1600nm or 1310nm, 1550nm
Return Loss: <=55 dB (APC)
Attenuation Accuracy: +/-0.5
Polarization Dependent Loss: <=0.2dB
Maximum Optical Input Power: 200mW
Operating Temperature: -40 ÷ 80°C

FTTH Equipment

#07423

Net Price:
1.85 USD
Unit: pcs

2 cores FTTH box, 1x SC duplex, w/o adaptors

FTTH box for 1 adaptor SC duplex. Wall mounting enabled. Adaptor not included.

#07776

Net Price:
1.17 USD
Unit: pcs

2 cores FTTH box, 1x SC simplex, w/o adaptors

FTTH box for 1 adaptor SC simplex or LC duplex. Wall mounting enabled. Adaptor not included.

#07775

Net Price:
0.654 USD
Unit: pcs

2 cores FTTH box, 2x SC simplex, w/o adaptors

FTTH box for 2 adaptor SC simplex, LC duplex or E2000. Wall mounting enabled. Adaptors not included.

#07418

Net Price:
0.727 USD
Unit: pcs

2 cores FTTH box, 2x SC simplex, w/o adaptors

FTTH box for 2 adaptor SC simplex, LC duplex or E2000. Wall mounting enabled. Adaptors not included.
Size: 86x86x22mm

#07419

Net Price:
3.07 USD
Unit: pcs

4 cores FTTH box, 4x SC simplex, w/o adaptor

FTTH box for 4 adaptor SC simplex, LC duplex or E2000. Wall mounting enabled. Adaptors not included.

Dimensions: 150x110x30mm

Fiber Optic Tools, Consumables

#04163

Net Price:
8.12 USD
Unit: tube

Adaptor cleaning stick, 1.25 mm (LC, MU)

Dust-free sticks for cleaning elements with a diameter of 1.25mm (such as adapters, holes in polishing wheels, ports in meters) or other hard-to-reach surfaces. They leave the surface perfectly clean and scratch-free.

#03800

Net Price:
0.417 USD
Unit: pcs

Adaptor cleaning stick, 1.25 mm (LC, MU)

Cleaning stick for 1.25mm adaptor cleaning.

Dust-free sticks for cleaning elements with a diameter of 1.25mm (such as adapters, holes in polishing wheels, ports in meters) or other hard-to-reach surfaces. They leave the surface perfectly clean and scratch-free.

#03801

Net Price:
0.417 USD
Unit: pcs

Adaptor cleaning stick, 2.5 mm

Dust-free sticks for cleaning elements with a diameter of 1.25mm (such as adapters, holes in polishing wheels, ports in meters) or other hard-to-reach surfaces. They leave the surface perfectly clean and scratch-free.

#04126
Net Price:
4.35 USD
Unit: pcs

Cleaning wipes

Kim-Wipes dust-free wipes for cleaning fiber optic connectors, can be used dry or soaked in ispopropyl alcohol.

Quantity in package: 280pcs.
Dimensions: 11x21cm

#04127
Net Price:
0.522 USD
Unit: pcs

Cleaning wipes with alcohol

Wipes soaked in a solution of 91% isopropyl alcohol and 9% distilled water. Dimensions: 100mm x 76mm

#02460
Net Price:
6.50 USD
Unit: pcs

Epoxy glue 353ndn, 5gram, for oven (not self curing)

Epoxy adhesive for fiber optic connectors with high thermal stability.
The package is intended for 50 joints.

#07940
Net Price:
99.50 USD
Unit: pcs

Handheld microscope, 400x

Handheld passive microscope for Ø 2.5 mm (ST, FC, SC) and 1.25mm (LC) ferrules inspection. Backlight powered by three AAA-type batteries.

Magnification: 400x
Power: 3xAAA
Adapters: 1.25mm; 2.5mm
Cover: aluminum in a rubber coating

#04170
Net Price:
5.72 USD
Unit: pcs

Isopropyl alcohol (Kontakt IPA Plus)

Isopropyl alcohol is used for cleaning all optical elements. It safely removes any pollution from their delicate surface. It is perfect for degreasing and removing impurities from optical fibers before installing or welding joints. It is also used to clean the ferrule face after polishing.

#04075
Net Price:
3.06 USD
Unit: pcs

Isopropyl alcohol (Kontakt IPA Plus) 300ml, spray

Isopropyl alcohol is used for cleaning all optical elements. It safely removes any pollution from their delicate surface. It is perfect for degreasing and removing impurities from optical fibers before installing or welding joints. It is also used to clean the ferrule face after polishing.

#03400
Net Price:
4.59 USD
Unit: pcs

Isopropyl alcohol (Kontakt IPA Plus) 600ml, spray

Isopropyl alcohol is used for cleaning all optical elements. It safely removes any pollution from their delicate surface. It is perfect for degreasing and removing impurities from optical fibers before installing or welding joints. It is also used to clean the ferrule face after polishing.

#07768
Net Price:
1.12 USD
Unit: pcs

Mechanical splice

#07769
Net Price:
1.49 USD
Unit: pcs

Mechanical splice with protection cover

#07781
Net Price:
0.088 USD
Unit: pcs

Mini splice box

Protector box can be used for joining two simplex fibers.

#03804
Net Price:
34.70 USD
Unit: pcs

One-click cleaner for 1,25mm ferrules (LC, MU)

The one-click cleaner is designed for cleaning the ferrules of LC and MU connectors.

Purpose: adapter and ferrules 1.25mm (LC;MU)
Lifetime: 800+ uses
Packaging: carboard box

#03803
Net Price:
34.70 USD
Unit: pcs

One-click cleaner for 2,5mm ferrules (SC, ST, FC)

This one-click cleaner is designed for cleaning the ferrules of SC, ST and FC connectors.

Purpose: adapter and ferrules 2.5mm (SC;ST)
Lifetime: 800+ uses
Packaging: Cardboard box

#07789
Net Price:
31.80 USD
Unit: pcs

Optic fiber connector cleaner

Meant for cleaning the ferrules of SC, LC, ST, FC, MU, MT connectors.

Purpose: SC; LC; ST; FC; MU; MT connectors
Lifetime: approx. 500 uses
Dimensions: 135x70x30mm
Packaging: cardboard box

#04168
Net Price:
1.72 USD
Unit: pcs

Polishing paper, 1 µm

Polishing paper, 1µm, pink, for manual polishing in A4 format.

#04130
Net Price:
1.72 USD
Unit: pcs

Polishing paper, 3 µm

Polishing paper, 3µm, yellow, for manual polishing in A4 format.

#04151
Net Price:
1.72 USD
Unit: pcs

Polishing paper, 5 µm

Polishing paper, 5µm, white, for manual polishing in A4 format.

#04153
Net Price:
1.72 USD
Unit: pcs

Polishing paper, 9 µm

Polishing paper, 9µm, dark blue, for manual polishing in A4 format.

#04128
Net Price:
1.72 USD
Unit: pcs

Polishing paper, 0.3 µm

Polishing paper, 0.3µm, blue, for manual polishing in A4 format.

#08413
Net Price:
1.72 USD
Unit: pcs

Polishing paper, 12 µm
Polishing paper, 9µm, salmon pink, for manual polishing in A4 format.

#04129
Net Price:
1.72 USD
Unit: pcs

Polishing paper, 30 µm
Polishing paper, 9µm, purple, for manual polishing in A4 format.

#04706
Net Price:
0.044 USD
Unit: pcs

Splice protector, 40mm, with 1 mm steel wire
Thermal shrinking tube / splice protector, 40 mm
Diameter before shrinking: 3,6-2,8 mm
Diameter after shrinking: 2,4 mm

#07445
Net Price:
0.044 USD
Unit: pcs

Splice protector, 45mm, with 1 mm steel wire
Thermal shrinking tube / splice protector, 45 mm
Diameter before shrinking: 3,6-2,8 mm
Diameter after shrinking: 2,4 mm

#04107
Net Price:
0.044 USD
Unit: pcs

Splice protector, 45mm, with 1.5 mm steel wire
Thermal shrinking tube / splice protector, 45 mm. Diameter of steel wire is 1.5mm
Length: 45mm
Diameter of steel wire: 1.5mm
Diameter before shrinking: 4,0-3,1 mm
Diameter after shrinking: 2,9 mm

#07444
Net Price:
0.044 USD
Unit: pcs

Splice protector, 60 mm, with 1 mm steel wire
Thermal shrinking tube / splice protector, 60 mm. Diameter of steel wire is 1mm
Length: 60mm
Diameter of steel wire: 1.0mm
Diameter before shrinking: 3,6-2,8 mm
Diameter after shrinking: 2,4 mm

#04139
Net Price:
0.044 USD
Unit: pcs

Splice protector, 60 mm, with 1.5mm steel wire
Thermal shrinking tube / splice protector, 60 mm. Diameter of steel wire is 1.5mm
Length: 60mm
Diameter of steel wire: 1.5mm
Diameter before shrinking: 4,0-3,1 mm
Diameter after shrinking: 2,9 mm

#06234
Net Price:
69.80 USD
Unit: pcs

Universal scribe pen
The double-sided sapphire stylus for precise cutting of the fiber end without damage to the ferrule.

Other

#08838
Net Price:
0.045 USD
Unit: pcs

Adaptor screw
Adaptor screw for patchpanel.

#07417
Net Price:
0.078 USD
Unit: pcs

Blank insert for SC duplex adapter
Dust cover for fiber optic patch panel for SC duplex adaptor.

#07416
Net Price:
0.078 USD
Unit: pcs

Blank insert for SC simplex adapter
Dust cover for fiber optic patch panel for SC simplex adaptor.

#07436
Net Price:
0.078 USD
Unit: pcs

Cable organizer
Cable organizer for FTTH cable installation use.

#07425
Net Price:
0.007 USD
Unit: pcs

FTTH Cable clip
Cable clip for FTTH cable installation use.

#07508
Net Price:
62.00 USD
Unit: pcs

Rack for spare cable with cover, 410x410x100mm

#07509
Net Price:
66.20 USD
Unit: pcs

Rack for spare cable with cover, 610x610x100mm

#04979
Net Price:
35.00 USD
Unit: pcs

Rack for spare cable, 400x400x120mm



#07460
Net Price:
10.80 USD
Unit: pcs

Rack for spare cable, 480mm

#07461
Net Price:
12.20 USD
Unit: pcs

Rack for spare cable, 600mm

#04108
Net Price:
0.873 USD
Unit: pcs

Splice tray with cover
Splice tray with cover for 12 cores suitable for patch panel.
Dimensions: 154x92x10mm
Central hole diameter: 6mm

#07415
Net Price:
0.898 USD
Unit: pcs

Splice tray with cover
Splice tray with cover for 24 cores suitable for patch panel (for very slim sleeve 2mm).

#07782

Net Price:
0.200 USD
Unit: pcs

Splice tray with cover

Splice tray with cover for 2 cores.

Dimensions: 57x94x12mm

#07783

Net Price:
0.263 USD
Unit: pcs

Splice tray with cover

Splice tray with cover for 4 cores.

Dimensions: 70x94x12mm

#07440

Net Price:
0.678 USD
Unit: pcs

Splice tray with cover

Economic splice tray with cover for 12 cores suitable for patch panel.

#08923

Net Price:
0.961 USD
Unit: pcs

Splice tray with cover

Splice tray with cover for 24 cores suitable for patch panel.

Index

Fiber Optic Patch Cords 1
Fiber Optic Pigtails 12
Fiber Optic Cables 15
Fiber Optic Adaptors 17
Fiber Optic Connectors 20
Measuring Instruments 21
Fiber Optic Splice Boxes 22
Attenuators, Couplers, Splitters 25
FTTH Equipment 29
Fiber Optic Tools, Consumables 29
Other 31

If you have any questions
please contact
our Sales Department:

Head Office Opole
tel. +48 (77) 455 60 76
fax +48 (77) 455 80 56
e-mail: cust@atel.com.pl