Flat cables		
#01829 Net Price: 9.29 USD Unit: roll 100m	#0819 Net Price: 9.29 USD Unit: roll 100m	#04917 Net Price 7.18 USD Unit: roll 100m
Flat cable, 2C, 12/7, black, 100 m/R Flat wires are covered by PVC isolation. Wire: braided copper 7x0.12mm, AWG 28 Wire's resistance: 200 Ohm/km Isolation resistance: 500 MOhm Working temperatures: -30°C up to +70°C Length: 100m	Flat cable, 2C, 12/7, white, 100 m/R Flat wires are covered by PVC isolation. Wire: braided copper 7x0.12mm, AWG 28 Wire's resistance: 200 Ohm/km Isolation resistance: 500 MOhm Working temperatures: -30°C up to +70°C Length: 100m	Flat cable, 4C, 10/6, black, 100 m/R CCS Wire: CCS 6x0.1mm Length: 100m
#04916 Net Price: 7.18 USD Unit: roll 100m	#01808 Net Price: 12.90 USD Unit: roll 100m	#04808 Net Price 38.60 USE Unit: roll 300m
Flat cable, 4C, 10/6, white, 100 m/R CCS Wire: CCS 6x0.1mm Length: 100m	Flat cable, 4C, 12/7, black, 100 m/R Flat wires are covered by PVC isolation. Wire: braided copper 7x0.12mm, AWG 28 Wire's resistance: 200 Ohm/km Isolation resistance: 500 MOhm Working temperatures: -30°C up to +70°C Length: 100m	Flat cable, 4C, 12/7, black, 300 m/R Flat wires are covered by PVC isolation. Wire: braided copper 7x0.12mm, AWG 28 Wire's resistance: 200 Ohm/km Isolation resistance: 500 M/Ohm Working temperatures: -30°C up to +70°C Length: 300m
#04001 Net Price: 12.90 USD Unit: roll 100m	#00820 Net Price: 12.90 USD Unit: roll 100m	#04807 Net Price: 38.60 USD Unit: roll 300m
Flat cable, 4C, 12/7, grey, 100 m/R Flat wires are covered by PVC isolation. Wire: braided copper 7x0.12mm, AWG 28 Wire's resistance: 200 Ohm/km Isolation resistance: 500 MOhm Working temperatures: -30°C up to +70°C Length: 100m	Flat cable, 4C, 12/7, white, 100 m/R Flat wires are covered by PVC isolation. Wire: braided copper 7x0.12mm, AWG 28 Wire's resistance: 200 Ohm/km Isolation resistance: 500 MOhm Working temperatures: -30°C up to +70°C Length: 100m	Flat cable, 4C, 12/7, white, 300 m/R Flat wires are covered by PVC isolation. Wire: braided copper 7x0.12mm, AWG 28 Wire's resistance: 200 Ohm/km Isolation resistance: 500 MOhm Working temperatures: -30°C up to +70°C Length: 300m
#01810 Net Price: 20.30 USD Unit: roll 100m	#00822 Net Price: 20.30 USD Unit: roll 100m	#01812 Net Price 25.90 USE Unit: roll 100m
Flat cable, 6C, 12/7, black, 100 m/R Flat wires are covered by PVC isolation. Wire: braided copper 7x0.12mm, AWG 28 Wire's resistance: 200 Ohm/km Isolation resistance: 500 MOhm Working temperatures: -30°C up to +70°C Length: 100m	Flat cable, 6C, 12/7, white, 100 m/R Flat wires are covered by PVC isolation. Wire: braided copper 7x0.12mm, AWG 28 Wire's resistance: 200 Ohm/km Isolation resistance: 500 MChm Working temperatures: -30°C up to +70°C Length: 100m	Flat cable, 8C, 12/7, black, 100 m/R Flat wires are covered by PVC isolation. Wire: braided copper 7x0.12mm, AWG 28 Wire's resistance: 200 Ohm/km Isolation resistance: 500 MOhm Working temperatures: -30°C up to +70°C Length: 100m
#00823 Net Price: 25.90 USD Unit: roll 100m		
Flat cable, 8C, 12/7, white, 100 m/R Flat wires are covered by PVC isolation. Wire: braided copper 7x0.12mm, AWG 28 Wire's resistance: 200 Ohm/km Isolation resistance: 500 MOhm Working temperatures: -30°C up to +70°C Length: 100m		

Handset and extension cords



#01819

Net Price: 0.571 USD Unit: pcs



#00855

Net Price: 0.571 USD Unit: pcs



#01830

Net Price: 0.402 USD Unit: pcs

Handset cord, 15ft, black

Spiral connection cords are made of flat wire 7x0.12mm in PCV coat. Every copper wire is covered by PVC isolation. Wire's resistance is 200 Ohm/km, isolation resistance is 500 MOhm, range of working temperatures -30°C up to +70°C. High quality assurance and well-chosen materials make SP1 wires very popular among installers and manufacturers.

Handset cord, 15ft, white

Spiral connection cords are made of flat wire 7x0.12mm in PCV coat. Every copper wire is covered by PVC isolation. Wire's resistance is 200 Ohm/km, isolation resistance is 500 MOhm, range of working temperatures -30°C up to +70°C. High quality assurance and well-chosen materials make SP1 wires very popular among installers and manufacturers.

Handset cord, 7ft, black

Spiral connection cord SP1 (terminated with two 4p4c modular plugs). Spiral connection cords are made of flat wire 7x0,12mm in PCV coat. Every copper wire is covered by PVC isolation. Wire's resistance is 200 Ohm/km, isolation resistance is 500 MOhm, range of working temperatures -30°C up to +70°C. High quality assurance and well-chosen materials make SP1 wires very popular among installers and manufacturers.

#00851

Net Price: 0.402 USD Unit: pcs



#01817

Net Price: 0.922 USD Unit: pcs



#00854

Net Price: 0.988 USD Unit: pcs

Handset cord, 7ft, white

Spiral connection cord SP1 (terminated with two 4p4c modular plugs). Spiral connection cords are made of flat wire 7x0,12mm in PCV coat. Every copper wire is covered by PVC isolation. Wire's resistance is 200 Ohm/km, isolation resistance is 500 MOhm, range of working temperatures -30°C up to +70°C. High quality assurance and well-chosen materials make SP1 wires very popular among installers and manufacturers

Handset cord, tinsel, 12ft, black

Spiral tinseled cords are used for interconnecting moving parts (i.e. handsets) of telecommunication indoor devices (i.e. desktop phones). Cord is made from flat, 4-wires cable strenghtened with tetron braid. High quality manufacturing and durability (can stand 100 thousand inflexions) make SP1..S cords very popular among installers and manufacturers.

Handset cord, tinsel, 12ft, white

Spiral tinseled cords are used for interconnecting moving parts (i.e. handsets) of telecommunication indoor devices (i.e. desktop phones). Cord is made from flat, 4-wires cable strenghtened with tetron braid. High quality manufacturing and durability (can stand 100 thousand inflexions) make SP1..S cords very popular among installers and manufacturers.



#01815

Net Price: 0.746 USD Unit: pcs

Handset cord, tinsel, 7ft, black

LSA installation equipment

Spiral tinseled cords are used for interconnecting moving parts (i.e. handsets) of telecommunication indoor devices (i.e. desktop phones). Cord is made from flat, 4-wires cable strenghtened with tetron braid. High quality manufacturing and durability (can stand 100 thousand inflexions) make SP1..S cords very popular among installers and

manufacturers.



#01901

Net Price: 1.40 USD Unit: pcs

Statistical of the hands of the

#01884

Net Price: 1.40 USD Unit: pcs



#01900

Net Price: 1.40 USD Unit: pcs

10 pairs connection module, number 0-9, grey

LSA terminal blocks consist of two rows of contacts, one for the permanent plowing of the cable and the other for the crossing.

10 pairs connection module. Base: grey, Housing: grey

LSA terminal blocks consist of two rows of contacts, one for the permanent plowing of the cable and the other for the crossing.

Crimping tools: #01889 - Punch down tool, krone type terminal (Hanlong HT-314KR)

#02303 - (CT-314KR) Punch down tool, Krone type terminal #04284 - Punch down tool, 110/88 terminal (Hanlong

HT-364BR) #04283 - Punch down tool, 110/88+krone type terminal (Hanlong HT-344KR) #04795 - Punch down tool, krone type terminal

Chosen panel mounts and distribution boxes

#01896 - Distribution box, 30 pairs, indoor

#04914 - Panel mount 19" 1U

#04906 - Mounting frame for 10 pairs module, 41 ways,

10 pairs disconnect module, number 0-9, white 10 pairs connection/disconnection module. Enables testing each line separately and mounting lighting protectors.



#01873

Net Price: 1.40 USD Unit: pcs



Mounting frame 1x10 pairs module

#07816

Net Price: 0.472 USD Unit: pcs



#04753

Net Price: 1.54 USD Unit: pcs

10 pairs disconnection module. Base: grey, Housing: white

LSA terminal blocks consist of two rows of contacts, one for the permanent plowing of the cable and the other for the

Crimping tools:
#01889 - Punch down tool, krone type terminal (Hanlong HT-314KR)
#02303 - (CT-314KR) Punch down tool, Krone type terminal
#04284 - Punch down tool, 110/88 terminal (Hanlong HT-364BR)

#04283 - Punch down tool, 110/88+krone type terminal

(Hanlong HT-344KR) #04795 - Punch down tool, krone type terminal

Chosen panel mounts and distribution boxes:

#04914 - Panel mount 19" 1U #04906 - Mounting frame for 10 pairs module, 41 ways,

#01896 - Distribution box, 30 pairs, indoor



Net Price: 2.41 USD Unit: pcs



#04752

Net Price: 4.83 USD Unit: pcs



#04906

Net Price: 22.20 USD Unit: pcs

Mounting frame for 10 pairs module, 5 ways

Mounting frame for 10 pairs module, 10 ways

Mounting frame for 10 pairs module, 41 ways, dividable

Mounting frame for 10 pairs module, 3 ways

Allows seperating (by breaking off) any required number of mounting brackets

Material: stainless steel sheet, 0.75 mm thick Lacquer cladding: no



#04914

Net Price: 8.75 USD Unit: pcs



#07409

Net Price: 14.90 USD Unit: pcs



#03810

Net Price: 13.20 USD Unit: pcs

Panel mount 19" 1U, 60 ways

The panels of telephone connectors are made of stainless steel. They have appropriate profiling allowing for "push-fit" mounting of all types of telephone connectors.

Width: 483mm Height: 44mm Depth: 81mm

Weight: 0.30kg Material: stainless steel sheet, 0.75mm thick Lacquer cladding: no

Panel mount 19" 3U, 150 ways

The panels of telephone connectors are made of stainless steel. They have appropriate profiling allowing for "push-fit" mounting of all types of telephone connectors.

Width: 483mm Height: 133mm Depth:70mm

Weight: 0.60kg Material: stainless steel sheet, 1.00mm thick, plastic cable

holders

Panel mount 19" 3U, 150 ways, black

The panels of telephone connectors are made of stainless steel. They have appropriate profiling allowing for "push-fit" mounting of all types of telephone connectors.



#07447

Net Price: 6.71 USD Unit: pcs



Net Price: 3.24 USD Unit: pcs

#01896

#01897

Net Price:

10.50 USD

Unit: pcs




#07449

Net Price: 9.63 USD Unit: pcs

#04788

Net Price: 12.40 USD

Unit: pcs



Water and dust resistance: compliant with IP 54. The height of the box enables installation in the terminal box together with the lightning arrester magazine #01885

Water and dust resistance: compliant with IP 54 Dimensions: 19x11.5x9 cm

Distribution box, 30 pairs, indoor

Height: 55mm Width: 100mm Length: 150mm

Distribution box, 30 pairs, indoor

Height: 92mm Width: 175mm Length: 165mm



Distribution box, 30 pairs, outdoor

Water and dust resistance: compliant with IP 54



3/10

Distribution box, 50 pairs, indoor Height: 105mm Width: 200mm Length: 185mm



Distribution box, 50 pairs, outdoor

Water and dust resistance: compliant with IP 54 Dimensions: 195x195x85mm





Distribution box, 100 pairs, indoor

Height: 105mm Width: 200mm Length: 370mm



Water and dust resistance: compliant with IP 54 Outer dimensions: 190x370x110mm (whd)



#08345

Net Price: 44.90 USD Unit: pcs

Distribution box, 100 pairs, outdoor Distribution box, 300 pairs, indoor

#04789

Net Price:

10.70 USD

Unit: pcs

Dimensions: 420x450x76mm (width x height x depth)



#07483

Net Price: 52.00 USD Unit: pcs



#07484

Net Price: 163.00 USD Unit: pcs



#04775

Net Price: 0.347 USD Unit: pcs

Distribution box, 300 pairs, indoor, metal

Distribution box designed for wall mounting, enabling the installation of 30 10-way connectors

Material: steel, 0.9mm Closing method: key-locked Dimensions: 600x450x130mm (width x height x depth)



Distribution box, 1000 pairs, indoor, metal

Dimensions: 700x1000x130mm (width x height x depth)



2 pole test male connector



#04776

Net Price: 0.571 USD Unit: pcs



#04777

Net Price: 1 19 USD Unit: pcs



#04778

Net Price: 1 49 USD Unit: pcs

4 pole test male connector



#01892

Net Price: 0.856 USD Unit: pcs



#01893 Net Price: 1.36 USD Unit: pcs



#01885

Net Price: 2.09 USD Unit: pcs

Test cord, 2P with modular 6P2C, 2 m

For use with diconnection modules



Test cord, 4P with modular 6P4C, 2 m

For use with disconnect modules



10 pairs 3-pole surge arrester magazine

Test cable with alligator clip 4 pole, 1.5m

#01888

Net Price: 0.022 USD Unit: pcs



#01895

Net Price: 0.605 USD Unit: pcs



#04762

Net Price: 0.307 USD Unit: pcs

Disconnection male connector

Gas tube surge arrester, 3-pole, fail safe

3 Pole Gas Arrester protects telecommunication circuits against overvoltage which are usually caused by lightning Arresters are placed individually in special magazines, for each contact separately. Resistance grounding system should not exceed 4 ohms, which will provide the most effective protection when connected to the 3 pole gas

Size: 8x10mm

Size: 8X1Ummi Voltage: 230V Maximum impulse spark-over voltage: 800V (1KV/µs) Impulse discharge current: 10kA, 8/20µs; 10 times Impulse discharge current: 100A, 10/100µs; 300 times





#01890

Net Price: 0.241 USD Unit: pcs



Numbering kits 0-9

#01905

Net Price: 0.176 USD Unit: pcs



#01906

Net Price: 0.176 USD Unit: pcs

Label holder for mounting frame



Net Price:

0.732 USD Unit: pcs

Protection male connector, A type, LSA

#04781

Numbering kits 10-100

Telephone Accessories

Modular connectors, female



#00886

Net Price: 0.488 USD Unit: 100pcs

Modular female connector, 4P4C, top entry, flangless

Modular female connector PCB jack 4p4c (RJ-10).

Modular connectors, male



#00876

Net Price: 1.69 USD Unit: 100pcs



#00877

Net Price: 1.65 USD Unit: 100pcs



#00878

Net Price: 1.93 USD Unit: 100pcs

Modular male connector, 4P4C (RJ-10), 100/bag

Modular male connectors are used for terminating wires in phone or computer installations. The body of a male connector is made from polycarbon, contacts from gilded phosphor bronze (layer of gold 3u").

Connector, contacts: RJ-10, 4p4c Materials: policarbonate, gold-plated phosphor bronze Contacts plating: 3u* Au Cable type: flat, stranded Connector type: unshielded



Net Price: 2.41 USD Unit: 100pcs



Type, contacts: 6p2c

#04794

Net Price: 10.10 USD Unit: 100pcs



#04975

Net Price: 11.00 USD Unit: 100pcs

Modular male connector, 6P6C (RJ-12), 100/bag

Modular male connectors are used for terminating wires in phone or computer installations. The body of a male connector is made from polycarbon, contacts from gilded phosphor bronze (layer of gold 3um).

Type, contacts: RJ-12, 6p6c Materials: policarbonate, gold-plated phosphor bronze Contacts plating: 3u" Au Cable type: flat, stranded Connector type: unshielded

Modular male connector, 8P8C (RJ-45), round, solid, shielded, cat. 5e, throughconnector (EZ type)

Modular male connector, 6P2C, 100/bag

phosphor bronze (layer of gold 3u").

Modular male connectors are used for terminating wires in

phone or computer installations. The body of a male connector is made from polycarbon, contacts from gilded

Materials: policarbonate, gold-plated phosphor bronze Contacts plating: 3u" Au Cable type: flat, stranded Connector type: unshielded

Modular male connectors are used for terminating wires in phone or computer installations. Shielded type - used for environments with high level of electromagnetic disturbances. The body of a male connector is made from polycarbon, contacts from gilded phosphor bronze (3um layer of gold).

Type, contacts: RJ-45, 8p8c

Type, contacts: K3-45, opec Category: 5e Materials: policarbonate, gold-plated phosphor bronze Contacts plating: 3u" Au Cable type: round, solid Connector type: shielded, EZ type

Modular male connector, 8P8C (RJ-45), round, solid, shielded, cat. 6A, throughconnector (EZ type)

Modular male connector, 6P4C (RJ-11), 100/bag

Modular male connectors are used for terminating wires in

phone or computer installations. The body of a male connector is made from polycarbon, contacts from gilded

ւ yye, ստագայ, «Ա-11, bp4c Materials: policarbonate, gold-plated phosphor bronze Contacts plating: 3u" Au Cable type: flat, stranded Connector type: unshielded

phosphor bronze (layer of gold 3um).

Type, contacts: RJ-11, 6p4c

Modular male connectors are used for terminating wires in phone or computer installations. Shielded type - used for environments with high level of electromagnetic disturbances. The body of a male connector is made from polycarbon, contacts from gilded phosphor bronze (3um layer of gold).

Type, contacts: RJ-45, 8p8c Contacts plating: 3u" Au Cable type: round, solid Connector type: shielded, EZ type

#04196

Net Price: 5.12 USD Unit: 100pcs



#04195

Net Price: 6.44 USD Unit: 100pcs



#04197

Net Price: 7.02 USD Unit: 100pcs

Modular male connector, 8P8C (RJ-45), round. solid, cat. 5e, throughconnector (EZ type)

Type, contacts: RJ-45, 8p8c Category: 5e Materials: policarbonate, gold-plated phosphor bronze Contacts plating: 3u" Au Cable type: round, solid Connector type: unshielded, EZ type

Modular male connector, 8P8C (RJ-45), round. solid, cat. 6, throughconnector (EZ type)

Modular male connectors are used for terminating wires in phone or computer installations. There also exists a shielded type of male connectors used for environments with high level of electromagnetic disturbances. The body of a male connector is made from polycarbon, contacts from gilded phosphor bronze (3u" layer of gold).

Type, contacts: RJ-45, 8p8c Category: 6 Materials: policarbonate, gold-plated phosphor bronze Contacts plating: 3u" Au Cable type: round, solid Connector type: unshielded, EZ type

Modular male connector, 8P8C (RJ-45), round. solid, cat. 6A, throughconnector (EZ type)

Modular male connectors are used for terminating wires in phone or computer installations. There also exists a shielded type of male connectors used for environments with high level of electromagnetic disturbances. The body of a male connector is made from polycarbon, contacts from gilded phosphor bronze (3u" layer of gold).

Type, contacts: RJ-45, 8p8c Category: 6a Materials: policarbonate, gold-plated phosphor bronze Contacts plating: 3u" Au
Cable type: round, solid
Connector type: unshielded, EZ type



#04955

Net Price: .02 USD Unit: pcs



Modular male connector, 8P8C (RJ-45), cat. 6, shielded, toolless

Modular male connectors are used for terminating wires in

Type, contacts, 10-0, 5p-1
Category: 6
Materials: policarbonate, gold-plated phosphor bronze
Contacts plating: 3u" Au
Cable type: round, solid and stranded
Connector type: shielded, toolless

Modular male connector, 8P8C (RJ-45), flat,

of electromagnetic disturbances. The body of a male connector is made from polycarbon, contacts from gilded

Category: 5e Materials: policarbonate, gold-plated phosphor bronze Contacts plating: 3u" Au Cable type: flat, solid

phosphor bronze (3u" layer of gold).

Type, contacts: RJ-45, 8p8c

Connector type: unshielded

Modular male connectors are used for terminating wires in

phone or computer installations. There also exists a shielded type of male connectors used for environments with high level

gilded phosphor bronze (3um layer of gold).

Type, contacts: RJ-45, 8p8c

phone or computer installations. Shielded - for environments

with high level of electromagnetic disturbances. The body of a male connector is made from polycarbon, contacts from

#03834

Net Price: .41 USD Unit: pcs



toolless

Modular male connector, 8P8C (RJ-45), cat. 6,

Modular male connectors are used for terminating wires in

of electromagnetic disturbances. The body of a male

connector is made from polycarbon, contacts from gilded phosphor bronze (3um layer of gold).

Materials: policarbonate, gold-plated phosphor bronze

Modular male connector, 8P8C (RJ-45), flat,

Modular male connectors are used for terminating wires in

of electromagnetic disturbances. The body of a male connector is made from polycarbon, contacts from gilded

Category: 5e Materials: policarbonate, gold-plated phosphor bronze Contacts plating: 3u" Au Cable type: flat, stranded

phone or computer installations. There also exists a shielded type of male connectors used for environments with high level

phone or computer installations. There also exists a shielded

type of male connectors used for environments with high level

#04956

Net Price: 1.10 USD Unit: pcs

Modular male connector, 8P8C (RJ-45), cat. 5e, toolless

Modular male connectors are used for terminating wires in phone or computer installations. There also exists a shielded type of male connectors used for environments with high level of electromagnetic disturbances. The body of a male connector is made from polycarbon, contacts from gilded phosphor bronze (3u" layer of gold).

Type, contacts: RJ-45, 8p8c Category: 5e Materials: policarbonate, gold-plated phosphor bronze Contacts plating: 3u" Au Cable type: round, solid and stranded

Connector type: unshielded, toolless



#03835

Net Price: 3.05 USD Unit: pcs



solid, cat. 5e

#00882

Net Price: 3.84 USD Unit: 100pcs



stranded, cat. 5e

Type, contacts: RJ-45, 8p8c Category: 6

Contacts plating: 3u" Au
Cable type: round, solid and stranded
Connector type: unshielded, toolless

#00880

Net Price: 3.95 USD Unit: 100pcs

Modular male connector, 8P8C (RJ-45), cat. 6A, shielded, toolless

Modular male connectors are used for terminating wires in phone or computer installations. Shielded - for environments with high level of electromagnetic disturbances. The body of a male connector is made from polycarbon, contacts from gilded phosphor bronze (3um layer of gold).

Type, contacts: RJ-45, 8p8c Category: 6a Materials: policarbonate, gold-plated phosphor bronze Contacts plating: 3u" Au Cable type: round, solid and stranded Connector type: shielded, toolless

Modular male connector, 8P8C (RJ-45), round,

Modular male connectors are used for terminating wires in

connector is made from polycarbon, contacts from gilded

Type, contacts: RJ-45, 8p8c Category: 5e Materials: policarbonate, gold-plated phosphor bronze

phosphor bronze (3u" layer of gold).

phone or computer installations. There also exists a shielded

type of male connectors used for environments with high level of electromagnetic disturbances. The body of a male



solid, cat, 5e

#00883

Net Price: 4.06 USD Unit: 100pcs



#00884

Net Price: 0.101 USD Unit: pcs



Modular male connector, 8P8C (RJ-45), round, solid, cat. 5e, shielded

Modular male connectors are used for terminating wires in phone or computer installations. Shielded type - used for environments with high level of electromagnetic disturbances. The body of a male connector is made from polycarbon contacts from gilded phosphor bronze (3um layer of gold).

Type, contacts: RJ-45, 8p8c

Category: 5e Materials: policarbonate, gold-plated phosphor bronze Contacts plating: 3u" Au Cable type: round, solid

Connector type: shielded



phosphor bronze (3u" layer of gold).

Type, contacts: RJ-45, 8p8c

Connector type: unshielded

#04912

Net Price: 0.099 USD Unit: pcs

Modular male connector, 8P8C (RJ-45), round, solid, cat, 6

Modular male connectors are used for terminating wires in phone or computer installations. There also exists a shielded type of male connectors used for environments with high level of electromagnetic disturbances. The body of a male connector is made from polycarbon, contacts from gilded phosphor bronze (3u" layer of gold).

Type, contacts: RJ-45, 8p8c Category: 6 Materials: policarbonate, gold-plated phosphor bronze Contacts plating: 3u" Au Cable type: round, solid Connector type: unshielded

Contacts plating: 3u" Au Cable type: round, solid Connector type: unshielded

#04913

Net Price: 0.143 USD Unit: pcs



#07165

Net Price: 0.224 USD Unit: pcs



#00881

Net Price: Unit: 100pcs

Modular male connector, 8P8C (RJ-45), round, solid, cat. 6, shielded

Modular male connectors are used for terminating wires in phone or computer installations. Shielded type of - for environments with high level of electromagnetic disturbances. The body of a male connector is made from polycarbon contacts from gilded phosphor bronze (3um layer of gold).

Type, contacts: RJ-45, 8p8c Category: 6 Materials: policarbonate, gold-plated phosphor bronze Contacts plating: 3u" Au Cable type: round, solid Connector type: shielded

Modular male connector, 8P8C (RJ-45), round, solid, cat. 6A, shielded

Modular male connectors are used for terminating wires in phone or computer installations. Shielded type - used for environments with high level of electromagnetic disturbances. The body of a male connector is made from polycarbon contacts from gilded phosphor bronze (3um layer of gold)

Type, contacts: RJ-45, 8p8c Category: 6A
Materials: policarbonate, gold-plated phosphor bronze Contacts plating: 3u" Au Cable type: round, solid Connector type: shielded Maximum core diameter: 1.02mm Operating temperature: -40° ÷ 125°C

Modular male connector, 8P8C (RJ-45), round, stranded, cat. 5e

Modular male connectors are used for terminating wires in phone or computer installations. There also exists a shielded type of male connectors used for environments with high level of electromagnetic disturbances. The body of a male connector is made from polycarbon, contacts from gilded phosphor bronze (3u" layer of gold).

Type, contacts: RJ-45, 8p8c

Type, contacts, 154-5, opoc Category: Se Materials: policarbonate, gold-plated phosphor bronze Contacts plating: 3u" Au Cable type: round, stranded Connector type: unshielded



#00897

Net Price: 0.112 USD Unit: pcs



#04919

Net Price: 0.037 USD Unit: pcs



#07408

Net Price: 0.132 USD Unit: pcs

Modular male connector, 8P8C (RJ-45), round, stranded, cat. 5e, shielded

Modular male connectors are used for terminating wires in phone or computer installations. Shielded type - used for environments with high level of electromagnetic disturbances. The body of a male connector is made from polycarbon, contacts from gilded phosphor bronze (3um layer of gold).

Type, contacts: RJ-45, 8p8c Type, contacts, Kd-4s, opec Category: Se Materials: policarbonate, gold-plated phosphor bronze Contacts plating: 3u" Au Cable type: round, stranded Connector type: shielded



Modular male connectors are used for terminating wires in phone or computer installations. There also exists a shielded type of male connectors used for environments with high level of electromagnetic disturbances. The body of a male connector is made from polycarbon, contacts from gilded phosphor bronze (6um layer of gold).

Type, contacts: RJ-45, 8p8c Category: 5e Materials: policarbonate, gold-plated phosphor bronze

Contacts plating: 3u" Au Cable type: round, stranded

Connector type: unshielded, short-body



Modular male connector, 8P8C (RJ-45), round, stranded, cat. 6, shielded

Modular male connectors are used for terminating wires in phone or computer installations. There also exists a shielded type of male connectors used for environments with high level of electromagnetic disturbances. The body of a male connector is made from polycarbon, contacts from gilded phosphor bronze (3um layer of gold).

Type, contacts: RJ-45, 8p8c Category: 6

Materials: policarbonate, gold-plated phosphor bronze

Contacts plating: 3u" Au Cable type: round, stranded Connector type: shielded



#04902

Net Price: 0.121 USD Unit: pcs



#07166

Net Price: 0.229 USD Unit: pcs



#07184

Net Price: 0.263 USD

Modular male connector, 8P8C (RJ-45), round, stranded, cat. 6, w/insert bar

Modular male connectors are used for terminating wires in phone or computer installations. There also exists a shielded type of male connectors used for environments with high level of electromagnetic disturbances. The body of a male connector is made from polycarbon, contacts from gilded phosphor bronze (3u" layer of gold).

Type, contacts: RJ-45, 8p8c Category: 6 Materials: policarbonate, gold-plated phosphor bronze Contacts plating: 3u" Au Cable type: round, stranded Connector type: unshielded

Modular male connector, 8P8C (RJ-45), round, stranded, cat. 6A, shielded

Modular male connectors are used for terminating wires in phone or computer installations. Shielded type - used for environments with high level of electromagnetic disturbances. The body of a male connector is made from polycarbor contacts from gilded phosphor bronze (3um layer of gold).

Type, contacts: RJ-45, 8p8c

Type, contacts: N3-45, opec Category: 6A Materials: policarbonate, gold-plated phosphor bronze Contacts plating: 3u" Au Cable type: round, stranded

Connector type: shielded



Modular male connector, 8P8C (RJ-45), round cat. 8, shielded

High quality plugs designed for cat. 8 applications. New 3 pongs contacts are suitable for both solid and stranded wires.

Type, contacts: RJ-45, 8p8c Category: 8

Materials: policarbonate, gold-plated phosphor bronze Contacts plating: 3u" Au

Cable type: round, solid and stranded Connector type: shielded Maximum core diameter: 1.45mm Operating temperature: -40° + 125°C Outer cable OD max: 8mm



#00895

Net Price: 0.057 USD Unit: pcs



#00896

Net Price: 0.057 USD Unit: pcs



#04796

Net Price: 0.105 USD Unit: pcs

Modular male connector, 10P10C (RJ-50), round,

The body of a male connector is made from polycarbon contacts from gilded phosphor bronze (3um layer of gold).

Type, contacts; RJ-50, 10p10c Category: n/a
Materials: policarbonate, gold-plated phosphor bronze Contacts plating: 3u" Au
Cable type: round, solid
Connector type: unshielded

Modular male connector, 10P10C (RJ-50), round,

The body of a male connector is made from polycarbon contacts from gilded phosphor bronze (3um layer of gold).

Type, contacts: RJ-50, 10p10c Type, contacts: RJ-50, T0pT0c Category: n/a Materials: policarbonate, gold-plated phosphor bronze Contacts plating: 3u" Au Cable type: round, stranded Connector type: unshielded

Modular male connector, 10P10C (RJ-50), round, stranded, shielded

Modular male connectors are used for terminating wires in phone or computer installations. There also exists a shielded type of male connectors used for environments with high level of electromagnetic disturbances. The body of a male connector is made from polycarbon, contacts from gilded phosphor bronze (6um layer of gold).

Type, contacts: RJ-50, 10p10c Category: n/a Materials: policarbonate, gold-plated phosphor bronze Contacts plating: 3u" Au
Cable type: round, stranded
Connector type: shielded



#04305

Net Price 0.244 USD Unit: pcs



#00494

Net Price 0.022 USD Unit: pcs



#00495

Net Price: 0.022 USD Unit: pcs

Swivel male connector WMP 2, anti-torsion, modular



#00496

Net Price: 0.022 USD Unit: pcs



#00425 Net Price: 0.022 USD Unit: pcs



#00497

Net Price: 0.022 USD Unit: pcs





Cable boot w/ear, o.d. 6.0 mm, grey

Cable boot w/ear, o.d. 6.0 mm, black

Cable boot w/ear, o.d. 6.0 mm, red

Cable boot w/ear, o.d. 6.0 mm, blue





#03751 Net Price: 0.022 USD Unit: pcs



Cable boot w/ear, o.d. 6.0 mm, yellow

#00498 Net Price: 0.022 USD Unit: pcs



Cable boot w/ear, o.d. 8.0 mm, grey

#07185 Net Price: 0.022 USD Unit: pcs

Cable boot w/ear, o.d. 6.0 mm, white



#05124 Net Price: 0.022 USD Unit: pcs



#05125 Net Price: 0.022 USD Unit: pcs



#05126 Net Price: 0.022 USD Unit: pcs

Cable boot w/inserts, black



#05127 Net Price: 0.022 USD Unit: pcs



#05128 Net Price: 0.022 USD Unit: pcs



#05130 Net Price: 0.022 USD Unit: pcs

Cable boot w/inserts, grey



#05129 Net Price: 0.022 USD Unit: pcs

Cable boot w/inserts, red

Cable boot w/inserts, blue





Cable boot w/inserts, yellow



#00873 Net Price: 6.34 USD Unit: pcs



Phone equipment, polish std.

UT-7 device amplifies the phones' ring signal and additionally includes a blinking light, which switches on when the phone is ringing. There is an option of choosing only the blinking light function which is a perfect solution for deaf people. Works with any analogue phone line.



#00816 Net Price: 0.478 USD Unit: pcs



#01838 Net Price: 0.500 USD Unit: pcs



Connector, polish male

#00874 Net Price: 0.150 USD Unit: pcs

Adaptor, polish male to 2 american female



Coupler, R1-4, 1F/1F 6p4c

#00813



Coupler, R1-6, 1F/1F 6p6c

Wall plate, polish female & american female

#00814 Net Price: 0.307 USD Unit: pcs



#00815 Net Price: 0.351 USD Unit: pcs

Coupler, R1-8, 1F/1F 8p8c

Coupler with two 8p8c sockets for telephone installations use.

Couplers meant for computer networks: #06492- Inline coupler, cat 5e, shielded #08317- Inline coupler, cat 5e, shielded, mini #04920- Cat 5e Coupler, UTP



Telephone Accessories



3 way coupler, 4C, white

#00842 Net Price: 0.395 USD Unit: pcs

#00850



3 way coupler, 6C, white

Net Price: 0.483 USD Unit: pcs

#00843

#00845

Net Price:



3 way coupler, 8C, white



Net Price: 1.43 USD Unit: pcs



0.141 USD Unit: pcs



Net Price: 0.461 USD Unit: pcs

#00846

#00844

Net Price:

Unit: pcs

0.461 USD

5 way adaptor, 4C, white

#00847

Duplex adaptor, 4C, white



Net Price: 0.549 USD Unit: pcs Duplex adaptor, 6C, white



Duplex adaptor, 8C, white

Surface-mount boxes



#04923 Net Price: 0.351 USD Unit: pcs



#04927 Net Price: 0.417 USD Unit: pcs



#04925 Net Price: 0.505 USD Unit: pcs

Surface box, 6P4C, economic. white

#01849 Net Price: 1 18 USD Unit: pcs



#04924 Net Price: 0.439 USD Unit: pcs



#04921

Net Price: 0.527 USD Unit: pcs

Wall box, 2x6P4C,ABS,top entry,white



Net Price: 0.593 USD Unit: pcs



Surface box, 6P6C, economic, white

Surface box, 6P4C, standard, white



Surface box, 6P6C, standard, white

Surface dual box, 2x6P4C, economic, white



Surface box, 8P8C, standard, white

Wall plate boxes



#01850

Net Price:

1.20 USD Unit: pcs



Other phone accessories



#01847 Net Price: Unit: 100pcs

#01846 Net Price: Unit: 100pcs



#04905


Net Price: Unit: 100pcs

UR connector, 100pcs/bag

UR connectors enable connecting wires without the need of isolation stripping. They are filled with gel, which protects wires from corrosion.

UR connectors should be used for wires with external coat up to 1.67mm in diameter and 0.4-0.9 wire diameter. Made of transparent polycarbonate with a red clamp

Purpose: connecting three wires Maximum diameter of the external coat: 1.67mm Core diameter: 0.4-0.9mm Dimensions: 19x12x8.5mm (6mm after tightening) Filling: hydrophobic gel, protecting against corrosion Packaging: cardboard, 61x63x57mm



UY connectors enable connecting wires without the need of isolation stripping. They are filled with gel, which protects wires from corrosion.

UY connectors should be used for wires with external coat up to 1.52mm in diameter and 0.4-0.7 wire diameter. Made of transparent polycarbonate with a yellow clamp.

Purpose: connecting two wires Maximum diameter of the external coat: 1.52mm Core diameter: 0.4-0.7mm Dimensions: 12x8.5x8mm (6mm after tightening) Filling: hydrophobic gel, protecting against corrosion Packaging: cardboard, 55x55x55mm

UY2 connector, 100pcs/bag

UY2 connectors enable connecting wires without the need of isolation stripping. They are filled with gel, which protects wires from corrosion.

UY2 connectors should be used for wires with external coat up to 1.52mm in diameter and 0.4-0.9 wire diameter. Made of transparent polycarbonate with an orange clamp.

Purpose: connecting two wires Maximum diameter of the external coat:1.52mm Core diameter:0.4-0.9mm Dimensions:15x10x8mm (6mm after tightening) Filling:hydrophobic gel, protecting against corrosion Temperature range: -30°C ÷ +70°C Packaging: cardboard, 55x55x55mm

Index

Flat cables	'
Handset and extension cords	2
LSA installation equipment	2
Modular connectors, female	5
Modular connectors, male	5
Other devices	
Phone equipment, polish std.	8
Splitters, couplers	8
Surface-mount boxes	9
Wall plate boxes	
Other whome accessive	(





