Flat cables				
#0 Net I 9.29 Unit: roll	JSD	#00819 Net Price: 9.29 USD Unit: roll 100m	#04917 Net Price: 7.18 USD Unit: roll 100m	
Flat cable, 2C, 12/7, black, 100 m/R Flat wires are covered by PVC isolation. Wire: braided copper 7x0.12mm, AWG 28 Wire's resistance: 200 Ohm/km Isolation resistance: 500 MOhm Working temperatures: -30°C up to +70°C Length: 100m	Flat cable, 2C, 12/7, white, 100 m/R Flat wires are covered by PVC isolation. Wire: braided copper 7x0.12mm, AWG 28 Wire's resistance: 200 Ohm/km Isolation resistance: 500 MOhm Working temperatures: -30°C up to +70°C Length: 100m	t	Flat cable, 4C, 10/6, black, 100 m/R CCS Wire: CCS 6x0.1mm Length: 100m	
#0 Net I 7.18 Unit: roll	JSD ======	#01808 Net Price: 12.90 USD Unit: roll 100m	#04808 Net Price: 38.60 USD Unit: roll 300m	
Flat cable, 4C, 10/6, white, 100 m/R CCS Wire: CCS 6x0.1mm Length: 100m	Flat cable, 4C, 12/7, black, 100 m/R Flat wires are covered by PVC isolation. Wire: braided copper 7x0.12mm, AWG 28 Wire's resistance: 200 Ohm/km Isolation resistance: 500 MOhm Working temperatures: -30°C up to +70°C Length: 100m	R	Flat cable, 4C, 12/7, black, 300 m/R Flat wires are covered by PVC isolation. Wire: braided copper 7x0.12mm, AWG 28 Wire's resistance: 200 Ohm/km Isolation resistance: 500 MOhm Working temperatures: -30°C up to +70°C Length: 300m	
Net I 12.90 Unit: roll	JSD	#00820 Net Price: 12.90 USD Unit: roll 100m	#04807 Net Price: 38.60 USD Unit: roll 300m	
Flat cable, 4C, 12/7, grey, 100 m/R Flat wires are covered by PVC isolation. Wire: braided copper 7x0.12mm, AWG 28 Wire's resistance: 200 Ohm/km Isolation resistance: 500 MOhm Working temperatures: -30°C up to +70°C Length: 100m	Flat cable, 4C, 12/7, white, 100 m/R Flat wires are covered by PVC isolation. Wire: braided copper 7x0.12mm, AWG 28 Wire's resistance: 200 0hm/km Isolation resistance: 500 MOhm Working temperatures: -30°C up to +70°C Length: 100m	t	Flat cable, 4C, 12/7, white, 300 m/R Flat wires are covered by PVC isolation. Wire: braided copper 7x0.12mm, AWG 28 Wire's resistance: 200 Ohm/km Isolation resistance: 500 MOhm Working temperatures: -30°C up to +70°C Length: 300m	
#0 Net I 20.30 Unit: roll	JSD	#00822 Net Price: 20.30 USD Unit: roll 100m	#01812 Net Price: 25.90 USD Unit: roll 100m	
Flat cable, 6C, 12/7, black, 100 m/R Flat wires are covered by PVC isolation. Wire: braided copper 7x0.12mm, AWG 28 Wire's resistance: 200 Ohm/km Isolation resistance: 500 MOhm Working temperatures: -30°C up to +70°C Length: 100m	Flat cable, 6C, 12/7, white, 100 m/R Flat wires are covered by PVC isolation. Wire: braided copper 7x0.12mm, AWG 28 Wire's resistance: 200 Ohm/km Isolation resistance: 500 MOhm Working temperatures: -30°C up to +70°C Length: 100m	t	Flat cable, 8C, 12/7, black, 100 m/R Flat wires are covered by PVC isolation. Wire: braided copper 7x0.12mm, AWG 28 Wire's resistance: 200 Ohm/km Isolation resistance: 500 MOhm Working temperatures: -30°C up to +70°C Length: 100m	
#0 Net I 25.90 Unit: roll	JSD			
Flat cable, 8C, 12/7, white, 100 m/R Flat wires are covered by PVC isolation. Wire: braided copper 7x0.12mm, AWG 28 Wire's resistance: 200 Ohm/km Isolation resistance: 500 MOhm Working temperatures: -30°C up to +70°C Length: 100m				

Handset and extension cords



#01819

Net Price: 0.571 USD Unit: pcs



#00855

Net Price: 0.571 USD Unit: pcs



#01830

Net Price: 0.402 USD Unit: pcs

Handset cord, 15ft, black

Spiral connection cords are made of flat wire 7x0.12mm in PCV coat. Every copper wire is covered by PVC isolation. Wire's resistance is 200 Ohm/km, isolation resistance is 500 MOhm, range of working temperatures -30°C up to +70°C. High quality assurance and well-chosen materials make SP1 wires very popular among installers and manufacturers.

Handset cord, 15ft, white

Spiral connection cords are made of flat wire 7x0.12mm in PCV coat. Every copper wire is covered by PVC isolation. Wire's resistance is 200 Ohm/km, isolation resistance is 500 MOhm, range of working temperatures -30°C up to +70°C. High quality assurance and well-chosen materials make SP1 wires very popular among installers and manufacturers.

Handset cord, 7ft, black

Spiral connection cord SP1 (terminated with two 4p4c modular plugs). Spiral connection cords are made of flat wire 7x0,12mm in PCV coat. Every copper wire is covered by PVC isolation. Wire's resistance is 200 Ohm/km, isolation resistance is 500 MOhm, range of working temperatures -30°C up to +70°C. High quality assurance and well-chosen materials make SP1 wires very popular among installers and manufacturers.



#00851

Net Price: 0.402 USD Unit: pcs



#01817

Net Price: 0.922 USD Unit: pcs



#00854

Net Price: 0.988 USD Unit: pcs

Handset cord, 7ft, white

Spiral connection cord SP1 (terminated with two 4p4c modular plugs). Spiral connection cords are made of flat wire 7x0,12mm in PCV coat. Every copper wire is covered by PVC isolation. Wire's resistance is 200 Ohm/km, isolation resistance is 500 MOhm, range of working temperatures -30°C up to +70°C. High quality assurance and well-chosen materials make SP1 wires very popular among installers and manufacturers

Handset cord, tinsel, 12ft, black

Spiral tinseled cords are used for interconnecting moving parts (i.e. handsets) of telecommunication indoor devices (i.e. desktop phones). Cord is made from flat, 4-wires cable strenghtened with tetron braid. High quality manufacturing and durability (can stand 100 thousand inflexions) make SP1..S cords very popular among installers and manufacturers.

Handset cord, tinsel, 12ft, white

Spiral tinseled cords are used for interconnecting moving parts (i.e. handsets) of telecommunication indoor devices (i.e. desktop phones). Cord is made from flat, 4-wires cable strenghtened with tetron braid. High quality manufacturing and durability (can stand 100 thousand inflexions) make SP1..S cords very popular among installers and manufacturers.



#01815

Net Price:

Handset cord, tinsel, 7ft, black

0.746 USD Unit: pcs

Spiral tinseled cords are used for interconnecting moving parts (i.e. handsets) of telecommunication indoor devices (i.e. desktop phones). Cord is made from flat, 4-wires cable strenghtened with tetron braid. High quality manufacturing and durability (can stand 100 thousand inflexions) make SP1..S cords very popular among installers and manufacturers.

LSA installation equipment



#01901

Net Price: 1.40 USD Unit: pcs

Statistical of this highlight and the statistical of the statistical o

#01884

Net Price: 1.40 USD Unit: pcs



#01900

Net Price: 1.40 USD Unit: pcs

10 pairs connection module, number 0-9, grey

LSA terminal blocks consist of two rows of contacts, one for the permanent plowing of the cable and the other for the crossing.

10 pairs connection module. Base: grey, Housing: grey

LSA terminal blocks consist of two rows of contacts, one for the permanent plowing of the cable and the other for the crossing.

Crimping tools: #01889 - Punch down tool, krone type terminal (Hanlong

HT-314KR)

#02303 - (CT-314KR) Punch down tool, Krone type terminal #04284 - Punch down tool, 110/88 terminal (Hanlong HT-364BR) #04283 - Punch down tool, 110/88+krone type terminal

(Hanlong HT-344KR) #04795 - Punch down tool, krone type terminal

Chosen panel mounts and distribution boxes:

#04914 - Panel mount 19" 1U

#04906 - Mounting frame for 10 pairs module, 41 ways, dividable

10 pairs disconnect module, number 0-9, white

10 pairs connection/disconnection module. Enables testing each line separately and mounting lighting protectors.



#01873 Net Price: 1.40 USD Unit: pcs



Net Price: 0.472 USD Unit: pcs

#07816



#04753

Net Price: 1.54 USD Unit: pcs

10 pairs disconnection module. Base: grey, Housing: white

LSA terminal blocks consist of two rows of contacts, one for the permanent plowing of the cable and the other for the

Crimping tools: #01889 - Punch down tool, krone type terminal (Hanlong HT-314KR)


#02303 - (CT-314KR) Punch down tool, Krone type terminal #04284 - Punch down tool, 110/88 terminal (Hanlong HT-364BR)

#04283 - Punch down tool, 110/88+krone type terminal

(Hanlong HT-344KR) #04795 - Punch down tool, krone type terminal

Chosen panel mounts and distribution boxes:

#04914 - Panel mount 19" 1U #04906 - Mounting frame for 10 pairs module, 41 ways, dividable



Mounting frame for 10 pairs module, 3 ways



#01902

Net Price: 2.41 USD Unit: pcs



#04752

Net Price: 4.83 USD Unit: pcs



#04906

Net Price: 22.20 USD Unit: pcs

Mounting frame for 10 pairs module, 5 ways

Mounting frame for 10 pairs module, 10 ways

Mounting frame for 10 pairs module, 41 ways,

Allows seperating (by breaking off) any required number of mounting brackets.

Material: stainless steel sheet, 0.75 mm thick Lacquer cladding: no



#04914

Net Price: 8.75 USD Unit: pcs



#07409

Net Price: 14.90 USD Unit: pcs



#03810

Net Price: 13.20 USD Unit: pcs

Panel mount 19" 1U, 60 ways

The panels of telephone connectors are made of stainless steel. They have appropriate profiling allowing for "push-fit" mounting of all types of telephone connectors.

Width: 483mm Height: 44mm Depth: 81mm

Weight: 0.30kg Material: stainless steel sheet, 0.75mm thick

Lacquer cladding: no



Panel mount 19" 3U, 150 ways

The panels of telephone connectors are made of stainless steel. They have appropriate profiling allowing for "push-fit" mounting of all types of telephone connectors.

Width: 483mm Height: 133mm Depth:70mm Weight: 0.60kg

Material: stainless steel sheet, 1.00mm thick, plastic cable

Panel mount 19" 3U, 150 ways, black

The panels of telephone connectors are made of stainless steel. They have appropriate profiling allowing for "push-fit" mounting of all types of telephone connectors.



#07447 Net Price:

6.71 USD Unit: pcs




Distribution box, 30 pairs, indoor Height: 55mm Width: 100mm Length: 150mm

#01896 Net Price:

3.07 USD Unit: pcs

#07449

Net Price: 8.49 USD Unit: pcs



Water and dust resistance: compliant with IP 54. The height of the box enables installation in the terminal box together with the lightning arrester magazine #01885

Water and dust resistance: compliant with IP 54 Dimensions: 19x11.5x9 cm

#04787

Net Price: 9.20 USD Unit: pcs



#01897

Net Price: 10.50 USD Unit: pcs




Height: 92mm Width: 175mm

Length: 165mm

#04788

Net Price: 12.40 USD Unit: pcs



Water and dust resistance: compliant with IP 54



Distribution box, 50 pairs, indoor

Height: 105mm Width: 200mm Length: 185mm



Distribution box, 50 pairs, outdoor

Distribution box, 30 pairs, indoor

Water and dust resistance: compliant with IP 54 Dimensions: 195x195x85mm

3/10



Distribution box, 100 pairs, indoor

Height: 105mm Width: 200mm Length: 370mm



Distribution box, 100 pairs, outdoor

Water and dust resistance: compliant with IP 54 Outer dimensions: 190x370x110mm (whd)



#08345

Net Price: 44.90 USD Unit: pcs

Distribution box, 300 pairs, indoor

Dimensions: 420x450x76mm (width x height x depth)

Test cable with alligator clip 4 pole, 1.5m



#07483

#01898 Net Price:

15.40 USD

Unit: pcs

Net Price: 52.00 USD Unit: pcs



#07484

#04789

Net Price:

8.54 USD

Unit: pcs

Net Price: 163.00 USD Unit: pcs



#04775

Net Price: 0.347 USD Unit: pcs

Distribution box, 300 pairs, indoor, metal

Distribution box designed for wall mounting, enabling the installation of 30 10-way connectors

Material: steel, 0.9mm Closing method: key-locked Dimensions: 600x450x130mm (width x height x depth)



Distribution box, 1000 pairs, indoor, metal

Dimensions: 700x1000x130mm (width x height x depth)



2 pole test male connector



#04776

Net Price: 0.571 USD Unit: pcs



#04777

Net Price: 1 19 USD Unit: pcs



#04778

Net Price: 1 49 USD Unit: pcs

4 pole test male connector



#01892

Net Price: 0.856 USD Unit: pcs



#01893 Net Price: 1.36 USD Unit: pcs



#01885

Net Price: 2.09 USD Unit: pcs

Test cord, 2P with modular 6P2C, 2 m


For use with diconnection modules



Test cord, 4P with modular 6P4C, 2 m

Test cable with alligator clip 2 pole, 1.5m

For use with disconnect modules



#04762 Net Price: 0.307 USD Unit: pcs



#01888

Net Price: 0.022 USD Unit: pcs



#01895

Net Price: 0.605 USD Unit: pcs



Hinged label holder for 10 pairs



Disconnection male connector

Gas tube surge arrester, 3-pole, fail safe

3 Pole Gas Arrester protects telecommunication circuits against overvoltage which are usually caused by lightning Arresters are placed individually in special magazines, for each contact separately. Resistance grounding system should not exceed 4 ohms, which will provide the most effective protection when connected to the 3 pole gas

Size: 8x10mm

Size: 8X IUmrii Voltage: 230V Maximum impulse spark-over voltage: 800V (1KV/µs) Impulse discharge current: 10kA, 8/20µs; 10 times Impulse discharge current: 100A, 10/100µs; 300 times



Net Price: 0.176 USD Unit: pcs



#01906

Net Price: 0.176 USD Unit: pcs



#01890

Net Price: 0.241 USD Unit: pcs



Numbering kits 0-9

Numbering kits 10-100

Label holder for mounting frame

Modular connectors, male



#00876

Net Price: 1.69 USD Unit: 100pcs



#00877

Net Price: 1.65 USD Unit: 100pcs



#00878

Net Price: 1.93 USD Unit: 100pcs

Modular male connector, 4P4C (RJ-10), 100/bag

Modular male connectors are used for terminating wires in phone or computer installations. The body of a male connector is made from polycarbon, contacts from gilded phosphor bronze (layer of gold 3µm).

Connector, contacts: RJ-10, 4p4c Materials: policarbonate, gold-plated phosphor bronze Contacts plating: 3µm Au Cable type: flat, stranded Connector type: unshielded



Net Price: 2.41 USD Unit: 100pcs



Contacts plating: 3µm Au Cable type: flat, stranded Connector type: unshielded

#04794

Net Price: 10.10 USD Unit: 100pcs



type)

#04975

Net Price: 11.00 USD Unit: 100pcs

Modular male connector, 6P6C (RJ-12), 100/bag

Modular male connectors are used for terminating wires in phone or computer installations. The body of a male connector is made from polycarbon, contacts from gilded phosphor bronze (layer of gold 3µm).

Type, contacts: RJ-12, 6p6c Materials: policarbonate, gold-plated phosphor bronze Contacts plating: 3µm Au Cable type: flat, stranded Connector type: unshielded

Modular male connector, 8P8C (RJ-45), round, solid, shielded, cat. 5e, throughconnector (EZ

Modular male connector, 6P2C, 100/bag

Modular male connectors are used for terminating wires in phone or computer installations. The body of a male

connector is made from polycarbon, contacts from gilded phosphor bronze (layer of gold 3µm).

Type, contacts: 6p2c Materials: policarbonate, gold-plated phosphor bronze

Modular male connectors are used for terminating wires in phone or computer installations. Shielded type - used for environments with high level of electromagnetic disturbances. The body of a male connector is made from polycarbon, contacts from gilded phosphor bronze (3µm layer of gold).

Type, contacts: RJ-45, 8p8c Category: 5e Materials: policarbonate, gold-plated phosphor bronze Contacts plating: 3µm Au Cable type: round, solid Connector type: shielded, EZ type

Modular male connector, 8P8C (RJ-45), round, solid, shielded, cat. 6A, throughconnector (EZ

Modular male connectors are used for terminating wires in phone or computer installations. Shielded type - used for environments with high level of electromagnetic disturbances. The body of a male connector is made from polycarbon, contacts from gilded phosphor bronze (3µm layer of gold).

Modular male connector, 6P4C (RJ-11), 100/bag

Modular male connectors are used for terminating wires in phone or computer installations. The body of a male

connector is made from polycarbon, contacts from gilded phosphor bronze (layer of gold $3\mu m).$

Type, contacts: RJ-11, 6p4c Materials: policarbonate, gold-plated phosphor bronze Contacts plating: 3µm Au Cable type: flat, stranded Connector type: unshielded

Type, contacts: RJ-45, 8p8c Category: 6a Materials: policarbonate, gold-plated phosphor bronze Contacts plating: 3µm Au Cable type: round, solid Connector type: shielded, EZ type

The se

#04196

Net Price: 5.12 USD Unit: 100pcs



#04195

Net Price: 6.44 USD Unit: 100pcs



#04197

Net Price: 7.02 USD Unit: 100pcs

Modular male connector, 8P8C (RJ-45), round, solid, cat. 5e, throughconnector (EZ type)

Type, contacts: RJ-45, 8p8c Category: 5e Materials: policarbonate, gold-plated phosphor bronze Contacts plating: 3µm Au Cable type: round, solid Connector type: unshielded, EZ type

Modular male connector, 8P8C (RJ-45), round, solid, cat. 6, throughconnector (EZ type)

Modular male connectors are used for terminating wires in phone or computer installations. There also exists a shielded type of male connectors used for environments with high level of electromagnetic disturbances. The body of a male connector is made from polycarbon, contacts from gilded phosphor bronze (3µm layer of gold).

Type, contacts: RJ-45, 8p8c Category: 6 Materials: policarbonate, gold-plated phosphor bronze Contacts plating: 3µm Au Cable type: round, solid Connector type: unshielded, EZ type

Modular male connector, 8P8C (RJ-45), round, solid, cat. 6A, throughconnector (EZ type)

Modular male connectors are used for terminating wires in phone or computer installations. There also exists a shielded type of male connectors used for environments with high level of electromagnetic disturbances. The body of a male connector is made from polycarbon, contacts from gilded phosphor bronze (3µm layer of gold).

Type, contacts: RJ-45, 8p8c Category: 6a Materials: policarbonate, gold-plated phosphor bronze Contacts plating: 3µm Au Cable type: round, solid Connector type: unshielded, EZ type



#04955

Net Price: 1.00 USD Unit: pcs



#03834

Net Price: 2.15 USD Unit: pcs



#04956

Net Price: 1.10 USD Unit: pcs

Modular male connector, 8P8C (RJ-45), cat. 5e, toolless

Modular male connectors are used for terminating wires in phone or computer installations. There also exists a shielded type of male connectors used for environments with high level of electromagnetic disturbances. The body of a male connector is made from polycarbon, contacts from gilded phosphor bronze (3µm layer of gold).

Type, contacts: RJ-45, 8p8c Category: 5e Materials: policarbonate, gold-plated phosphor bronze Contacts plating: 3µm Au Cable type: round, solid and stranded Connector type: unshielded, toolless

Modular male connector, 8P8C (RJ-45), cat. 6, shielded, toolless

Modular male connectors are used for terminating wires in phone or computer installations. Shielded – for environments with high level of electromagnetic disturbances. The body of a male connector is made from polycarbon, contacts from gilded phosphor bronze (3 μm layer of gold).

Type, contacts: RJ-45, 8p8c Category: 6 Materials: policarbonate, gold-plated phosphor bronze Contacts plating: 3µm Au Cable type: round, solid and stranded Connector type: shielded, toolless

Modular male connector, 8P8C (RJ-45), cat. 6, toolless

Modular male connectors are used for terminating wires in phone or computer installations. There also exists a shielded type of male connectors used for environments with high level of electromagnetic disturbances. The body of a male connector is made from polycarbon, contacts from gilded phosphor bronze (3µm layer of gold).

phosphor bronze (3µm layer of gold).

Type, contacts: RJ-45, 8p8c
Category: 6
Materials: policarbonate, gold-plated phosphor bronze
Contacts plating: 3µm Au
Cable type: round, solid and stranded
Connector type: unshielded, toolless



#03835

Net Price: 2.78 USD Unit: pcs



#00882

Net Price: 3.84 USD Unit: 100pcs



#00880

Net Price: 3.95 USD Unit: 100pcs

Modular male connector, 8P8C (RJ-45), cat. 6A, shielded, toolless

Modular male connectors are used for terminating wires in phone or computer installations. Shielded - for environments with high level of electromagnetic disturbances. The body of a male connector is made from polycarbon, contacts from gilded phosphor bronze (3µm layer of gold).

Type, contacts: RJ-45, 8p8c Type, contacts: K3-45, opoc Category: 6a Materials: policarbonate, gold-plated phosphor bronze Contacts plating: 3µm Au Cable type: round, solid and stranded Connector type: shielded, toolless



#00883 Net Price: 4.06 USD Unit: 100pcs



Modular male connector, 8P8C (RJ-45), round, solid, cat. 5e

Modular male connectors are used for terminating wires in phone or computer installations. There also exists a shielded type of male connectors used for environments with high level of electromagnetic disturbances. The body of a male connector is made from polycarbon, contacts from gilded phosphor bronze (3µm layer of gold).

Type, contacts: RJ-45, 8p8c Category: 5e Materials: policarbonate, gold-plated phosphor bronze Contacts plating: 3µm Au Cable type: round, solid Connector type: unshielded



#04913



Modular male connector, 8P8C (RJ-45), round, solid, cat. 6, shielded

Modular male connectors are used for terminating wires in phone or computer installations. Shielded type of environments with high level of electromagnetic disturbances. The body of a male connector is made from polycarbon, contacts from gilded phosphor bronze (3µm layer of gold).

Type, contacts: RJ-45, 8p8c Category: 6 Materials: policarbonate, gold-plated phosphor bronze Contacts plating: 3µm Au Cable type: round, solid Connector type: shielded



#00897

Net Price: 0.112 USD Unit: pcs

Modular male connector, 8P8C (RJ-45), round, stranded, cat. 5e, shielded

Modular male connectors are used for terminating wires in phone or computer installations. Shielded type - used for environments with high level of electromagnetic disturbances. The body of a male connector is made from polycarbon, contacts from gilded phosphor bronze (3µm layer of gold).

Type, contacts: RJ-45, 8p8c Type, Collidates, Na-43, opoc Category: Se Materials: policarbonate, gold-plated phosphor bronze Contacts plating: 3µm Au Cable type: round, stranded Connector type: shielded



Modular male connector, 8P8C (RJ-45), flat, solid, cat. 5e


Modular male connectors are used for terminating wires in phone or computer installations. There also exists a shielded type of male connectors used for environments with high level of electromagnetic disturbances. The body of a male connector is made from polycarbon, contacts from gilded phosphor bronze (3µm layer of gold).

Type, contacts: RJ-45, 8p8c Category: 5e Materials: policarbonate, gold-plated phosphor bronze Contacts plating: 3µm Au Cable type: flat, solid

Connector type: unshielded

#00884

Net Price: 0.101 USD Unit: pcs



Modular male connectors are used for terminating wires in phone or computer installations. Shielded type - used for environments with high level of electromagnetic disturbances. The body of a male connector is made from polycarbor contacts from gilded phosphor bronze (3µm layer of gold).

Type, contacts: RJ-45, 8p8c

Type, contacts: K3-45, opec Category: Se Materials: policarbonate, gold-plated phosphor bronze Contacts plating: 3µm Au Cable type: round, solid Connector type: shielded



#07165

Net Price: 0.215 USD Unit: pcs



Modular male connectors are used for terminating wires in phone or computer installations. Shielded type - used for environments with high level of electromagnetic disturbances. The body of a male connector is made from polycarbon contacts from gilded phosphor bronze (3µm layer of gold).

Type, contacts: RJ-45, 8p8c

Category: 6A Materials: policarbonate, gold-plated phosphor bronze Contacts plating: 3µm Au Cable type: round, solid

Connector type: shielded Maximum core diameter: 1.02mm Operating temperature: -40° ÷ 125°C



#04919

Net Price: 0.037 USD Unit: pcs



Modular male connector, 8P8C (RJ-45), round, stranded, cat. 5e, short body

Modular male connectors are used for terminating wires in phone or computer installations. There also exists a shielded type of male connectors used for environments with high level of electromagnetic disturbances. The body of a male connector is made from polycarbon, contacts from gilded phosphor bronze (3µm layer of gold).

Type, contacts: RJ-45, 8p8c

Category: 5e Materials: policarbonate, gold-plated phosphor bronze Contacts plating: 3µm Au Cable type: round, stranded

Connector type: unshielded, short-body



Modular male connector, 8P8C (RJ-45), flat, stranded, cat. 5e

Modular male connectors are used for terminating wires in phone or computer installations. There also exists a shielded type of male connectors used for environments with high level of electromagnetic disturbances. The body of a male connector is made from polycarbon, contacts from gilded phosphor bronze (3 μ m layer of gold).

Type, contacts: RJ-45, 8p8c Category: 5e Materials: policarbonate, gold-plated phosphor bronze

Contacts plating: 3µm Au Cable type: flat, stranded Connector type: unshielded

#04912

Net Price: 0.099 USD

Modular male connector, 8P8C (RJ-45), round, solid, cat. 6

Modular male connectors are used for terminating wires in phone or computer installations. There also exists a shielded type of male connectors used for environments with high level of electromagnetic disturbances. The body of a male connector is made from polycarbon, contacts from gilded phosphor bronze (3µm layer of gold).

Type, contacts: RJ-45, 8p8c

Category: 6
Materials: policarbonate, gold-plated phosphor bronze
Contacts plating: 3µm Au
Cable type: round, solid Connector type: unshielded

#00881

Net Price: Unit: 100pcs

Modular male connector, 8P8C (RJ-45), round, stranded, cat. 5e

Modular male connectors are used for terminating wires in phone or computer installations. There also exists a shielded type of male connectors used for environments with high level of electromagnetic disturbances. The body of a male connector is made from polycarbon, contacts from gilded phosphor bronze (3 μ m layer of gold).

Type, contacts: RJ-45, 8p8c Category: 5e Materials: policarbonate, gold-plated phosphor bronze Contacts plating: 3µm Au Cable type: round, stranded Connector type: unshielded



#07408

Net Price: 0.132 USD Unit: pcs

Modular male connector, 8P8C (RJ-45), round, stranded, cat. 6, shielded

Modular male connectors are used for terminating wires in phone or computer installations. There also exists a shielded type of male connectors used for environments with high level of electromagnetic disturbances. The body of a male connector is made from polycarbon, contacts from gilded phosphor bronze (3µm layer of gold).

Type, contacts: RJ-45, 8p8c Type, conteats, 1543, ppot Category: 6 Materials: policarbonate, gold-plated phosphor bronze Contacts plating: 3µm Au Cable type: round, stranded Connector type: shielded



#04902 Net Price: 0.117 USD Unit: pcs



#07166 Net Price: 0.215 USD Unit: pcs



#07184 Net Price: 0.263 USD Unit: pcs

Modular male connector, 8P8C (RJ-45), round, stranded, cat. 6, w/insert bar

Modular male connectors are used for terminating wires in phone or computer installations. There also exists a shielded type of male connectors used for environments with high level of electromagnetic disturbances. The body of a male connector is made from polycarbon, contacts from gilded phosphor bronze (3µm layer of gold).

Type, contacts: RJ-45, 8p8c Category: 6 Category. o Materials: policarbonate, gold-plated phosphor bronze Contacts plating: 3µm Au Cable type: round, stranded Connector type: unshielded

Modular male connector, 8P8C (RJ-45), round, stranded, cat. 6A, shielded

Modular male connectors are used for terminating wires in phone or computer installations. Shielded type - used for environments with high level of electromagnetic disturbances. The body of a male connector is made from polycarbon, contacts from gilded phosphor bronze (3µm layer of gold).

Type, contacts: RJ-45, 8p8c Type, contacts, K3-45, opoc Category: 6A Materials: policarbonate, gold-plated phosphor bronze Contacts plating: 3µm Au Cable type: round, stranded Connector type: shielded

Modular male connector, 8P8C (RJ-45), round cat. 8, shielded

High quality plugs designed for cat. 8 applications. New 3 pongs contacts are suitable for both solid and stranded wires.

Type, contacts: RJ-45, 8p8c Category: 8

Materials: policarbonate, gold-plated phosphor bronze

Contacts plating: 3µm Au
Cable type: round, solid and stranded
Connector type: shielded Maximum core diameter: 1.45mm Operating temperature: -40° ÷ 125°C Outer cable OD max: 8mm



#00895

Net Price: 0.057 USD Unit: pcs



#00896

Net Price: 0.057 USD Unit: pcs



#04796

Net Price: 0.105 USD Unit: pcs

Modular male connector, 10P10C (RJ-50), round, solid

The body of a male connector is made from polycarbon, contacts from gilded phosphor bronze (3µm layer of gold).

Type, contacts: RJ-50, 10p10c Category: n/a

Materials: policarbonate, gold-plated phosphor bronze Contacts plating: 3μm Au Cable type: round, solid Connector type: unshielded

Modular male connector, 10P10C (RJ-50), round, stranded

The body of a male connector is made from polycarbon contacts from gilded phosphor bronze (3µm layer of gold).

Type, contacts: RJ-50, 10p10c Category: n/a

Materials: policarbonate, gold-plated phosphor bronze Contacts plating: 3µm Au Cable type: round, stranded Connector type: unshielded

Modular male connector, 10P10C (RJ-50), round, stranded, shielded

Modular male connectors are used for terminating wires in phone or computer installations. There also exists a shielded type of male connectors used for environments with high level of electromagnetic disturbances. The body of a male connector is made from polycarbon, contacts from gilded phosphor bronze (3µm layer of gold).

Type, contacts: RJ-50, 10p10c Category: n/a Materials: policarbonate, gold-plated phosphor bronze Contacts plating: 3µm Au Cable type: round, stranded Connector type: shielded



#04305

Net Price: 0.220 USD Unit: pcs



#00494

Net Price: 0.022 USD Unit: pcs



#00495

Net Price: 0.022 USD Unit: pcs

Swivel male connector WMP 2, anti-torsion,



#00496

Net Price: 0.022 USD Unit: pcs



Cable boot w/ear, o.d. 6.0 mm, black

#00425

Net Price: 0.022 USD Unit: pcs




Cable boot w/ear, o.d. 6.0 mm, red

Cable boot w/ear, o.d. 8.0 mm, grey

Cable boot w/ear, o.d. 6.0 mm, blue

#00497

Net Price: Unit: pcs





#03751

Net Price: 0.022 USD Unit: pcs



Cable boot w/ear, o.d. 6.0 mm, grey

#00498

Net Price: 0.022 USD Unit: pcs



#07185

Net Price: 0.022 USD Unit: pcs





Net Price: 0.022 USD Unit: pcs



Cable boot w/ear, o.d. 6.0 mm, yellow

#05125

Net Price: 0.022 USD Unit: pcs



Cable boot w/inserts, black

#05124



Cable boot w/inserts, blue

Cable boot w/inserts, green

#05126

Net Price: 0.022 USD Unit: pcs

A Line	#05127 Net Price: 0.022 USD Unit: pcs		#05128 Net Price: 0.022 USD Unit: pcs		#05130 Net Price: 0.022 USD Unit: pcs
Cable boot w/inserts, grey		Cable boot w/inserts, red		Cable boot w/inserts, white	
and the same of th	#05129 Net Price: 0.022 USD Unit: pcs				
Cable boot w/inserts, yellow					
Other devices					
	#00873 Net Price: 6.34 USD Unit: pcs				
Bell ringer with light, B type UT-7 device amplifies the phones' ring includes a blinking light, which switches ringing. There is an option of choosing function which is a perfect solution for of Works with any analogue phone line.	s on when the phone is only the blinking light				
Phone equipment, polish std.					
	#00816 Net Price: 0.450 USD Unit: pcs		#01838 Net Price: 0.190 USD Unit: pcs	6	#00874 Net Price: 0.140 USD Unit: pcs
Adaptor, polish male to 2 american female		Wall plate, polish female & american female		Connector, polish male	
Splitters, couplers					
	#00813 Net Price: 0.241 USD Unit: pcs		#00814 Net Price: 0.307 USD Unit: pcs		#00815 Net Price: 0.351 USD Unit: pcs
Coupler, R1-4, 1F/1F 6p4c		Coupler, R1-6, 1F/1F 6p6c		Coupler, R1-8, 1F/1F 8p8c	
				Coupler with two 8p8c sockets for t Couplers meant for computer netw #06492- Inline coupler, cat 5e, shie #08317- Inline coupler, cat 5e, shie #04920- Cat 5e Coupler, UTP	orks: Ided
	#00842 Net Price: 0.395 USD Unit: pcs		#00843 Net Price: 0.483 USD Unit: pcs		#00844 Net Price: 0.461 USD Unit: pcs



3 way coupler, 4C, white

5 way adaptor, 4C, white

#00850 Net Price: 1.43 USD Unit: pcs

Duplex adaptor, 4C, white

3 way coupler, 6C, white





3 way coupler, 8C, white

Duplex adaptor, 6C, white

#00846 Net Price: 0.461 USD Unit: pcs



Telephone Accessories



#00847

Net Price: 0.549 USD Unit: pcs

Duplex adaptor, 8C, white



#04923

Net Price: 0.351 USD Unit: pcs



#04927

Net Price: 0.417 USD Unit: pcs



#04925

Net Price: 0.505 USD Unit: pcs

Surface box, 6P4C, economic. white

Dimensions: 28x42x24 mm



Surface dual box, 2x6P4C, economic, white



#01849

Net Price: 1.10 USD Unit: pcs



#04924

Net Price: 0.439 USD Unit: pcs



#04921

Net Price: 0.527 USD Unit: pcs

Wall box, 2x6P4C,ABS,top entry,white



#04922

Net Price: 0.576 USD Unit: pcs

Surface box, 6P6C, economic, white

Surface box, 6P6C, standard, white



Other phone accessories



#01847

Net Price: 4.65 USD Unit: 100pcs



#01846

Net Price: 1.58 USD Unit: 100pcs



#04905

Net Price: 2.33 USD Unit: 100pcs

UR connector, 100pcs/bag

UR connectors enable connecting wires without the need of isolation stripping. They are filled with gel, which protects wires from corrosion.

wires from corrosion. UR connectors should be used for wires with external coat up to 1.67mm in diameter and 0.4-0.9 wire diameter. Made of transparent polycarbonate with a red clamp.

Purpose: connecting three wires
Maximum diameter of the external coat: 1.67mm
Core diameter: 0.4-0.9mm
Dimensions: 19x12x8.5mm (6mm after tightening)
Filling: hydrophobic gel, protecting against corrosion
Packaging: cardboard, 61x63x57mm

UY connector, 100pcs/bag

UY connectors enable connecting wires without the need of isolation stripping. They are filled with gel, which protects wires from corrosion.

UY connectors should be used for wires with external coat up to 1.52mm in diameter and 0.4-0.7 wire diameter.

Made of transparent polycarbonate with a yellow clamp.

Purpose: connecting two wires Maximum diameter of the external coat: 1.52mm Core diameter: 0.4-0.7mm Dimensions: 12x8.5x8mm (6mm after tightening) Filling: hydrophobic gel, protecting against corrosion Packaging: cardboard, 55x55x55mm

UY2 connector, 100pcs/bag

UY2 connectors enable connecting wires without the need of isolation stripping. They are filled with gel, which protects wires from corrosion.

UY2 connectors should be used for wires with external coat up to 1.52mm in diameter and 0.4-0.9 wire diameter.

Made of transparent polycarbonate with an orange clamp.

Purpose: connecting two wires Maximum diameter of the external coat:1.52mm Core diameter:0.4-0.9mm Dimensions:15x10x8mm (6mm after tightening) Filling:hydrophobic gel, protecting against corrosion Temperature range: -30°C + +70°C Packaging: cardboard, 55x55x55mm

Index

Flat cables	1
Handset and extension cords	2
LSA installation equipment	2
Modular connectors, male	
Other devices	8
Phone equipment, polish std.	
Splitters, couplers	8
Splitters, couplers Surface-mount boxes	9
Other phone accessories	9



Head Office Opole tel. +48 (77) 455 60 76 fax +48 (77) 455 80 56 e-mail: cust@atel.com.pl

