



## 802.11bx (WiFi 7)

NEW



#09446

Net Price:  
556.00 USD  
Unit: pcs**19000Mbps Outdoor Wireless Access Point, BE19000 (TP-Link EAP783)**

- BE22000 Tri-Band Wi-Fi 7 (11520 Mbps on 6 GHz + 8640 Mbps on 5 GHz + 1376 Mbps on 2.4 GHz).
- A clear 6 GHz band brings cleaner and wider band resources.
- 2× 10G ports unlock the full potential of Wi-Fi 7.
- 320 MHz bandwidth enables many more simultaneous transmissions.
- Multi-Link Operation and Multi-RUs ensure the high performance of your network.
- Advanced Functions: Centralized management, mesh, and Seamless roaming.

Ports: 2× 10G Ethernet Ports (20G Aggregation Speed)  
Bluetooth: V5.2  
Button: Reset

Frequency range: 6 GHz, 5 GHz and 2.4 GHz  
Signal Rate: 6 GHz Up to 11520 Mbps, 5 GHz Up to 8640 Mbps, 2.4 GHz Up to 1376 Mbps  
Wireless Functions: Multiple SSIDs (Up to 16 SSIDs, 8 for each band), Enable/Disable Wireless Radio, Automatic Channel Assignment, Transmit Power Control (Adjust Transmit Power on dBm), QoS(WMM), Airtime Fairness, Beamforming, Band Steering, Load Balance, Rate Limit, Link Aggregation, Reboot Schedule, Wireless Schedule, Wireless Statistics based on SSID/AP/Client



#09388

Net Price:  
594.00 USD  
Unit: pcs**19000Mbps Wireless 10G Router Tri-band BE19000, MU-MIMO (TP-Link Archer BE800)**

- Redefining WiFi Routers: With powerful WiFi 7 performance, lightning-fast wired connections, brand-new design, and LED screen.
- Lightning-Fast 19 Gbps Tri-Band WiFi 7: Enables your devices to run at full speed. Enjoy fluent 4K/8K streaming, immersive AR/VR gaming, and lightning-fast downloads.
- Multi-Link Operation (MLO): Increases throughput, reduces latency, and improves reliability for emerging applications.
- Dual 10G Ports: 1× 10 Gbps Ethernet/Fiber Combo WAN/LAN port + 1× 10 Gbps WAN/LAN port + 4× 2.5 Gbps ports + 1× USB 3.0 port ensure max flexibility and boosted throughput.
- Maximized Coverage: Proprietary WiFi optimization and 8× optimally positioned antennas along with Beamforming deliver more capacity, stronger and more reliable connections, and less interference.
- EasyMesh-Compatible: Works with EasyMesh routers and range extenders to form seamless whole home Mesh WiFi, preventing drops and lag when moving between signals.
- TP-Link HomeShield: Enhanced security defends against the latest cyber threats.
- Easy and Fun to Use: Conveniently manage everything with the Tether app, and visually display the time, weather, and playful graphics with the LED screen.
- Great Compatibility: Works with all WiFi generations and devices and all internet providers.

**HARDWARE FEATURES:**

Standards and Protocols: IEEE 802.11be/ax 6 GHz, IEEE 802.11be/ax/ac/n/a 5 GHz, IEEE802.11be/ax/n/b/g 2.4 GHz  
Interface: 1× 10 Gbps WAN/LAN Port + 1× 10 Gbps SFP+/RJ45 Combo WAN/LAN Port + 4× 2.5 Gbps LAN Ports, 1 port USB-C 3.0  
Button: WPS/Reset Button, Wireless On/Off Button, Power On/Off Button, LED On/Off

Power Supply: 15V/5A  
Dimensions (W X D X H): 3.8 × 11.9 × 10.3 in (96 × 302 × 262.5 mm)

Antenna: 8× High-Performance Antennas

**WIRELESS FEATURES:**

Frequency: 2.4GHz, 5GHz & 6GHz

NEW



#09539

Net Price:  
505.00 USD  
Unit: pcs**19000Mbps Wireless 10G Router Tri-band BE19000, MU-MIMO (TP-Link Archer GE800)**

- Unprecedented 19 Gbps Tri-Band WiFi 7: Delivering 11520 Mbps on the 6 GHz band, 5764 Mbps on 5 GHz, and 1376 Mbps on 2.4 GHz. Make sure your network is primed for intense gaming.
- Two 10G Ports for Future-Proof Connectivity: 2× 10 Gbps WAN/LAN ports, and 4× 2.5 Gbps LAN ports support massive bandwidth for wired gaming devices and ultra-fast connections, accommodating all gaming needs.
- Exclusive Acceleration for Games: Accelerate game applications, game devices, mobile games, and game servers. Stabilize connections, minimize jitter, lag and ping while boosting speed.
- Dedicated Game Panel: An intuitive game panel provides real-time insights into the battle environment, network status, router performance, rgb settings, accelerated games and gears, enabling players to strategize effectively.
- Game-Style Design: High-performance launch pad appearance, seamless multicolor lighting, and optimized antenna layout ensure quality connections and a vibrant atmosphere.
- TP-Link HomeShield: HomeShield provides robust antivirus protection for a secure gaming experience. It defends all your devices and personal data against online threats, ensuring peace of mind while gaming.
- EasyMesh Compatibility-Works with EasyMesh routers and range extenders to form seamless whole home Mesh WiFi. This connectivity ensures consistent coverage, allowing gamers to collaborate efficiently and dominate team battles.

**HARDWARE FEATURES:**

Standards and Protocols: IEEE 802.11be/ax 6 GHz, IEEE 802.11be/ax/ac/n/a 5 GHz, IEEE802.11be/ax/n/b/g 2.4 GHz  
Interface: 1× 10 Gbps WAN/LAN Port + 1× 10 Gbps SFP+/RJ45 Combo WAN/LAN Port + 4× 2.5 Gbps LAN Ports, 1 port USB-C 3.0  
Dimensions (W X D X H): 11.5 × 8.1 × 8.8 in (292 × 207 × 224 mm)

Antenna: 8× High-Performance Antennas

**WIRELESS FEATURES:**

Frequency: 2.4GHz, 5GHz & 6GHz  
Signal Rate: 6 GHz- 11520 Mb/s (802.11be), 5 GHz- 5760 Mb/s (802.11be), 2.4 GHz- 1376 Mb/s (802.11be)

NEW



#09558

Net Price:  
115.00 USD  
Unit: pcs**3600Mbps Outdoor Wireless Access Point, BE3600 (TP-Link EAP723)**

- BE5000 Dual-Band Wi-Fi 7 (4324 Mbps on 5 GHz + 688 Mbps on 2.4 GHz).
- 1× 2.5G port unlocks the full potential of Wi-Fi 7.
- 240 MHz bandwidth enables many more simultaneous transmissions.
- Multi-RUs ensure the high performance of your network.
- Advanced Functions: Centralized management, Mesh, and Seamless Roaming.

Ports: 1× 2.5G Ethernet Port

Button: Reset

Frequency range: 5 GHz and 2.4 GHz

Signal Rate: 5 GHz Up to 2882 Mbps, 2.4 GHz Up to 688 Mbps

Wireless Functions: Multiple SSIDs (Up to 16 SSIDs, 8 for each band), Enable/Disable Wireless Radio, Automatic Channel Assignment, Transmit Power Control (Adjust Transmit Power on dBm), QoS(WMM), Airtime Fairness, Beamforming, Band Steering, Load Balance, Rate Limit, Link Aggregation, Reboot Schedule, Wireless Schedule, Wireless Statistics based on SSID/AP/Client

NEW



#09559

Net Price:  
123.00 USD  
Unit: pcs**3600Mbps Outdoor Wireless Access Point, BE3600 (TP-Link EAP725-Wall)**

- BE3600 Wi-Fi 7 (2882 Mbps on 5 GHz + 688 Mbps on 2.4 GHz).
- 1× 2.5G PoE input port + 1× 2.5G pass-through port + 2× Gigabit RJ45 downlink ports.
- 160 MHz bandwidth enables many more simultaneous transmissions.
- Multi-RUs ensure the high performance of your network.
- Advanced Functions: Centralized management, Mesh, and Seamless Roaming.

Ports: 1× 2.5G Ethernet Port, Downlink 1× 2.5G Ethernet Port + 2× Gigabit Ethernet Ports (The 2.5G port supports PoE pass-through. The PoE pass-through feature requires 802.3at/bt input. If the power consumption of the AP's downstream device exceeds 7W, the AP needs an 802.3bt input.)

Button: Reset

Frequency range: 5 GHz and 2.4 GHz

Signal Rate: 5 GHz Up to 2882 Mbps, 2.4 GHz Up to 688 Mbps

Wireless Functions: Multiple SSIDs (Up to 16 SSIDs, 8 for each band), Enable/Disable Wireless Radio, Automatic Channel Assignment, Transmit Power Control (Adjust Transmit Power on dBm), QoS(WMM), Airtime Fairness, Beamforming, Band Steering, Load Balance, Rate Limit, Link Aggregation, Reboot Schedule, Wireless Schedule, Wireless Statistics based on SSID/AP/Client



#09390

Net Price:  
95.60 USD  
Unit: pcs**3600Mbps Wireless 2.5G Router Dual-band BE3600, MU-MIMO (TP-Link Archer BE230 (BE3600))**

- 3.6 Gbps Dual-Band WiFi 7: BE3600 Dual-Band WiFi delivers WiFi speeds up to 3.6 Gbps.
- 2× 2.5G Ports: 1× 2.5 Gbps WAN port, 1× 2.5 Gbps LAN port and 3× 1 Gbps LAN ports offer high-speed data transmissions.
- Maximized Coverage: 4× external antennas along with Beamforming deliver more capacity, stronger and more reliable connections, and less interference.
- EasyMesh-Compatible: Works with EasyMesh routers and range extenders to form seamless whole home Mesh WiFi, preventing drops and lag when moving between signals.
- Easy Setup and Use: Network management has never been easier with the Tether app.
- TP-Link HomeShield: Enhanced security defends against the latest cyber threats.
- Great Compatibility: Supports all Wi-Fi generations and devices and all internet providers.

**HARDWARE FEATURES:**

Standards and Protocols: IEEE 802.11be/ax/ac/n/a 5 GHz, IEEE 802.11be/ax/n/g/b 2.4 GHz  
Interface: 1× 2.5 Gbps WAN, 1× 2.5 Gbps LAN, 3× 1 Gbps LAN, 1 port USB-C 3.0

Button: WPS/Reset Button, Wireless On/Off Button, Power On/Off Button, LED On/Off

Power Supply: 12V/1.5A

Dimensions (W X D X H): 10.7 × 5.8 × 1.6 in (272.7 × 147 × 41.7 mm)

Antenna: 4× High-Performance Antennas

**WIRELESS FEATURES:**

Frequency: 2.4GHz, 5GHz  
Signal Rate: 5 GHz- 2882 Mb/s (802.11be), 2.4 GHz- 688 Mb/s (802.11be)



**#09520**  
Net Price:  
74.80 USD  
Unit: pcs

**3600Mbps Wireless 2.5G Router Dual-band BE3600, MU-MIMO (TP-Link Marcusys MR27BE)**

- Fast 3.6 Gbps Mbps Dual Band Speeds: Enables your devices to run at full speed. Enjoy fluent 4K/8K streaming, immersive AR/VR gaming, and blazing-fast downloads.
- Newest WiFi 7: Armed with the 160 MHz channels, 4K-QAM, MLO, and other features that WiFi 7 offers, your network will arrive with a jaw-dropping performance.
- Multi-Link Operation (MLO): Increases throughput, reduces latency, and improves reliability for emerging applications.&#8225;
- 2.5G Ports: 1× 2.5 Gbps WAN port, 1× 2.5 Gbps LAN port and 2× 1 Gbps LAN ports break through the 1G bottleneck, driving your devices to peak performance.
- Maximized Coverage: 4× Omni directional antennas, proprietary Wi-Fi optimization, and Beamforming technology deliver broader coverage, more capacity, stronger and more reliable connections, and less interference.
- EasyMesh-Compatible: Works with EasyMesh routers and range extenders to form seamless whole home Mesh WiFi, preventing drops and lag when moving between signals.
- Easy Setup and Use: Network management has never been easier with the MERCUSYS app.

**HARDWARE FEATURES:**

Standards and Protocols:802.11be/ax/ac/a/b/g/n  
Interface: 1× 2.5 Gbps WAN Port + 1× 2.5 Gbps LAN Port + 2× 1 Gbps LAN Ports  
Button:WPS/Reset Button  
Dimensions (W X D X H): 250 × 119 × 43.3 mm (9.8 × 4.7 × 1.7 in)

Antenna: 4× Fixed Omni-Directional Antennas

**WIRELESS FEATURES:**

Frequency:2.4GHz & 5GHz  
Signal Rate: BE3600, 5 GHz@ 2880 Mb/s, 2.4 GHz@ 688 Mb/s  
Wireless Functions:Multi-Link Operation (MLO), 160 MHz Channel, 4K-QAM, Multi-RUs  
Wireless Security:WPA-PSK/WPA2-PSK/WPA3-SAE

NEW



**#09579**  
Net Price:  
54.90 USD  
Unit: pcs

**3600Mbps Wireless Router Dual-band BE3600, MU-MIMO (TP-Link Marcusys MR25BE)**

- Fast 3.6 Gbps Mbps Dual-Band Speeds: Enables your devices to run at full speed. Enjoy fluent 4K/8K streaming, immersive AR/VR gaming, and blazing-fast downloads.
- Newest WiFi 7: Armed with the 160 MHz channels, 4K-QAM, MLO, and other features that WiFi 7 offers, your network will arrive with a jaw-dropping performance.
- Multi-Link Operation (MLO): Increases throughput, reduces latency, and improves reliability for emerging applications.
- Gigabit Wired Connections: Make full use of your internet access and transfer data at dizzying speeds for peak performance.
- Maximized Coverage: 4× Omnidirectional antennas, proprietary WiFi optimization, and Beamforming technology deliver broader coverage, more capacity, stronger and more reliable connections, and less interference.
- EasyMesh-Compatible: Works with EasyMesh routers and range extenders to form seamless whole home Mesh WiFi, preventing drops and lag when moving between signals.
- Easy Setup and Use: Network management has never been easier with the MERCUSYS app.

**HARDWARE FEATURES:**

Standards and Protocols:802.11be/ax/ac/a/b/g/n  
Interface: 1× 1 Gbps WAN Port + 3× 1 Gbps LAN Ports  
Button:WPS/Reset Button  
Dimensions (W X D X H): 6.6 × 4.6 × 1.6 in (167 × 117.5 × 41.5 mm)

Antenna: 4× Fixed Omni-Directional Antennas

**WIRELESS FEATURES:**

Frequency:2.4GHz & 5GHz  
Signal Rate: BE3600, 5 GHz@ 2880 Mb/s, 2.4 GHz@ 688 Mb/s  
Wireless Functions:Multi-Link Operation (MLO), 160 MHz Channel, 4K-QAM, Multi-RUs  
Wireless Security:WPA-PSK/WPA2-PSK/WPA3-SAE  
**SOFTWARE FEATURES:**

NEW



**#09540**  
Net Price:  
187.00 USD  
Unit: pcs

**6500Mbps Wireless 2.5G Router Dual-band BE6500, MU-MIMO (TP-Link Archer BE400)**

- 6.5 Gbps Dual-Band WiFi 7: Enables your devices to run at full speed. Enjoy fluent 4K/8K streaming, immersive AR/VR gaming, and blazing-fast downloads.
- Multi-Link Operation (MLO): Transmits data with Wi-Fi 7 clients across multiple bands simultaneously to increase throughput, reduce latency, and improve reliability for various networking behaviors.
- 2.5G Wired Connection: 1× 2.5 Gbps WAN port, 1× 2.5 Gbps LAN port and 3× 1 Gbps LAN ports offer high-speed data transmissions.
- Maximized Coverage: 6× external antennas along with Beamforming deliver more capacity, stronger and more reliable connections, and less interference.
- EasyMesh-Compatible: Works with EasyMesh routers and range extenders to form seamless whole home Mesh WiFi, preventing drops and lag when moving between signals.
- Easy Setup and Use: Network management has never been easier with the Tether app.
- TP-Link HomeShield: Enhanced security defends against the latest cyber threats.
- Great Compatibility: Supports all Wi-Fi generations and devices and all internet providers.

**HARDWARE FEATURES:**

Standards and Protocols:IEEE 802.11be/ax 6 GHz, IEEE 802.11be/ax/ac/n/a 5 GHz, IEEE802.11be/ax/n/b/g 2.4 GHz  
Interface:1× 2.5 Gbps WAN Port + 1× 2.5 Gbps LAN Port + 3× 1 Gbps LAN Ports, 1 port USB-C 3.0  
Button:WPS/Reset Button, Wireless On/Off Button, Power On/off Button, LED On/Off  
Power Supply: 12V/2.5A  
Dimensions (W X D X H): 10.6 × 6.0 × 1.9 in (268.6 × 153.0 × 47.6 mm)  
Antenna: 6× High-Performance Antennas  
**WIRELESS FEATURES:**  
Frequency:2.4GHz, 5GHz  
Signal Rate: 5 GHz- 5764 Mb/s (802.11be), 2.4 GHz- 688 Mb/s (802.11be)

NEW



**#09413**  
Net Price:  
59.30 USD  
Unit: pcs

**6500Mbps Wireless Tri Band PCI-Express BE6500, Wi-Fi 7, Bluetooth 5.4 (TP-Link Archer TBE400E)**

- Unparalleled Tri-Band Speed - Boost your overall speeds up to 2882 Mbps (6 GHz) + 2882 Mbps (5 GHz) + 688 Mbps (2.4 GHz)
- WiFi 7 Standard - Unleash the full potential of the 6 GHz band to double the bandwidth of the last generation
- Reliable Bluetooth 5.4 - Security and reliability improvement than last-gen high-speed Bluetooth 5.3
- Wider Signal Coverage - Two powerful signal-boosting high-gain antennas greatly extend existing Wi-Fi coverage, offering a fast, smooth online experience from farther away
- Cutting Edge WPA3 - Protect your network with the latest WPA3 security protocol so your information transmitted via the wireless adapter is secure from hackers
- Minimized Lag for your PC - OFDMA and MU-MIMO technology reduces lag so you can enjoy real-time gaming or an immersive VR experience on even busy networks
- Low-Profile Brackets - Both a standard and low-profile bracket for mini tower computer cases are provided
- Supported Operating System - Windows 11(64-bit) only

**HARDWARE FEATURES:**

Interface:PCI Express x1  
Antenna Type: 2× High-Performance Tri-Band Antennas  
Chipset: Intel Wi-Fi 7 Chipset  
**WIRELESS FEATURES:**  
Wireless Standards:IEEE 802.11a/b/g/n/ac/ax/be  
Signal Rate: 2882Mbps at 6GHz, 2880Mbps at 5GHz, 688Mbps at 2.4GHz  
Wireless Modes: Infrastructure mode  
Wireless Security:WPA/WPA2/WPA3, WPA-PSK/WPA2-PSK  
**OTHERS:**  
Dimensions: 4.8 × 3.09 × 0.85 in (120.8 × 78.5 × 21.5 mm)  
Package Contents:Archer TBE400E, Magnetized Antenna Base with 1m RF Cable, Two High Gain Antennas, Low-Profile Bracket, Bluetooth Header Cable, Quick Installation Guide, Resource CD

NEW



**#09448**  
Net Price:  
152.00 USD  
Unit: pcs

**9300Mbps Outdoor Wireless Access Point, BE9300 (TP-Link EAP772)**

- BE9300 Tri-Band Wi-Fi 7: 5760 Mbps (6 GHz) + 2880 Mbps (5 GHz) + 574 Mbps (2.4 GHz). Buffering will no longer be a problem.
- 1× 2.5G Port: Unlock the full potential of Wi-Fi 7.
- Clear 6 GHz Band: Brings cleaner and wider band resources to your Wi-Fi.
- 320 MHz Bandwidth: Up to 320 MHz bandwidth enables many more simultaneous transmissions at the fastest possible speeds.
- Low Latency and Interference: Multi-Link Operation, and Multi-RUs ensure high performance of your network.
- Advanced Functions&#65306;Supports centralized management, mesh, and AI roaming.

Ports: 1× 2.5G Ethernet Port

Bluetooth: V5.2

Button: Reset

Frequency range: 6 GHz, 5 GHz and 2.4 GHz  
Signal Rate: 574 Mbps (2.4 GHz) + 2880 Mbps (5 GHz) + 5760 Mbps (6 GHz)

Wireless Functions: Multiple SSIDs (Up to 16 SSIDs, 8 for each band), Enable/Disable Wireless Radio, Automatic Channel Assignment, Transmit Power Control (Adjust Transmit Power on dBm), QoS(WMM), Airtime Fairness, Beamforming, Band Steering, Load Balance, Rate Limit, Link Aggregation, Reboot Schedule, Wireless Schedule, Wireless Statistics based on SSID/AP/Client

NEW



**#09447**  
Net Price:  
202.00 USD  
Unit: pcs

**9300Mbps Outdoor Wireless Access Point, BE9300 (TP-Link EAP773)**

- BE9300 Tri-Band Wi-Fi 7: 5760 Mbps (6 GHz) + 2880 Mbps (5 GHz) + 574 Mbps (2.4 GHz). Buffering will no longer be a problem.
- 1× 10G Port: Unlock the full potential of Wi-Fi 7.
- Clear 6 GHz Band: Brings cleaner and wider band resources to your Wi-Fi.
- 320 MHz Bandwidth: Up to 320 MHz bandwidth enables many more simultaneous transmissions at the fastest possible speeds.
- Low Latency and Interference: Multi-Link Operation, and Multi-RUs ensure high performance of your network.
- Advanced Functions&#65306;Supports centralized management, mesh, and AI roaming.

Ports: 1× 10G Ethernet Port

Bluetooth: V5.2

Button: Reset

Frequency range: 6 GHz, 5 GHz and 2.4 GHz  
Signal Rate: 574 Mbps (2.4 GHz) + 2880 Mbps (5 GHz) + 5760 Mbps (6 GHz)

Wireless Functions: Multiple SSIDs (Up to 16 SSIDs, 8 for each band), Enable/Disable Wireless Radio, Automatic Channel Assignment, Transmit Power Control (Adjust Transmit Power on dBm), QoS(WMM), Airtime Fairness, Beamforming, Band Steering, Load Balance, Rate Limit, Link Aggregation, Reboot Schedule, Wireless Schedule, Wireless Statistics based on SSID/AP/Client



**#09389**

Net Price:  
369.00 USD  
Unit: pcs

## 9300Mbps Wireless 2,5G Router Tri-band BE9300, MU-MIMO (TP-Link Archer BE550)

- Redefining WiFi Routers: With powerful WiFi 7 performance, lightning-fast wired connections, and brand-new design.
- Blazing-Fast 9214 Mbps Tri-Band WiFi 7: Enables your devices to run at full speed. Enjoy fluent 4K/8K streaming, immersive AR/VR gaming, and blazing-fast downloads.
- Multi-Link Operation (MLO): Increases throughput, reduces latency, and improves reliability for emerging applications.
- 5x 2.5G Ports: 1x 2.5 Gbps WAN port and 4x 2.5 Gbps LAN ports break through the 1G bottleneck, driving your devices to peak performance.
- Maximized Coverage: Proprietary WiFi optimization and optimally positioned antennas along with Beamforming deliver more capacity, stronger and more reliable connections, and less interference.
- EasyMesh-Compatible: Works with EasyMesh routers and range extenders to form seamless whole home Mesh WiFi, preventing drops and lag when moving between signals.
- Easy Setup and Use: Network management has never been easier with the Tether app.
- TP-Link HomeShield: Enhanced security defends against the latest cyber threats.
- Great Compatibility: Supports all Wi-Fi generations and devices and all internet providers

### HARDWARE FEATURES:

Standards and Protocols: IEEE 802.11b/a/x 6 GHz, IEEE 802.11b/a/x/ac/n/a 5 GHz, IEEE802.11b/a/x/n/b/g 2.4 GHz  
Interface: 1× 2.5 Gbps WAN, 4× 2.5 Gbps LAN, 1 port USB-C 3.0  
Button: WPS/Reset Button, Wireless On/Off Button, Power On/off Button, LED On/Off  
Power Supply: 12V/3.3A  
Dimensions (W X D X H): 3.0 × 9.1 × 8.0 in (76 × 231.7 × 203 mm)  
Antenna: 6× High-Performance Antennas  
WIRELESS FEATURES:  
Frequency: 2.4GHz, 5GHz & 6GHz  
Signal Rate: 6 GHz- 5760 Mb/s (802.11be), 5 GHz- 2880 Mb/s (802.11be), 2.4 GHz- 574 Mb/s (802.11be)



**#09519**

Net Price:  
148.00 USD  
Unit: pcs

**9300Mbps Wireless 2,5G Router Tri-band  
BE9300, MU-MIMO (TP-Link Marcusys MR47BE)**

- **Blazing-Fast 9.3Gbps Tri-Band Speeds:** Enables your devices to run at full speed. Enjoy fluent 4K/8K streaming, immersive AR/VR gaming, and blazing-fast downloads.
- **Newest WiFi 7:** Armed with the 320 MHz channels, 4K-QAM, MLO, the 6 GHz band, and other features that WiFi 7 offers, your network will arrive with a jaw-dropping performance.
- **Multi-Link Operation (MLO):** Increases throughput, reduces latency, and improves reliability for emerging applications.
- **4x 2.5G Ports:** 1x 2.5 Gbps WAN port and 3x 2.5 Gbps LAN ports break through the 1G bottleneck, driving your devices to peak performance.
- **Maximized Coverage:** 6x Omni directional antennas, proprietary Wi-Fi optimization, and Beamforming technology deliver broader coverage, more capacity, stronger and more reliable connections, and less interference.
- **EasyMesh-Compatible:** Works with EasyMesh routers and range extenders to form seamless whole home Mesh WiFi, preventing drops and lag when moving between signals.
- **Easy Setup and Use:** Network management has never been easier with the MERCUSYS app.

#### HARDWARE FEATURES:

Standards and Protocols: 802.11be/ax/ae/ab/g/n  
Interface: 1x 2.5 Gbps WAN Port + 3x 2.5 Gbps LAN Ports  
Button: WPS/Reset Button  
Dimensions (W X D X H): 10.1 × 4.7 × 1.7 in (258 × 119 × 43.3 mm)  
Antenna: 6x Fixed Omni-Directional Antennas  
WIRELESS FEATURES:  
Frequency: 2.4GHz & 5GHz & 6GHz  
Signal Rate: BE900h, 6 GHz@ 5760 Mb/s (802.11be), 5 GHz@ 2880 Mb/s (802.11be), 2.4 GHz@ 574 Mb/s (802.11ax)  
Wireless Functions: Multi-Link Operation (MLO), 320 MHz Channel, 4K-QAM, Multi-RUS



**#09412**

Net Price:  
89.60 USD  
Unit: pcs

**9300Mbps Wireless Tri Band PCI-Express  
BE9300, Wi-Fi 7, Bluetooth 5.4 (TP-Link Archer  
TBE550E)**

- Unparalleled Tri-Band Speed - Boost your overall speeds up to 5760 Mbps (6 GHz) + 2880 Mbps (5 GHz) + 688 Mbps (2.4 GHz)
- WiFi 7 Standard - Unleash the full potential of the 6 GHz band to double the bandwidth of the last generation.
- Wider Signal Coverage - Two multi-directional antennas with a magnetized base are designed for optimal signal reception.
- Reliable Bluetooth 5.4 - Security and reliability improvement than last-gen high-speed Bluetooth 5.3
- Improved Security - The latest security enhancement, WPA3, provides enhanced protection in personal password safety.
- Fast Installation with USB Drive - Plug in the resource USB drive provided with Archer TBE550E to quickly drive without network. Enjoy the simple and friendly adapter installation.
- Multicolor Wi-Fi Status Lighting - Equipped with vibrant LED lighting effects, the base provides an intuitive indication of network status, enhancing both functionality and aesthetics.
- Supported Operating System - Windows 11(64-bit)  
only<#8203;&#8203;&#8203;&#8203;&#8203;&#8203;&#8203;&#8203;

### HARDWARE FEATURES:

Interface:PCI Express x1  
 Antenna Type: 2x High-Performance Tri-Band Antennas  
 Chipset: Intel Wi-Fi 7 Chipset  
**WIRELESS FEATURES:**  
 Wireless Standards:IEEE 802.11a/b/g/n/ac/ax/be  
 Signal Rate: 5760Mbps at 6GHz, 2880Mbps at 5GHz,  
 688Mbps at 2.4GHz  
 Wireless Modes: Infrastructure mode  
 Wireless Security:WPA/WPA2/WPA3, WPA-PSK/WPA2-PSK  
**OTHERS:**  
 Dimensions: 3.7 x 4.8 x 0.8 in (95.2 x 120.8 x 21.5 mm)  
 Package Contents:Archer TBE550E, Magnetized Antenna  
 Base with 1m RF Cable, Two High Gain Antennas,  
 Low-Profile Bracket, Bluetooth Header Cable, Quick  
 Installation Guide, Resource CD



**#09375**

Net Price:  
117.00 USD  
Unit: pcs

**Router Mesh Deco BE25 1-pack, BE3600 (TP-Link DECO BE25(1-Pack))**

- 3.6 Gbps Dual-Band WiFi - 2882 Mbps (5 GHz) + 688 Mbps (2.4 GHz).
- 2.5 Gbps Wired Connections - 2x 2.5 Gbps ports ensure max flexibility and boosted throughput.
- Wireless and Wired Combined Backhaul - Connects a wireless and wired backhaul with each unit simultaneously to improve overall throughput and reduce latency.
- Multi-Link Operation (MLO) - Simultaneously send and receive data across different bands and channels to increase throughput, reduce latency, and improve reliability.
- Seamless AI-Driven Roaming - Forms a unified network with built-in AI-Roaming creating the ideal Wi-Fi solution for your home.
- TP-Link HomeShield - Provides comprehensive network protection, robust parental controls, and real-time IoT security.
- Universal Compatibility - Backward compatible with all WiFi generations and works with any internet service provider (ISP) and modem.

Standards: IEEE 802.11be/ax/ac/n/a 5 GHz, IEEE 802.11be/ax/n/b/g 2.4 GHz  
Ports: 2x 2.5 Gbps  
Button: 1 Reset button, 1 WPS  
Frequency range: 2.4 GHz, 5 GHz  
Signal Rate: 5 GHz- 2882 Mb/s (802.11be), 2.4 GHz- 688 Mb/s (802.11be)  
Advanced Functions: Multi-Link Operation (MLO), 320 MHz Channel, 4K-QAM, Multi-RUs, Works with Alexa and Google Assistant  
Wireless Security: WPA-Personal, WPA2-Personal, WPA3-Personal  
Software Features: Quality of Service - WMM, IPv6 Support, WAN Type - Dynamic IP/Static IP/PPPoE, Local Management, Remote Management, DHCP - Server, Client, Port Forwarding Support, Access Control Blacklist, Firewall Security SPI Firewall, Protocols Supports IPv4 and IPv6, Homecare - Antivirus, Parental Controls, Quality of Service, Speedtest, Monthly Usage Reports, Auto FW Update, Expand for more deco, Guest Network 2.4 GHz guest network \* 1 - 5 GHz guest network \* 1, Beamformig, Easy setup by Deco App



**#09374**

Net Price:  
220.00 USD  
Unit: pcs

## Router Mesh Deco BE25 2-pack, BE3600 (TP-Link DECO BE25(2-Pack))

- 3.6 Gbps Dual-Band WiFi - 2882 Mbps (5 GHz) + 688 Mbps (2.4 GHz).
- 2.5 Gbps Wired Connections - 2x 2.5 Gbps ports ensure max flexibility and boosted throughput.
- Wireless and Wired Combined Backhaul - Connects a wireless and wired backhaul with each unit simultaneously to improve overall throughput and reduce latency.
- Multi-Link Operation (MLO) - Simultaneously send and receive data across different bands and channels to increase throughput, reduce latency, and improve reliability.
- Seamless AI-Driven Roaming - Forms a unified network with built-in AI-Roaming creating the ideal Wi-Fi solution for your home.
- TP-Link HomeShield - Provides comprehensive network protection, robust parental controls, and real-time IoT security.
- Universal Compatibility - Backward compatible with all WiFi generations and works with any internet service provider (ISP) and modem.

Standards: IEEE 802.11be/ax/ac/n/a 5 GHz, IEEE 802.11be/ax/n/b/g 2.4 GHz  
Ports: 2x 2.5 Gbps  
Button: 1 Reset button, 1 WPS  
Frequency range: 2.4 GHz, 5 GHz  
Signal Rate: 5 GHz- 2882 Mb/s (802.11be), 2.4 GHz- 688 Mb/s (802.11be)  
Advanced Functions: Multi-Link Operation (MLO), 320 MHz Channel, 4K-QAM, Multi-RUs, Works with Alexa and Google Assistant  
Wireless Security: WPA-Personal, WPA2-Personal, WPA3-Personal  
Software Features: Quality of Service - WMM, IPv6 Support, WAN Type - Dynamic IP/Static IP/PPPoE, Local Management, Remote Management, DHCP - Server, Client, Port Forwarding Support, Access Control Blacklist, Firewall Security SPI Firewall, Protocols Supports IPv4 and IPv6, Homecare - Antivirus, Parental Controls, Quality of Service, Speedtest, Monthly Usage Reports, Auto FW Update, Expand for more deco, Guest Network 2.4 GHz guest network \* 1 - 5 GHz guest network \* 1, Beamformig, Easy setup by Deco App



**#09373**

Net Price:  
304.00 USD  
Unit: pcs

## Router Mesh Deco BE25 3-pack, BE3600 (TP-Link DECO BE25(3-Pack))

- 3.6 Gbps Dual-Band WiFi - 2882 Mbps (5 GHz) + 688 Mbps (2.4 GHz).
- 2.5 Gbps Wired Connections - 2x 2.5 Gbps ports ensure max flexibility and boosted throughput.
- Wireless and Wired Combined Backhaul - Connects a wireless and wired backhaul with each unit simultaneously to improve overall throughput and reduce latency.
- Multi-Link Operation (MLO) - Simultaneously send and receive data across different bands and channels to increase throughput, reduce latency, and improve reliability.
- Seamless AI-Driven Roaming - Forms a unified network with built-in AI-Roaming creating the ideal Wi-Fi solution for your home.
- TP-Link HomeShield - Provides comprehensive network protection, robust parental controls, and real-time IoT security.
- Universal Compatibility - Backward compatible with all WiFi generations and works with any internet service provider (ISP) and modem.

Standards: IEEE 802.11be/ax/ac/n/a 5 GHz, IEEE 802.11be/ax/n/b/g 2.4 GHz  
Ports: 2x 2.5 Gbps  
Button: 1 Reset button, 1 WPS  
Frequency range: 2.4 GHz, 5 GHz  
Signal Rate: 5 GHz- 2882 Mb/s (802.11be), 2.4 GHz- 688 Mb/s (802.11be)  
Advanced Functions: Multi-Link Operation (MLO), 320 MHz Channel, 4K-QAM, Multi-RUs, Works with Alexa and Google Assistant  
Wireless Security: WPA-Personal, WPA2-Personal, WPA3-Personal  
Software Features: Quality of Service - WMM, IPv6 Support, WAN Type - Dynamic IP/Static IP/PPPoE, Local Management, Remote Management, DHCP - Server, Client, Port Forwarding Support, Access Control Blacklist, Firewall Security SPI Firewall, Protocols Supports IPv4 and IPv6, Homecare - Antivirus, Parental Controls, Quality of Service, Speedtest, Monthly Usage Reports, Auto FW Update, Expand for more deco, Guest Network 2.4 GHz guest network \* 1 - 5 GHz guest network \* 1, Beamformig, Easy setup by Deco App



#09372

Net Price:  
374.00 USD  
Unit: pcs

**Router Mesh Deco BE65 1-pack, BE9300 (TP-Link DECO BE65(1-Pack))**

- 9.3 Gbps Tri-Band WiFi - 5764 Mbps (6 GHz) + 2882 Mbps (5 GHz) + 688 Mbps (2.4 GHz).
- 2.5 Gbps Wired Connections - 4× 2.5 Gbps ports ensure max flexibility and boosted throughput.
- Wireless and Wired Combined Backhaul - Connects a wireless and wired backhaul with each unit simultaneously to improve overall throughput and reduce latency.
- Multi-Link Operation (MLO) - Simultaneously send and receive data across different bands and channels to increase throughput, reduce latency, and improve reliability.
- 320 MHz Channels - Double the bandwidth and enables many more simultaneous transmissions at the fastest possible speeds.
- Works on the 6 GHz Band - Minimizes congestion with greenfield spectrum, delivering robust high-speed connections.
- TP-Link HomeShield - Provides comprehensive network protection, robust parental controls, and real-time IoT security.
- Universal Compatibility - Backward compatible with all WiFi generations and works with any internet service provider (ISP) and modem.

Standards: IEEE 802.11be/ax 6 GHz, IEEE 802.11be/ax/ac/n/a 5 GHz, IEEE 802.11ax/n/b/g 2,4 GHz  
Ports: 4× 2.5 Gbps, 1× USB 3.0 Port  
Button: 1 Reset button, 1 WPS  
Frequency range: 2.4 GHz, 5 GHz and 6 GHz  
Signal Rate: 6 GHz- 5760 Mb/s (802.11be), 5 GHz- 2880 Mb/s (802.11be), 2,4 GHz- 574 Mb/s (802.11ax)  
Advanced Functions: Multi-Link Operation (MLO), 320 MHz Channel, 4K-QAM, Multi-RUs, Works with Alexa and Google Assistant  
Wireless Security: WPA-Personal, WPA2-Personal, WPA3-Personal  
Software Features: Quality of Service - WMM, IPv6 Support, WAN Type - Dynamic IP/Static IP/PPPoE, Local Management, Remote Management, DHCP - Server, Client, Port Forwarding Support, Access Control Blacklist, Firewall Security SPI Firewall, Protocols Supports IPv4 and IPv6, Homecare - Antivirus, Parental Controls, Quality of Service, Speedtest, Monthly Usage Reports, Auto FW Update, Expand for more deco, Guest Network 2.4 GHz guest network \* 1 - 5 GHz guest network \* 1, 6 GHz guest network \* 1, Beamformig, Easy setup by Deco App



#09371

Net Price:  
678.00 USD  
Unit: pcs

**Router Mesh Deco BE65 2-pack, BE9300 (TP-Link DECO BE65(2-Pack))**

- 9.3 Gbps Tri-Band WiFi - 5764 Mbps (6 GHz) + 2882 Mbps (5 GHz) + 688 Mbps (2.4 GHz).
- 2.5 Gbps Wired Connections - 4× 2.5 Gbps ports ensure max flexibility and boosted throughput.
- Wireless and Wired Combined Backhaul - Connects a wireless and wired backhaul with each unit simultaneously to improve overall throughput and reduce latency.
- Multi-Link Operation (MLO) - Simultaneously send and receive data across different bands and channels to increase throughput, reduce latency, and improve reliability.
- 320 MHz Channels - Double the bandwidth and enables many more simultaneous transmissions at the fastest possible speeds.
- Works on the 6 GHz Band - Minimizes congestion with greenfield spectrum, delivering robust high-speed connections.
- TP-Link HomeShield - Provides comprehensive network protection, robust parental controls, and real-time IoT security.
- Universal Compatibility - Backward compatible with all WiFi generations and works with any internet service provider (ISP) and modem.

Standards: IEEE 802.11be/ax 6 GHz, IEEE 802.11be/ax/ac/n/a 5 GHz, IEEE 802.11ax/n/b/g 2,4 GHz  
Ports: 4× 2.5 Gbps, 1× USB 3.0 Port  
Button: 1 Reset button, 1 WPS  
Frequency range: 2.4 GHz, 5 GHz and 6 GHz  
Signal Rate: 6 GHz- 5760 Mb/s (802.11be), 5 GHz- 2880 Mb/s (802.11be), 2,4 GHz- 574 Mb/s (802.11ax)  
Advanced Functions: Multi-Link Operation (MLO), 320 MHz Channel, 4K-QAM, Multi-RUs, Works with Alexa and Google Assistant  
Wireless Security: WPA-Personal, WPA2-Personal, WPA3-Personal  
Software Features: Quality of Service - WMM, IPv6 Support, WAN Type - Dynamic IP/Static IP/PPPoE, Local Management, Remote Management, DHCP - Server, Client, Port Forwarding Support, Access Control Blacklist, Firewall Security SPI Firewall, Protocols Supports IPv4 and IPv6, Homecare - Antivirus, Parental Controls, Quality of Service, Speedtest, Monthly Usage Reports, Auto FW Update, Expand for more deco, Guest Network 2.4 GHz guest network \* 1 - 5 GHz guest network \* 1, 6 GHz guest network \* 1, Beamformig, Easy setup by Deco App



#09370

Net Price:  
959.00 USD  
Unit: pcs

**Router Mesh Deco BE65 3-pack, BE9300 (TP-Link DECO BE65(3-Pack))**

- 9.3 Gbps Tri-Band WiFi - 5764 Mbps (6 GHz) + 2882 Mbps (5 GHz) + 688 Mbps (2.4 GHz).
- 2.5 Gbps Wired Connections - 4× 2.5 Gbps ports ensure max flexibility and boosted throughput.
- Wireless and Wired Combined Backhaul - Connects a wireless and wired backhaul with each unit simultaneously to improve overall throughput and reduce latency.
- Multi-Link Operation (MLO) - Simultaneously send and receive data across different bands and channels to increase throughput, reduce latency, and improve reliability.
- 320 MHz Channels - Double the bandwidth and enables many more simultaneous transmissions at the fastest possible speeds.
- Works on the 6 GHz Band - Minimizes congestion with greenfield spectrum, delivering robust high-speed connections.
- TP-Link HomeShield - Provides comprehensive network protection, robust parental controls, and real-time IoT security.
- Universal Compatibility - Backward compatible with all WiFi generations and works with any internet service provider (ISP) and modem.

Standards: IEEE 802.11be/ax 6 GHz, IEEE 802.11be/ax/ac/n/a 5 GHz, IEEE 802.11ax/n/b/g 2,4 GHz  
Ports: 4× 2.5 Gbps, 1× USB 3.0 Port  
Button: 1 Reset button, 1 WPS  
Frequency range: 2.4 GHz, 5 GHz and 6 GHz  
Signal Rate: 6 GHz- 5760 Mb/s (802.11be), 5 GHz- 2880 Mb/s (802.11be), 2,4 GHz- 574 Mb/s (802.11ax)  
Advanced Functions: Multi-Link Operation (MLO), 320 MHz Channel, 4K-QAM, Multi-RUs, Works with Alexa and Google Assistant  
Wireless Security: WPA-Personal, WPA2-Personal, WPA3-Personal  
Software Features: Quality of Service - WMM, IPv6 Support, WAN Type - Dynamic IP/Static IP/PPPoE, Local Management, Remote Management, DHCP - Server, Client, Port Forwarding Support, Access Control Blacklist, Firewall Security SPI Firewall, Protocols Supports IPv4 and IPv6, Homecare - Antivirus, Parental Controls, Quality of Service, Speedtest, Monthly Usage Reports, Auto FW Update, Expand for more deco, Guest Network 2.4 GHz guest network \* 1 - 5 GHz guest network \* 1, 6 GHz guest network \* 1, Beamformig, Easy setup by Deco App



#09369

Net Price:  
1 460.00 USD  
Unit: pcs

**Router Mesh Deco BE85 2-pack, BE19000 (TP-Link DECO BE85(2-Pack))**

- 12-Stream 19 Gbps Tri-Band WiFi - 11520 Mbps (6 GHz) + 5760 Mbps (5 GHz) + 1376 Mbps (2.4 GHz).
- Unprecedented 10 Gbps Network - 1× 10 Gbps Ethernet/Fiber Combo WAN/LAN port + 1× 10 Gbps WAN/LAN port + 2× 2.5 Gbps ports ensure max flexibility and boosted throughput.
- Wireless and Wired Combined Backhaul - Connects a wireless and wired backhaul with each unit simultaneously to improve overall throughput and reduce latency.
- Multi-Link Operation (MLO) - Simultaneously send and receive data across different bands and channels to increase throughput, reduce latency, and improve reliability.
- 320 MHz Channels - Double the bandwidth and enables many more simultaneous transmissions at the fastest possible speeds.
- Works on the 6 GHz Band - Minimizes congestion with greenfield spectrum, delivering robust high-speed connections.
- TP-Link HomeShield - Provides comprehensive network protection, robust parental controls, and real-time IoT security.
- Universal Compatibility - Backward compatible with all WiFi generations and works with any internet service provider (ISP) and modem.

Standards: IEEE 802.11be/ax 6 GHz, IEEE 802.11be/ax/ac/n/a 5 GHz, IEEE 802.11be/ax/n/b/g 2,4 GHz  
Ports: 1× 10 Gbps, 1× 10 Gbps SFP+/RJ45 Combo, 2× 2.5 Gbps, 1× USB 3.0 Port  
Button: 1 Reset button, 1 WPS  
Frequency range: 2.4 GHz, 5 GHz and 6 GHz  
Signal Rate: 6 GHz- 11520 Mb/s (802.11be), 5 GHz- 5760 Mb/s (802.11be), 2,4 GHz- 1376 Mb/s (802.11be)  
Advanced Functions: Multi-Link Operation (MLO), 320 MHz Channel, 4K-QAM, Multi-RUs, Works with Alexa and Google Assistant  
Wireless Security: WPA-Personal, WPA2-Personal, WPA3-Personal



Mikrotik Routerboard		
 <p><b>#08132</b> Net Price: 37.00 USD Unit: pcs</p> <p><b>Routerboard MikroTik RB711-5Hn-uFL</b> CPU: Atheros AR7240 400MHz Memory: 32MB, SDRAM Wireless standards: Built in 5GHz AR9280 802.11a/n card, 1 MMCX/uFL connector (depends on model) Copper ports: 1x 10/100 Mbps RJ-45 Auto MDI/MDI-X: yes Bootloader: RouterBOOT Data storage: 64MB NAND, build-in Speaker: beeper Dimensions: 105x105 mm Power: PoE 10 V + 28 V DC Power consumption: 4.5W Operating system: MikroTik Router OS 2.9 Level 4</p>	 <p><b>#07093</b> Net Price: 38.20 USD Unit: pcs</p> <p><b>Routerboard MikroTik RB750</b> CPU: QCA9533 850 MHz Memory: 64 MB Data storage: 16 MB Copper ports: 5x 10/100 Mbps RJ-45 Ethernet ports Number of DC inputs: 2 (DC jack, PoE-IN) DC jack input Voltage: 6-30 V Max power consumption: 2 W Cooling type: Passive PoE in: Passive PoE PoE in input Voltage: 6-30 V Dimensions: 113x89x28mm Tested ambient temperature: -40°C to 70°C Operating system: RouterOS Certification: CE, EAC, ROHS IP: IP20</p>	 <p><b>#06640</b> Net Price: 41.70 USD Unit: pcs</p> <p><b>Wireless access point 2.4GHz (MikroTik Routerboard RB951Ui-2nD)</b> This small home access point is the perfect device for homes or small offices where all you need is a wireless AP and a few wired devices connected. Based on our popular RB951-2n, the new hAP is an improvement in many areas.</p> <p>The device can be powered from the power jack or with passive PoE from a PoE injector. The power adapter is included.</p> <p>hAP provides PoE output function for port #5 - it can power other PoE capable devices with the same voltage as applied to the unit. Maximum load on the port is 500mA.</p> <p>The hAP is preconfigured, so all you need to do, is plug in the internet cable, the power, and start using the internet by connecting to the MikroTik network.</p> <p>Standards: IEEE 802.11b/g/n Ports: 5x 10/100 Mbps RJ-45, 1x USB Chipset: MIPSBE, QCA9531, 650 MHz Operating memory: 64MB DDR SDRAM Storage size: 16 MB Frequency range: 2.4 - 2.5GHz Antenna: build-in, 2 dBi Beam width: 360° Dimensions: 113 x 89 x 28mm Mounting: mast or wall with the aid of antenna wall support Max. power consumption: 5 W Power: 6 V - 30 V (Jack or Passive PoE) Operating temperatures: -30°C + 70°C Operating humidity: 5% + 95%, non-condensing Certificates: CE, FCC, IC, EAC, ROHS</p>
 <p><b>#06472</b> Net Price: 2.48 USD Unit: pcs</p> <p><b>Adapter Kit, Power over Ethernet</b></p>	 <p><b>#06406</b> Net Price: 3.35 USD Unit: pcs</p> <p><b>Adapter Kit, Power over Ethernet (injector + splitter)</b></p>	 <p><b>#08058</b> Net Price: 3.52 USD Unit: pcs</p> <p><b>Routerboard Power Adapter, 12V 1.0A</b></p>
 <p><b>#06869</b> Net Price: 3.55 USD Unit: pcs</p> <p><b>Routerboard Power Adapter, 12V 1.2A</b></p>	 <p><b>#06404</b> Net Price: 5.72 USD Unit: pcs</p> <p><b>Routerboard Power Adapter, 24V 1.0A</b></p>	 <p><b>#06611</b> Net Price: 14.20 USD Unit: pcs</p> <p><b>Routerboard Power Adapter, 24V 1.6A</b></p>
 <p><b>#06378</b> Net Price: 12.90 USD Unit: pcs</p> <p><b>Routerboard Power Adapter, 48V</b></p>	 <p><b>#06644</b> Net Price: 33.20 USD Unit: pcs</p> <p><b>Routerboard RB604 extension card</b> Extension card for 4 mini-PCI cards. Designed to use with RB600 and RB532A</p>	



## 802.11ax (WiFi 6)



#09041

Net Price:  
46.50 USD  
Unit: pcs**1500Mbps Wireless Gigabit Router Dual-band AX1500, MU-MIMO (TP-Link Archer AX10)**

- Wi-Fi 6 Technology-Archer AX10 comes equipped with the latest wireless technology, Wi-Fi 6, for faster speeds, greater capacity, and reduced network congestion.
- Next-Gen 1.5 Gbps Speeds-Archer AX10 dual-band router reaches even faster speeds up to 1.5 Gbps (1201 Mbps on 5 GHz band and 300 Mbps on 2.4 GHz band).
- Connect Dozens of Devices-More simultaneous connections and reduced latency with OFDMA and MU-MIMO.
- Triple-Core CPU-Instant response to all your network activity with a 1.5 GHz triple-core CPU.
- Broader Coverage-4 Antennas and Beamforming technology focus signal towards individual clients for broader coverage.
- Full Gigabit Ports-Take full advantage of broadband speeds up to 1 Gbps.
- Easy Setup-Finish your network upgrade in minutes with Tether app.
- Compatible with Alexa-Control your router via voice commands and make your life smarter and easier with Amazon Alexa.

## HARDWARE FEATURES:

Standards and Protocols:IEEE 802.11ax/ac/n/a 5GHz, IEEE 802.11b/g/n 2.4GHz, Wi-Fi 6  
Interface:4 10/100/1000Mbps LAN Ports, 1 1G/100Mbps WAN Port,  
Button:WPS/Reset Button, Wireless On/Off Button, Power On/off Button, LED On/Off  
Power Supply: 12V/1A  
Dimensions (W X D X H): 10.2 × 5.3 × 1.5 in (260.2 × 135.0 × 38.6 mm)

Antenna: 4 × External Antennas

## WIRELESS FEATURES:

Frequency:2.4GHz & 5GHz  
Signal Rate: 5 GHz@ 1201 Mbps (802.11ax), 2.4 GHz@ 300 Mbps (802.11n)  
Wireless Functions:Enable/Disable Wireless Radio, Guest Network, DFS, MU-MIMO, OFDMA



#09309

Net Price:  
54.80 USD  
Unit: pcs**1500Mbps Wireless Gigabit Router Dual-band AX1500, MU-MIMO (TP-Link Archer AX12)**

- Wi-Fi 6 Technology-Archer AX12 comes equipped with the latest wireless technology, Wi-Fi 6, for faster speeds, greater capacity and reduced network congestion.
- Next-Gen 1.5 Gbps Speeds-Archer AX12 dual-band router reaches even faster speeds up to 1.5 Gbps (1201 Mbps on 5 GHz band and 300 Mbps on 2.4 GHz band)
- Connect More Devices: Wi-Fi 6 technology communicates more data to more devices using revolutionary OFDMA and MU-MIMO technology while simultaneously reducing lag.
- More Reliable Coverage: Achieve the strongest, most reliable WiFi coverage with Archer AX12 as it focuses signal strength to your devices using Beamforming technology and four antennas.
- Increased Battery Life: Target Wake Time technology reduces your devices' power consumption to extend their battery life.
- Easy Setup: Set up your router in minutes with the powerful TP-Link Tether App.
- Backward Compatible: Archer AX12 supports all previous 802.11 standards and all WiFi devices.

## HARDWARE FEATURES:

Standards and Protocols:IEEE 802.11ax/ac/n/a 5GHz, IEEE 802.11b/g/n 2.4GHz, Wi-Fi 6  
Interface:3 10/100/1000Mbps LAN Ports, 1 1G/100Mbps WAN Port,  
Button:WPS/Reset Button, Wireless On/Off Button, Power On/off Button, LED On/Off  
Power Supply: 12V/1A  
Dimensions (W X D X H): 8.5 × 4.6 × 1.3 in (215 × 117 × 32 mm)

Antenna: 4 × External Antennas

## WIRELESS FEATURES:

Frequency:2.4GHz & 5GHz  
Signal Rate: 5 GHz@ 1201 Mbps (802.11ax), 2.4 GHz@ 300 Mbps (802.11n)  
Wireless Functions:Enable/Disable Wireless Radio, Guest Network, DFS, MU-MIMO, OFDMA

NEW



#09394

Net Price:  
46.50 USD  
Unit: pcs**1500Mbps Wireless Gigabit Router Dual-band AX1500, MU-MIMO (TP-Link Archer AX1500)**

- Wi-Fi 6 Technology-Archer AX10 comes equipped with the latest wireless technology, Wi-Fi 6, for faster speeds, greater capacity, and reduced network congestion.
- Next-Gen 1.5 Gbps Speeds-Archer AX10 dual-band router reaches even faster speeds up to 1.5 Gbps (1201 Mbps on 5 GHz band and 300 Mbps on 2.4 GHz band).
- Connect Dozens of Devices-More simultaneous connections and reduced latency with OFDMA and MU-MIMO.
- Triple-Core CPU-Instant response to all your network activity with a 1.5 GHz triple-core CPU.
- Broader Coverage-4 Antennas and Beamforming technology focus signal towards individual clients for broader coverage.
- Full Gigabit Ports-Take full advantage of broadband speeds up to 1 Gbps.
- Easy Setup-Finish your network upgrade in minutes with Tether app.
- Backward Compatible: Archer AX1500 supports all previous 802.11 standards and all WiFi devices.

## HARDWARE FEATURES:

Standards and Protocols:IEEE 802.11ax/ac/n/a 5GHz, IEEE 802.11b/g/n 2.4GHz, Wi-Fi 6  
Interface:4 10/100/1000Mbps LAN Ports, 1 1G/100Mbps WAN Port,  
Button:WPS/Reset Button, Wireless On/Off Button, Power On/off Button, LED On/Off  
Power Supply: 12V/1.5A  
Dimensions (W X D X H): 10.2 × 5.3 × 1.5 in (260.2 × 135.0 × 38.6 mm)

Antenna: 4 × External Antennas

## WIRELESS FEATURES:

Frequency:2.4GHz & 5GHz  
Signal Rate: 5 GHz@ 1201 Mbps (802.11ax), 2.4 GHz@ 300 Mbps (802.11n)  
Wireless Functions:Enable/Disable Wireless Radio, Guest Network, DFS, MU-MIMO, OFDMA

NEW



#09395

Net Price:  
34.80 USD  
Unit: pcs**1500Mbps Wireless Gigabit Router Dual-band AX1500, MU-MIMO (TP-Link Archer AX17)**

- Wi-Fi 6 Technology-Archer AX17 comes equipped with the latest wireless technology, Wi-Fi 6, for faster speeds, greater capacity and reduced network congestion.
- Next-Gen 1.5 Gbps Speeds-Archer AX17 dual-band router reaches even faster speeds up to 1.5 Gbps (1201 Mbps on 5 GHz band and 300 Mbps on 2.4 GHz band)
- Connect More Devices: Wi-Fi 6 technology communicates more data to more devices using revolutionary OFDMA and MU-MIMO technology while simultaneously reducing lag.
- More Reliable Coverage: Achieve the strongest, most reliable WiFi coverage with Archer AX17 as it focuses signal strength to your devices using Beamforming technology and four antennas.
- Increased Battery Life: Target Wake Time technology reduces your devices' power consumption to extend their battery life.
- Easy Setup: Set up your router in minutes with the powerful TP-Link Tether App.
- Backward Compatible: Archer AX17 supports all previous 802.11 standards and all WiFi devices.

## HARDWARE FEATURES:

Standards and Protocols:IEEE 802.11ax/ac/n/a 5GHz, IEEE 802.11b/g/n 2.4GHz, Wi-Fi 6  
Interface:3 10/100/1000Mbps LAN Ports, 1 1G/100Mbps WAN Port,  
Button:WPS/Reset Button, Wireless On/Off Button, Power On/off Button, LED On/Off  
Power Supply: 12V/1A  
Dimensions (W X D X H): 8.5 × 4.6 × 1.3 in (215 × 117 × 32 mm)

Antenna: 4 × External Antennas

## WIRELESS FEATURES:

Frequency:2.4GHz & 5GHz  
Signal Rate: 5 GHz@ 1201 Mbps (802.11ax), 2.4 GHz@ 300 Mbps (802.11n)  
Wireless Functions:Enable/Disable Wireless Radio, Guest Network, DFS, MU-MIMO, OFDMA



#09525

Net Price:  
28.40 USD  
Unit: pcs**1500Mbps Wireless Range Extender, AX1500 (TP-Link Mercusys ME60X)**

- Dual Band Speeds up to 1800 Mbps - 1201 Mbps on 5 GHz and 300 Mbps on 2.4 GHz.
- Armed with WiFi 6 - Improves virtually every aspect of your network: speed, efficiency, and capacity.
- Gigabit Wired Connection - Provides speedy wired connections for PCS, IPTVS.and game consoles.
- Works with Any Routers - To Extend WiFi to Where You Need It Most.
- Easy One-Touch Setup - Press the WPS button to expand your Wi-Fi coverage in seconds.
- Built-In Access Point Mode - Works as RE mode and AP mode.
- Manage Your Network with App - Set up in minutes and manage your Wi-Fi at home or away through your iOS or Android devices.

## HARDWARE FEATURES:

Ports: 1 \* 10/100/1000M Ethernet Port (RJ45)  
Plug Type: EU  
Button:WPS Button, Reset Button  
Power Consumption:About 10W  
Wireless Standards:IEEE802.11ax, IEEE802.11ac,IEEE 802.11n, IEEE 802.11g, IEEE 802.11b  
Dimensions ( W x D x H ): 84.7 × 39 × 112 mm

## WIRELESS FEATURES:

Frequency:2.4GHz & 5GHz  
Signal Rate: 5GHz Up to 1201Mbps, 2.4GHz Up to 300Mbps  
Wireless Security: WPA-PSK/WPA2-PSK  
OTHERS  
Certification:CE, RoHS  
Package Contents:ME60X, Quick Installation Guide



#09219

Net Price:  
51.20 USD  
Unit: pcs**1500Mbps Wireless Range Extender, AX1500 (TP-Link RE500X)**

- RE500X comes equipped with the latest wireless technology, Wi-Fi 6, for faster speeds, greater capacity, and reduced network congestion.
- Creates a Mesh network by connecting to a OneMesh router for seamless whole-home coverage.
- Gigabit Ethernet Port - Provide faster-wired connections to smart TVs, computers and gaming consoles
- Intelligent Signal Light - Helps to determine the best location for optimal Wi-Fi coverage by indicating the signal strength in the current placement
- AP Mode - create a new Wi-Fi access point to enhance your wired network with Wi-Fi capability
- TP-LINK Tether App - Easily access and manage your network using any iOS or Android mobile device
- Ultimate Compatibility - Extend the range of any Wi-Fi router or wireless access point

## HARDWARE FEATURES:

Ports: 1 Gigabit Ethernet Port  
Plug Type: EU  
Button:Reset Button, WPS Button  
Power Consumption:About 10W  
Wireless Standards:IEEE802.11ac,IEEE 802.11n, IEEE 802.11g, IEEE 802.11b  
Dimensions ( W x D x H ): 78×36×149 mm

## WIRELESS FEATURES:

Frequency:2.4GHz & 5GHz  
Signal Rate: 300 Mbps at 2.4GHz, 1200 Mbps at 5GHz  
EIRP:CE 2.4 GHz <= 20 dBm, 5 GHz <= 30 dBm  
Wireless Modes:Range Extender  
Wireless Functions: WMM (Wi-Fi Multimedia), Wireless Statistic, Domain Login Function



#09063

Net Price:  
51.20 USD  
Unit: pcs

**1500Mbps Wireless Range Extender, AX1500 (TP-Link RE505X)**

- RE505X comes equipped with the latest wireless technology, Wi-Fi 6, for faster speeds, greater capacity, and reduced network congestion.
- Creates a Mesh network by connecting to a OneMesh router for seamless whole-home coverage.
- Gigabit Ethernet Port - Provide faster-wired connections to smart TVs, computers and gaming consoles
- Intelligent Signal Light - Helps to determine the best location for optimal Wi-Fi coverage by indicating the signal strength in the current placement
- AP Mode - create a new Wi-Fi access point to enhance your wired network with Wi-Fi capability
- TP-LINK Tether App - Easily access and manage your network using any iOS or Android mobile device
- Ultimate Compatibility - Extend the range of any Wi-Fi router or wireless access point

**HARDWARE FEATURES:**

Ports: 1 Gigabit Ethernet Port  
Plug Type: EU  
Button: Reset Button, WPS Button  
Power Consumption: About 10W  
Wireless Standards: IEEE802.11ac, IEEE 802.11n, IEEE 802.11g, IEEE 802.11b  
Dimensions (W x D x H): 74.0 x 46 x 124.8 mm  
Antenna Type: 2 x External Antennas

**WIRELESS FEATURES**

Frequency: 2.4GHz & 5GHz  
Signal Rate: 300 Mbps at 2.4GHz, 1200 Mbps at 5GHz  
EIRP: CE 2.4 GHz <= 20 dBm, 5 GHz <= 30 dBm  
Wireless Modes: Range Extender  
Wireless Functions: WMM (Wi-Fi Multimedia), Wireless Statistic, Domain Login Function



#09190

Net Price:  
75.60 USD  
Unit: pcs

**1800Mbps Outdoor Wireless Access Point, AX1800 (TP-Link EAP615-Wall)**

- Superior WiFi 6 Speeds: Simultaneous 574 Mbps on 2.4 GHz and 1201 Mbps on 5 GHz totals 1775 Mbps Wi-Fi speeds.
- High-Performance Connectivity: Guarantee higher network efficiency and lower latency.
- Four Gigabit Ports: 4 Gigabit Ethernet ports (1x uplink + 3x downlink), with one downlink port supporting PoE pass-through to provide power for wired device.
- Centralized Management: Integrates into Omada SDN for cloud access and remote management.
- Secure Guest Network: Along with multiple authentication options (SMS/Facebook Wi-Fi Voucher, etc.) and abundant wireless security technologies.
- Easy Installation and PoE Support: Easy-to-install design, compatible with 86 mm & EU & US standard junction box, and 802.3af/at PoE support.

Standards: IEEE 802.11ax/ac/n/g/b/a  
Ports: 10/100/1000Mbps (RJ-45) Port \*1, Downlink-10/100/1000Mbps Ethernet Port\*3 (One port supports PoE OUT. The PoE OUT feature requires 802.3at PoE+ input and the maximum output is 13W.)  
Frequency range: 2.4GHz and 5GHz  
Signal Rate: 5GHz Up to 1201Mbps, 2.4GHz Up to 574Mbps  
EIRP: CE <20dBm(2.4GHz) <23dBm(5GHz), FCC <27dBm  
Wireless Functions: Multiple SSIDs (Up to 16 SSIDs, 8 for each band), Enable/Disable Wireless Radio, Automatic Channel Assignment, Transmit Power Control (Adjust Transmit Power on dBm), QoS(WMM), Airtime Fairness, Beamforming, Band Steering, Load Balance, Rate Limit, Link Aggregation, Reboot Schedule, Wireless Schedule, Wireless Statistics based on SSID/AP/Client



#09091

Net Price:  
110.00 USD  
Unit: pcs

**1800Mbps Outdoor Wireless Access Point, AX1800 (TP-Link EAP620 HD)**

- Ultra-Fast Wi-Fi 6 Speeds: Simultaneous 574 Mbps on 2.4 GHz and 1201 Mbps on 5 GHz totals 1775 Mbps Wi-Fi speeds.
- High-Density Connectivity: 4x increased capacity to connect more devices simultaneously.
- Integrated into Omada SDN: Zero-Touch Provisioning (ZTP), Centralized Cloud Management, and Intelligent Monitoring.
- Centralized Management: Cloud access and Omada app for ultra convenience and easy management.
- Seamless Roaming: Even video streams and voice calls are unaffected as users move between locations.
- PoE+ Support: Supports Power over Ethernet (802.3at) for convenient deployment and installation.
- Secure Guest Network: Along with multiple authentication options (SMS/Facebook Wi-Fi Voucher, etc.) and abundant wireless security technologies.

Standards: IEEE 802.11ax/ac/n/g/b/a  
Ports: 1x Gigabit Ethernet (RJ-45) Port (supports IEEE802.3at PoE)  
Button: Reset  
Frequency range: 2.4GHz and 5GHz  
Signal Rate: 5GHz Up to 1201Mbps, 2.4GHz Up to 574Mbps  
EIRP: CE <20dBm(2.4GHz) <23dBm(5GHz), FCC <27dBm  
Wireless Functions: Multiple SSIDs (Up to 16 SSIDs, 8 for each band), Enable/Disable Wireless Radio, Automatic Channel Assignment, Transmit Power Control (Adjust Transmit Power on dBm), QoS(WMM), Airtime Fairness, Beamforming, Band Steering, Load Balance, Rate Limit, Link Aggregation, Reboot Schedule, Wireless Schedule, Wireless Statistics based on SSID/AP/Client



#09189

Net Price:  
70.60 USD  
Unit: pcs

**1800Mbps Wireless Access Point, AX1800 (TP-Link EAP610)**

- Ultra-Fast WiFi 6 Speeds: Simultaneous 574 Mbps on 2.4 GHz and 1201 Mbps on 5 GHz totals 1775 Mbps Wi-Fi speeds.
- High-Efficiency WiFi 6: More connected devices can enjoy faster speeds.
- Centralized Cloud Management: Manage the whole network locally or from the cloud via web UI or Omada app.
- Seamless Roaming: Even video streams and voice calls are unaffected as users move between locations.
- Omada Mesh: Enables wireless connectivity between access points for extended range and flexible deployment.
- PoE+ Powered: Supports both Power over Ethernet (802.3at) and DC power supply for flexible installations.
- Secure Guest Network: Along with multiple authentication options (SMS/Facebook Wi-Fi Voucher, etc.) and abundant wireless security technologies.

Standards: IEEE 802.11ax/ac/n/g/b/a  
Ports: 1x Gigabit Ethernet (RJ-45) Port (supports IEEE802.3at PoE)  
Button: Reset  
Frequency range: 2.4GHz and 5GHz  
Signal Rate: 5GHz Up to 1201Mbps, 2.4GHz Up to 574Mbps  
EIRP: CE <20dBm(2.4GHz) <23dBm(5GHz), FCC <27dBm  
Wireless Functions: Multiple SSIDs (Up to 16 SSIDs, 8 for each band), Enable/Disable Wireless Radio, Automatic Channel Assignment, Transmit Power Control (Adjust Transmit Power on dBm), QoS(WMM), Airtime Fairness, Beamforming, Band Steering, Load Balance, Rate Limit, Link Aggregation, Reboot Schedule, Wireless Schedule, Wireless Statistics based on SSID/AP/Client



#09215

Net Price:  
145.00 USD  
Unit: pcs

**1800Mbps Wireless Access Point, AX1800 (TP-Link EAP610-Outdoor)**

- Superior WiFi 6 Speeds: Delivers dual-band speeds of up to 1.8 Gbps powered by the latest WiFi 6 technology
- Higher Network Efficiency: Enjoy faster speeds on more devices with less lag via OFDMA and MU-MIMO
- Long-Range Coverage: Dedicated high-power amplifier and professional antennas with IP67 weatherproof enclosure
- Omada Mesh Technology: Enables wireless connectivity between access points for extended range and flexible deployment
- Stay Smooth with Fast Roaming: Users can enjoy seamless streaming across the property with their devices switching effortlessly between access points
- Centralized Cloud Management: Integrates into Omada SDN for cloud access and remote management

Standards: IEEE 802.11ax/ac/n/g/b/a  
Ports: 1x Gigabit Ethernet (RJ-45) Port (supports IEEE802.3at PoE and Passive PoE)  
Button: Reset  
Frequency range: 2.4GHz and 5GHz  
Signal Rate: 5GHz Up to 1201Mbps, 2.4GHz Up to 574Mbps  
EIRP: CE <20dBm(2.4GHz) <23dBm(5GHz), FCC <27dBm  
Wireless Functions: Multiple SSIDs (Up to 16 SSIDs, 8 for each band), Enable/Disable Wireless Radio, Automatic Channel Assignment, Transmit Power Control (Adjust Transmit Power on dBm), QoS(WMM), Airtime Fairness, Beamforming, Band Steering, Load Balance, Rate Limit, Link Aggregation, Reboot Schedule, Wireless Schedule, Wireless Statistics based on SSID/AP/Client



#09252

Net Price:  
67.70 USD  
Unit: pcs

**1800Mbps Wireless Access Point, AX1800 (TP-Link EAP613)**

- Ultra-Fast WiFi 6 Speeds: Simultaneous 574 Mbps on 2.4 GHz and 1201 Mbps on 5 GHz totals 1775 Mbps Wi-Fi speeds.
- High-Efficiency WiFi 6: More connected devices can enjoy faster speeds.
- Centralized Cloud Management: Manage the whole network locally or from the cloud via web UI or Omada app.
- Seamless Roaming: Even video streams and voice calls are unaffected as users move between locations.
- Omada Mesh: Enables wireless connectivity between access points for extended range and flexible deployment.
- PoE+ Powered: Supports both Power over Ethernet (802.3at) and DC power supply for flexible installations.
- Secure Guest Network: Along with multiple authentication options (SMS/Facebook Wi-Fi Voucher, etc.) and abundant wireless security technologies.

Standards: IEEE 802.11ax/ac/n/g/b/a  
Ports: 1x Gigabit Ethernet (RJ-45) Port (supports IEEE802.3at PoE)  
Button: Reset  
Frequency range: 2.4GHz and 5GHz  
Signal Rate: 5GHz Up to 1201Mbps, 2.4GHz Up to 574Mbps  
EIRP: CE <20dBm(2.4GHz) <23dBm(5GHz), FCC <27dBm  
Wireless Functions: Multiple SSIDs (Up to 16 SSIDs, 8 for each band), Enable/Disable Wireless Radio, Automatic Channel Assignment, Transmit Power Control (Adjust Transmit Power on dBm), QoS(WMM), Airtime Fairness, Beamforming, Band Steering, Load Balance, Rate Limit, Link Aggregation, Reboot Schedule, Wireless Schedule, Wireless Statistics based on SSID/AP/Client



NEW



#09453

Net Price:  
150.00 USD  
Unit: pcs

**1800Mbps Wireless Access Point, AX1800 (TP-Link EAP623-Outdoor HD)**

- Up to 1.8 Gbps WiFi 6 Speeds: 574 Mbps on 2.4 GHz + 1201 Mbps on 5 GHz.
- Supports WiFi 6 technologies, such as 1024-QAM, OFDMA, etc.
- High-density connectivity up to 1,000+ clients.
- Long-range coverage with the high-power amplifier and 2x detachable antennas.
- IP67 weatherproof enclosure for various outdoor environments.
- Advanced Functions: Centralized management, Omada mesh, and seamless roaming.
- PoE+ Powered: Supports both 802.3at PoE (adapter not included).

Standards: IEEE 802.11ax/ac/n/g/b/a  
Ports: 1x Gigabit Ethernet (RJ-45) Port (supports IEEE802.3at PoE and Passive PoE)

Bluetooth: Yes

Button: Reset

Frequency range: 2.4GHz and 5GHz

Signal Rate: 5GHz Up to 1201Mbps, 2.4GHz Up to 574Mbps  
EIRP: CE <20dBm(2.4GHz) <23dBm(5GHz), FCC <27dBm  
Wireless Functions: Multiple SSIDs (Up to 16 SSIDs, 8 for each band), Enable/Disable Wireless Radio, Automatic Channel Assignment, Transmit Power Control (Adjust Transmit Power on dBm), QoS(WMM), Airtime Fairness, Beamforming, Band Steering, Load Balance, Rate Limit, Link Aggregation, Reboot Schedule, Wireless Schedule, Wireless Statistics based on SSID/AP/Client



#09452

Net Price:  
168.00 USD  
Unit: pcs

**1800Mbps Wireless Access Point, AX1800 (TP-Link EAP625-Outdoor HD)**

- Up to 1.8 Gbps WiFi 6 Speeds: 574 Mbps on 2.4 GHz + 1201 Mbps on 5 GHz.
- Supports WiFi 6 technologies, such as 1024-QAM, OFDMA, etc.
- High-density connectivity up to 1,000+ clients.
- Long-range coverage with the high-power amplifier and 2x detachable antennas.
- IP67 weatherproof enclosure for various outdoor environments.
- Advanced Functions: Centralized management, Omada mesh, and seamless roaming.
- PoE+ Powered: Supports both 802.3at PoE (adapter not included).

Standards: IEEE 802.11ax/ac/n/g/b/a  
Ports: 1x Gigabit Ethernet (RJ-45) Port (supports IEEE802.3at PoE and Passive PoE)

Bluetooth: Yes

Button: Reset

Frequency range: 2.4GHz and 5GHz

Signal Rate: 5GHz Up to 1201Mbps, 2.4GHz Up to 574Mbps  
EIRP: CE <20dBm(2.4GHz) <23dBm(5GHz), FCC <27dBm  
Wireless Functions: Multiple SSIDs (Up to 16 SSIDs, 8 for each band), Enable/Disable Wireless Radio, Automatic Channel Assignment, Transmit Power Control (Adjust Transmit Power on dBm), QoS(WMM), Airtime Fairness, Beamforming, Band Steering, Load Balance, Rate Limit, Link Aggregation, Reboot Schedule, Wireless Schedule, Wireless Statistics based on SSID/AP/Client



#09310

Net Price:  
25.50 USD  
Unit: pcs

**1800Mbps Wireless Dual Band PCI-Express AX1800, Wi-Fi 6, Bluetooth 5.2 (TP-Link Archer TX20E)**

- Unrivaled Wi-Fi 6 Speed-Breaks the gigabit barrier with speed up to 1201 Mbps (5 GHz) + 574 Mbps (2.4 GHz)
- Smoother Experience-75% lower latency ensures ultra-responsive gaming, uninterrupted video chatting and seamless live streaming
- Reliable Connections-IntelC Wi-Fi 6 chipset brings faster and clearer Wi-Fi to fully unlock the potential of your Wi-Fi 6 router
- Wider Signal Coverage- Connect to your Wi-Fi in more parts of your home with two external high-gain antennas ensuring greater coverage and enhanced stability
- Bluetooth 5.2-The latest Bluetooth technology achieves 2x Faster Speed and 4x Broader Coverage than BT 4.2
- Improved Security-The latest security enhancements WPA3 provides enhanced protection in personal password safety
- Fine Crafting-Specialized heatsink and gold plating is crafted to improve stability and reliability even in hot environments
- Backward Compatibility - Full support for 802.11ac/a/b/g/n standards

**HARDWARE FEATURES:**

Interface:PCI Express x1

Antenna Type: Two High-Gain Dual Band Antennas

Chipset: Intel Wi-Fi 6 Chipset

**WIRELESS FEATURES:**

Wireless Standards:5 GHz@ IEEE 802.11ax/ac/n/a, 2.4 GHz@ IEEE 802.11ax/n/g/b, Bluetooth 5.2  
Frequency: 2.4-2.4835GHz, 5.180-5.240GHz, 5.745-5.825GHz

Signal Rate: 1201Mbps at 5GHz, 574Mbps at 2.4GHz

EIRP:5 GHz @ 27 dBm (FCC) / 23 dBm (CE) (EIRP), 2.4 GHz @ 25 dBm (FCC) / 20 dBm (CE) (EIRP)

Wireless Modes: Infrastructure mode

Wireless Security:Support 64/128 bit WEP, WPA/WAP2/WPA3, WPA-PSK/WPA2-PSK, 802.1x

NEW



#09393

Net Price:  
46.50 USD  
Unit: pcs

**1800Mbps Wireless Gigabit Router Dual-band AX1800, MU-MIMO (TP-Link Archer AX1800)**

- Super-Fast 1.8 Gbps Wi-Fi - Enjoy smooth 4K streaming and downloading with super-fast Wi-Fi speeds of 1.8 Gbps.
- Connect More Devices - Communicates with more devices using OFDMA while simultaneously reducing lag.
- Broader Coverage - Improved algorithm, beamforming, and high-performance antennas enhance the Wi-Fi coverage performance.
- Next-Gen Platform - The Next-Gen High-Efficiency Chipset provides fast and stable Wi-Fi while saving power consumption.
- Parental Controls - Enjoy the most versatile yet free parental controls features among all routers, including URL blocking, profile management, pausing, and more.
- Works with Most ISPs - Compatible with most ISPs with extra L2TP/PPTP support. IPTV support works with your existing TV over the Internet contract.
- OneMesh - Use with OneMesh extenders to get whole-home coverage and enjoy smooth roaming between signals.
- Easy Setup - Set up your router in minutes with the powerful TP-Link Tether App.
- Backward Compatible - Supports all previous 802.11 standards Wi-Fi devices.

**HARDWARE FEATURES:**

Standards and Protocols:IEEE 802.11ax/ac/n/a 5GHz, IEEE 802.11ax/b/g/n 2.4GHz, Wi-Fi 6  
Interface:4 10/100/1000Mbps LAN Ports, 1 1G/100Mbps WAN Port

Button:WPS/Reset Button, Wireless On/Off Button, Power On/Off Button, LED On/Off

Power Supply: 12V/1A

Dimensions (W X D X H): 10.2 x 5.3 x 1.5 in (260.2 x 135.0 x 38.6 mm)

Antenna: 4 x External Antennas

**WIRELESS FEATURES:**

Frequency:2.4GHz &amp; 5GHz

Signal Rate: 5 GHz@ 1201 Mbps (802.11ax), 2.4 GHz@ 574 Mbps (802.11ax)

Wireless Functions:Enable/Disable Wireless Radio, Guest Network, DFS, MU-MIMO, OFDMA



#09182

Net Price:  
46.50 USD  
Unit: pcs

**1800Mbps Wireless Gigabit Router Dual-band AX1800, MU-MIMO (TP-Link Archer AX23)**

- Super-Fast 1.8 Gbps Wi-Fi - Enjoy smooth 4K streaming and downloading with super-fast Wi-Fi speeds of 1.8 Gbps.
- Connect More Devices - Communicates with more devices using OFDMA while simultaneously reducing lag.
- Broader Coverage - Improved algorithm, beamforming, and high-performance antennas enhance the Wi-Fi coverage performance.
- Next-Gen Platform - The Next-Gen High-Efficiency Chipset provides fast and stable Wi-Fi while saving power consumption.
- Parental Controls - Enjoy the most versatile yet free parental controls features among all routers, including URL blocking, profile management, pausing, and more.
- Works with Most ISPs - Compatible with most ISPs with extra L2TP/PPTP support. IPTV support works with your existing TV over the Internet contract.
- OneMesh - Use with OneMesh extenders to get whole-home coverage and enjoy smooth roaming between signals.
- Easy Setup - Set up your router in minutes with the powerful TP-Link Tether App.
- Backward Compatible - Supports all previous 802.11 standards Wi-Fi devices.

**HARDWARE FEATURES:**

Standards and Protocols:IEEE 802.11ax/ac/n/a 5GHz, IEEE 802.11ax/b/g/n 2.4GHz, Wi-Fi 6  
Interface:4 10/100/1000Mbps LAN Ports, 1 1G/100Mbps WAN Port

Button:WPS/Reset Button, Wireless On/Off Button, Power On/Off Button, LED On/Off

Power Supply: 12V/1A

Dimensions (W X D X H): 10.2 x 5.3 x 1.5 in (260.2 x 135.0 x 38.6 mm)

Antenna: 4 x External Antennas

**WIRELESS FEATURES:**

Frequency:2.4GHz &amp; 5GHz

Signal Rate: 5 GHz@ 1201 Mbps (802.11ax), 2.4 GHz@ 574 Mbps (802.11ax)

Wireless Functions:Enable/Disable Wireless Radio, Guest Network, DFS, MU-MIMO, OFDMA



#09109

Net Price:  
37.30 USD  
Unit: pcs

**1800Mbps Wireless Gigabit Router Dual-band AX1800, MU-MIMO (TP-Link Marcusys MR70X)**

- Next-Gen WiFi 6 Speeds - Optimal WiFi 6 speeds reaching up to 1.8 Gbps (1201 Mbps on the 5 GHz band and 574 Mbps on the 2.4 GHz band)
- 4x More Capacity - OFDMA and MU-MIMO allow simultaneous data transmission to and from several devices, improving overall network efficiency
- Broader, Stronger Coverage - 4x multi-directional high-gain antennas with Beamforming boost stable connections throughout your home for strong WiFi signals in every corner
- Overall Security Protection - The latest WPA3 provides improved WiFi security
- Gigabit Wired Connections - Make full use of your internet access and transfer data at dizzying speeds for peak performance
- Eco-Friendly Power Saving - Target Wake Time (TWT) reduces power consumption for your mobile and IoT devices during data transmissions
- Less WiFi Interference - Minimizes the interference from neighboring signals to improve transmission efficiency with BSS color
- Smart Connect - Intelligently chooses the best available band for each device
- Access Point Mode - Extends a wired network and makes it wireless

**HARDWARE FEATURES:**

Standards and Protocols:IEEE 802.11ax/ac/n/a 5GHz, IEEE 802.11ax/b/g/n 2.4GHz, Wi-Fi 6  
Interface:3 10/100/1000Mbps LAN Ports, 1 1G/100Mbps WAN Port

Button:WPS/Reset Button

Dimensions (W X D X H): 8.2 x 6.8 x 1.6 in (208.8 x 171.6 x 41.7 mm)

Antenna: 4x 5 dBi Fixed Omni-Directional Antennas

**WIRELESS FEATURES:**

Frequency:2.4GHz &amp; 5GHz

Signal Rate: 5 GHz@ 1201 Mbps (802.11ax), 2.4 GHz@ 574 Mbps (802.11ax)

Wireless Functions:Enable/Disable Wireless Radio, WMM

Wireless Security:WPA-PSK / WPA2-PSK/ WPA3





#09265

Net Price:  
39.40 USD  
Unit: pcs

**1800Mbps Wireless Range Extender, AX1800 (TP-Link Mercusys ME70X)**

- Dual Band Speeds up to 1800 Mbps - 1201 Mbps on 5 GHz and 574 Mbps on 2.4 GHz.
- Armed with WiFi 6 - Improves virtually every aspect of your network: speed, efficiency, and capacity.
- Gigabit Wired Connection - Provides speedy wired connections for PCS, IPTVS, and game consoles.
- Works with Any Routers - To Extend WiFi to Where You Need It Most.
- Easy One-Touch Setup - Press the WPS button to expand your Wi-Fi coverage in seconds.
- Built-In Access Point Mode - Works as RE mode and AP mode.
- Manage Your Network with App - Set up in minutes and manage your Wi-Fi at home or away through your iOS or Android devices.

**HARDWARE FEATURES:**

Ports: 1 \* 10/100/1000M Ethernet Port (RJ45)

Plug Type: EU

Button: WPS Button, Reset Button

Power Consumption: About 13W

Wireless Standards: IEEE802.11ax, IEEE802.11ac, IEEE802.11n, IEEE 802.11g, IEEE 802.11b

Dimensions (W x D x H): 138,6 x 100,3 x 68,4 mm

Antenna Type: 2 x external

**WIRELESS FEATURES**

Frequency: 2.4GHz & 5GHz

Signal Rate: 5GHz Up to 1201Mbps, 2.4GHz Up to 574Mbps

EIRP: < 20 dBm

Wireless Security: WPA-PSK/WPA2-PSK

OTHERS

Certification: CE, RoHS

Package Contents: ME70X, Quick Installation Guide



#09220

Net Price:  
58.20 USD  
Unit: pcs

**1800Mbps Wireless Range Extender, AX1800 (TP-Link RE600X)**

- RE600X comes equipped with the latest wireless technology, Wi-Fi 6, for faster speeds, greater capacity, and reduced network congestion.
- Creates a Mesh network by connecting to a OneMesh router for seamless whole-home coverage.
- Gigabit Ethernet Port - Provide faster-wired connections to smart TVs, computers and gaming consoles
- Intelligent Signal Light - Helps to determine the best location for optimal Wi-Fi coverage by indicating the signal strength in the current placement
- AP Mode - create a new Wi-Fi access point to enhance your wired network with Wi-Fi capability
- TP-LINK Tether App - Easily access and manage your network using any iOS or Android mobile device
- Ultimate Compatibility - Extend the range of any Wi-Fi router or wireless access point

**HARDWARE FEATURES:**

Ports: 1 Gigabit Ethernet Port

Plug Type: EU

Button: Reset Button, WPS Button

Power Consumption: About 10W

Wireless Standards: IEEE802.11ac, IEEE 802.11n, IEEE 802.11g, IEEE 802.11b

Dimensions (W x D x H): 78x36x149 mm

Antenna Type: 2 x Internal Antennas

**WIRELESS FEATURES**

Frequency: 2.4GHz & 5GHz

Signal Rate: 574 Mbps at 2.4GHz, 1201 Mbps at 5GHz

EIRP: CE 2.4 GHz <= 15 dBm, 5 GHz <= 21 dBm

Wireless Modes: Range Extender

Wireless Functions: WMM (Wi-Fi Multimedia), Wireless Statistic, Domain Login Function



#09128

Net Price:  
60.60 USD  
Unit: pcs

**1800Mbps Wireless Range Extender, AX1800 (TP-Link RE605X)**

- RE605X comes equipped with the latest wireless technology, Wi-Fi 6, for faster speeds, greater capacity, and reduced network congestion.
- Creates a Mesh network by connecting to a OneMesh router for seamless whole-home coverage.
- Gigabit Ethernet Port - Provide faster-wired connections to smart TVs, computers and gaming consoles
- Intelligent Signal Light - Helps to determine the best location for optimal Wi-Fi coverage by indicating the signal strength in the current placement
- AP Mode - create a new Wi-Fi access point to enhance your wired network with Wi-Fi capability
- TP-LINK Tether App - Easily access and manage your network using any iOS or Android mobile device
- Ultimate Compatibility - Extend the range of any Wi-Fi router or wireless access point

**HARDWARE FEATURES:**

Ports: 1 Gigabit Ethernet Port

Plug Type: EU

Button: Reset Button, WPS Button

Power Consumption: About 10W

Wireless Standards: IEEE802.11ac, IEEE 802.11n, IEEE 802.11g, IEEE 802.11b

Dimensions (W x D x H): 74,0 x 46 x 124,8 mm

Antenna Type: 2 x External Antennas

**WIRELESS FEATURES**

Frequency: 2.4GHz & 5GHz

Signal Rate: 574 Mbps at 2.4GHz, 1201 Mbps at 5GHz

EIRP: CE 2.4 GHz <= 15 dBm, 5 GHz <= 21 dBm

Wireless Modes: Range Extender

Wireless Functions: WMM (Wi-Fi Multimedia), Wireless Statistic, Domain Login Function



#09216

Net Price:  
94.30 USD  
Unit: pcs

**3000Mbps Outdoor Wireless Access Point, AX3000 (TP-Link EAP650)**

- Ultra-Fast WiFi 6 Speeds: Simultaneous 574 Mbps on 2.4 GHz and 2402 Mbps on 5 GHz totals 2976 Mbps WiFi speeds.
- High-Efficiency WiFi 6: More connected devices can enjoy faster speeds.
- Centralized Cloud Management: Omada SDN integration manages the whole network locally or from the cloud via web UI or Omada app.
- 160 MHz Channel: Double the data at peak transmission times on a single stream with HE160.
- Seamless Roaming: Video streams and voice calls are unaffected as users move between locations.
- Omada Mesh: Enables wireless connectivity between access points for extended range and flexible deployment.
- PoE+ Powered: Supports both 802.3at PoE+ and DC (adapter included) power supply for flexible installations.
- Ultra-Slim Design: &#934;160 mm x 33.6 mm elegant design brings more agility.

Standards: IEEE 802.11ax/ac/n/g/b/a

Ports: 1 x 1 Gbps Ethernet Port (supports IEEE802.3at PoE)

Button: Reset

Frequency range: 2.4GHz and 5GHz

Signal Rate: 5GHz Up to 2402Mbps, 2.4GHz Up to 574Mbps

EIRP: CE <20dBm(2.4GHz) <23dBm(5GHz), FCC <27dBm

Wireless Functions: Multiple SSIDs (Up to 16 SSIDs, 8 for each band), Enable/Disable Wireless Radio, Automatic Channel Assignment, Transmit Power Control (Adjust Transmit Power on dBm), QoS(WMM), Airtime Fairness, Beamforming, Band Steering, Load Balance, Rate Limit, Link Aggregation, Reboot Schedule, Wireless Schedule, Wireless Statistics based on SSID/AP/Client

NEW



#09561

Net Price:  
111.00 USD  
Unit: pcs

**3000Mbps Outdoor Wireless Access Point, AX3000 (TP-Link EAP650-Desktop)**

- Blazing-Fast AX3000 WiFi 6 Speeds: 574 Mbps on 2.4 GHz and 2402 Mbps on 5GHz totals 2976 Mbps WiFi speeds. &#8224;
- Multiple Gigabit Ports: Connect multiple devices with 4x Gigabit Ethernet Ports.
- Convenient Deployment: Supports both 802.3bt PoE++ and DC (adapter included) for easy and quick deployment.
- No Installation needed: Supports desktop installation without the need for additional setup.
- High Flexibility: Provide flexible installation solutions for both desktop and wall mounting.
- Advanced Functions: Omada Mesh, Seamless Roaming, Centralized Cloud Management.

Standards: IEEE 802.11ax/ac/n/g/b/a

Ports: 1 x 1 Gbps Ethernet Port, 1 x FXS Port (One Ethernet port supports PoE Out 802.3at/af output at 802.3bt input, 802.3af class 2 output at 802.3at input)

Button: Reset

Frequency range: 2.4GHz and 5GHz

Signal Rate: 5GHz Up to 2402Mbps, 2.4GHz Up to 574Mbps

EIRP: CE <20dBm(2.4GHz) <23dBm(5GHz), FCC <27dBm

Wireless Functions: Multiple SSIDs (Up to 16 SSIDs, 8 for each band), Enable/Disable Wireless Radio, Automatic Channel Assignment, Transmit Power Control (Adjust Transmit Power on dBm), QoS(WMM), Airtime Fairness, Beamforming, Band Steering, Load Balance, Rate Limit, Link Aggregation, Reboot Schedule, Wireless Schedule, Wireless Statistics based on SSID/AP/Client

NEW



#09451

Net Price:  
106.00 USD  
Unit: pcs

**3000Mbps Outdoor Wireless Access Point, AX3000 (TP-Link EAP653 UR)**

- Ultra-fast WiFi 6 speeds: 2402 Mbps on 5 GHz + 574 Mbps on 2.4 GHz
- Ultra-range wireless coverage by more antennas with higher transmit power
- Supports WiFi 6 technologies, such as HE160, 1024-QAM, etc
- Advanced Features: Omada Mesh, Seamless Roaming, etc
- PoE+ Powered: Supports both 802.3at PoE+ and DC (adapter not included)
- Ultra-Slim Design: &#934;6.3 in x 1.3 in elegant design brings more agility
- Integrates with the Omada SDN platform for centralized management

Ports: 1 x Gigabit PoE+ Port

Button: Reset

Frequency range: 5 GHz and 2.4 GHz

Signal Rate: 5 GHz Up to 4804 Mbps, 2.4 GHz Up to 574 Mbps

Wireless Functions: Multiple SSIDs (Up to 16 SSIDs, 8 for each band), Enable/Disable Wireless Radio, Automatic Channel Assignment, Transmit Power Control (Adjust Transmit Power on dBm), QoS(WMM), Airtime Fairness, Beamforming, Band Steering, Load Balance, Rate Limit, Link Aggregation, Reboot Schedule, Wireless Schedule, Wireless Statistics based on SSID/AP/Client



#09230

Net Price:  
85.30 USD  
Unit: pcs

### 3000Mbps Outdoor Wireless Access Point, AX3000 (TP-Link EAP653)

- Ultra-Fast WiFi 6 Speeds: Simultaneous 574 Mbps on 2.4 GHz and 2402 Mbps on 5 GHz totals 2976 Mbps WiFi speeds.
- High-Efficiency WiFi 6: More connected devices can enjoy faster speeds.
- Centralized Cloud Management: Omada SDN integration manages the whole network locally or from the cloud via web UI or Omada app.
- 160 MHz Channel: Double the data at peak transmission times on a single stream with HE160.
- Seamless Roaming: Video streams and voice calls are unaffected as users move between locations.
- Omada Mesh: Enables wireless connectivity between access points for extended range and flexible deployment.
- PoE+ Powered: Supports both 802.3at PoE+ and DC (DC adapter sold separately) power supply for flexible installations.
- Ultra-Slim Design: 89x34x160 mm × 33.6 mm elegant design brings more agility.

Standards: IEEE 802.11ax/ac/n/g/b/a  
Ports: 1 × 1 Gbps Ethernet Port (supports IEEE802.3at PoE) Button: Reset  
Frequency range: 2.4GHz and 5GHz  
Signal Rate: 5GHz Up to 2402Mbps, 2.4GHz Up to 574Mbps  
EIRP: CE <20dBm(2.4GHz) <23dBm(5GHz), FCC <27dBm  
Wireless Functions: Multiple SSIDs (Up to 16 SSIDs, 8 for each band), Enable/Disable Wireless Radio, Automatic Channel Assignment, Transmit Power Control (Adjust Transmit Power on dBm), QoS(WMM), Airtime Fairness, Beamforming, Band Steering, Load Balance, Rate Limit, Link Aggregation, Reboot Schedule, Wireless Schedule, Wireless Statistics based on SSID/AP/Client



#09253

Net Price:  
111.00 USD  
Unit: pcs

### 3000Mbps Outdoor Wireless Access Point, AX3000 (TP-Link EAP655-Wall)

- Blazing-Fast AX3000 WiFi 6 Speeds:: Simultaneous 574 Mbps on 2.4 GHz and 2402 Mbps on 5 GHz totals 2976 Mbps WiFi speeds.
- Higher Network Efficiency: Deliver data to more devices at the same time with less lag.
- Complete In-Room WiFi Coverage: Guaranteed strong signals and corner-to-corner WiFi coverage.
- Multiple Gigabit Ports: Connect multiple devices with three downlink gigabit ports, one with PoE pass-through.
- Centralized Cloud Management: Integrates into Omada SDN for cloud access and remote management.
- Secure Guest Network: Implement multiple authentication options (SMS/Voucher) packed with high-quality wireless security technologies.
- Easy Installation and PoE Support: Easy-to-install design, compatible with 86 mm & EU & US standard junction box, and 802.3af/at PoE support.

Standards: IEEE 802.11ax/ac/n/g/b/a  
Ports: 10/100/1000Mbps (RJ-45) Port \*1, Downlink-10/100/1000Mbps Ethernet Port\*3 (One port supports PoE OUT. The PoE OUT feature requires 802.3at PoE+ input and the maximum output is 13W.)  
Frequency range: 2.4GHz and 5GHz  
Signal Rate: 5GHz Up to 1201Mbps, 2.4GHz Up to 574Mbps  
EIRP: CE <20dBm(2.4GHz) <23dBm(5GHz), FCC <27dBm  
Wireless Functions: Multiple SSIDs (Up to 16 SSIDs, 8 for each band), Enable/Disable Wireless Radio, Automatic Channel Assignment, Transmit Power Control (Adjust Transmit Power on dBm), QoS(WMM), Airtime Fairness, Beamforming, Band Steering, Load Balance, Rate Limit, Link Aggregation, Reboot Schedule, Wireless Schedule, Wireless Statistics based on SSID/AP/Client



#09243

Net Price:  
74.60 USD  
Unit: pcs

### 3000Mbps Wireless 2.5 Gigabit Router Dual-band AX3000, MU-MIMO (TP-Link Archer AX55 Pro)

- Faster Dual-Band AX3000 WiFi: Up to 3.0 Gbps (2402 Mbps + 574 Mbps) WiFi for faster browsing, streaming, and downloading, all at the same time.
- 2.5G Multi-Gigabit Port: 1 × 2.5 Gbps WAN/LAN port + 1 × 1 Gbps WAN/LAN port + 3 × Gigabit LAN ports + 1 × USB 3.0 port ensure max flexibility and boosted throughput.
- Maximized Coverage: Four high-gain antennas equipped with Beamforming ensure vast coverage.
- Connect More Devices: OFDMA technology increases capacity by 4 times to enable simultaneous transmission to more devices.
- VPN Client Supported: Allow devices in your home network to access remote VPN servers without needing to install VPN software on every device.
- TP-Link HomeShield: Enhanced security defends against the latest cyber threats.
- TP-Link OneMesh Supported: Flexibly Create Whole Home WiFi with Archer AX55 Pro by adding a OneMesh supported Range Extender.
- Compatible with Alexa: Control your router via voice commands and make your life smarter and easier with Amazon Alexa.

HARDWARE FEATURES:  
Standards and Protocols: IEEE 802.11ax/ac/n/a 5GHz, IEEE 802.11ax/b/g/n 2.4GHz, Wi-Fi 6  
Interface: 3 10/100/1000Mbps LAN Ports, 1 1G/100Mbps WAN Port, 1 2.5G WAN Port, 1 USB-A 3.0 Port  
Button: WPS/Reset Button, Wireless On/Off Button, Power On/Off Button  
Power Supply: 12V/1.5A  
Dimensions (W X D X H): 261.1 × 134.5 × 41.0 mm  
Antenna: 4 × External Antennas  
WIRELESS FEATURES:  
Frequency: 2.4GHz & 5GHz  
Signal Rate: 5 GHz @ 2402 Mbps (802.11ax), 2.4 GHz @ 574 Mbps (802.11ax)  
Wireless Functions: Enable/Disable Wireless Radio, Guest Network, DFS, MU-MIMO, OFDMA



#09010

Net Price:  
39.50 USD  
Unit: pcs

### 3000Mbps Wireless Dual Band PCI-Express AX3000, Wi-Fi 6, Bluetooth 5.0 (TP-Link Archer TX3000E)

- Unrivaled Wi-Fi 6 Speed-Breaks the gigabit barrier with speed up to 2402 Mbps (5 GHz) + 574 Mbps (2.4 GHz)
- Smoother Experience-75% lower latency ensures ultra-responsive real-time gaming
- Reliable Connections-IntelC Wi-Fi 6 chipset brings faster and clearer Wi-Fi to fully unlock the potential of your Wi-Fi 6 router
- Wider Signal Coverage-Two multi-directional antennas with magnetized base are designed for optimum signal reception
- Bluetooth 5.0-The latest Bluetooth technology achieves 2× Faster Speed and 4× Broader Coverage than BT 4.2
- Improved Security-The latest security enhancements WPA3 provides enhanced protection in personal password safety
- Fine Crafting-Specialized heatsink and gold plating is crafted to improve stability and reliability even in hot environments
- Backward Compatibility - Full support for 802.11ac/a/b/g/n standards

HARDWARE FEATURES:  
Interface: PCI Express x1  
Antenna Type: Two High-Gain Dual Band Antennas, Magnetized Antenna Base  
Chipset: Intel Wi-Fi 6 Chipset  
WIRELESS FEATURES:  
Wireless Standards: 5 GHz @ IEEE 802.11ax/ac/n/a, 2.4 GHz @ IEEE 802.11ax/n/g/b, Bluetooth 5.0/4.2/4.0  
Frequency: 2.4-2.4835GHz, 5.180-5.240GHz, 5.745-5.825GHz  
Signal Rate: 2402Mbps at 5GHz, 574Mbps at 2.4GHz  
EIRP: 5 GHz @ 27 dBm (FCC) / 23 dBm (CE) (EIRP), 2.4 GHz @ 26 dBm (FCC) / 20 dBm (CE) (EIRP)  
Wireless Modes: Infrastructure mode



#09083

Net Price:  
30.20 USD  
Unit: pcs

### 3000Mbps Wireless Dual Band PCI-Express AX3000, Wi-Fi 6, Bluetooth 5.0 (TP-Link Archer TX50E)

- Unrivaled Wi-Fi 6 Speed-Breaks the gigabit barrier with speed up to 2402 Mbps (5 GHz) + 574 Mbps (2.4 GHz)
- Smoother Experience-75% lower latency ensures ultra-responsive gaming, uninterrupted video chatting and seamless live streaming
- Reliable Connections-IntelC Wi-Fi 6 chipset brings faster and clearer Wi-Fi to fully unlock the potential of your Wi-Fi 6 router
- Wider Signal Coverage- Connect to your Wi-Fi in more parts of your home with two external high-gain antennas ensuring greater coverage and enhanced stability
- Bluetooth 5.0-The latest Bluetooth technology achieves 2× Faster Speed and 4× Broader Coverage than BT 4.2
- Improved Security-The latest security enhancements WPA3 provides enhanced protection in personal password safety
- Fine Crafting-Specialized heatsink and gold plating is crafted to improve stability and reliability even in hot environments
- Backward Compatibility - Full support for 802.11ac/a/b/g/n standards

HARDWARE FEATURES:  
Interface: PCI Express x1  
Antenna Type: Two High-Gain Dual Band Antennas  
Chipset: Intel Wi-Fi 6 Chipset  
WIRELESS FEATURES:  
Wireless Standards: 5 GHz @ IEEE 802.11ax/ac/n/a, 2.4 GHz @ IEEE 802.11ax/n/g/b, Bluetooth 5.0/4.2/4.0  
Frequency: 2.4-2.4835GHz, 5.180-5.240GHz, 5.745-5.825GHz  
Signal Rate: 2402Mbps at 5GHz, 574Mbps at 2.4GHz  
EIRP: 5 GHz @ 27 dBm (FCC) / 23 dBm (CE) (EIRP), 2.4 GHz @ 26 dBm (FCC) / 20 dBm (CE) (EIRP)  
Wireless Modes: Infrastructure mode  
Wireless Security: Support 64/128 bit WEP, WPA/WAP2/WPA3, WPA-PSK/WPA2-PSK, 802.1x



#09213

Net Price:  
27.80 USD  
Unit: pcs

### 3000Mbps Wireless Dual Band PCI-Express AX3000, Wi-Fi 6, Bluetooth 5.2 (TP-Link Archer TX55E)

- Unrivaled Wi-Fi 6 Speed-Breaks the gigabit barrier with speed up to 2402 Mbps (5 GHz) + 574 Mbps (2.4 GHz)
- Smoother Experience-75% lower latency ensures ultra-responsive gaming, uninterrupted video chatting and seamless live streaming
- Reliable Connections-IntelC Wi-Fi 6 chipset brings faster and clearer Wi-Fi to fully unlock the potential of your Wi-Fi 6 router
- Wider Signal Coverage- Connect to your Wi-Fi in more parts of your home with two external high-gain antennas ensuring greater coverage and enhanced stability
- Bluetooth 5.2-The latest Bluetooth technology achieves Faster Speed and Broader Coverage than the previous version
- Improved Security-The latest security enhancements WPA3 provides enhanced protection in personal password safety
- Fine Crafting-Specialized heatsink and gold plating is crafted to improve stability and reliability even in hot environments
- Backward Compatibility - Full support for 802.11ac/a/b/g/n standards

HARDWARE FEATURES:  
Interface: PCI Express x1  
Antenna Type: Two High-Gain Dual Band Antennas  
Chipset: Intel Wi-Fi 6 Chipset  
WIRELESS FEATURES:  
Wireless Standards: 5 GHz @ IEEE 802.11ax/ac/n/a, 2.4 GHz @ IEEE 802.11ax/n/g/b, Bluetooth 5.0/4.2/4.0  
Frequency: 2.4-2.4835GHz, 5.180-5.240GHz, 5.745-5.825GHz  
Signal Rate: 2402Mbps at 5GHz, 574Mbps at 2.4GHz  
EIRP: 5 GHz @ 27 dBm (FCC) / 23 dBm (CE) (EIRP), 2.4 GHz @ 26 dBm (FCC) / 20 dBm (CE) (EIRP)  
Wireless Modes: Infrastructure mode  
Wireless Security: Support 64/128 bit WEP, WPA/WAP2/WPA3, WPA-PSK/WPA2-PSK, 802.1x



#09183

Net Price:  
63.00 USD  
Unit: pcs

**3000Mbps Wireless Gigabit Router Dual-band AX3000, MU-MIMO (TP-Link Archer AX55)**

- Next-Gen Gigabit Wi-Fi 6 Speed-2402 Mbps on 5 GHz and 574 Mbps on 2.4 GHz band ensure smoother streaming and faster downloads.
- Connect More Devices-OFDMA technology increases capacity by 4 times to enable simultaneous transmission to more devices.
- Ultra-Low Latency-Up to 75% reduction in latency enables more responsive gaming and video chatting.
- Expanded Wi-Fi Coverage-Four high-gain external antennas and Beamforming technology combine to extend strong, reliable Wi-Fi throughout your home.
- TP-Link HomeShield - Enhanced security defends against the latest cyber threats.
- Improved Battery Life-Target Wake Time helps your devices to communicate more while consuming less power.
- Compatible with Alexa-Control your router via voice commands and make your life smarter and easier with Amazon Alexa.

**HARDWARE FEATURES:**

Standards and Protocols:IEEE 802.11ax/ac/n/a 5GHz, IEEE 802.11ax/b/g/n 2.4GHz, Wi-Fi 6  
Interface:4 10/100/1000Mbps LAN Ports, 1 1G/100Mbps WAN Port, 1 USB-A 3.0 Port

Button:WPS/Reset Button, Wireless On/Off Button, Power On/off Button

Power Supply: 12V/2A

Dimensions (W X D X H): 261.1 × 134.5 × 41.0 mm

Antenna: 4 × External Antennas

**WIRELESS FEATURES:**

Frequency:2.4GHz & 5GHz

Signal Rate: 5 GHz@ 2402 Mbps (802.11ax), 2.4 GHz@ 574 Mbps (802.11ax)

Wireless Functions:Enable/Disable Wireless Radio, Guest Network, DFS, MU-MIMO, OFDMA



#09218

Net Price:  
39.50 USD  
Unit: pcs

**3000Mbps Wireless Gigabit Router Dual-band AX3000, MU-MIMO (TP-Link Marcusys MR80X)**

- OPTIMAL WIFI 6 SPEEDS - Optimal WiFi 6 speeds reaching up to 3 Gbps for faster browsing, streamings, and downloading, all at the same time.
- MORE DEVICES, MORE FUN - Supports MU-MIMO and OFDMA to reduce congestion and quadruple the average throughput.
- WIFI THAT GOES FARTHER - 4× multi-directional high-gain antennas with Beamforming boost stable connections throughout your home for strong WiFi signals in every corner
- OVERALL SECURITY PROTECTION - The latest WPA3 provides improved WiFi security
- GIGABIT WIRED CONNECTIONS - Make full use of your internet access and transfer data at dizzying speeds for peak performance
- ECO-FRIENDLY POWER SAVING - Target Wake Time (TWT) reduces power consumption for your mobile and IoT devices during data transmissions
- LESS WIFI INTERFERENCE - Minimizes the interference from neighboring signals to improve transmission efficiency with BSS coloring
- SMART CONNECT - Intelligently chooses the best available band for each device

**HARDWARE FEATURES:**

Standards and Protocols:IEEE 802.11ax/ac/n/a 5GHz, IEEE 802.11ax/b/g/n 2.4GHz, Wi-Fi 6

Interface:3 10/100/1000Mbps LAN Ports, 1 1G/100Mbps WAN Port

Button:WPS/Reset Button

Dimensions (W X D X H): 8.2 × 6.8 × 1.6 in (208.8 × 171.6 × 41.7 mm)

Antenna: 4× 5 dBi Fixed Omni-Directional Antennas

**WIRELESS FEATURES:**

Frequency:2.4GHz & 5GHz

Signal Rate: 5 GHz@ 2402 Mbps (802.11ax), 2.4 GHz@ 574 Mbps (802.11ax)

Wireless Functions:Enable/Disable Wireless Radio, WMM Wireless Security:WPA-PSK / WPA2-PSK/ WPA3

NEW



#09562

Net Price:  
284.00 USD  
Unit: pcs

**3000Mbps Wireless outdoor gigabit VPN Router Omada, PoE, 5x 10/100/1000 RJ-45, 1 SFP slots, (TP-Link ER703WP-4G-Outdoor)**

- 4G+ Cat6 up to 300 Mbps
- AX3000 Wi-Fi 6 with 2402 Mbps on 5GHz and 574 Mbps on 2.4GHz
- 3 × Gigabit WAN/LAN Ports (2 × PoE Out, 1 × PoE In)
- 1 × Nano SIM Card Slot
- 802.3at/bt PoE or 12V/2A DC Power Supply
- 4G and Ethernet WAN Auto Backup with Load Balancing
- IPsec/L2TP/PPTP/OpenVPN/GRE/WireGuard/SSL VPN\$
- Centralized Management
- IP55 Weatherproofing

Standards: IEEE 802.3u/ab/z/x/q

Copper ports: 1 Gigabit SFP WAN/LAN Port, 1 Gigabit WAN Port, 4 Gigabit LAN/WAN Ports

Flash: 256 MB NAND

DRAM: 512 MB DDR4

Antenna: Wi-Fi Two 5GHz 4.0dBi & 2.4GHz 2.3 dBi

dual-band build-in antennas, LTE Two 4.0dBi omnidirectional detachable antennas

Network Type: LTE Band of EU, 4G LTE-FDD

B1/B3/B5/B7/B8/B20/B28/B32

(2100/1800/850/2600/900/800/700/1450 MHz), 4G LTE-TDD B38/B40/B41 (2600/2300/2500 MHz), 3G

DC-HSDPA/HSPA+/HSDPA/HSPA/WCDMA B1/B3/B5/B8 (2100/1800/850/900 MHz), Carrier Aggregation of EU-

B1+B3/B5/B7/B8/B20/B28/B38/B40/B41,

B3+B3/B5/B7/B8/B20/B28/B38/B40/B41,

B5+B5/B7/B38/B40/B41, B7+B7/B8/B20/B28/B32,

B8+B32/B38/B40/B41, B20+B32/B38/B40,

B28+B32/B38/B40/B41, B38+B38, B40+B40, B41+B41, LTE

Band of US- 4G LTE-FDD

B2/B4/B5/B7/B12/B13/B14/B25/B26/B29/B30/B66/B71,

(1950/2100/850/2600/750/750/1950/850/700/2350/2150/650 MHz), 4G LTE-TDD B41/B48 (2500/3600 MHz), Carrier

Aggregation of US-

B2+B2/B4/B5/B7/B12/B13/B14/B29/B30/B48/B66/B71,

B4+B4/B5/B7/B12/B13/B29/B30/B71,

B5+B5/B7/B25/B30/B41/B66, B7+B7/B12/B66,

B12+B12/B25/B30/B66, B13+B66, B14+B30/B66,

B25+B25/B26/B41, B26+B41, B29+B30/B66, B30+B66,

B41+B41, B48+B48, B66+B66/B71

NEW



#09580

Net Price:  
37.30 USD  
Unit: pcs

**3000Mbps Wireless Range Extender, AX3000 (TP-Link Mercusys ME80X)**

- Dual Band Speeds up to 3000 Mbps - 2402 Mbps on 5 GHz and 574 Mbps on 2.4 GHz.
- Armed with WiFi 6 - Improves virtually every aspect of your network: speed, efficiency, and capacity.
- Gigabit Wired Connection - Provides speedy wired connections for PCS, IPTVS.and game consoles.
- Works with Any Routers - To Extend WiFi to Where You Need It Most.
- Easy One-Touch Setup - Press the WPS button to expand your Wi-Fi coverage in seconds.
- Built-In Access Point Mode - Works as RE mode and AP mode.
- Manage Your Network with App - Set up in minutes and manage your Wi-Fi at home or away through your iOS or Android devices.

**HARDWARE FEATURES:**

Ports:1 \* 10/100/1000M Ethernet Port (RJ45)

Plug Type: EU

Button:WPS Button, Reset Button

Power Consumption: About 13W

Wireless Standards:IEEE802.11ax, IEEE802.11ac,IEEE

802.11n, IEEE 802.11g, IEEE 802.11b

Dimensions ( W x D x H ): 138,6 × 100,3 × 68,4 mm

Antenna Type: 2 x external

**WIRELESS FEATURES:**

Frequency:2.4GHz & 5GHz

Signal Rate: 5GHz Up to 2402Mbps, 2.4GHz Up to 574Mbps

Wireless Security: WPA-PSK/WPA2-PSK

**OTHERS**

Certification:CE, RoHS

Package Contents:ME60X, Quick Installation Guide



#09221

Net Price:  
60.90 USD  
Unit: pcs

**3000Mbps Wireless Range Extender, AX3000 (TP-Link RE700X)**

- Dual Band WiFi 6 - Separates 5 GHz (2402 Mbps) and 2.4 GHz (574 Mbps) WiFi bands for faster speeds and greater capacity with the latest technology
- Uninterrupted Streaming - Easily create a TP-Link OneMeshTM network for seamless whole home WiFi coverage
- AP Mode - Create a new WiFi access point through the Gigabit Ethernet port to enhance your wired network with WiFi capability
- Adaptive Path Selection - Automatically choosing the fastest connection path to the router
- App Control -Easy Setup and management with your network using the TP-Link Tether app

**HARDWARE FEATURES:**

Ports: 1 Gigabit Ethernet Port

Plug Type: EU

Button:Reset Button, WPS Button

Power Consumption: 11.2W

Wireless Standards:IEEE802.11ac,IEEE 802.11n, IEEE

802.11g, IEEE 802.11b

Dimensions ( W x D x H ): 78×36×149 mm

Antenna Type: 2 x Internal Antennas

**WIRELESS FEATURES:**

Frequency:2.4GHz & 5GHz

Signal Rate: 574 Mbps at 2.4GHz, 2402 Mbps at 5GHz

EIRP:CE 2.4 GHz <= 16 dBm, 5 GHz <= 21 dBm

Wireless Modes:Range Extender

Wireless Functions: WMM (Wi-Fi Multimedia), Wireless

Statistic, Domain Login Function



#09231

Net Price:  
65.20 USD  
Unit: pcs

**3000Mbps Wireless Range Extender, AX3000 (TP-Link RE705X)**

- Dual Band WiFi 6 - Separates 5 GHz (2402 Mbps) and 2.4 GHz (574 Mbps) WiFi bands for faster speeds and greater capacity with the latest technology
- Uninterrupted Streaming - Easily create a TP-Link OneMeshTM network for seamless whole home WiFi coverage
- AP Mode - Create a new WiFi access point through the Gigabit Ethernet port to enhance your wired network with WiFi capability
- Gigabit Ethernet Port - Provides high-speed wired access, ideal for smart TVs, PCs, and game consoles
- App Control -Easy Setup and management with your network using the TP-Link Tether app

**HARDWARE FEATURES:**

Ports: 1 Gigabit Ethernet Port

Plug Type: EU

Button:Reset Button, WPS Button

Power Consumption: 12.6W

Wireless Standards:IEEE802.11ac,IEEE 802.11n, IEEE

802.11g, IEEE 802.11b

Dimensions ( W x D x H ): 97×46×158 mm

Antenna Type: 2 x Internal Antennas

**WIRELESS FEATURES:**

Frequency:2.4GHz & 5GHz

Signal Rate: 574 Mbps at 2.4GHz, 2402 Mbps at 5GHz

EIRP:CE 2.4 GHz <= 16 dBm, 5 GHz <= 21 dBm

Wireless Modes:Range Extender

Wireless Functions: WMM (Wi-Fi Multimedia), Wireless

Statistic, Domain Login Function





#09092

Net Price:  
184.00 USD  
Unit: pcs

### 3600Mbps Outdoor Wireless Access Point, AX3600 (TP-Link EAP660 HD)

- Ultra-Fast Wi-Fi 6 Speeds: Simultaneous 1148 Mbps on 2.4 GHz and 2402 Mbps on 5 GHz totals 3550 Mbps Wi-Fi speeds.
- High-Density Connectivity: 4× increased capacity to connect more devices simultaneously.
- Integrated into Omada SDN: Zero-Touch Provisioning (ZTP), Centralized Cloud Management, and Intelligent Monitoring.
- Centralized Management: Cloud access and Omada app for ultra convenience and easy management.
- 2.5G Port: A 2.5 Gbps Ethernet port boosts total internet throughput.
- Seamless Roaming: Even video streams and voice calls are unaffected as users move between locations.
- PoE+ Support: Supports Power over Ethernet (802.3at) for convenient deployment and installation.
- Secure Guest Network: Along with multiple authentication options (SMS/Facebook Wi-Fi/ Voucher, etc.) and abundant wireless security technologies.

Standards: IEEE 802.11ax/ac/n/g/b/a  
Ports: 1× 2.5 Gbps Ethernet Port (supports IEEE802.3at PoE)  
Button: Reset  
Frequency range: 2.4GHz and 5GHz  
Signal Rate: 5GHz Up to 2402Mbps, 2.4GHz Up to 1148Mbps  
EIRP: CE <20dBm(2.4GHz) <23dBm(5GHz), FCC <27dBm  
Wireless Functions: Multiple SSIDs (Up to 16 SSIDs, 8 for each band), Enable/Disable Wireless Radio, Automatic Channel Assignment, Transmit Power Control (Adjust Transmit Power on dBm), QoS(WMM), Airtime Fairness, Beamforming, Band Steering, Load Balance, Rate Limit, Link Aggregation, Reboot Schedule, Wireless Schedule, Wireless Statistics based on SSID/AP/Client



#09217

Net Price:  
133.00 USD  
Unit: pcs

### 5400Mbps Outdoor Wireless Access Point, AX5400 (TP-Link EAP670)

- Blazing-Fast WiFi 6 Speeds: Simultaneous 574 Mbps on 2.4 GHz and 4804 Mbps on 5 GHz totals 5378 Mbps Wi-Fi speeds.
- High-Efficiency WiFi 6: More connected devices can enjoy faster speeds.
- Centralized Cloud Management: Omada SDN integration manages the whole network locally or from the cloud via web UI or Omada app.
- 160 MHz Channel: Double the data at peak transmission times on a single stream with HE160.
- Seamless Roaming: Video streams and voice calls are unaffected as users move between locations.
- Omada Mesh: Enables wireless connectivity between access points for extended range and flexible deployment.
- PoE+ Powered: Supports both 802.3at PoE+ and DC (adapter included) power supply for flexible installations.

Standards: IEEE 802.11ax/ac/n/g/b/a  
Ports: 1× 2.5 Gbps Ethernet Port (supports IEEE802.3at PoE)  
Button: Reset  
Frequency range: 2.4GHz and 5GHz  
Signal Rate: 5GHz Up to 4804Mbps, 2.4GHz Up to 574Mbps  
EIRP: CE <20 dBm(2.4 GHz, EIRP), <23 dBm(5 GHz, band1 & band2, EIRP), <30 dBm(5 GHz, , band3, EIRP), FCC <25 dBm(2.4 GHz), <28 dBm(5 GHz)  
Wireless Functions: Multiple SSIDs (Up to 16 SSIDs, 8 for each band), Enable/Disable Wireless Radio, Automatic Channel Assignment, Transmit Power Control (Adjust Transmit Power on dBm), QoS(WMM), Airtime Fairness, Beamforming, Band Steering, Load Balance, Rate Limit, Link Aggregation, Reboot Schedule, Wireless Schedule, Wireless Statistics based on SSID/AP/Client

NEW



#09450

Net Price:  
128.00 USD  
Unit: pcs

### 5400Mbps Outdoor Wireless Access Point, AX5400 (TP-Link EAP673)

- Blazing-Fast WiFi 6 Speeds (574 Mbps on 2.4 GHz + 4804 Mbps on 5 GHz).
- Integrated into Omada SDN, supporting centralized cloud Management, ZTP and more.
- 160 MHz Channel double the data at peak transmission times on a single stream.
- Advanced features: Supports seamless roaming\$, Omada Mesh\$, and more.
- Supports both 802.3at PoE+ and DC (adapter not included) power supply for flexible installations.

Ports: 1× 2.5G Ethernet Port  
Bluetooth: yes  
Button: Reset  
Frequency range: 5 GHz and 2.4 GHz  
Signal Rate: 5 GHz Up to 4804 Mbps, 2.4 GHz Up to 574 Mbps  
Wireless Functions: Multiple SSIDs (Up to 16 SSIDs, 8 for each band), Enable/Disable Wireless Radio, Automatic Channel Assignment, Transmit Power Control (Adjust Transmit Power on dBm), QoS(WMM), Airtime Fairness, Beamforming, Band Steering, Load Balance, Rate Limit, Link Aggregation, Reboot Schedule, Wireless Schedule, Wireless Statistics based on SSID/AP/Client

NEW



#09560

Net Price:  
111.00 USD  
Unit: pcs

### 5400Mbps Outdoor Wireless Extender, AX5400 (TP-Link EAP673-Extender)

- AX5400 Dual-Band WiFi 6: Up to 5.4 Gbps wireless speeds
- Wi-Fi Dead-Zone Killer: Four high-gain external antennas extend WiFi signals to every dead zone.
- AP Mode: Simply plug in an Ethernet cable to create a new WiFi AP.
- Seamless Mesh Networking: Supports Omada Mesh and Roaming for reliable networking, ideal for large-scale scenarios.
- Easy & Quick Installation: Standard AC power supply for flexible deployment.
- Quick adoption: Conveninet operation via Omada web or app once the extender powers on.
- Centralized Cloud Management: Integrates into Omada SDN for cloud access and remote management.

Ports: 1× 1G Ethernet Port  
Bluetooth: yes  
Button: Reset  
Frequency range: 5 GHz and 2.4 GHz  
Signal Rate: 5 GHz Up to 4804 Mbps, 2.4 GHz Up to 574 Mbps  
Wireless Functions: Multiple SSIDs (Up to 16 SSIDs, 8 for each band), Enable/Disable Wireless Radio, Automatic Channel Assignment, Transmit Power Control (Adjust Transmit Power on dBm), QoS(WMM), Airtime Fairness, Beamforming, Band Steering, Load Balance, Rate Limit, Link Aggregation, Reboot Schedule, Wireless Schedule, Wireless Statistics based on SSID/AP/Client



#09244

Net Price:  
117.00 USD  
Unit: pcs

### 5400Mbps Wireless 2.5 Gigabit Router Dual-band AX5400, MU-MIMO (TP-Link Archer AX72 Pro)

- Gigabit WiFi for 8K Streaming - 5400 Mbps WiFi for faster browsing, streamings, and downloading, all at the same time.
- Fully Featured Wi-Fi 6 - Equips with the top structure of 4T4R and HE160 on the 5 GHz band to enable a 4.8 Gbps ultra-fast connection.
- Connect 100+ Devices - Supports MU-MIMO and OFDMA to reduce congestion and quadruple the average throughput.
- Extensive Coverage - 6× antennas and Beamforming ensure broad coverage.
- HomeShield - TP-Link's premium security services keep your home network safe with cutting-edge features for network and IoT protection.
- More Vents, Less Heat - Improved vents area unleashes the full power of the whole machine.
- USB Sharing - 1× USB 3.0 port enables easy media sharing and private cloud building.
- Easy Setup - Set up the router in minutes with the Tether app.

HARDWARE FEATURES:  
Standards and Protocols: IEEE 802.11ax/ac/n/a 5GHz, IEEE 802.11ax/b/g/n 2.4GHz, Wi-Fi 6  
Interface: 3 10/100/1000Mbps LAN Ports, 1 1G/100Mbps WAN Port, 1 2.5G WAN Port, 1 USB 3.0 Port  
Button: WPS/Reset Button, Wireless On/Off Button, Power On/Off Button, LED On/Off  
Power Supply: 12V/2.5A  
Dimensions (W X D X H): 10.7 × 5.8 × 1.9 in (272.5 × 147.2 × 49.2 mm)  
Antenna: 6 × External Antennas  
WIRELESS FEATURES:  
Frequency: 2.4GHz & 5GHz  
Signal Rate: 5 GHz@ 4804 Mbps (802.11ax), 2.4 GHz@ 574 Mbps (802.11ax)



#09184

Net Price:  
107.00 USD  
Unit: pcs

### 5400Mbps Wireless Gigabit Router Dual-band AX5400, MU-MIMO (TP-Link Archer AX72)

- Gigabit WiFi for 8K Streaming - 5400 Mbps WiFi for faster browsing, streamings, and downloading, all at the same time.
- Fully Featured Wi-Fi 6 - Equips with the top structure of 4T4R and HE160 on the 5 GHz band to enable 4.8 Gbps ultra-fast connection.
- Connect 100+ Devices - Supports MU-MIMO and OFDMA to reduce congestion and quadruple the average throughput.
- Extensive Coverage - 6× antennas and Beamforming ensure broad coverage.
- HomeShield - TP-Link's premium security services keep your home network safe with cutting-edge features for network and IoT protection.
- More Vents, Less Heat - Improved vents area unleash the full power of the whole machine.
- USB Sharing - 1× USB 3.0 port enables easy media sharing and private cloud building.
- Easy Setup - Set up the router in minutes with Tether app.

HARDWARE FEATURES:  
Standards and Protocols: IEEE 802.11ax/ac/n/a 5GHz, IEEE 802.11ax/b/g/n 2.4GHz, Wi-Fi 6  
Interface: 4 10/100/1000Mbps LAN Ports, 1 1G/100Mbps WAN Port, 1 USB 3.0 Port  
Button: WPS/Reset Button, Wireless On/Off Button, Power On/Off Button, LED On/Off  
Power Supply: 12V/2.5A  
Dimensions (W X D X H): 10.7 × 5.8 × 1.9 in (272.5 × 147.2 × 49.2 mm)  
Antenna: 6 × External Antennas  
WIRELESS FEATURES:  
Frequency: 2.4GHz & 5GHz  
Signal Rate: 5 GHz@ 4804 Mbps (802.11ax), 2.4 GHz@ 574 Mbps (802.11ax)





#09076

Net Price:  
112.00 USD  
Unit: pcs

**5400Mbps Wireless Gigabit Router Dual-band AX5400, MU-MIMO (TP-Link Archer AX73)**

- Gigabit WiFi for 8K Streaming - 5400 Mbps WiFi for faster browsing, streamings, and downloading, all at the same time.
- Fully Featured Wi-Fi 6 - Equips with the top structure of 4T4R and HE160 on the 5 GHz band to enable 4.8 Gbps ultra-fast connection.
- Connect 200+ Devices - Supports MU-MIMO and OFDMA to reduce congestion and quadruple the average throughput.
- Extensive Coverage - 6× antennas and Beamforming ensure broad coverage.
- HomeShield - TP-Link's premium security services keep your home network safe with cutting-edge features for network and IoT protection.
- More Vents, Less Heat - Improved vents area unleash the full power of the whole machine.
- USB Sharing - 1× USB 3.0 port enables easy media sharing and private cloud building.
- Easy Setup - Set up the router in minutes with Tether app.

**HARDWARE FEATURES:**

Standards and Protocols: IEEE 802.11ax/ac/n/a 5GHz, IEEE 802.11ax/b/g/n 2.4GHz, Wi-Fi 6  
Interface: 4 10/100/1000Mbps LAN Ports, 1 1G/100Mbps WAN Port, 1 USB 3.0 Port  
Button: WPS/Reset Button, Wireless On/Off Button, Power On/off Button, LED On/Off  
Power Supply: 12V/2.5A  
Dimensions (W X D X H): 10.7 × 5.8 × 1.9 in (272.5 × 147.2 × 49.2 mm)  
Antenna: 6 × External Antennas  
**WIRELESS FEATURES:**  
Frequency: 2.4GHz & 5GHz  
Signal Rate: 5 GHz@ 4804 Mbps (802.11ax), 2.4 GHz@ 574 Mbps (802.11ax)

NEW



#09392

Net Price:  
177.00 USD  
Unit: pcs

**5400Mbps Wireless Gigabit Router Tri-band AXE5400, MU-MIMO (TP-Link Archer AXE75)**

- AXE5400 Tri-Band - AXE5400 Tri-Band Wi-Fi delivers Wi-Fi speeds up to 5400 Mbps.
- Cutting-Edge Processing - Armed with a 1.7 GHz Quad-Core CPU.
- SuperSpeed USB 3.0 - Up to 10× faster transfer speeds than USB 2.0.
- Wi-Fi 6E Unleashed - The brand new 6 GHz band brings more bandwidth, faster speeds, and near-zero latency.
- HomeShield - Customize your home network with enhanced security and control.
- OneMesh™ - Creates a Mesh network by connecting to a TP-Link OneMesh Extender for seamless whole-home coverage.
- Connect More Devices-OFDMA technology increases capacity by 4 times to enable simultaneous transmission to more devices.
- Ultra-Low Latency-Enables more responsive gaming and video chatting.
- Compatible with Alexa-Control your router via voice commands and make your life smarter and easier with Amazon Alexa.

**HARDWARE FEATURES:**

Standards and Protocols: IEEE 802.11ax 6 GHz, IEEE 802.11ax/ac/n/a 5GHz, IEEE 802.11ax/b/g/n 2.4GHz, Wi-Fi 6  
Interface: 4 10/100/1000Mbps LAN Ports, 1 1G/100Mbps WAN Port, 1 USB 3.0 Port  
Button: WPS/Reset Button, Wireless On/Off Button, Power On/off Button, LED On/Off  
Power Supply: 12V/2.5A  
Dimensions (W X D X H): 10.7 × 5.8 × 1.9 in (272.5 × 147.2 × 49.2 mm)  
Antenna: 6 × External Antennas  
**WIRELESS FEATURES:**  
Frequency: 2.4GHz & 5GHz  
Signal Rate: 6 GHz@ 2402 Mb/s (802.11ax), 5 GHz@ 2402 Mbps (802.11ax), 2.4 GHz@ 574 Mbps (802.11ax)

NEW



#09541

Net Price:  
173.00 USD  
Unit: pcs

**5400Mbps Wireless Gigabit Router Tri-band AXE5400, MU-MIMO (TP-Link Archer AXE75)**

- 5.4 Gbps Tri-Band Wi-Fi: Up to 5.4 Gbps Tri-Band WiFi enables your devices always ready for the fiercest battles. The brand new 6 GHz band provides exceptional bandwidth and congestion-free channels exclusive to Wi-Fi 6E devices.
  - 2.5G Multi-Gigabit Port: Supercharge your gaming network with the Archer GXE75 featuring a lightning-fast 2.5G WAN port and four 1G LAN ports for unrivaled speed and seamless multiplayer gaming.
  - 4× Optimally Positioned Antennas: Enjoy uninterrupted gaming in every corner of your home with 4× optimally positioned antennas, proprietary Wi-Fi optimization, and Beamforming technology.
  - Exclusive Acceleration for Games: Accelerate game applications, game devices, mobile games, and game servers. Stabilize connections, minimize jitter, lag and ping while boosting speed.
  - Dedicated Game Panel: An intuitive game panel provides real-time insights into the battle environment, network status, router performance, rgb settings, accelerated games and gears, enabling players to strategize effectively.
  - Game-Style Design: Ignites gaming passions with its volcano-inspired design. Customizable RGB lighting casts a fiery aura, making Archer GXE75 a stylish focal point for any gamer's den.
  - TP-Link HomeShield: HomeShield provides robust antivirus protection for a secure gaming experience. It defends all your devices and personal data against online threats, ensuring peace of mind while gaming.
  - EasyMesh Compatibility-Works with EasyMesh routers and range extenders to form seamless whole home Mesh WiFi. This connectivity ensures consistent coverage, allowing gamers to collaborate efficiently and dominate team battles.
- HARDWARE FEATURES:**  
Standards and Protocols: IEEE 802.11ax 6 GHz, IEEE 802.11ax/ac/n/a 5GHz, IEEE 802.11ax/b/g/n 2.4GHz, Wi-Fi 6  
Interface: 1 2.5G LAN/WAN Port, 1 1GMbps LAN/WAN Port, 3 1GMbps LAN Ports, 1 USB 3.0 Port  
Button: WPS/Reset Button, Wireless On/Off Button, Power On/off Button, LED On/Off  
**WIRELESS FEATURES:**  
Frequency: 2.4GHz & 5GHz  
Signal Rate: 6 GHz@ 2402 Mb/s (802.11ax), 5 GHz@ 2402 Mbps (802.11ax), 2.4 GHz@ 574 Mbps (802.11ax)  
Wireless Functions: Enable/Disable Wireless Radio, Guest Network, DFS, MU-MIMO, OFDMA

NEW



#09406

Net Price:  
173.00 USD  
Unit: pcs

**5400Mbps Wireless Range Extender, AX5400 (TP-Link RE815XE)**

- AXE5400 Tri-Band Wi-Fi: Boosts overall speeds up to an incredible 5400 Mbps.
- 6 GHz Band: Provides a clearer band to prevent Wi-Fi interference and congestion.
- 160 MHz Channel Bandwidth: Expands bandwidth to double the network speed of traditional 80 MHz.
- Smart Roaming: Walk from room to room and stay connected with the fastest possible speeds.
- Improved Capacity, Less Lag: Experience flawless streams on more screens throughout your home.
- Easy Setup: Plug in and then easily set up via a press of the WPS button or via the Tether App.

**HARDWARE FEATURES:**

Ports: 1 Gigabit Ethernet Port  
Plug Type: EU  
Button: Reset Button, WPS Button  
Power Consumption: 23W  
Wireless Standards: IEEE 802.11ac, IEEE 802.11n, IEEE 802.11g, IEEE 802.11b  
Dimensions (W x D x H): 4.2×1.6×13.7 in. (106.6×39.7×348.2 mm)  
Antenna Type: 4 External Antennas  
**WIRELESS FEATURES**  
Frequency: 2.4GHz & 5GHz & 6GHz  
Signal Rate: 574 Mbps at 2.4GHz, 2402 Mbps at 5GHz, 2402 Mbps at 6GHz  
Wireless Modes: Range Extender  
Wireless Functions: WMM (Wi-Fi Multimedia), Wireless Statistic, Domain Login Function



NEW



#09415

Net Price:  
32.70 USD  
Unit: pcs

## 5400Mbps Wireless Tri Band PCI-Express AXE5400, Wi-Fi 6E, Bluetooth 5.3 (TP-Link Archer TXE72E)

- Unparalleled Tri-Band Speed - Boost your overall speeds up to 2402 Mbps (6 GHz) + 2402 Mbps (5 GHz) + 574 Mbps (2.4 GHz)
- Wi-Fi 6E Standard - Expand to the clearer, broader 6 GHz band for more bandwidth and faster speeds. Currently 6 GHz Band only supported on Windows 11.
- Reliable Connections - The latest IntelC Wi-Fi 6E chipset's reduced latency and improved reliability unlocks your Wi-Fi 6E router's full potential
- Wider Signal Coverage - Two multi-directional antennas with a magnetized base are designed for optimal signal reception
- Bluetooth 5.3 - Security and reliability improvement than last-gen high-speed Bluetooth 5.2
- Improved Security - The latest security enhancement, WPA3, provides enhanced protection in personal password safety
- Reliably Engineered - The specialized heatsink and gold plating improve stability and performance even at high CPU temps
- Backward Compatibility - Full support for 802.11ax/ac/a/b/g/n standards

### HARDWARE FEATURES:

Interface:PCI Express x1

Antenna Type: 2× High-Gain Tri-Band Antennas

Chipset: Intel Wi-Fi 6E Chipset

### WIRELESS FEATURES:

Wireless Standards:IEEE 802.11a/b/g/n/ac/ax

Signal Rate: 2402Mbps at 6GHz, 2402Mbps at 5GHz,

574Mbps at 2.4GHz

Wireless Modes: Infrastructure mode

Wireless Security:WEP, WPA/WPA2/WPA3,

WPA-PSK/WPA2-PSK

### OTHERS:

Dimensions: 3.09 × 4.8 × 0.85 in (78.5×120.8×21.5mm)

Certification:CE, FCC, RoHS, Wi-Fi

Package Contents:Archer TXE72E, Two High Gain Antennas,

Low-Profile Bracket, Bluetooth Header Cable, Quick

Installation Guide, Resource CD

NEW



#09414

Net Price:  
56.00 USD  
Unit: pcs

## 5400Mbps Wireless Tri Band PCI-Express AXE5400, Wi-Fi 6E, Bluetooth 5.3 (TP-Link Archer TXE75E)

- Unparalleled Tri-Band Speed - Boost your overall speeds up to 2402 Mbps (6 GHz) + 2402 Mbps (5 GHz) + 574 Mbps (2.4 GHz)
- Wi-Fi 6E Standard - Expand to the clearer, broader 6 GHz band for more bandwidth and faster speeds. Currently 6 GHz Band only supported on Windows 11.
- Reliable Connections - The latest IntelC Wi-Fi 6E chipset's reduced latency and improved reliability unlocks your Wi-Fi 6E router's full potential
- Wider Signal Coverage - Two multi-directional antennas with a magnetized base are designed for optimal signal reception
- Bluetooth 5.3 - Security and reliability improvement than last-gen high-speed Bluetooth 5.2
- Improved Security - The latest security enhancement, WPA3, provides enhanced protection in personal password safety
- Reliably Engineered - The specialized heatsink and gold plating improve stability and performance even at high CPU temps
- Backward Compatibility - Full support for 802.11ax/ac/a/b/g/n standards

### HARDWARE FEATURES:

Interface:PCI Express x1

Antenna Type: 2× High-Gain Tri-Band Antennas

Chipset: Intel Wi-Fi 6E Chipset

### WIRELESS FEATURES:

Wireless Standards:IEEE 802.11a/b/g/n/ac/ax

Signal Rate: 2402Mbps at 6GHz, 2402Mbps at 5GHz,

574Mbps at 2.4GHz

Wireless Modes: Infrastructure mode

Wireless Security:WEP, WPA/WPA2/WPA3,

WPA-PSK/WPA2-PSK

### OTHERS:

Dimensions: 3.7 × 4.8 × 0.8 in (95.2 × 120.8 × 21.5 mm)

Certification:CE, FCC, RoHS, Wi-Fi

Package Contents:Archer TXE75E, Magnetized Antenna

Base with 1m RF Cable, Two 5 dBi High Gain Antennas,

Low-Profile Bracket, Bluetooth Header Cable, Quick

Installation Guide, Resource CD

NEW



#09401

Net Price:  
297.00 USD  
Unit: pcs

## 5G Router, AX1800 (TP-Link Archer NX200)

- Boost Your 5G Speed - Take advantage of your advanced 5G network with download speeds up to 4.67 Gbps. Share your 5G network with multiple Wi-Fi devices and enjoy uninterrupted Ultra HD movies, blazingly fast file downloads, and smooth video chats and video conferences.
- AX1800 Dual-Band Wi-Fi 6 Speed - 1201 Mbps (5 GHz) + 574 Mbps (2.4 GHz).
- Plug & Play - Enjoy 5G network right after inserting a SIM card.
- EasyMesh-Compatible - Co-work with EasyMesh products, to provide a more flexible and cost-effective Mesh network with a single Wi-Fi name for seamless whole-home coverage.
- Gigabit WAN/LAN Port - The gigabit WAN/LAN port enables NX200 to work as a traditional wireless router which is compatible with cable, fiber, and DSL modems.

Standards: IEEE 802.11 ax/ac/n/a 5 GHz, IEEE 802.11

ax/n/g/b 2.4 GHz

Power: 12V &#9107;2A

Ports: 1× 1 Gigabit port + 2× 1 Gigabit ports, SIM Card

Format Nano-SIM

Button: WPS Button, Reset Button, Power On/Off Button,

Wi-Fi On/Off Button

Frequency range: 2.4 GHz and 5 GHz

Signal Rate: 574 Mbps on 2.4 GHz, 1201 Mbps on 5 GHz

Advanced Functions: Router/ Access Point Mode, Optional

Ethernet Backhaul, Guest network, TP-Link Mesh Technology

MU-MIMO, Auto Path Selection, Self-Healing, AP Steering,

Band Steering, Beamforming

NEW



#09542

Net Price:  
297.00 USD  
Unit: pcs

## 5G Router, AX1800 (TP-Link Archer NX210)

- Boost Your 5G Speed - Take advantage of your advanced 5G network with download speeds up to 4.67 Gbps. Share your 5G network with multiple Wi-Fi devices and enjoy uninterrupted Ultra HD movies, blazingly fast file downloads, and smooth video chats and video conferences.
- AX1800 Dual-Band Wi-Fi 6 Speed - 1201 Mbps (5 GHz) + 574 Mbps (2.4 GHz).
- Plug & Play - Enjoy 5G network right after inserting a SIM card.
- EasyMesh-Compatible - Co-work with EasyMesh products, to provide a more flexible and cost-effective Mesh network with a single Wi-Fi name for seamless whole-home coverage.
- Gigabit WAN/LAN Port - The gigabit WAN/LAN port enables NX200 to work as a traditional wireless router which is compatible with cable, fiber, and DSL modems.

Standards: IEEE 802.11 ax/ac/n/a 5 GHz, IEEE 802.11

ax/n/g/b 2.4 GHz

Power: 12V &#9107;2A

Ports: 1× 1 Gigabit port + 2× 1 Gigabit ports, SIM Card

Format Nano-SIM

Button: WPS Button, Reset Button, Power On/Off Button,

Wi-Fi On/Off Button

Frequency range: 2.4 GHz and 5 GHz

Signal Rate: 574 Mbps on 2.4 GHz, 1201 Mbps on 5 GHz

Advanced Functions: Router/ Access Point Mode, Optional

Ethernet Backhaul, Guest network, TP-Link Mesh Technology

MU-MIMO, Auto Path Selection, Self-Healing, AP Steering,

Band Steering, Beamforming

NEW



#09400

Net Price:  
318.00 USD  
Unit: pcs

## 5G Router, AX3600 (TP-Link Archer NX600)

- Boost Your 5G Speed - Take advantage of your advanced 5G network with download speeds up to 4.67 Gbps. Share your 5G network with multiple Wi-Fi devices and enjoy uninterrupted Ultra HD movies, blazingly fast file downloads, and smooth video chats and video conferences.
- AX3600 Dual-Band Wi-Fi 6 Speed - 2402 Mbps (5 GHz) + 1148 Mbps (2.4 GHz).
- Plug & Play - Enjoy 5G network right after inserting a SIM card.
- EasyMesh-Compatible - Co-work with EasyMesh products, to provide a more flexible and cost-effective Mesh network with a single Wi-Fi name for seamless whole-home coverage.
- Gigabit WAN/LAN Port - The gigabit WAN/LAN port enables NX200 to work as a traditional wireless router which is compatible with cable, fiber, and DSL modems.

Standards: IEEE 802.11 ax/ac/n/a 5 GHz, IEEE 802.11

ax/n/g/b 2.4 GHz

Power: 12V &#9107;2A

Ports: 1× 2.5 Gigabit port + 2× 1 Gigabit ports, SIM Card

Format Nano-SIM

Button: WPS Button, Reset Button, Power On/Off Button,

Wi-Fi On/Off Button

Frequency range: 2.4 GHz and 5 GHz

Signal Rate: 1148 Mbps on 2.4 GHz, 2402 Mbps on 5 GHz

Advanced Functions: Router/ Access Point Mode, Optional

Ethernet Backhaul, Guest network, TP-Link Mesh Technology

MU-MIMO, Auto Path Selection, Self-Healing, AP Steering,

Band Steering, Beamforming

NEW



#09449

Net Price:  
147.00 USD  
Unit: pcs

## 6000Mbps Outdoor Wireless Access Point, AX6000 (TP-Link EAP683 UR)

- Up to 5952 Mbps WiFi 6 Speeds: 1148 Mbps on 2.4 GHz + 4804 Mbps on 5 GHz
- Ultra-range wireless coverage by 4×4 MIMO dual-band internal antennas with high transmission power.
- Supports WiFi 6 technologies, such as HE160, 1024-QAM, etc.
- Integrates with the Omada SDN platform for centralized management.
- Advanced Features: Omada Mesh, Seamless Roaming, and more.
- PoE+ Powered: Supports both 802.3at PoE+ and DC (adapter not included).

Ports: 1× 2.5G Ethernet Port

Bluetooth: yes

Button: Reset

Frequency range: 5 GHz and 2.4 GHz

Signal Rate: 5 GHz Up to 4804 Mbps, 2.4 GHz Up to 1148

Mbps

Wireless Functions: Multiple SSIDs (Up to 16 SSIDs, 8 for

each band), Enable/Disable Wireless Radio, Automatic

Channel Assignment, Transmit Power Control (Adjust

Transmit Power on dBm), QoS(WMM), Airtime Fairness,

Beamforming, Band Steering, Load Balance, Rate Limit, Link

Aggregation, Reboot Schedule, Wireless Schedule, Wireless

Statistics based on SSID/AP/Client



#09391

Net Price:  
128.00 USD  
Unit: pcs**6000Mbps Wireless Gigabit Router Dual-band AX6000, MU-MIMO (TP-Link Archer AX80)**

- Lightning-Fast AX6000 WiFi: Up to 6.0 Gbps (4804 Mbps + 1148 Mbps) WiFi for faster browsing, streaming, and downloading, all at the same time.
- 2.5G Multi-Gigabit Port: 1× 2.5 Gbps WAN/LAN port + 1× 1 Gbps WAN/LAN port + 3× Gigabit LAN ports + 1× USB 3.0 port ensure max flexibility and boosted throughput.
- Maximized Coverage: Four dual-band high-gain antennas equipped with Beamforming ensure vast coverage.
- More Devices with Less Lag: OFDMA and MU-MIMO technology deliver data to multiple devices simultaneously.
- Powerful CPU: Top-notch quad-core processor ensures fast transmission speeds and smooth operation of numerous devices and applications.
- VPN Client Supported: Allow devices in your home network to access remote VPN servers without needing to install VPN software on every device.
- TP-Link HomeShield: Enhanced security defends against the latest cyber threats.
- EasyMesh-Compatible - Flexibly creates a Mesh network by connecting to an EasyMesh-compatible router for seamless whole-home coverage
- Compatible with Alexa: Control your router via voice commands and make your life smarter and easier with Amazon Alexa.

**HARDWARE FEATURES:**

Memory: 1 GB RAM and 128 MB Flash  
Standards and Protocols: IEEE 802.11ax/ac/n/a 5GHz, IEEE 802.11ax/b/g/n 2.4GHz  
Interface: 1× 2.5 Gigabit WAN/LAN Port, 1× Gigabit WAN/LAN Port, 3× Gigabit LAN Ports, 1 USB-A 3.0 Port  
Button: WPS/Reset Button, Wireless On/Off Button, Power On/Off Button, LED On/Off  
Power Supply: 12V/2A  
Dimensions (W X D X H): 7.9 × 7.4 × 2.3 in (200 × 189 × 59 mm)  
Antenna: 4 × Antennas  
**WIRELESS FEATURES:**  
Frequency: 2.4GHz & 5GHz  
Signal Rate: 5 GHz@ 4804 Mbps (802.11ax), 2.4 GHz@ 1148 Mbps (802.11ax)



#09081

Net Price:  
220.00 USD  
Unit: pcs**6600Mbps Wireless Gigabit Router Tri-band AX6600, MU-MIMO (TP-Link Archer GX90)**

- Game Band - Tri-Band structure provides a 4.8 Gbps Game Band exclusive for your gaming rigs and brings pure immersion.
- Game Accelerator - Detect and optimize gaming streams, to ensure your gaming stays immersive.
- Game Statistics - Real-time latency, game duration and network resource allocation in a glance with fine-tuned UI.
- Game Protector - Keep your accounts and documents safe with Homecare™ security system.
- Expansive Coverage - 8 antennas, Beamforming, high-power FEM, 4T4R combine to deliver WiFi coverage up to a 4-bedroom house.
- 2.5 Gbps Wired Connection - Unleash the potential of your next-level bandwidth network with a 2.5 Gbps WAN/LAN port.
- Powerful Processing - 1.5 GHz Quad-Core CPU ensure your network performance always at peak run.
- Easy Setup - Sset it up in minutes with the powerful Tether app.

**HARDWARE FEATURES:**

Processor: 1.5 GHz 64 bit Quad-Core CPU  
Standards and Protocols: IEEE 802.11ax/ac/n/a 5GHz, IEEE 802.11ax/b/g/n 2.4GHz, Wi-Fi 6  
Interface: 3 10/100/1000Mbps LAN Ports, 1 2.5G/1G/100Mbps WAN Port, 1 USB 3.0 Port, 1 USB 2.0 Port  
Button: WPS/Reset Button, Wireless On/Off Button, Power On/Off Button, LED On/Off  
Power Supply: 12V/5A  
Dimensions (W X D X H): 8.3 × 8.3 × 2.0 in (212 × 212 × 51.8 mm)  
Antenna: 8× High-Performance External Antennas  
**WIRELESS FEATURES:**  
Frequency: 2.4GHz & 5GHz



#09411

Net Price:  
20.80 USD  
Unit: pcs**AX1800 Wireless Dual Band nano USB 2.0 Adapter (TP-Link Archer TX20U Nano)**

- Fast WiFi 6 - Break the gigabit barrier with speeds up to 1201 Mbps (5 GHz) + 574 Mbps (2.4 GHz).
- Dual Band Wireless - 2.4 GHz and 5 GHz bands for flexible connectivity.
- Lower Latency Gameplay - OFDMA and MU-MIMO ensure the most efficient WiFi connection for your PC.
- Improved Security - WPA3 provides the latest security enhancements for personal password protection.
- Nano design - Small, unobtrusive design allows you to plug it in and forget it is even there
- Setup Made Easy - TX20U Nano comes with its driver pre-loaded. Just plug and install.

Standards: IEEE 802.11a/b/g/n/ac/ax

Interface: USB 2.0

Frequency range: 5GHz, 2.4GHz

Antenna: 2× External 5 dBi High Gain Antennas

Max. speed: up to 5GHz 1201Mbps or 2.4GHz 574Mbps

Wireless Modes: Infrastructure mode

Wireless Security: WEP, WPA/WPA2/WPA3,

WPA-PSK/WPA2-PSK

Drivers: Supported operating systems include Windows 11/10

Dimensions: 26.8 × 15.7 × 7.5 mm (1.06 × 0.62 × 0.30 in)

Operating temperatures: 0°C + 40°C

Operating humidity: 10% + 90%, non-condensing

Certificates: CE, FCC, RoHS



#09247

Net Price:  
32.50 USD  
Unit: pcs**AX1800 Wireless Dual Band USB 3.0 Adapter (TP-Link Archer TX20U Plus)**

- Lightning-Fast WiFi 6 - Stream flawless video with 1800 Mbps wireless speeds (1201 Mbps on 5 GHz + 574 Mbps on 2.4 GHz)
- Flexible Dual Band - Ensure your PC has the best connection with 5 GHz and 2.4 GHz bands
- Dual High-Gain Antennas - Connect from farther away with high-quality signals and transmissions
- MU-MIMO - Maintain high download and upload speeds even when other devices are eating up your bandwidth
- OFDMA - Reduce your latency for impeccable conferencing and gameplay on crowded networks
- SuperSpeed USB 3.0 - Up to 10x faster transfer speeds than USB 2.0
- Refined Security - Protect your personal data with the latest WPA3 encryption

Standards: IEEE 802.11ac, IEEE 802.11a, IEEE 802.11n,

IEEE 802.11g, IEEE 802.11b

Interface: USB 3.0

Frequency range: 5GHz, 2.4GHz

Antenna: 2× External 5 dBi High Gain Antennas

Max. speed: up to 5GHz 1201Mbps or 2.4GHz 574Mbps

Max. output power: 20 dBm

Wireless Modes: Infrastructure mode

Wireless Security: WEP, WPA/WPA2, WPA-PSK/WPA2-PSK

Drivers: Supported operating systems include Windows

11/10, macOS

Dimensions: 84 × 156.3 × 19.2 mm (3.3 × 6.2 × 0.76 in)

Operating temperatures: 0°C + 40°C

NEW



#09410

Net Price:  
32.50 USD  
Unit: pcs**AX1800 Wireless Dual Band USB 3.0 Adapter (TP-Link Archer TX20U)**

- Fast WiFi 6 - Break the gigabit barrier with speeds up to 1201 Mbps (5 GHz) + 574 Mbps (2.4 GHz).
- Dual Band Wireless - 2.4 GHz and 5 GHz bands for flexible connectivity.
- Broader Coverage - Connect to your WiFi from wherever in your home with high-gain antennas and Beamforming.
- Lower Latency Gameplay - OFDMA and MU-MIMO ensure the most efficient WiFi connection for your PC.
- Improved Security - WPA3 provides the latest security enhancements for personal password protection.
- SuperSpeed USB 3.0 - Up to 10x faster transfer speeds than USB 2.0.

Standards: IEEE 802.11ac, IEEE 802.11a, IEEE 802.11n,

IEEE 802.11g, IEEE 802.11b

Interface: USB 3.0

Frequency range: 5GHz, 2.4GHz

Antenna: 2× External 5 dBi High Gain Antennas

Max. speed: up to 5GHz 1201Mbps or 2.4GHz 574Mbps

Wireless Modes: Infrastructure mode

Wireless Security: WEP, WPA/WPA2, WPA-PSK/WPA2-PSK

Drivers: Supported operating systems include Windows 11/10

Dimensions: 90.2 × 29.2 × 12.9 mm (3.55 × 1.15 × 0.51 in)

Operating temperatures: 0°C + 40°C

Operating humidity: 10% + 90%, non-condensing



#09311

Net Price:  
44.20 USD  
Unit: pcs**AX1800 Wireless Dual Band USB 3.0 Adapter (TP-Link Archer TX20UH)**

- Fast WiFi 6 - Break the gigabit barrier with speeds up to 1201 Mbps (5 GHz) + 574 Mbps (2.4 GHz).
- Dual Band Wireless - 2.4 GHz and 5 GHz bands for flexible connectivity.
- Broader Coverage - Connect to your WiFi from wherever in your home with high-gain antennas and Beamforming.
- Lower Latency Gameplay - OFDMA and MU-MIMO ensure the most efficient WiFi connection for your PC.
- Improved Security - WPA3 provides the latest security enhancements for personal password protection.
- SuperSpeed USB 3.0 - Up to 10x faster transfer speeds than USB 2.0.

Standards: IEEE 802.11ac, IEEE 802.11a, IEEE 802.11n,

IEEE 802.11g, IEEE 802.11b

Interface: USB 3.0

Frequency range: 5GHz, 2.4GHz

Antenna: 2× External 5 dBi High Gain Antennas

Max. speed: up to 5GHz 1201Mbps or 2.4GHz 574Mbps

Max. output power: 20 dBm

Wireless Modes: Infrastructure mode

Wireless Security: WEP, WPA/WPA2, WPA-PSK/WPA2-PSK

Drivers: Supported operating systems include Windows 11/10

Dimensions: 30.5 × 14.8 × 11.7 mm (1.2 × 0.58 × 0.4 in)

Operating temperatures: 0°C + 40°C



NEW



#09581

Net Price:  
5.74 USD  
Unit: pcs

### AX300 Wireless nano USB 2.0 Adapter (TP-Link MA14N)

- High Speed WiFi - Up to 287 Mbps speeds, upgrades your devices to higher AX WiFi speeds.
- Nano Design - Small, unobtrusive design allows you to plug it in and forget it is even there.
- Pre-loaded Internal Driver - Plug in MA14N with its internal driver and enjoy simple installation.
- Operating Systems - Supports Windows 11/10/7 (32/64 bit) and Linux (Kernel 3.10 and later).

Standards: IEEE 802.11b/g/n/ax  
Interface: USB 2.0  
Frequency range: 2.4GHz  
Max. speed: up to 2.4GHz 287Mbps  
Wireless Modes: Infrastructure mode  
Wireless Security: WPA-PSK/WPA2-PSK, WPA/WPA2  
Drivers: Supported operating systems include Windows 11/10  
Dimensions: 19,15 × 14,94 × 7,19 mm

NEW



#09409

Net Price:  
44.20 USD  
Unit: pcs

### AX3000 Wireless Dual Band USB 3.0 Adapter (TP-Link Archer TX50UH)

- Fast WiFi 6 - Break the gigabit barrier with speeds up to 2402 Mbps (5 GHz) + 574 Mbps (2.4 GHz).
- Dual Band Wireless - 2.4 GHz and 5 GHz bands for flexible connectivity.
- Broader Coverage - Connect to your WiFi from wherever in your home with high-gain antennas and Beamforming.
- Lower Latency Gameplay - OFDMA and MU-MIMO ensure the most efficient WiFi connection for your PC.
- Improved Security - WPA3 provides the latest security enhancements for personal password protection.
- SuperSpeed USB 3.0 - Up to 10x faster transfer speeds than USB 2.0.

Standards: IEEE 802.11a/b/g/n/ac/ax  
Interface: USB 3.0  
Frequency range: 5GHz, 2.4GHz  
Antenna: 2x High-Gain Dual-Band Antennas  
Max. speed: up to 5GHz 2402Mbps or 2.4GHz 574Mbps  
Wireless Modes: Infrastructure mode  
Wireless Security: WEP, WPA/WPA2/WPA3, WPA-PSK/WPA2-PSK  
Drivers: Supported operating systems include Windows 11/10  
Dimensions: 30,5 × 14,8 × 111,7 mm (1,2 × 0,58 × 4,4 in)  
Operating temperatures: 0°C + 40°C  
Operating humidity: 5% + 90%, non-condensing  
Certificates: CE, FCC, RoHS

NEW



#09544

Net Price:  
16.10 USD  
Unit: pcs

### AX900 Wireless Dual Band nano USB 2.0 Adapter, Bluetooth 5.3 (TP-Link Archer TX10U Nano)

- Fast WiFi 6 - Break the gigabit barrier with speeds up to 600 Mbps (5 GHz) + 287 Mbps (2.4 GHz).
- Dual Band Wireless - 2.4 GHz and 5 GHz bands for flexible connectivity.
- Lower Latency Gameplay - OFDMA and MU-MIMO ensure the most efficient WiFi connection for your PC.
- Improved Security - WPA3 provides the latest security enhancements for personal password protection.
- Nano design - Small, unobtrusive design allows you to plug it in and forget it is even there
- Setup Made Easy - TX20U Nano comes with its driver pre-loaded. Just plug and install.

Standards: IEEE 802.11a/b/g/n/ac/ax  
Interface: USB 2.0  
Frequency range: 5GHz, 2.4GHz  
Max. speed: up to 5GHz 600Mbps or 2.4GHz 287Mbps  
Wireless Modes: Infrastructure mode  
Wireless Security: WEP, WPA/WPA2/WPA3, WPA-PSK/WPA2-PSK  
Drivers: Supported operating systems include Windows 11/10  
Dimensions: 19.2\*15.7\*7.4mm  
Operating temperatures: 0°C + 40°C  
Operating humidity: 10% + 90%, non-condensing  
Certificates: CE, FCC, RoHS



#09526

Net Price:  
28.40 USD  
Unit: pcs

### AXE5400 Wi-Fi 6E Bluetooth 5.3 PCIe Adapter (TP-Link Mercusys MA86XE)

- Unstoppable Tri-Band Speed - Speeds up to 2402 Mbps (6 GHz) + 2402 Mbps (5 GHz) + 574 Mbps (2.4 GHz)
- WiFi 6E Standard - Expand to the clearer, broader 6 GHz band
- Wider Signal Coverage - Two high-performance antennas
- Bluetooth 5.3 - The latest Bluetooth technology achieves faster speeds and broader coverage
- Improved Security - The latest security enhancement, WPA3, provides enhanced protection in personal password safety
- Backward Compatibility - Full support for 802.11ax/ac/a/b/g/n standards
- Windows Compatible - Supported operating system: Windows 10, 11 (64 bit), and currently 6 GHz Band only supported on Windows 11.

**HARDWARE FEATURES:**  
Wireless Standards: IEEE802.11ax, IEEE802.11ac, IEEE802.11n, IEEE802.11g, IEEE802.11b  
Dimensions (W x D x H): 228 × 120.8 × 21.5 mm  
Antenna Type: 2x Fixed High-Performance Omni-Directional Antennas

**WIRELESS FEATURES**  
Frequency: 2.4GHz & 5GHz & 6GHz  
Signal Rate: 2402 Mbps on 6 GHz, 2402 Mbps on 5 GHz, 574 Mbps on 2.4 GHz  
Wireless Security: WPA-PSK/WPA2-PSK/WPA3-SAE  
**OTHERS**

Environment: Operating Temperature 0°~40° (32°~104°), Storage Temperature -40°~70° (-40°~158°), Operating Humidity 10%~90% non-condensing, Storage Humidity 5%~90% non-condensing  
Warranty: 2 years limited warranty. Advanced replacement service is available.

NEW



#09408

Net Price:  
53.50 USD  
Unit: pcs

### AXE5400 Wireless Tri Band USB 3.0 Adapter (TP-Link Archer TXE70UH)

- Lighting-Fast WiFi 6E - Congestion-free speeds up to 2402 Mbps (6 GHz) + 2402 Mbps (5 GHz) + 574 Mbps (2.4 GHz).
- Tri-Band Wireless - 2.4 GHz, 5 GHz and 6 GHz bands for flexible connectivity.
- Broader Coverage - Connect to your WiFi from wherever in your home with high-gain antennas and Beamforming.
- Lower Latency Gameplay - OFDMA and MU-MIMO ensure the most efficient WiFi connection for your PC.
- Improved Security - WPA3 provides the latest security enhancements for personal password protection.
- SuperSpeed USB 3.0 - Up to 10x faster transfer speeds than USB 2.0.

Standards: IEEE 802.11a/b/g/n/ac/ax  
Interface: USB 3.0  
Frequency range: 6GHz, 5GHz, 2.4GHz  
Antenna: 2x High-Gain Tri-Band Antennas  
Max. speed: up to 6GHz 2402Mbps, 5GHz 2402Mbps or 2.4GHz 574Mbps  
Wireless Modes: Infrastructure mode  
Wireless Security: WEP, WPA/WPA2/WPA3, WPA-PSK/WPA2-PSK  
Drivers: Supported operating systems include Windows 11/10  
Dimensions: 30,5 × 14,8 × 111,7 mm (1,2 × 0,58 × 4,4 in)  
Operating temperatures: 0°C + 40°C  
Operating humidity: 5% + 90%, non-condensing  
Certificates: CE, FCC, RoHS

NEW



#09455

Net Price:  
146.00 USD  
Unit: pcs

### Outdoor Wireless Bridge (TP-Link EAP211-Bridge KIT)

- 802.11ac for up to 867 Mbps on the 5 GHz wireless data rate.
- Ideal for long-range wireless transmission up to 1 km.
- Auto-pairing and agile LEDs for efficient deployment.
- 3x Gigabit Ethernet ports for more high-speed IP camera connections.
- Supports Omada SDN for remote and centralized management.
- IP65 weatherproof enclosure and 6kV lightning protection ensure all-weather suitability.
- Supports Passive PoE for flexible deployment (adapter included).

Standards: IEEE 802.11ac/n/g/b/a  
Ports: Gigabit Ethernet (RJ-45) Port \*3 (Support IEEE802.3af PoE)  
Frequency range: 5GHz  
Signal Rate: 5GHz Up to 867Mbps  
Wireless Functions: Mesh, MU-MIMO 5G 2x2 MU-MIMO DL, Load Balance, Beamforming, Seamless Roaming(802.11r), Airtime Fairness, Multiple SSIDs 8, Wireless Statistics, Wireless Schedule, Reboot Schedule, RADIUS Accounting, MAC Authentication, Static IP/Dynamic IP  
Wireless Security: VLAN, Access Control, Rogue AP Detection, Captive Portal Authentication, Maximum number of MAC Filter 4,000, WPA-Personal/Enterprise, WPA2-Personal/Enterprise





NEW



#09454

Net Price:  
156.00 USD  
Unit: pcs

#### Outdoor Wireless Bridge (TP-Link EAP215-Bridge KIT)

- 802.11ac for up to 867 Mbps on the 5 GHz wireless data rate.
- Ideal for long-range wireless transmission up to 5 km.
- Auto-pairing and agile LEDs for efficient deployment.
- 3× Gigabit Ethernet ports for more high-speed IP camera connections.
- Supports Omada SDN for remote and centralized management.
- IP65 weatherproof enclosure and 6kV lightning protection ensure all-weather suitability.
- Supports Passive PoE for flexible deployment (adapter included).

Standards: IEEE 802.11ac/n/g/b/a  
Ports: Gigabit Ethernet (RJ-45) Port \*3 (Support IEEE802.3af PoE)  
Frequency range: 5GHz  
Signal Rate: 5GHz Up to 867Mbps  
Wireless Functions: Mesh, MU-MIMO 5G 2x2 MU-MIMO DL, Load Balance, Beamforming, Seamless Roaming(802.11r), Airtime Fairness, Multiple SSIDs 8, Wireless Statistics, Wireless Schedule, Reboot Schedule, RADIUS Accounting, MAC Authentication, Static IP/Dynamic IP  
Wireless Security: VLAN, Access Control, Rogue AP Detection, Captive Portal Authentication, Maximum number of MAC Filter 4,000, WPA-Personal/Enterprise, WPA2-Personal/Enterprise



#09312

Net Price:  
44.20 USD  
Unit: pcs

#### Router Mesh Deco X10 1-pack, AX1500 (TP-Link DECO X10(1-Pack))

- Faster Connections: Wi-Fi 6 speeds up to 1,800 Mbps-1,201 Mbps on 5 GHz and 300 Mbps on 2.4 GHz.
- Connect More Devices: OFDMA and MU-MIMO technology quadruple capacity to enable simultaneous transmission to more devices.
- Boosted Seamless Coverage: Achieve seamless whole home coverage with a clearer and stronger whole home Wi-Fi signal generated by Wi-Fi 6.
- Ultra-Low Latency: Greater reduction in latency enables more responsive gaming and video chatting.
- One Unified Network: Multiple units form a whole-home network that auto-selects the best connection as you move around your home.
- Total Security: WPA3 encryption and TP-Link HomeCare™ provide personalized features, including Parental Controls, Antivirus, and Quality of Service (QoS) to ensure a safer online experience.
- Setup Made Easier Than Ever: The Deco app walks you through setup step-by-step.

Standards: IEEE 802.11 ax/ac/n/a 5 GHz, IEEE 802.11 ax/n/g/b 2.4 GHz  
Processor: Qualcomm 1 GHz Quad-core CPU  
Ports: 2 ports 10/100/1000 Mb/s WAN/LAN  
Button: 1 Reset button  
Flash: 16 MB  
SDRAM: 128 MB  
Frequency range: 2.4 GHz and 5 GHz  
Signal Rate: 300 Mbps on 2.4 GHz, 1201 Mbps on 5 GHz  
EIRP: FCC <30 dBm, CE <20 dBm (2.4 GHz) <23 dBm (5 GHz)  
Advanced Functions: Router/ Access Point Mode, Optional Ethernet Backhaul, Guest network, TP-Link Mesh Technology MU-MIMO, Auto Path Selection, Self-Healing, AP Steering, Band Steering, Beamforming



#09313

Net Price:  
83.90 USD  
Unit: pcs

#### Router Mesh Deco X10 2-pack, AX1500 (TP-Link DECO X10(2-Pack))

- Faster Connections: Wi-Fi 6 speeds up to 1,800 Mbps-1,201 Mbps on 5 GHz and 300 Mbps on 2.4 GHz.
- Connect More Devices: OFDMA and MU-MIMO technology quadruple capacity to enable simultaneous transmission to more devices.
- Boosted Seamless Coverage: Achieve seamless whole home coverage with a clearer and stronger whole home Wi-Fi signal generated by Wi-Fi 6.
- Ultra-Low Latency: Greater reduction in latency enables more responsive gaming and video chatting.
- One Unified Network: Multiple units form a whole-home network that auto-selects the best connection as you move around your home.
- Total Security: WPA3 encryption and TP-Link HomeCare™ provide personalized features, including Parental Controls, Antivirus, and Quality of Service (QoS) to ensure a safer online experience.
- Setup Made Easier Than Ever: The Deco app walks you through setup step-by-step.

Standards: IEEE 802.11 ax/ac/n/a 5 GHz, IEEE 802.11 ax/n/g/b 2.4 GHz  
Processor: Qualcomm 1 GHz Quad-core CPU  
Ports: 2 ports 10/100/1000 Mb/s WAN/LAN  
Button: 1 Reset button  
Flash: 16 MB  
SDRAM: 128 MB  
Frequency range: 2.4 GHz and 5 GHz  
Signal Rate: 300 Mbps on 2.4 GHz, 1201 Mbps on 5 GHz  
EIRP: FCC <30 dBm, CE <20 dBm (2.4 GHz) <23 dBm (5 GHz)  
Advanced Functions: Router/ Access Point Mode, Optional Ethernet Backhaul, Guest network, TP-Link Mesh Technology MU-MIMO, Auto Path Selection, Self-Healing, AP Steering, Band Steering, Beamforming



#09314

Net Price:  
124.00 USD  
Unit: pcs

#### Router Mesh Deco X10 3-pack, AX1500 (TP-Link DECO X10(3-Pack))

- Faster Connections: Wi-Fi 6 speeds up to 1,800 Mbps-1,201 Mbps on 5 GHz and 300 Mbps on 2.4 GHz.
- Connect More Devices: OFDMA and MU-MIMO technology quadruple capacity to enable simultaneous transmission to more devices.
- Boosted Seamless Coverage: Achieve seamless whole home coverage with a clearer and stronger whole home Wi-Fi signal generated by Wi-Fi 6.
- Ultra-Low Latency: Greater reduction in latency enables more responsive gaming and video chatting.
- One Unified Network: Multiple units form a whole-home network that auto-selects the best connection as you move around your home.
- Total Security: WPA3 encryption and TP-Link HomeCare™ provide personalized features, including Parental Controls, Antivirus, and Quality of Service (QoS) to ensure a safer online experience.
- Setup Made Easier Than Ever: The Deco app walks you through setup step-by-step.

Standards: IEEE 802.11 ax/ac/n/a 5 GHz, IEEE 802.11 ax/n/g/b 2.4 GHz  
Processor: Qualcomm 1 GHz Quad-core CPU  
Ports: 2 ports 10/100/1000 Mb/s WAN/LAN  
Button: 1 Reset button  
Flash: 16 MB  
SDRAM: 128 MB  
Frequency range: 2.4 GHz and 5 GHz  
Signal Rate: 300 Mbps on 2.4 GHz, 1201 Mbps on 5 GHz  
EIRP: FCC <30 dBm, CE <20 dBm (2.4 GHz) <23 dBm (5 GHz)  
Advanced Functions: Router/ Access Point Mode, Optional Ethernet Backhaul, Guest network, TP-Link Mesh Technology MU-MIMO, Auto Path Selection, Self-Healing, AP Steering, Band Steering, Beamforming

NEW



#09538

Net Price:  
117.00 USD  
Unit: pcs

#### Router Mesh Deco X10-4G, AX1500, LTE (TP-Link DECO X10-4G)

- Internet Everywhere with 4G+ Speed - Provides WiFi 6 Mesh coverage through 4G+ CAT6 access.
- AX1500 Dual-Band WiFi - 1201 Mbps (5 GHz) and 300 Mbps (2.4 GHz) dual band WiFi with WiFi 6 technology.
- Seamless Roaming - Walk through your home and stay connected with the fastest possible speeds.&#8225;
- Ultra-Low Latency - Greater reduction in latency enables more responsive gaming and video chatting.
- Gigabit Wired Speeds - 3× Gigabit ports provide sufficient connectivity.
- Parental Controls - Limit online time and block inappropriate websites according to unique profiles you create for each family member.

Standards: IEEE 802.11 ax/ac/n/a 5 GHz, IEEE 802.11 ax/n/g/b 2.4 GHz  
Ports: 3 ports 10/100/1000 Mb/s WAN/LAN  
Button: 1 Reset button  
Frequency range: 2.4 GHz and 5 GHz  
Signal Rate: 300 Mbps on 2.4 GHz, 1201 Mbps on 5 GHz  
EIRP: FCC <30 dBm, CE <20 dBm (2.4 GHz) <23 dBm (5 GHz)  
Advanced Functions: 3G/4G, Router/ Access Point Mode, Optional Ethernet Backhaul, Guest network, TP-Link Mesh Technology MU-MIMO, Auto Path Selection, Self-Healing, AP Steering, Band Steering, Beamforming  
Wireless Security: WPA-PSK/WPA2-PSK



#09248

Net Price:  
67.60 USD  
Unit: pcs

#### Router Mesh Deco X20 1-pack, AX1800 (TP-Link DECO X20(1-Pack))

- Faster Connections: Wi-Fi 6 speeds up to 1,800 Mbps-1,201 Mbps on 5 GHz and 574 Mbps on 2.4 GHz.
- Connect More Devices: OFDMA and MU-MIMO technology quadruple capacity to enable simultaneous transmission to more devices.
- Boosted Seamless Coverage: Achieve seamless whole home coverage with a clearer and stronger whole home Wi-Fi signal generated by Wi-Fi 6.
- Ultra-Low Latency: Greater reduction in latency enables more responsive gaming and video chatting.
- One Unified Network: Multiple units form a whole-home network that auto-selects the best connection as you move around your home.
- Total Security: WPA3 encryption and TP-Link HomeCare™ provide personalized features, including Parental Controls, Antivirus, and Quality of Service (QoS) to ensure a safer online experience.
- Setup Made Easier Than Ever: The Deco app walks you through setup step-by-step.

Standards: IEEE 802.11 ax/ac/n/a 5 GHz, IEEE 802.11 ax/n/g/b 2.4 GHz  
Processor: Qualcomm 1 GHz Quad-core CPU  
Ports: 2 ports 10/100/1000 Mb/s WAN/LAN  
Button: 1 Reset button  
Flash: 16 MB  
SDRAM: 128 MB  
Frequency range: 2.4 GHz and 5 GHz  
Signal Rate: 574 Mbps on 2.4 GHz, 1201 Mbps on 5 GHz  
EIRP: FCC <30 dBm, CE <20 dBm (2.4 GHz) <23 dBm (5 GHz)  
Advanced Functions: Router/ Access Point Mode, Optional Ethernet Backhaul, Guest network, TP-Link Mesh Technology MU-MIMO, Auto Path Selection, Self-Healing, AP Steering, Band Steering, Beamforming



#09085

Net Price:  
126.00 USD  
Unit: pcs

**Router Mesh Deco X20 2-pack, AX1800 (TP-Link DECO X20(2-Pack))**

- Faster Connections: Wi-Fi 6 speeds up to 1,800 Mbps-1,201 Mbps on 5 GHz and 574 Mbps on 2.4 GHz.
- Connect More Devices: OFDMA and MU-MIMO technology quadruple capacity to enable simultaneous transmission to more devices.
- Boosted Seamless Coverage: Achieve seamless whole home coverage with a clearer and stronger whole home Wi-Fi signal generated by Wi-Fi 6.
- Ultra-Low Latency: Greater reduction in latency enables more responsive gaming and video chatting.
- One Unified Network: Multiple units form a whole-home network that auto-selects the best connection as you move around your home.
- Total Security: WPA3 encryption and TP-Link HomeCare™ provide personalized features, including Parental Controls, Antivirus, and Quality of Service (QoS) to ensure a safer online experience.
- Setup Made Easier Than Ever: The Deco app walks you through setup step-by-step.

Standards: IEEE 802.11 ax/ac/n/a 5 GHz, IEEE 802.11 ax/n/g/b 2.4 GHz  
Processor: Qualcomm 1 GHz Quad-core CPU  
Ports: 2 ports 10/100/1000 Mb/s WAN/LAN  
Button: 1 Reset button  
Flash: 16 MB  
SDRAM: 128 MB  
Frequency range: 2.4 GHz and 5 GHz  
Signal Rate: 574 Mbps on 2.4 GHz, 1201 Mbps on 5 GHz  
EIRP: FCC <30 dBm, CE <20 dBm (2.4 GHz) <23 dBm (5 GHz)  
Advanced Functions: Router/ Access Point Mode, Optional Ethernet Backhaul, Guest network, TP-Link Mesh Technology MU-MIMO, Auto Path Selection, Self-Healing, AP Steering, Band Steering, Beamforming



#09053

Net Price:  
187.00 USD  
Unit: pcs

**Router Mesh Deco X20 3-pack, AX1800 (TP-Link DECO X20(3-Pack))**

- Faster Connections: Wi-Fi 6 speeds up to 1,800 Mbps-1,201 Mbps on 5 GHz and 574 Mbps on 2.4 GHz.
- Connect More Devices: OFDMA and MU-MIMO technology quadruple capacity to enable simultaneous transmission to more devices.
- Boosted Seamless Coverage: Achieve seamless whole home coverage with a clearer and stronger whole home Wi-Fi signal generated by Wi-Fi 6.
- Ultra-Low Latency: Greater reduction in latency enables more responsive gaming and video chatting.
- One Unified Network: Multiple units form a whole-home network that auto-selects the best connection as you move around your home.
- Total Security: WPA3 encryption and TP-Link HomeCare™ provide personalized features, including Parental Controls, Antivirus, and Quality of Service (QoS) to ensure a safer online experience.
- Setup Made Easier Than Ever: The Deco app walks you through setup step-by-step.

Standards: IEEE 802.11 ax/ac/n/a 5 GHz, IEEE 802.11 ax/n/g/b 2.4 GHz  
Processor: Qualcomm 1 GHz Quad-core CPU  
Ports: 2 ports 10/100/1000 Mb/s WAN/LAN  
Button: 1 Reset button  
Flash: 16 MB  
SDRAM: 128 MB  
Frequency range: 2.4 GHz and 5 GHz  
Signal Rate: 574 Mbps on 2.4 GHz, 1201 Mbps on 5 GHz  
EIRP: FCC <30 dBm, CE <20 dBm (2.4 GHz) <23 dBm (5 GHz)  
Advanced Functions: Router/ Access Point Mode, Optional Ethernet Backhaul, Guest network, TP-Link Mesh Technology MU-MIMO, Auto Path Selection, Self-Healing, AP Steering, Band Steering, Beamforming



#09186

Net Price:  
168.00 USD  
Unit: pcs

**Router Mesh Deco X20-4G, AX1800, LTE (TP-Link DECO X20-4G)**

- Internet Everywhere with 4G+ Speed - Provides WiFi 6 Mesh coverage through 4G+ CAT6 access
- Superior WiFi 6 speeds up to 1.8 Gbps - 1201 Mbps (5 GHz) and 574 Mbps (2.4 GHz) dual band WiFi with WiFi 6 technology
- Fully Gigabit Ethernet - 3x Gigabit WAN/LAN Ethernet ports provide flexible internet access at warp speed\*\*
- TP-Link HomeShield - Real-time IoT and network protection, robust Parental Controls, and comprehensive reports
- 3G/4G Failover - Flexible access from Ethernet to 3G/4G to prevent data loss

Standards: IEEE 802.11 ax/ac/n/a 5 GHz, IEEE 802.11 ax/n/g/b 2.4 GHz  
Processor: 1.5 GHz Quad-Core CPU  
Ports: 3 ports 10/100/1000 Mb/s WAN/LAN  
Button: 1 Reset button  
USB Support: 12 V / 1.5 A  
Frequency range: 2.4 GHz and 5 GHz  
Signal Rate: 574 Mbps on 2.4 GHz, 1201 Mbps on 5 GHz  
EIRP: FCC <30 dBm, CE <20 dBm (2.4 GHz) <23 dBm (5 GHz)  
Advanced Functions: 3G/4G, Router/ Access Point Mode, Optional Ethernet Backhaul, Guest network, TP-Link Mesh Technology MU-MIMO, Auto Path Selection, Self-Healing, AP Steering, Band Steering, Beamforming



#09214

Net Price:  
76.90 USD  
Unit: pcs

**Router Mesh Deco X50 1-pack, AX3000 (TP-Link DECO X50(1-Pack))**

- AX3000 Dual Band WiFi - Super-fast WiFi 6 with speeds up to 3.0 Gbps
- 4 Streams, Less Lag - 2x2/HE160 2402 Mbps + 2x2 574 Mbps
- Gigabit Wired Speed - 3x Gigabit ports provide sufficient connectivity
- Boosted Seamless Coverage - Seamless mesh WiFi coverage up to 2,500 ft2 (1-pack)
- AI-Driven Mesh - Intelligently learns the network environment to provide ideal WiFi unique to your home
- TP-Link HomeShield - Provides comprehensive network protection, robust parental controls, and real-time IoT protection
- Setup Made Easier Than Ever - The Deco app walks you through the setup step-by-step

Standards: IEEE 802.11 ax/ac/n/a 5 GHz, IEEE 802.11 ax/n/g/b 2.4 GHz  
Processor: 1 GHz Dual-core CPU  
Power: 12V & #9107:1.5A  
Ports: 3 ports 10/100/1000 Mb/s WAN/LAN  
Button: 1 Reset button  
Frequency range: 2.4 GHz and 5 GHz  
Signal Rate: 574 Mbps on 2.4 GHz, 2402 Mbps on 5 GHz  
EIRP: FCC <30 dBm, CE <20 dBm (2.4 GHz) <23 dBm (5 GHz)  
Advanced Functions: Router/ Access Point Mode, Optional Ethernet Backhaul, Guest network, TP-Link Mesh Technology MU-MIMO, Auto Path Selection, Self-Healing, AP Steering, Band Steering, Beamforming



#09384

Net Price:  
329.00 USD  
Unit: pcs

**Router Mesh Deco X50 5G 1-pack, AX3000 (TP-Link DECO X50-5G(1-Pack))**

- Ultra-Fast Broadband Connection: Supports Sub-6 GHz 5G technology boosts download speeds up to 4.67 Gbps
- Ultra-Low Latency: 5G brings responsive network connections with only 1 ms latency
- AX3000 Dual-Band Wi-Fi 6 Speed: 2402 Mbps (5 GHz) + 574 Mbps (2.4 GHz)
- 2.5 Gigabit Wired Connections: 1x 2.5 Gbps port + 2x Gigabit port
- Mesh Network: Deco mesh technology ensures strong Wi-Fi signals everywhere
- Flexible Network Access: 4G, 5G, Fixed-Line Internet Access
- Simplified Setup: Easily set up and manage your network with the TP-Link Deco app
- TP-Link HomeShield: Provides comprehensive network protection, robust parental controls, and real-time IoT security

Standards: IEEE 802.11 ax/ac/n/a 5 GHz, IEEE 802.11 ax/n/g/b 2.4 GHz  
Power: 12V & #9107:2.5A  
Ports: 1x 2.5 Gigabit port + 2x 1 Gigabit ports, SIM Card Format Nano-SIM  
Button: 1 Reset button  
Frequency range: 2.4 GHz and 5 GHz  
Signal Rate: 574 Mbps on 2.4 GHz, 2402 Mbps on 5 GHz  
EIRP: FCC <30 dBm, CE <20 dBm (2.4 GHz) <23 dBm (5 GHz)  
Advanced Functions: Router/ Access Point Mode, Optional Ethernet Backhaul, Guest network, TP-Link Mesh Technology MU-MIMO, Auto Path Selection, Self-Healing, AP Steering, Band Steering, Beamforming



#09383

Net Price:  
133.00 USD  
Unit: pcs

**Router Mesh Deco X50 Outdoor 1-pack, AX3000 (TP-Link DECO X50-Outdoor(1-Pack))**

- AX3000 Dual-Band Wi-Fi 6- Enjoy binge-watching your favorite series in 4K with combined speeds of up to 3000 Mbps (574 Mbps on 2.4 GHz and 2402 Mbps on 5 GHz )
- Multiple mount options - Pole mount, wall mount, and tabletop
- Working outdoor - Industry-leading IP65 dust & water resistance
- Powered over Ethernet - Provide both data connection and electric power with a single cable
- Full Gigabit Ethernet - 2 x Gigabit WAN/LAN Ethernet ports provide solid internet access at high speeds.
- Work With All Decos - Compatible with every other Deco model to form a Mesh network.
- TP-Link HomeShield - Provides comprehensive network protection, robust parental controls, and real-time

Standards: IEEE 802.11 ax/ac/n/a 5 GHz, IEEE 802.11 ax/n/g/b 2.4 GHz  
Processor: 1 GHz Dual-core CPU  
Power: IEEE 802.3at PoE or 100-240V~50/60Hz 0.5A AC  
Ports: 2x Gigabit port (Per Deco Unit)  
Button: 1 Reset button  
Frequency range: 2.4 GHz and 5 GHz  
Signal Rate: 574 Mbps on 2.4 GHz, 2402 Mbps on 5 GHz  
EIRP: FCC <30 dBm, CE <20 dBm (2.4 GHz) <23 dBm (5 GHz)  
Advanced Functions: Router/ Access Point Mode, Optional Ethernet Backhaul, Guest network, TP-Link Mesh Technology MU-MIMO, Auto Path Selection, Self-Healing, AP Steering, Band Steering, Beamforming



**#09382**  
Net Price:  
112.00 USD  
Unit: pcs

**Router Mesh Deco X50 PoE 1-pack, AX3000 (TP-Link DECO X50-PoE(1-Pack))**

- AX3000 Dual-Band WiFi - 2402 Mbps (5 GHz) + 574 Mbps (2.4 GHz).
- Multiple Installation Options - Place it on a tabletop or install it on a ceiling or wall with the adaptive accessories.
- PoE Supported - Power over Ethernet for simplified network deployment.
- Multi-Gig 2.5 Gbps Wired Network - 1× 2.5 Gbps port + 1× Gigabit Port.
- Seamless AI-Driven Mesh - Intelligently learns your network environment to provide the ideal WiFi unique to your home.
- TP-Link HomeShield - Provides comprehensive network protection, robust parental controls, and real-time IoT security.
- Universal Compatibility - Backward compatible with all WiFi generations and works with any internet service provider (ISP) and modem.
- Setup Made Easier Than Ever - The Deco app walks you through setup step-by-step.

Standards: IEEE 802.11 ax/ac/n/a 5 GHz, IEEE 802.11 ax/n/g/b 2.4 GHz  
Processor: 1 GHz Dual-core CPU  
Power: 802.3at PoE, 12V DC (EU Version 12V/1.2A DC. US Version 12V/1.5A DC). Note- DC adapter is included in the package  
Ports: 1× 2.5 Gbps port + 1× Gigabit port (Per Deco Unit)  
Button: 1 Reset button  
Frequency range: 2.4 GHz and 5 GHz  
Signal Rate: 574 Mbps on 2.4 GHz, 2402 Mbps on 5 GHz  
EIRP: FCC <30 dBm, CE <20 dBm (2.4 GHz) <23 dBm (5 GHz)  
Advanced Functions: Router/ Access Point Mode, Optional Ethernet Backhaul, Guest network, TP-Link Mesh Technology MU-MIMO, Auto Path Selection, Self-Healing, AP Steering, Band Steering, Beamforming



**#09315**  
Net Price:  
220.00 USD  
Unit: pcs

**Router Mesh Deco X50 PoE 2-pack, AX3000 (TP-Link DECO X50-PoE(2-Pack))**

- AX3000 Dual-Band WiFi - 2402 Mbps (5 GHz) + 574 Mbps (2.4 GHz).
- Multiple Installation Options - Place it on a tabletop or install it on a ceiling or wall with the adaptive accessories.
- PoE Supported - Power over Ethernet for simplified network deployment.
- Multi-Gig 2.5 Gbps Wired Network - 1× 2.5 Gbps port + 1× Gigabit Port.
- Seamless AI-Driven Mesh - Intelligently learns your network environment to provide the ideal WiFi unique to your home.
- TP-Link HomeShield - Provides comprehensive network protection, robust parental controls, and real-time IoT security.
- Universal Compatibility - Backward compatible with all WiFi generations and works with any internet service provider (ISP) and modem.
- Setup Made Easier Than Ever - The Deco app walks you through setup step-by-step.

Standards: IEEE 802.11 ax/ac/n/a 5 GHz, IEEE 802.11 ax/n/g/b 2.4 GHz  
Processor: 1 GHz Dual-core CPU  
Power: 802.3at PoE, 12V DC (EU Version 12V/1.2A DC. US Version 12V/1.5A DC). Note- DC adapter is included in the package  
Ports: 1× 2.5 Gbps port + 1× Gigabit port (Per Deco Unit)  
Button: 1 Reset button  
Frequency range: 2.4 GHz and 5 GHz  
Signal Rate: 574 Mbps on 2.4 GHz, 2402 Mbps on 5 GHz  
EIRP: FCC <30 dBm, CE <20 dBm (2.4 GHz) <23 dBm (5 GHz)  
Advanced Functions: Router/ Access Point Mode, Optional Ethernet Backhaul, Guest network, TP-Link Mesh Technology MU-MIMO, Auto Path Selection, Self-Healing, AP Steering, Band Steering, Beamforming



**#09249**  
Net Price:  
344.00 USD  
Unit: pcs

**Router Mesh Deco X50 PoE 3-pack, AX3000 (TP-Link DECO X50-PoE(3-Pack))**

- AX3000 Dual-Band WiFi - 2402 Mbps (5 GHz) + 574 Mbps (2.4 GHz).
- Multiple Installation Options - Place it on a tabletop or install it on a ceiling or wall with the adaptive accessories.
- PoE Supported - Power over Ethernet for simplified network deployment.
- Multi-Gig 2.5 Gbps Wired Network - 1× 2.5 Gbps port + 1× Gigabit Port.
- Seamless AI-Driven Mesh - Intelligently learns your network environment to provide the ideal WiFi unique to your home.
- TP-Link HomeShield - Provides comprehensive network protection, robust parental controls, and real-time IoT security.
- Universal Compatibility - Backward compatible with all WiFi generations and works with any internet service provider (ISP) and modem.
- Setup Made Easier Than Ever - The Deco app walks you through setup step-by-step.

Standards: IEEE 802.11 ax/ac/n/a 5 GHz, IEEE 802.11 ax/n/g/b 2.4 GHz  
Processor: 1 GHz Dual-core CPU  
Power: 802.3at PoE, 12V DC (EU Version 12V/1.2A DC. US Version 12V/1.5A DC). Note- DC adapter is included in the package  
Ports: 1× 2.5 Gbps port + 1× Gigabit port (Per Deco Unit)  
Button: 1 Reset button  
Frequency range: 2.4 GHz and 5 GHz  
Signal Rate: 574 Mbps on 2.4 GHz, 2402 Mbps on 5 GHz  
EIRP: FCC <30 dBm, CE <20 dBm (2.4 GHz) <23 dBm (5 GHz)  
Advanced Functions: Router/ Access Point Mode, Optional Ethernet Backhaul, Guest network, TP-Link Mesh Technology MU-MIMO, Auto Path Selection, Self-Healing, AP Steering, Band Steering, Beamforming

NEW



**#09537**  
Net Price:  
280.00 USD  
Unit: pcs

**Router Mesh Deco X50 Pro 3-pack, AX3000 (TP-Link DECO X50 Pro(3-Pack))**

- AX3000 Dual Band WiFi 6 Speed - Super-fast WiFi 6 with speeds up to 3.0 Gbps
- 4 Streams, Less Lag - 2×2/HE160 2402 Mbps + 2×2 574 Mbps
- 2.5G Access from Every Port - 2× 2.5 Gbps ports make full use of gigabit speeds from your local ISP
- Boosted Seamless Coverage - Seamless mesh WiFi coverage up to 2,500 ft2 (1-pack)
- AI-Driven Mesh - Intelligently learns the network environment to provide ideal WiFi unique to your home
- TP-Link HomeShield - Provides comprehensive network protection, robust parental controls, and real-time IoT protection
- Setup Made Easier Than Ever - The Deco app walks you through the setup step-by-step

Standards: IEEE 802.11 ax/ac/n/a 5 GHz, IEEE 802.11 ax/n/g/b 2.4 GHz  
Ports: 2 ports 2.5 Gb/s  
Button: 1 Reset button  
Frequency range: 2.4 GHz and 5 GHz  
Signal Rate: 574 Mbps on 2.4 GHz, 2402 Mbps on 5 GHz  
EIRP: FCC <30 dBm, CE <20 dBm (2.4 GHz) <23 dBm (5 GHz)  
Advanced Functions: Router/ Access Point Mode, Optional Ethernet Backhaul, Guest network, TP-Link Mesh Technology MU-MIMO, Auto Path Selection, Self-Healing, AP Steering, Band Steering, Beamforming  
Wireless Security: WPA-PSK/WPA2-PSK



**#09086**  
Net Price:  
224.00 USD  
Unit: pcs

**Router Mesh Deco X60 2-pack, AX3000 (TP-Link DECO X60(2-Pack))**

- Faster Connections: Wi-Fi 6 speeds up to 3,000 Mbps-2,402 Mbps on 5 GHz and 574 Mbps on 2.4 GHz.
- Connect More Devices: OFDMA and MU-MIMO technology quadruple capacity to enable simultaneous transmission to more devices.
- Boosted Seamless Coverage: Achieve seamless whole-home coverage with a clearer and stronger whole-home Wi-Fi signal generated by Wi-Fi 6.
- Ultra-Low Latency: Greater reduction in latency enables more responsive gaming and video chatting.
- One Unified Network: Multiple units form a whole-home network that auto-selects the best connection as you move around your home.
- Total Security: WPA3 encryption and TP-Link HomeCareTM provide personalized features, including Parental Controls, Antivirus, and Quality of Service (QoS) to ensure a safer online experience.
- Setup Made Easier Than Ever: The Deco app walks you through the setup step-by-step.

Standards: IEEE 802.11 ax/ac/n/a 5 GHz, IEEE 802.11 ax/n/g/b 2.4 GHz  
Processor: Qualcomm 1 GHz Quad-core CPU  
Ports: 2 ports 10/100/1000 Mb/s WAN/LAN  
Button: 1 Reset button  
Flash: 16 MB  
SDRAM: 128 MB  
Frequency range: 2.4 GHz and 5 GHz  
Signal Rate: 574 Mbps on 2.4 GHz, 2402 Mbps on 5 GHz  
EIRP: FCC <30 dBm, CE <20 dBm (2.4 GHz) <23 dBm (5 GHz)  
Advanced Functions: Router/ Access Point Mode, Optional Ethernet Backhaul, Guest network, TP-Link Mesh Technology MU-MIMO, Auto Path Selection, Self-Healing, AP Steering, Band Steering, Beamforming



**#09054**  
Net Price:  
329.00 USD  
Unit: pcs

**Router Mesh Deco X60 3-pack, AX3000 (TP-Link DECO X60(3-Pack))**

- Faster Connections: Wi-Fi 6 speeds up to 3,000 Mbps-2,402 Mbps on 5 GHz and 574 Mbps on 2.4 GHz.
- Connect More Devices: OFDMA and MU-MIMO technology quadruple capacity to enable simultaneous transmission to more devices.
- Boosted Seamless Coverage: Achieve seamless whole-home coverage with a clearer and stronger whole-home Wi-Fi signal generated by Wi-Fi 6.
- Ultra-Low Latency: Greater reduction in latency enables more responsive gaming and video chatting.
- One Unified Network: Multiple units form a whole-home network that auto-selects the best connection as you move around your home.
- Total Security: WPA3 encryption and TP-Link HomeCareTM provide personalized features, including Parental Controls, Antivirus, and Quality of Service (QoS) to ensure a safer online experience.
- Setup Made Easier Than Ever: The Deco app walks you through the setup step-by-step.

Standards: IEEE 802.11 ax/ac/n/a 5 GHz, IEEE 802.11 ax/n/g/b 2.4 GHz  
Processor: Qualcomm 1 GHz Quad-core CPU  
Ports: 2 ports 10/100/1000 Mb/s WAN/LAN  
Button: 1 Reset button  
Flash: 16 MB  
SDRAM: 128 MB  
Frequency range: 2.4 GHz and 5 GHz  
Signal Rate: 574 Mbps on 2.4 GHz, 2402 Mbps on 5 GHz  
EIRP: FCC <30 dBm, CE <20 dBm (2.4 GHz) <23 dBm (5 GHz)  
Advanced Functions: Router/ Access Point Mode, Optional Ethernet Backhaul, Guest network, TP-Link Mesh Technology MU-MIMO, Auto Path Selection, Self-Healing, AP Steering, Band Steering, Beamforming



#09381

Net Price:  
199.00 USD  
Unit: pcs

**Router Mesh Deco XE75 1-pack, AXE5400 (TP-Link DECO XE75(1-Pack))**

- Boosted Seamless Coverage - Mesh WiFi coverage up to 7,200 ft2 (3-pack), 5,500 ft2 (2-pack), and 2,900 ft2 (1-pack).
- True Tri-Band Speed - All three WiFi bands work together to unleash your network's total speeds up to 5,400 Mbps for 200 devices
- AI-Driven Mesh - Unites your home under one name and password while delivering the best connections as you move room to room
- TP-Link HomeShield - Provides comprehensive network protection, robust parental controls, and real-time IoT security
- Universal Compatibility - Backward compatible with all WiFi generations and works with any internet service provider (ISP) and modem
- Setup Made Easier Than Ever - The Deco app walks you through setup step-by-step.

Standards: IEEE 802.11ax 6 GHz, IEEE 802.11ax/ac/n/a 5 GHz, IEEE 802.11ax/n/b/g 2.4 GHz  
Ports: 3x Gigabit Ports  
Button: 1 Reset button  
Frequency range: 2.4 GHz, 5 GHz and 6 GHz  
Signal Rate: 6 GHz- 2402 Mb/s (802.11ax, HE160), 5 GHz- 2402 Mb/s (802.11ax, HE160), 2.4 GHz- 574 Mb/s (802.11ax)  
Advanced Functions: Multi-Link Operation (MLO), 320 MHz Channel, 4K-QAM, Multi-RUs, Works with Alexa and Google Assistant  
Wireless Security: WPA-Personal, WPA2-Personal, WPA3-Personal  
Software Features: Quality of Service - WMM, IPv6 Support, WAN Type - Dynamic IP/Static IP/PPPoE, Local Management, Remote Management, DHCP - Server, Client, Port Forwarding Support, Access Control Blacklist, Firewall Security SPI Firewall, Protocols Supports IPv4 and IPv6, Homecare - Antivirus, Parental Controls, Quality of Service, Speedtest, Monthly Usage Reports, Auto FW Update, Expand for more deco, Guest Network 2.4 GHz guest network \* 1 - 5 GHz guest network \* 1, 6 GHz guest network \* 1, Beamformig, Easy setup by Deco App



#09380

Net Price:  
390.00 USD  
Unit: pcs

**Router Mesh Deco XE75 2-pack, AXE5400 (TP-Link DECO XE75(2-Pack))**

- Boosted Seamless Coverage - Mesh WiFi coverage up to 7,200 ft2 (3-pack), 5,500 ft2 (2-pack), and 2,900 ft2 (1-pack).
- True Tri-Band Speed - All three WiFi bands work together to unleash your network's total speeds up to 5,400 Mbps for 200 devices
- AI-Driven Mesh - Unites your home under one name and password while delivering the best connections as you move room to room
- TP-Link HomeShield - Provides comprehensive network protection, robust parental controls, and real-time IoT security
- Universal Compatibility - Backward compatible with all WiFi generations and works with any internet service provider (ISP) and modem
- Setup Made Easier Than Ever - The Deco app walks you through setup step-by-step.

Standards: IEEE 802.11ax 6 GHz, IEEE 802.11ax/ac/n/a 5 GHz, IEEE 802.11ax/n/b/g 2.4 GHz  
Ports: 3x Gigabit Ports  
Button: 1 Reset button  
Frequency range: 2.4 GHz, 5 GHz and 6 GHz  
Signal Rate: 6 GHz- 2402 Mb/s (802.11ax, HE160), 5 GHz- 2402 Mb/s (802.11ax, HE160), 2.4 GHz- 574 Mb/s (802.11ax)  
Advanced Functions: Multi-Link Operation (MLO), 320 MHz Channel, 4K-QAM, Multi-RUs, Works with Alexa and Google Assistant  
Wireless Security: WPA-Personal, WPA2-Personal, WPA3-Personal  
Software Features: Quality of Service - WMM, IPv6 Support, WAN Type - Dynamic IP/Static IP/PPPoE, Local Management, Remote Management, DHCP - Server, Client, Port Forwarding Support, Access Control Blacklist, Firewall Security SPI Firewall, Protocols Supports IPv4 and IPv6, Homecare - Antivirus, Parental Controls, Quality of Service, Speedtest, Monthly Usage Reports, Auto FW Update, Expand for more deco, Guest Network 2.4 GHz guest network \* 1 - 5 GHz guest network \* 1, 6 GHz guest network \* 1, Beamformig, Easy setup by Deco App



#09379

Net Price:  
533.00 USD  
Unit: pcs

**Router Mesh Deco XE75 3-pack, AXE5400 (TP-Link DECO XE75(3-Pack))**

- Boosted Seamless Coverage - Mesh WiFi coverage up to 7,200 ft2 (3-pack), 5,500 ft2 (2-pack), and 2,900 ft2 (1-pack).
- True Tri-Band Speed - All three WiFi bands work together to unleash your network's total speeds up to 5,400 Mbps for 200 devices
- AI-Driven Mesh - Unites your home under one name and password while delivering the best connections as you move room to room
- TP-Link HomeShield - Provides comprehensive network protection, robust parental controls, and real-time IoT security
- Universal Compatibility - Backward compatible with all WiFi generations and works with any internet service provider (ISP) and modem
- Setup Made Easier Than Ever - The Deco app walks you through setup step-by-step.

Standards: IEEE 802.11ax 6 GHz, IEEE 802.11ax/ac/n/a 5 GHz, IEEE 802.11ax/n/b/g 2.4 GHz  
Ports: 3x Gigabit Ports  
Button: 1 Reset button  
Frequency range: 2.4 GHz, 5 GHz and 6 GHz  
Signal Rate: 6 GHz- 2402 Mb/s (802.11ax, HE160), 5 GHz- 2402 Mb/s (802.11ax, HE160), 2.4 GHz- 574 Mb/s (802.11ax)  
Advanced Functions: Multi-Link Operation (MLO), 320 MHz Channel, 4K-QAM, Multi-RUs, Works with Alexa and Google Assistant  
Wireless Security: WPA-Personal, WPA2-Personal, WPA3-Personal  
Software Features: Quality of Service - WMM, IPv6 Support, WAN Type - Dynamic IP/Static IP/PPPoE, Local Management, Remote Management, DHCP - Server, Client, Port Forwarding Support, Access Control Blacklist, Firewall Security SPI Firewall, Protocols Supports IPv4 and IPv6, Homecare - Antivirus, Parental Controls, Quality of Service, Speedtest, Monthly Usage Reports, Auto FW Update, Expand for more deco, Guest Network 2.4 GHz guest network \* 1 - 5 GHz guest network \* 1, 6 GHz guest network \* 1, Beamformig, Easy setup by Deco App



#09378

Net Price:  
234.00 USD  
Unit: pcs

**Router Mesh Deco XE75 Pro 2-pack, AXE5400 (TP-Link DECO XE75 Pro(2-Pack))**

- Boosted Seamless Coverage - Mesh WiFi coverage up to 7,200 ft2 (3-pack), 5,500 ft2 (2-pack), and 2,900 ft2 (1-pack).
- True Tri-Band Speed - All three WiFi bands work together to unleash your network's total speeds up to 5,400 Mbps for 200 devices
- AI-Driven Mesh - Unites your home under one name and password while delivering the best connections as you move room to room
- TP-Link HomeShield - Provides comprehensive network protection, robust parental controls, and real-time IoT security
- Universal Compatibility - Backward compatible with all WiFi generations and works with any internet service provider (ISP) and modem
- Setup Made Easier Than Ever - The Deco app walks you through setup step-by-step.

Standards: IEEE 802.11ax 6 GHz, IEEE 802.11ax/ac/n/a 5 GHz, IEEE 802.11ax/n/b/g 2.4 GHz  
Ports: 1x 2.5 Gbps Port + 2x Gigabit Ports  
Button: 1 Reset button  
Frequency range: 2.4 GHz, 5 GHz and 6 GHz  
Signal Rate: 6 GHz- 2402 Mb/s (802.11ax, HE160), 5 GHz- 2402 Mb/s (802.11ax, HE160), 2.4 GHz- 574 Mb/s (802.11ax)  
Advanced Functions: Multi-Link Operation (MLO), 320 MHz Channel, 4K-QAM, Multi-RUs, Works with Alexa and Google Assistant  
Wireless Security: WPA-Personal, WPA2-Personal, WPA3-Personal  
Software Features: Quality of Service - WMM, IPv6 Support, WAN Type - Dynamic IP/Static IP/PPPoE, Local Management, Remote Management, DHCP - Server, Client, Port Forwarding Support, Access Control Blacklist, Firewall Security SPI Firewall, Protocols Supports IPv4 and IPv6, Homecare - Antivirus, Parental Controls, Quality of Service, Speedtest, Monthly Usage Reports, Auto FW Update, Expand for more deco, Guest Network 2.4 GHz guest network \* 1 - 5 GHz guest network \* 1, 6 GHz guest network \* 1, Beamformig, Easy setup by Deco App



#09377

Net Price:  
453.00 USD  
Unit: pcs

**Router Mesh Deco XE75 Pro 2-pack, AXE5400 (TP-Link DECO XE75 Pro(2-Pack))**

- Boosted Seamless Coverage - Mesh WiFi coverage up to 7,200 ft2 (3-pack), 5,500 ft2 (2-pack), and 2,900 ft2 (1-pack).
- True Tri-Band Speed - All three WiFi bands work together to unleash your network's total speeds up to 5,400 Mbps for 200 devices
- AI-Driven Mesh - Unites your home under one name and password while delivering the best connections as you move room to room
- TP-Link HomeShield - Provides comprehensive network protection, robust parental controls, and real-time IoT security
- Universal Compatibility - Backward compatible with all WiFi generations and works with any internet service provider (ISP) and modem
- Setup Made Easier Than Ever - The Deco app walks you through setup step-by-step.

Standards: IEEE 802.11ax 6 GHz, IEEE 802.11ax/ac/n/a 5 GHz, IEEE 802.11ax/n/b/g 2.4 GHz  
Ports: 1x 2.5 Gbps Port + 2x Gigabit Ports  
Button: 1 Reset button  
Frequency range: 2.4 GHz, 5 GHz and 6 GHz  
Signal Rate: 6 GHz- 2402 Mb/s (802.11ax, HE160), 5 GHz- 2402 Mb/s (802.11ax, HE160), 2.4 GHz- 574 Mb/s (802.11ax)  
Advanced Functions: Multi-Link Operation (MLO), 320 MHz Channel, 4K-QAM, Multi-RUs, Works with Alexa and Google Assistant  
Wireless Security: WPA-Personal, WPA2-Personal, WPA3-Personal  
Software Features: Quality of Service - WMM, IPv6 Support, WAN Type - Dynamic IP/Static IP/PPPoE, Local Management, Remote Management, DHCP - Server, Client, Port Forwarding Support, Access Control Blacklist, Firewall Security SPI Firewall, Protocols Supports IPv4 and IPv6, Homecare - Antivirus, Parental Controls, Quality of Service, Speedtest, Monthly Usage Reports, Auto FW Update, Expand for more deco, Guest Network 2.4 GHz guest network \* 1 - 5 GHz guest network \* 1, 6 GHz guest network \* 1, Beamformig, Easy setup by Deco App



#09376

Net Price:  
666.00 USD  
Unit: pcs

**Router Mesh Deco XE75 Pro 3-pack, AXE5400 (TP-Link DECO XE75 Pro(3-Pack))**

- Boosted Seamless Coverage - Mesh WiFi coverage up to 7,200 ft2 (3-pack), 5,500 ft2 (2-pack), and 2,900 ft2 (1-pack).
- True Tri-Band Speed - All three WiFi bands work together to unleash your network's total speeds up to 5,400 Mbps for 200 devices
- AI-Driven Mesh - Unites your home under one name and password while delivering the best connections as you move room to room
- TP-Link HomeShield - Provides comprehensive network protection, robust parental controls, and real-time IoT security
- Universal Compatibility - Backward compatible with all WiFi generations and works with any internet service provider (ISP) and modem
- Setup Made Easier Than Ever - The Deco app walks you through setup step-by-step.

Standards: IEEE 802.11ax 6 GHz, IEEE 802.11ax/ac/n/a 5 GHz, IEEE 802.11ax/n/b/g 2.4 GHz  
Ports: 1x 2.5 Gbps Port + 2x Gigabit Ports  
Button: 1 Reset button  
Frequency range: 2.4 GHz, 5 GHz and 6 GHz  
Signal Rate: 6 GHz- 2402 Mb/s (802.11ax, HE160), 5 GHz- 2402 Mb/s (802.11ax, HE160), 2.4 GHz- 574 Mb/s (802.11ax)  
Advanced Functions: Multi-Link Operation (MLO), 320 MHz Channel, 4K-QAM, Multi-RUs, Works with Alexa and Google Assistant  
Wireless Security: WPA-Personal, WPA2-Personal, WPA3-Personal  
Software Features: Quality of Service - WMM, IPv6 Support, WAN Type - Dynamic IP/Static IP/PPPoE, Local Management, Remote Management, DHCP - Server, Client, Port Forwarding Support, Access Control Blacklist, Firewall Security SPI Firewall, Protocols Supports IPv4 and IPv6, Homecare - Antivirus, Parental Controls, Quality of Service, Speedtest, Monthly Usage Reports, Auto FW Update, Expand for more deco, Guest Network 2.4 GHz guest network \* 1 - 5 GHz guest network \* 1, 6 GHz guest network \* 1, Beamformig, Easy setup by Deco App





#09518

Net Price:  
61.50 USD  
Unit: pcs

**Router Mesh Halo H60X 2-pack, Wi-Fi 6, AX1500 (TP-Link Mercusys Halo H60X(2-pack))**

- Dual Band WiFi 6 Speeds up to 3000 Mbps - 1201 Mbps on 5 GHz and 300 Mbps on 2.4 GHz.
- Seamless Roaming with One Unified Network - Halo units work together to automatically switch between Halos as you move around your home with a single unified WiFi name and password.
- Whole Home Coverage - Blanket up to 6,000 ft2 (550 m2) with high-speed WiFi, eliminating WiFi dead zones at your home.
- Connect over 100 Devices - Provide fast and stable connections over 100 devices.
- Easily Manage Your Home Network - Use the MERCUSYS App to quickly set up and manage your WiFi. You can also manage your kids' online time and contents.
- Full Gigabit Ports - Gigabit ports per Halo unit for lightning-fast wired connections.

Standards: Wi-Fi 6 IEEE 802.11ax/ac/n/a 5 GHz, IEEE 802.11n/b/g 2.4 GHz  
Ports: 3 x 10/100/1000 Mb/s ports per Halo unit (WAN/LAN auto-sensing)  
Button: 1 Reset button  
Frequency range: 2.4 GHz and 5 GHz  
Signal Rate: 300 Mbps on 2.4 GHz, 1201 Mbps on 5 GHz  
EIRP: CE <20 dBm (2.4 GHz) <23 dBm (5 GHz)  
Wireless Security: WPA2-PSK + AES  
Wireless Functions: Enable/Disable Wireless Radio, Wireless Statistics  
Mesh protocol: 802.11k/v  
WAN Type: Dynamic IP/Static IP/PPPoE/PPTP/L2TP  
Management: Access Control, Local Management, Remote Management



#09517

Net Price:  
88.00 USD  
Unit: pcs

**Router Mesh Halo H60X 3-pack, Wi-Fi 6, AX1500 (TP-Link Mercusys Halo H60X(3-pack))**

- Dual Band WiFi 6 Speeds up to 3000 Mbps - 1201 Mbps on 5 GHz and 300 Mbps on 2.4 GHz.
- Seamless Roaming with One Unified Network - Halo units work together to automatically switch between Halos as you move around your home with a single unified WiFi name and password.
- Whole Home Coverage - Blanket up to 6,000 ft2 (550 m2) with high-speed WiFi, eliminating WiFi dead zones at your home.
- Connect over 100 Devices - Provide fast and stable connections over 100 devices.
- Easily Manage Your Home Network - Use the MERCUSYS App to quickly set up and manage your WiFi. You can also manage your kids' online time and contents.
- Full Gigabit Ports - Gigabit ports per Halo unit for lightning-fast wired connections.

Standards: Wi-Fi 6 IEEE 802.11ax/ac/n/a 5 GHz, IEEE 802.11n/b/g 2.4 GHz  
Ports: 3 x 10/100/1000 Mb/s ports per Halo unit (WAN/LAN auto-sensing)  
Button: 1 Reset button  
Frequency range: 2.4 GHz and 5 GHz  
Signal Rate: 300 Mbps on 2.4 GHz, 1201 Mbps on 5 GHz  
EIRP: CE <20 dBm (2.4 GHz) <23 dBm (5 GHz)  
Wireless Security: WPA2-PSK + AES  
Wireless Functions: Enable/Disable Wireless Radio, Wireless Statistics  
Mesh protocol: 802.11k/v  
WAN Type: Dynamic IP/Static IP/PPPoE/PPTP/L2TP  
Management: Access Control, Local Management, Remote Management



#09260

Net Price:  
77.00 USD  
Unit: pcs

**Router Mesh Halo H70X 2-pack, Wi-Fi 6, AX1800 (TP-Link Mercusys Halo H70X(2-pack))**

- Dual Band WiFi 6 Speeds up to 1800 Mbps - 1201 Mbps on 5 GHz and 574 Mbps on 2.4 GHz.
- Seamless Roaming with One Unified Network - Halo units work together to automatically switch between Halos as you move around your home with a single unified WiFi name and password.
- Whole Home Coverage - Blanket up to 4,000 ft2 (350 m2) with high-speed WiFi, eliminating WiFi dead zones at your home.
- Connect over 150 Devices - Provide fast and stable connections over 150 devices.
- Easily Manage Your Home Network - Use the MERCUSYS App to quickly set up and manage your WiFi. You can also manage your kids' online time and contents.
- Full Gigabit Ports - 3x Gigabit ports per Halo unit for lightning-fast wired connections.

Standards: Wi-Fi 6 IEEE 802.11ax/ac/n/a 5 GHz, IEEE 802.11ax/n/b/g 2.4 GHz  
Ports: 3 x 10/100/1000 Mb/s ports per Halo unit (WAN/LAN auto-sensing)  
Button: 1 Reset button  
Frequency range: 2.4 GHz and 5 GHz  
Signal Rate: 574 Mbps on 2.4 GHz, 1201 Mbps on 5 GHz  
EIRP: CE <20 dBm (2.4 GHz) <23 dBm (5 GHz)  
Wireless Security: WPA2-PSK + AES  
Wireless Functions: Enable/Disable Wireless Radio, Wireless Statistics  
Mesh protocol: 802.11k/v  
WAN Type: Dynamic IP/Static IP/PPPoE/PPTP/L2TP  
Management: Access Control, Local Management, Remote Management



#09261

Net Price:  
110.00 USD  
Unit: pcs

**Router Mesh Halo H70X 3-pack, Wi-Fi 6, AX1800 (TP-Link Mercusys Halo H70X(3-pack))**

- Dual Band WiFi 6 Speeds up to 1800 Mbps - 1201 Mbps on 5 GHz and 574 Mbps on 2.4 GHz.
- Seamless Roaming with One Unified Network - Halo units work together to automatically switch between Halos as you move around your home with a single unified WiFi name and password.
- Whole Home Coverage - Blanket up to 4,000 ft2 (350 m2) with high-speed WiFi, eliminating WiFi dead zones at your home.
- Connect over 150 Devices - Provide fast and stable connections over 150 devices.
- Easily Manage Your Home Network - Use the MERCUSYS App to quickly set up and manage your WiFi. You can also manage your kids' online time and contents.
- Full Gigabit Ports - 3x Gigabit ports per Halo unit for lightning-fast wired connections.

Standards: Wi-Fi 6 IEEE 802.11ax/ac/n/a 5 GHz, IEEE 802.11ax/n/b/g 2.4 GHz  
Ports: 3 x 10/100/1000 Mb/s ports per Halo unit (WAN/LAN auto-sensing)  
Button: 1 Reset button  
Frequency range: 2.4 GHz and 5 GHz  
Signal Rate: 574 Mbps on 2.4 GHz, 1201 Mbps on 5 GHz  
EIRP: CE <20 dBm (2.4 GHz) <23 dBm (5 GHz)  
Wireless Security: WPA2-PSK + AES  
Wireless Functions: Enable/Disable Wireless Radio, Wireless Statistics  
Mesh protocol: 802.11k/v  
WAN Type: Dynamic IP/Static IP/PPPoE/PPTP/L2TP  
Management: Access Control, Local Management, Remote Management



#09262

Net Price:  
88.00 USD  
Unit: pcs

**Router Mesh Halo H80X 2-pack, Wi-Fi 6, AX3000 (TP-Link Mercusys Halo H80X(2-pack))**

- Dual Band WiFi 6 Speeds up to 3000 Mbps - 2402 Mbps on 5 GHz and 574 Mbps on 2.4 GHz.
- Seamless Roaming with One Unified Network - Halo units work together to automatically switch between Halos as you move around your home with a single unified WiFi name and password.
- Whole Home Coverage - Blanket up to 7,000 ft2 (650 m2) with high-speed WiFi, eliminating WiFi dead zones at your home.
- Connect over 150 Devices - Provide fast and stable connections over 150 devices.
- Easily Manage Your Home Network - Use the MERCUSYS App to quickly set up and manage your WiFi. You can also manage your kids' online time and contents.
- Full Gigabit Ports - 3x Gigabit ports per Halo unit for lightning-fast wired connections.

Standards: Wi-Fi 6 IEEE 802.11ax/ac/n/a 5 GHz, IEEE 802.11ax/n/b/g 2.4 GHz  
Ports: 3 x 10/100/1000 Mb/s ports per Halo unit (WAN/LAN auto-sensing)  
Button: 1 Reset button  
Frequency range: 2.4 GHz and 5 GHz  
Signal Rate: 574 Mbps on 2.4 GHz, 2402 Mbps on 5 GHz  
EIRP: CE <20 dBm (2.4 GHz) <23 dBm (5 GHz)  
Wireless Security: WPA2-PSK + AES  
Wireless Functions: Enable/Disable Wireless Radio, Wireless Statistics  
Mesh protocol: 802.11k/v  
WAN Type: Dynamic IP/Static IP/PPPoE/PPTP/L2TP  
Management: Access Control, Local Management, Remote Management



#09263

Net Price:  
132.00 USD  
Unit: pcs

**Router Mesh Halo H80X 3-pack, Wi-Fi 6, AX3000 (TP-Link Mercusys Halo H80X(3-pack))**

- Dual Band WiFi 6 Speeds up to 3000 Mbps - 2402 Mbps on 5 GHz and 574 Mbps on 2.4 GHz.
- Seamless Roaming with One Unified Network - Halo units work together to automatically switch between Halos as you move around your home with a single unified WiFi name and password.
- Whole Home Coverage - Blanket up to 7,000 ft2 (650 m2) with high-speed WiFi, eliminating WiFi dead zones at your home.
- Connect over 150 Devices - Provide fast and stable connections over 150 devices.
- Easily Manage Your Home Network - Use the MERCUSYS App to quickly set up and manage your WiFi. You can also manage your kids' online time and contents.
- Full Gigabit Ports - 3x Gigabit ports per Halo unit for lightning-fast wired connections.

Standards: Wi-Fi 6 IEEE 802.11ax/ac/n/a 5 GHz, IEEE 802.11ax/n/b/g 2.4 GHz  
Ports: 3 x 10/100/1000 Mb/s ports per Halo unit (WAN/LAN auto-sensing)  
Button: 1 Reset button  
Frequency range: 2.4 GHz and 5 GHz  
Signal Rate: 574 Mbps on 2.4 GHz, 2402 Mbps on 5 GHz  
EIRP: CE <20 dBm (2.4 GHz) <23 dBm (5 GHz)  
Wireless Security: WPA2-PSK + AES  
Wireless Functions: Enable/Disable Wireless Radio, Wireless Statistics  
Mesh protocol: 802.11k/v  
WAN Type: Dynamic IP/Static IP/PPPoE/PPTP/L2TP  
Management: Access Control, Local Management, Remote Management



NEW



#09399

Net Price:  
55.70 USD  
Unit: pcs

#### Wireless Access Point AX1800 (TP-Link TL-WA1801)

- Gigabit WiFi 6 Speed - 1.8 Gbps Dual Band WiFi for faster browsing, streaming and downloading, all at the same time.
- Flexible Deployment - Supports Passive PoE to carry electrical power and data simultaneously.
- Multiple Modes - Supports Access Point, Range Extender, Multi-SSID, and Client modes to meet any network needs.
- Boosted Coverage - Four fixed antennas equipped with Beamforming technology extend and concentrate the Wi-Fi signals.
- Captive Portal - Offers a designed portal page for heightened security and marketing.

Standards: IEEE 802.11n, IEEE 802.11b/g 2.4 GHz, IEEE 802.11ac/n/a 5 GHz  
Ports: 1x 10/100/1000 Mbps RJ-45 PoE (LAN)  
Frequency range: 2.4 GHz and 5 GHz  
Modulation: DBPSK, DQPSK, CCK, OFDM, 16-QAM, 64-QAM  
Operating modes: AP Mode, Multi-SSID Mode, AP Client Mode, Repeater Mode (WDS / Universal), AP+ Bridge mode  
Max. speed: 1201 Mbps at 5 GHz, 574 Mbps at 2.4 GHz  
Antenna: 4 Fixed High Performance Antennas  
WLAN security: WEP 64/128/152-bit, WPA, WPA-PSK, WPA2, WPA2-PSK, TKIP, AES  
WLAN features: 3T3R MIMO, CCA, QSS button, 4x SSIDs, VLAN support

NEW



#09396

Net Price:  
50.40 USD  
Unit: pcs

#### Wireless Travel Router AX1500 (TP-Link TL-WR1502X)

- Faster Dual-Band AX1500 WiFi 6: Reaches incredible speeds up to 1.5 Gbps (1201 Mbps on 5 GHz band and 300 Mbps on 2.4 GHz band) for no-lag AR/VR gaming, uninterrupted 4K streaming, and smooth video calls.
- Full Gigabit Ports for Reliable Connections: 1x Gigabit WAN port + 1x Gigabit LAN port provide reliable, warp-speed connections for high-intensive wired devices such as your smart TV, game console, NAS, and more.
- Portable and Durable Design: TL-WR1502X is a pocket-sized travel router compactly designed for your next trip or adventure. Its small size is designed for travel-friendly storage.
- Enjoy Reliable Network Anywhere: With versatile modes including Router, USB Tethering, 3G/4G USB Modem, Hotspot, Access Point, Range Extender, and Client, TL-WR1502X enables flexible WiFi setup for homes, hotel stays, and travel.
- Easily Access Your Files From Anywhere: By plugging an external USB hard disc into the router, you can easily share files between connected devices.
- 24/7 Secure Surfing with VPN Encryption: Supporting OpenVPN and WireGuardC, TL-WR1502X can keep your network private and secure from anywhere in the world, whether you're working remotely abroad, or browsing on the public WiFi.
- Power It with a Power Bank: With a Type-C interface, you can flexibly turn it into a mobile router with a power bank.

Standards: IEEE 802.11ax/ac/n/a 5 GHz, IEEE 802.11n/b/g 2.4 GHz  
Ports: 1x 10/100/1000 Mbps RJ-45 (LAN), 1x 10/100/1000 Mbps RJ-45 (WAN), 1 port USB 2.0  
Frequency range: 2.4GHz and 5GHz  
Modulation: DBPSK, DQPSK, CCK, OFDM, 16-QAM, 64-QAM  
Operating modes: AP Router  
Max. speed: 5 GHz@ 1201 Mb/s (802.11ax), 2.4 GHz@ 300 Mb/s (802.11n)  
Wireless Functions: Enable/Disable Wireless Radio, WDS Bridge, WMM, Wireless Statistics  
WLAN security: 64/128-bit WEP, WPA / WPA2, WPA-PSK / WPA2-PSK  
WAN Type: Dynamic IP, Static IP, PPPoE, PPTP, L2TP

#### Standard AC



#09009

Net Price:  
23.10 USD  
Unit: pcs

#### 1200Mbps Wireless Dual Band PCI-Express AC1200 (TP-Link Archer T4E)

- Easy Installation - Plug the adapter into an available PCI-E slot to upgrade your desktop
- High Speed Wi-Fi - Up to 1200 Mbps Wi-Fi speeds (867 Mbps on 5 GHz band and 300 Mbps on 2.4 GHz band)
- 802.11ac Dual Band - 3 times faster than the 802.11n standard, perfect for high-intensity network usage
- Beamforming - Wi-Fi signals are strengthened towards certain direction where client exists
- Multiple-Size Brackets - Low profile and full height brackets are both provided, suitable for all PCs
- 2x2 MIMO - Users can easily access to high-speed wireless connection
- Broad Wireless Range - Two external antennas ensure greater Wi-Fi coverage and enhanced stability

**HARDWARE FEATURES:**  
Interface: PCI Express x1  
Antenna Type: Omni Directional, Detachable (RP-SMA)  
**WIRELESS FEATURES:**  
Wireless Standards: IEEE 802.11ac, IEEE 802.11a, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n  
Frequency: 2.4-2.4835GHz, 5.180-5.240GHz, 5.745-5.825GHz  
Signal Rate: 867Mbps at 5GHz, 300Mbps at 2.4GHz  
EIRP: <20dBm (EIRP)  
Reception Sensitivity: 5GHz- 11a -68dBm, 11n HT20 -64dBm, 11n HT40 -61dBm, 11ac HT20 -59dBm, 11ac HT40 -54dBm, 11ac HT80 -51dBm, 2.4GHz- 11b -76dBm, 11g -68dBm, 11n HT20 -64dBm, 11n HT40 -61dBm

NEW



#09416

Net Price:  
17.10 USD  
Unit: pcs

#### 600Mbps Wireless Dual Band PCI-Express AC600 (TP-Link Archer T2E)

- AC600 Dual Band WiFi - Make full use of your network with Wi-Fi speeds up to 600 Mbps (433 Mbps on the 5 GHz band and 200 Mbps on the 2.4 GHz band)
- MU-MIMO Supported - Boost network throughput and efficiency when working with a compatible MU-MIMO router
- Broad Wireless Range - Connect to your Wi-Fi in more parts of your home with powerful signal-boosting high-gain antenna
- WPA3 Supported - Improve cybersecurity with more secure and individualized protection
- Low-Profile and Full-Height Brackets - Customized options give you the flexibility to find a bracket that perfectly fits your board design

**HARDWARE FEATURES:**  
Interface: PCI Express x1  
Antenna Type: 1 Detachable External Antenna  
**WIRELESS FEATURES:**  
Wireless Standards: IEEE 802.11ac, IEEE 802.11a, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n  
Frequency: 2.4-2.4835GHz, 5.180-5.240GHz, 5.745-5.825GHz  
Signal Rate: 433Mbps at 5GHz, 200Mbps at 2.4GHz  
Wireless Modes: Infrastructure mode  
Wireless Security: WEP, WPA/WPA2/WPA3, WPA-PSK/WPA2-PSK/WPA3-PAE  
Modulation Technology: DBPSK, DQPSK, CCK, OFDM, 16-QAM, 64-QAM, 256-QAM  
**OTHERS:**  
Dimensions: 4.76 x 3.09 x 0.85 in (120.8 x 78.5 x 21.5 mm)



#07167

Net Price:  
23.10 USD  
Unit: pcs

#### AC1200 Wireless Dual Band USB 3.0 Adapter (TP-Link Archer T4U)

- Ultra-fast 1200 (867+300)Mbps wireless speed with 802.11ac
- Dual Band connections for lag-free HD video streaming and gaming
- SuperSpeed USB 3.0 port - Up to 10x faster than USB 2.0
- Easy wireless security encryption at a push of the WPS button
- Equipped with a USB Extension Cable for flexible deployment

Standards: IEEE 802.11ac, IEEE 802.11a, IEEE 802.11n, IEEE 802.11g, IEEE 802.11b  
Interface: USB 3.0  
Frequency range: 5GHz, 2.4GHz  
Max. speed: up to 5GHz 867Mbps or 2.4GHz 300Mbps  
Max. output power: 20 dBm  
Modulation type: DBPSK, DQPSK, CCK, OFDM, 16-QAM, 64-QAM, 256-QAM  
Operating modes: Ad-hoc, infrastructure  
WLAN security: Support 64/128 bit WEP, WPA-PSK/WPA2-PSK, 802.1x  
Drivers: Windows 8 (32/64bits), Windows 7 (32/64bits), Windows XP (32/64bits)  
Dimensions: 92.2x29x14.6 mm  
Operating temperatures: 0°C ~ 40°C



#09246

Net Price:  
14.40 USD  
Unit: pcs

**AC1300 Wireless Dual Band USB 2.0 Adapter (TP-Link Archer T3U Nano)**

- Ultimate Wi-Fi Speed - AC1300 (400 Mbps on 2.4GHz band and 867 Mbps on 5GHz band) wireless speed with the next generation Wi-Fi - 802.11ac
- Dual Band Wireless - 2.4GHz and 5GHz band for flexible connectivity
- Mini design -Mini-sized design for convenient portability with a reliable high performance
- MU-MIMO - Delivers highly efficient wireless connection
- Supported Operating System - Windows 10/8.1/8/7/XP, Mac OS X (Mac OS 10.15 will be supported soon.)

Standards: IEEE 802.11ac, IEEE 802.11a, IEEE 802.11n, IEEE 802.11g, IEEE 802.11b  
Interface: USB 2.0  
Antenna Type: Omni Directional  
Frequency range: 5GHz, 2.4GHz  
Max. speed: up to 5GHz 867Mbps or 2.4GHz 400Mbps  
EIRP: <23dBm (EIRP)  
Modulation type: DBPSK, DQPSK, CCK, OFDM, 16-QAM, 64-QAM, 256-QAM  
Operating modes: Ad-hoc, infrastructure  
WLAN security: Support 64/128 bit WEP, WPA-PSK/WPA2-PSK, 802.1x  
Drivers: Windows 10 (32/64bits), Windows 8.1 (32/64bits), Windows 8 (32/64bits), Windows 7 (32/64bits), Windows XP(32/64bits)



#09527

Net Price:  
10.80 USD  
Unit: pcs

**AC1300 Wireless Dual Band USB 2.0 Adapter (TP-Link Mercusys MA30H)**

- Strong Dual Band Wi-Fi Speed - Speeds up to 867 Mbps (5 GHz) + 400 Mbps (2.4 GHz)
- Wider Signal Coverage - A high-performance antenna
- Plug and Play - With the built-in inbox driver by Windows operation systems, you just need to plug into your computer and play.
- MU-MIMO - Simultaneously serve several devices with no more latency or bandwidth congestion
- Improved Security - The latest security enhancement, WPA3, provides enhanced protection in personal password safety
- Backward Compatibility - Full support for 802.11ac/a/b/g/n standards
- Windows Compatible - Supported operating system: Windows 10, 11

Standards: IEEE 802.11ac, IEEE 802.11a, IEEE 802.11n, IEEE 802.11g, IEEE 802.11b  
Interface: USB 2.0  
LED: Status  
Antena: 5dBi  
Frequency range: 5GHz, 2.4GHz  
Max. speed: up to 5GHz 867Mbps or 2.4GHz 400Mbps  
WLAN security: WPA-PSK, WPA2-PSK, WPA3-SAE  
Drivers: Windows 11/10 (32/64 bit)  
Dimensions: 57,8 × 16,8 × 173,4 mm  
Manufacturer: TP-Link



#09528

Net Price:  
9.93 USD  
Unit: pcs

**AC1300 Wireless Dual Band USB 2.0 Nano Adapter (TP-Link Mercusys MA30N)**

- Dual Band Wi-Fi Speed - Speeds up to 867 Mbps (5 GHz) + 400 Mbps (2.4 GHz)
- Plug and Play - With the built-in inbox driver by Windows operation systems, you just need to plug into your computer and play.
- Nano Size- A compact, convenient solution to make your device wireless. Much smaller than a regular USB flash drive.
- Improved Security - The latest security enhancement, WPA3, provides enhanced protection in personal password safety
- Windows Compatible - Supported operating system: Windows 11,10 (32/64bit)

Standards: IEEE 802.11ac, IEEE 802.11a, IEEE 802.11n, IEEE 802.11g, IEEE 802.11b  
Interface: USB 2.0  
LED: Status  
Antena: Internal Antenna  
Frequency range: 5GHz, 2.4GHz  
Max. speed: up to 5GHz 867Mbps or 2.4GHz 400Mbps  
WLAN security: WPA-PSK, WPA2-PSK, WPA3-SAE  
Drivers: Windows 11/10 (32/64 bit)  
Dimensions: 26,9 × 16,1 × 7,6 mm  
Manufacturer: TP-Link



#09008

Net Price:  
14.00 USD  
Unit: pcs

**AC1300 Wireless Dual Band USB 3.0 Adapter (TP-Link Archer T3U)**

- Ultimate Wi-Fi Speed - AC1300 (400 Mbps on 2.4GHz band and 867 Mbps on 5GHz band) wireless speed with the next generation Wi-Fi - 802.11ac
- Dual Band Wireless - 2.4GHz and 5GHz band for flexible connectivity
- Mini design -Mini-sized design for convenient portability with a reliable high performance
- Super Speed USB 3.0 Port - Up to 10x faster transfer speeds than USB 2.0
- MU-MIMO - Delivers highly efficient wireless connection
- Supported Operating System - Windows 10/8.1/8/7/XP, Mac OS X (Mac OS 10.15 will be supported soon.)

Standards: IEEE 802.11ac, IEEE 802.11a, IEEE 802.11n, IEEE 802.11g, IEEE 802.11b  
Interface: USB 3.0  
Antenna Type: Omni Directional  
Frequency range: 5GHz, 2.4GHz  
Max. speed: up to 5GHz 867Mbps or 2.4GHz 400Mbps  
EIRP: <23dBm (EIRP)  
Modulation type: DBPSK, DQPSK, CCK, OFDM, 16-QAM, 64-QAM, 256-QAM  
Operating modes: Ad-hoc, infrastructure  
WLAN security: Support 64/128 bit WEP, WPA-PSK/WPA2-PSK, 802.1x  
Drivers: Windows 10 (32/64bits), Windows 8.1 (32/64bits), Windows 8 (32/64bits), Windows 7 (32/64bits), Windows XP(32/64bits)



#09082

Net Price:  
25.50 USD  
Unit: pcs

**AC1300 Wireless Dual Band USB 3.0 Adapter (TP-Link Archer T4U Plus)**

- Ultra-Fast Wi-Fi - 1300Mbps wireless speeds (400Mbps on the 2.4GHz band and 867Mbps on the 5GHz band) with support for the next generation 802.11ac Wi-Fi standard
- Dual Band Wireless - 2.4GHz and 5GHz bands for flexible connectivity
- Dual High-Gain antennas - Improved range, signal quality and transmission performance
- MU-MIMO -Delivers highly efficient wireless connection
- Super Speed USB 3.0 Port - Up to 10x faster transfer speeds than USB 2.0
- Adjustable, Multi-Directional Antenna - Enable flexible deployment for the best reception

Standards: IEEE 802.11ac, IEEE 802.11a, IEEE 802.11n, IEEE 802.11g, IEEE 802.11b  
Interface: USB 3.0  
Frequency range: 5GHz, 2.4GHz  
Antenna: 2x External 5 dBi High Gain Antennas  
Max. speed: up to 5GHz 867Mbps or 2.4GHz 400Mbps  
Max. output power: 20 dBm  
Wireless Modes: Infrastructure mode  
Wireless Security: WEP, WPA/WPA2, WPA-PSK/WPA2-PSK  
Drivers: Supported operating systems include Windows 10/8.1/8/7, macOS  
Dimensions: 84 × 156.3 × 19.2 mm (3.3 × 6.2 × 0.76 in)  
Operating temperatures: 0°C ~ 40°C



#09043

Net Price:  
16.10 USD  
Unit: pcs

**AC1300 Wireless High Gain Dual Band USB 3.0 Adapter (TP-Link Archer T3U Plus)**

- AC1300 Lightning-Fast Speed - AC1300 (867 Mbps on the 5 GHz band or 400 Mbps on the 2.4 GHz band) dual-band Wi-Fi to ensure all your devices run at full speed
- MU-MIMO Technology - Improves the throughput and efficiency of the whole network with MU-MIMO technology
- Dual-Band Wireless - The 2.4 GHz and 5 GHz bands provide flexible connectivity, giving your devices access to the latest dual-band Wi-Fi router for faster speed and extended range
- High-Gain Antennas - Advanced external high-gain antennas greatly enhance the reception and transmission signal strength of the USB adapter
- Supports the Latest Operating Systems - Fully compatible with Windows 10/8.1/8/7/XP and macOS

Standards: IEEE 802.11ac, IEEE 802.11a, IEEE 802.11n, IEEE 802.11g, IEEE 802.11b  
Interface: USB 3.0  
LED: Status  
Antenna Type: 2 External High Gain Antennas  
Frequency range: 5GHz, 2.4GHz  
Max. speed: up to 5GHz 867Mbps or 2.4GHz 400Mbps  
EIRP: 5 GHz- 20 dBm (FCC) / 20 dBm (CE) (EIRP), 2.4 GHz- 18 dBm (FCC) / 18 dBm (CE) (EIRP)  
Modulation type: DBPSK, DQPSK, CCK, OFDM, 16-QAM, 64-QAM, 256-QAM  
Operating modes: Ad-hoc, infrastructure  
WLAN security: Support 64/128 bit WEP, WPA-PSK/WPA2-PSK, 802.1x



#09006

Net Price:  
9.19 USD  
Unit: pcs

**AC600 Wireless Dual Band USB 2.0 Adapter (TP-Link Archer T2U Nano)**

- High Speed WiFi: Up to 600Mbps speeds with 200Mbps on 2.4GHz and 433 Mbps on 5GHz, upgrades your devices to higher AC WiFi speeds.
- Dual Band Wireless - 2.4GHz and 5GHz band for flexible connectivity, upgrades your devices to work with the latest dual-band WiFi router for faster speed and extended range.
- Nano design - Small, unobtrusive design allows you to plug it in and forget it is even there
- Operating System - Supports Windows 10/8.1/8/7/XP, Mac OS X
- Advanced Security - Supports 64/128-bit WEP, WPA/WPA2, and WPA-PSK/WPA2-PSK encryption standards

Standards: IEEE 802.11ac, IEEE 802.11a, IEEE 802.11n, IEEE 802.11g, IEEE 802.11b  
Interface: USB 2.0

Frequency range: 5GHz, 2.4GHz  
Max. speed: up to 5GHz 433Mbps or 2.4GHz 200Mbps  
Max. output power: 20 dBm  
Modulation type: DBPSK, DQPSK, CCK, OFDM, 16-QAM, 64-QAM, 256-QAM  
Operating modes: Ad-hoc, infrastructure  
WLAN security: Support 64/128 bit WEP, WPA-PSK/WPA2-PSK, 802.1x  
Drivers: Windows 10 (32/64bits), Windows 8.1 (32/64bits), Windows 8 (32/64bits), Windows 7 (32/64bits), Windows XP(32/64bits)



#09007

Net Price:  
12.40 USD  
Unit: pcs

**AC600 Wireless Dual Band USB 2.0 Adapter (TP-Link Archer T2U Plus)**

- High-Speed Wi-Fi: 256QAM support increases the 2.4 GHz data rate from 150 Mbps to 200 Mbps, 200 Mbps on the 2.4 GHz band and 433 Mbps on the 5 GHz band, ensure you fully enjoy fast AC Wi-Fi.
- Dual Band Wireless: 2.4 GHz and 5 GHz band provide flexible connectivity, giving your devices access to the latest dual-band Wi-Fi router for faster speed and extended range
- High-Gain Antenna: A 5dBi high-gain antenna greatly enhances the reception and transmission signal strength of the USB adapter
- Supports the Latest Operating Systems: Fully compatible with Windows 10/8.1/8/7/XP and Mac OS X

Standards: IEEE 802.11ac, IEEE 802.11a, IEEE 802.11n, IEEE 802.11g, IEEE 802.11b  
Interface: USB 2.0

LED: Status  
Antenna: 5dBi  
Frequency range: 5GHz, 2.4GHz  
Max. speed: up to 5GHz 433Mbps or 2.4GHz 200Mbps  
Modulation type: DBPSK, DQPSK, CCK, OFDM, 16-QAM, 64-QAM, 256-QAM  
Operating modes: Ad-hoc, infrastructure  
WLAN security: Support 64/128 bit WEP, WPA-PSK/WPA2-PSK, 802.1x  
Drivers: Windows 10 (32/64bits), Windows 8.1 (32/64bits), Windows 8 (32/64bits), Windows 7 (32/64bits), Windows XP(32/64bits)



#08939

Net Price:  
10.10 USD  
Unit: pcs

**AC600 Wireless Dual Band USB 2.0 Adapter (TP-Link Archer T2U)**

- Ultra-fast 600 (433+150)Mbps wireless speed with 802.11ac
- Dual Band connections for lag-free HD video streaming and gaming

Standards: IEEE 802.11ac, IEEE 802.11a, IEEE 802.11n, IEEE 802.11g, IEEE 802.11b  
Interface: USB 2.0  
Frequency range: 5GHz, 2.4GHz  
Max. speed: up to 5GHz 433Mbps or 2.4GHz 150Mbps  
Max. output power: 20 dBm  
Modulation type: DBPSK, DQPSK, CCK, OFDM, 16-QAM, 64-QAM  
Operating modes: Ad-hoc, infrastructure  
WLAN security: Support 64/128 bit WEP, WPA-PSK/WPA2-PSK, 802.1x  
Drivers: Windows 8.1 (32/64bits), Windows 8 (32/64bits), Windows 7 (32/64bits), Windows XP(32/64bits)  
Dimensions: 1.6×0.7×0.3 in. (41×19.5×8.7mm)



#09114

Net Price:  
8.59 USD  
Unit: pcs

**AC650 Wireless Dual Band USB 2.0 Adapter (TP-Link Mercusys MU6H)**

- High-Speed Dual-Band Wi-Fi: 256-QAM support increases the 2.4 GHz data rate from 150 Mbps to 200 Mbps. Enjoy speeds of up to 200 Mbps on the 2.4 GHz band and 433 Mbps on the 5 GHz band, to take full advantage of your AC Wi-Fi.
- High-Gain Antenna: A 5dBi high-gain antenna greatly enhances the reception and transmission strength of the USB adapter
- Internal Driver: Smart easy-install for Windows operating system
- Supports the Latest Operating Systems: Fully compatible with Windows 10/8.1/8/7/XP

Standards: IEEE 802.11ac, IEEE 802.11a, IEEE 802.11n, IEEE 802.11g, IEEE 802.11b  
Interface: USB 2.0

LED: Status  
Antenna: 5dBi  
Frequency range: 5GHz, 2.4GHz  
Max. speed: up to 5GHz 433Mbps or 2.4GHz 200Mbps  
Modulation type: DBPSK, DQPSK, CCK, OFDM, 16-QAM, 64-QAM, 256-QAM  
Operating modes: Ad-hoc, infrastructure  
WLAN security: WEP, WPA/WPA2, WPA-PSK/ WPA2-PS, 802.1X  
Drivers: Windows 10 (32/64bits), Windows 8.1 (32/64bits), Windows 8 (32/64bits), Windows 7 (32/64bits), Windows XP(32/64bits)  
Dimensions: 57,8 × 16,8 × 173,4 mm



#09529

Net Price:  
7.72 USD  
Unit: pcs

**AC650 Wireless Dual Band USB 2.0 Nano Adapter (TP-Link Mercusys MA20N)**

- Dual Band Wi-Fi Speed - Speeds up to 433 Mbps (5 GHz) + 200 Mbps (2.4 GHz)
- Plug and Play - With the built-in inbox driver by Windows operation systems, you just need to plug into your computer and play.
- Nano Size- A compact, convenient solution to make your device wireless. Much smaller than a regular USB flash drive.
- Improved Security - The latest security enhancement, WPA3, provides enhanced protection in personal password safety
- Windows Compatible - Supported operating system: Windows 11, 10 (32/64bit)

Standards: IEEE 802.11ac, IEEE 802.11a, IEEE 802.11n, IEEE 802.11g, IEEE 802.11b  
Interface: USB 2.0

LED: Status  
Antenna: Internal Antenna  
Frequency range: 5GHz, 2.4GHz  
Max. speed: up to 5GHz 433Mbps or 2.4GHz 200Mbps  
WLAN security: WPA-PSK, WPA2-PSK, WPA3-SAE  
Drivers: Windows 11/10 (32/64 bit)  
Dimensions: 14,94 \* 7,19 \* 19,15 mm  
Manufacturer: TP-Link



#06260

Net Price:  
75.60 USD  
Unit: pcs

**1200Mbps Outdoor Wireless Access Point, AC1200 (TP-Link EAP225-Outdoor)**

- Durable, weatherproof enclosure for outdoor Wi-Fi applications
- Up to 1200Mbps with 2x2 MIMO technology
- Omada Mesh Technology enables wireless connectivity between APs for extended range, making wireless deployments more flexible and convenient
- Supports Seamless Roaming so even video streams and voice calls are unaffected as users move between locations
- High transmission power and high gain antennas provide a long-range coverage area
- Free cloud centralized management and Omada app for ultra convenience and easy management
- Secure guest network along with multiple authentication options (SMS/Facebook Wi-Fi Voucher, etc.) and abundant wireless security technologies
- 802.3af/Passive PoE (PoE Adapter Included) compatible and simple mounting design allow for flexible deployment and convenient installation

Standards: IEEE 802.11ac/n/g/b/a  
Ports: Gigabit Ethernet (RJ-45) Port \*1 (ETH1 Support IEEE802.3af PoE)  
Frequency range: 2.4GHz and 5GHz  
Signal Rate: 5GHz Up to 867Mbps, 2.4GHz Up to 300Mbps  
EIRP: CE <20dBm(2.4GHz) <23dBm(5GHz), FCC <27dBm  
Wireless Functions: Multiple SSIDs (Up to 16 SSIDs, 8 for each band), Enable/Disable Wireless Radio, Automatic Channel Assignment, Transmit Power Control (Adjust Transmit Power on dBm), QoS(WMM), Airtime Fairness, Beamforming, Band Steering, Load Balance, Rate Limit, Link Aggregation, Reboot Schedule, Wireless Schedule, Wireless Statistics based on SSID/AP/Client





#09089

Net Price:  
66.70 USD  
Unit: pcs

## 1200Mbps Outdoor Wireless Access Point, AC1200 (TP-Link EAP235-Wall)

- Fast Dual-Band Wi-Fi: Simultaneous 300 Mbps on 2.4 GHz and 867 Mbps on 5 GHz totals 1,167 Mbps Wi-Fi speeds with MU-MIMO.&#8224;
- Four Gigabit Ports: 4 Gigabit Ethernet ports (1× uplink + 3× downlink), with one downlink port supporting PoE pass-through to provide power for wired device.
- Integrated into Omada SDN: Zero-Touch Provisioning (ZTP)&#8225;, Centralized Cloud Management, and Intelligent Monitoring.
- Centralized Management: Cloud access and Omada app for ultra convenience and easy management.
- Elegant Appearance: Ultra slimmest and conspicuous design blends into hotel rooms, hospitals, offices, dormitories and any other environments.
- Easy Installation and PoE Support: Easy-mount construction, compatible with 86 mm & EU & US standard junction box, and 802.3af/at PoE support.
- Secure Guest Network: Along with multiple authentication options (SMS/Facebook Wi-Fi/ Voucher, etc.) and abundant wireless security technologies.
- Advanced Wireless Tech: Optimize network performance with MU-MIMO, Band Steering, and Beamforming technologies.

Standards: IEEE 802.11ac/n/g/b/a  
Ports: Uplink 1x 10/100/1000Mbps (RJ-45) Port, Downlink- 3x 10/100/1000 Mbps Ethernet Ports (One port supports PoE OUT. The PoE OUT feature requires 802.3at PoE+ input and the maximum output is 13 W.)  
Frequency range: 2.4GHz and 5GHz  
Signal Rate: 5GHz Up to 867Mbps, 2.4GHz Up to 300Mbps  
EIRP: CE <20dBm(2.4GHz) <23dBm(5GHz), FCC <27dBm  
Wireless Functions: Multiple SSIDs (Up to 16 SSIDs, 8 for each band), Enable/Disable Wireless Radio, Automatic Channel Assignment, Transmit Power Control (Adjust Transmit Power on dBm), QoS(WMM), Airtime Fairness, Beamforming, Band Steering, Load Balance, Rate Limit, Link Aggregation, Reboot Schedule, Wireless Schedule, Wireless Statistics based on SSID/AP/Client



#09088

Net Price:  
53.40 USD  
Unit: pcs

## 1200Mbps Wireless Access Point, AC1200 (TP-Link EAP230-Wall)

- Fast Dual-Band Wi-Fi: Simultaneous 300 Mbps on 2.4 GHz and 867 Mbps on 5 GHz totals 1,167 Mbps Wi-Fi speeds with MU-MIMO.
- Gigabit Ports: 2 Gigabit Ethernet ports (1× uplink + 1× downlink).
- Integrated into Omada SDN: Zero-Touch Provisioning (ZTP), Centralized Cloud Management, and Intelligent Monitoring.
- Centralized Management: Cloud access and Omada app for ultra convenience and easy management.
- Private Connection for Every Room: Designed to meet every network need in environments with numerous separated rooms, like hotels, offices, and dormitories.
- Elegant Appearance: Unprecedented thin design with just 11 mm, the same size and shape as a light switch or power outlet faceplate to fit perfectly in any room.
- Easy Installation and PoE Support: Easy-mount construction, compatible with 86 mm & EU standard junction box, and 802.3af/at PoE support.
- Secure Guest Network: Along with multiple authentication options (SMS/Facebook Wi-Fi/ Voucher, etc.) and abundant wireless security technologies.

Standards: IEEE 802.11ac/n/g/b/a  
Ports: 10/100/1000Mbps (RJ-45) Port \*1, Downlink- 10/100/1000Mbps Ethernet Port\*1  
Frequency range: 2.4GHz and 5GHz  
Signal Rate: 5GHz Up to 867Mbps, 2.4GHz Up to 300Mbps  
EIRP: CE <20dBm(2.4GHz) <23dBm(5GHz), FCC <27dBm  
Wireless Functions: Multiple SSIDs (Up to 16 SSIDs, 8 for each band), Enable/Disable Wireless Radio, Automatic Channel Assignment, Transmit Power Control (Adjust Transmit Power on dBm), QoS(WMM), Airtime Fairness, Beamforming, Band Steering, Load Balance, Rate Limit, Link Aggregation, Reboot Schedule, Wireless Schedule, Wireless Statistics based on SSID/AP/Client



#09251

Net Price:  
64.50 USD  
Unit: pcs

## 1350Mbps Outdoor Wireless Access Point, AC1350 (TP-Link EAP223)

- Simultaneous 450Mbps on 2.4GHz and 867Mbps on 5GHz totals 1317Mbps Wi-Fi speeds
- Free EAP Controller Software lets administrators easily manage hundreds of EAPs
- Support Power over Ethernet(802.3af) for convenient and affordable installation
- Captive portal provides a convenient method for guest authentication
- Band Steering Automatically moves dual band devices onto the wider 5GHz band for faster connections

Standards: IEEE 802.11ac/n/g/b/a  
Ports: Gigabit Ethernet (RJ-45) Port \*1 (ETH1 Support IEEE802.3af PoE)  
Frequency range: 2.4GHz and 5GHz  
Signal Rate: 5GHz Up to 867Mbps, 2.4GHz Up to 450Mbps  
EIRP: CE <20dBm(2.4GHz) <23dBm(5GHz), FCC <27dBm  
Wireless Functions: Multiple SSIDs (Up to 16 SSIDs, 8 for each band), Enable/Disable Wireless Radio, Automatic Channel Assignment, Transmit Power Control (Adjust Transmit Power on dBm), QoS(WMM), Airtime Fairness, Beamforming, Band Steering, Load Balance, Rate Limit, Link Aggregation, Reboot Schedule, Wireless Schedule, Wireless Statistics based on SSID/AP/Client



#04658

Net Price:  
67.30 USD  
Unit: pcs

## 1350Mbps Outdoor Wireless Access Point, AC1350 (TP-Link EAP225)

- Simultaneous 450Mbps on 2.4GHz and 867Mbps on 5GHz totals 1317Mbps Wi-Fi speeds
- Free EAP Controller Software lets administrators easily manage hundreds of EAPs
- Support Power over Ethernet(802.3af) for convenient and affordable installation
- Captive portal provides a convenient method for guest authentication
- Band Steering Automatically moves dual band devices onto the wider 5GHz band for faster connections

Standards: IEEE 802.11ac/n/g/b/a  
Ports: Gigabit Ethernet (RJ-45) Port \*1 (ETH1 Support IEEE802.3af PoE)  
Frequency range: 2.4GHz and 5GHz  
Signal Rate: 5GHz Up to 867Mbps, 2.4GHz Up to 450Mbps  
EIRP: CE <20dBm(2.4GHz) <23dBm(5GHz), FCC <27dBm  
Wireless Functions: Multiple SSIDs (Up to 16 SSIDs, 8 for each band), Enable/Disable Wireless Radio, Automatic Channel Assignment, Transmit Power Control (Adjust Transmit Power on dBm), QoS(WMM), Airtime Fairness, Beamforming, Band Steering, Load Balance, Rate Limit, Link Aggregation, Reboot Schedule, Wireless Schedule, Wireless Statistics based on SSID/AP/Client



#04657

Net Price:  
80.00 USD  
Unit: pcs

## 1750Mbps Outdoor Wireless Access Point, AC1750 (TP-Link EAP245)

- Simultaneous 450Mbps on 2.4GHz and 1300Mbps on 5GHz totals 1750Mbps Wi-Fi speeds
- Free EAP Controller Software lets administrators easily manage hundreds of EAPs
- Support Power over Ethernet(802.3at) for convenient and affordable installation
- Captive portal provides a convenient method for guest authentication
- Band Steering Automatically moves dual band devices onto the wider 5GHz band for faster connections
- Load balance ensures large numbers of users have smooth network experiences in high density business networks

Standards: IEEE 802.11ac/n/g/b/a  
Ports: Gigabit Ethernet (RJ-45) Port \*1 (ETH1 Support IEEE802.3at PoE)  
Frequency range: 2.4GHz and 5GHz  
Signal Rate: 5GHz Up to 1300Mbps, 2.4GHz Up to 450Mbps  
EIRP: CE <20dBm(2.4GHz) <23dBm(5GHz), FCC <27dBm  
Wireless Functions: Multiple SSIDs (Up to 16 SSIDs, 8 for each band), Enable/Disable Wireless Radio, Automatic Channel Assignment, Transmit Power Control (Adjust Transmit Power on dBm), QoS(WMM), Airtime Fairness, Beamforming, Band Steering, Load Balance, Rate Limit, Link Aggregation, Reboot Schedule, Wireless Schedule, Wireless Statistics based on SSID/AP/Client



#09090

Net Price:  
95.80 USD  
Unit: pcs

## 1750Mbps Outdoor Wireless Access Point, AC1750 (TP-Link EAP265 HD)

- Fast Dual-Band Wi-Fi: Simultaneous 450 Mbps on 2.4 GHz and 1300 Mbps on 5 GHz totals 1750 Mbps Wi-Fi speeds.
- High-Density Connectivity: MU-MIMO, Load Balance, and professional antennas improve capacity in high-density environments to connect more devices simultaneously.
- Integrated into Omada SDN: Supports Zero-Touch Provisioning (ZTP), Centralized Cloud Management, and Intelligent Monitoring.
- Centralized Management: Cloud access and Omada app for ultra convenience and easy management.
- Seamless Roaming: Even video streams and voice calls are unaffected as users move between locations.§
- PoE Support: Supports both standard 802.3af/at and Passive PoE (PoE adapter included) for flexible installations.
- Secure Guest Network: Along with multiple authentication options (SMS/Facebook Wi-Fi/ Voucher, etc.) and abundant wireless security technologies.

Standards: IEEE 802.11ac/n/g/b/a  
Ports: 2 × Gigabit Ethernet (RJ-45) Port (One port supports IEEE802.3af/at PoE and Passive PoE)  
Button: Reset  
Frequency range: 2.4GHz and 5GHz  
Signal Rate: 5GHz Up to 1300Mbps, 2.4GHz Up to 450Mbps  
EIRP: CE <20dBm(2.4GHz) <23dBm(5GHz), FCC <27dBm  
Wireless Functions: Multiple SSIDs (Up to 16 SSIDs, 8 for each band), Enable/Disable Wireless Radio, Automatic Channel Assignment, Transmit Power Control (Adjust Transmit Power on dBm), QoS(WMM), Airtime Fairness, Beamforming, Band Steering, Load Balance, Rate Limit, Link Aggregation, Reboot Schedule, Wireless Schedule, Wireless Statistics based on SSID/AP/Client



#09047

Net Price:  
71.30 USD  
Unit: pcs

## 867Mbps Wireless access point, 5GHz (TP-LINK CPE710)

- 802.11ac for up to 867Mbps on 5GHz wireless data rate
- 23dBi high-gain directional 2x2 MIMO, ideal for long-distance application
- Excellent beam directivity, improved latency and noise cancellation
- Innovative snap-lock parts make for fast assembly and a sturdy structural design keeps CPE710 stable even in strong winds
- Durable IP65 weatherproof enclosure along with 15kV ESD and 6kV lightning protection ensures all-weather suitability
- Pharos Control gives administrators a free, centralized management system
- Passive PoE supports to allow flexible deployment and convenient installation

Processor: Qualcomm 750 MHz, MIPS 74Kc  
Memory: 128 MB DDR2 RAM, 16 MB Flash  
Standards: IEEE 802.11a, IEEE 802.11n, IEEE 802.11ac  
Ports: 1 10/100/1000Mbps Shielded Ethernet Port (LAN0, Passive PoE in), 1 Reset Button  
Wireless Configurations: Pharos MAXstream TDMA Technology, 802.11a/n Modes, Selectable Channel Width 5/10/20/40MHz, Automatic Channel Selection, Transmission Power Control, Dynamic Frequency Selection (DFS), WDS Enable/Disable, SSID Broadcast Enable/Disable, Multi-SSID with VLAN Tagging (AP mode only), Distance/ACK Timeout Setting, Wireless MAC Address Filter



#07018

Net Price:  
114.00 USD  
Unit: pcs

## Wireless access point Ubiquiti NanoBeam M5 (Ubiquiti NBE-5AC-Gen2)

Standards: IEEE 802.11ac/n  
Ports: 2x 10/100/1000 Mbps RJ-45  
Chipset: Atheros MIPS 74Kc, 720 MHz  
Operating memory: 128 MB DDR2  
Flash memory: 8 MB  
Antenna: build-in, 19 dBi  
VSWR: 1.5  
Dimensions: 189 x 189 x 125 mm  
Weight: 0.530 kg  
Mounting: mast or wall with the aid of antenna wall support  
Max. power consumption: 8.5 W  
Power: PoE 24V 0.5A Gigabit PoE Adapter (Included)  
Operating temperatures: -40°C + 80°C  
Operating humidity: 5% + 95%, Non-condensing  
Wind Loading: 45.4 N @ 200 km/h (10.2 lbf @ 125 mph)



#07004

Net Price:  
121.00 USD  
Unit: pcs

## Wireless Access Point Ubiquiti NanoStation 5 AC (Ubiquiti NS-5AC)

Ports: 2x 10/100/1000 Mbps RJ-45  
Chipset: Atheros MIPS 74Kc, 560 MHz  
Operating memory: 64 MB DDR2  
Frequency range: 5150 MHz + 5875 MHz  
VSWR: 1.6  
Beam width: 45°  
Dimensions: 257 x 84 x 41 mm  
Weight: 233 g  
Mounting: Pole-Mount (Kit Included)  
Max. power consumption: 8.5 W  
Power: 802.3af Alternative A (Pairs 1, 2+; 3, 6 Return), 24V  
Passive PoE (Pairs 4, 5+; 7, 8 Return)  
Operating temperatures: -40°C + 70°C  
Operating humidity: 5% + 95%, non-condensing  
Certificates: CE, FCC, IC



#07005

Net Price:  
57.80 USD  
Unit: pcs

## Wireless Access Point Ubiquiti NanoStation AC Loco (Ubiquiti NS-5ACL)

Ports: 10/100/1000 Mbps RJ-45  
Chipset: Atheros MIPS 74Kc, 560 MHz  
Operating memory: 64 MB DDR2  
Frequency range: 5150 MHz + 5875 MHz  
VSWR: 1.8  
Beam width: 45°  
Dimensions: 179 x 77.5 x 59.1 mm  
Weight: 180 g  
Mounting: Pole-Mount (Kit Included)  
Max. power consumption: 8.5 W  
Power: 24V, 0.5A Gigabit PoE Supply (The product is delivered without a power adapter)  
Operating temperatures: -40°C + 70°C  
Operating humidity: 5% + 95%, non-condensing  
Certificates: CE, FCC, IC



#07039

Net Price:  
217.00 USD  
Unit: pcs

## Wireless Access Point Ubiquiti NanoStation AC Loco 5-pack (Ubiquiti NS-5ACL)

Ports: 10/100/1000 Mbps RJ-45  
Chipset: Atheros MIPS 74Kc, 560 MHz  
Operating memory: 64 MB DDR2  
Frequency range: 5150 MHz + 5875 MHz  
VSWR: 1.8  
Beam width: 45°  
Dimensions: 179 x 77.5 x 59.1 mm  
Weight: 180 g  
Mounting: Pole-Mount (Kit Included)  
Max. power consumption: 8.5 W  
Power: 24V, 0.5A Gigabit PoE Supply (The product is delivered without a power adapter)  
Operating temperatures: -40°C + 70°C  
Operating humidity: 5% + 95%, non-condensing  
Certificates: CE, FCC, IC



#05349

Net Price:  
200.00 USD  
Unit: pcs

## Wireless Access Point Ubiquiti UniFi UAP AC M PRO, AC Mesh; (Ubiquiti UAP-AC-M-PRO)

Networking Interface (Mbps): 2 x 10/100/1000 Ethernet Ports  
Buttons: Reset  
Antennas: 3x Internal Dual-Band Antennas (8 dBi)  
Wi-Fi Standards: 802.11 a/b/g/n/ac  
Power Method: 802.3af PoE (Supported Voltage Range- 44 to 57VDC)  
Power Supply: 48V, 0.5A Gigabit PoE Adapter  
Maximum Power Consumption: 9 W  
Maximum TX Power: 22 dBm  
BSSID: Up to 8 per Radio  
Dimensions: 343.2 x 181.2 x 60.2 mm  
Weight: 633 g  
Power Save: Supported  
Wireless Security: WEP, WPA-PSK, WPA-Enterprise (WPA/WPA2, TKIP/AES)



#05348

Net Price:  
94.50 USD  
Unit: pcs

## Wireless Access Point Ubiquiti UniFi UAP AC M, AC Mesh; (Ubiquiti UAP-AC-M)

Networking Interface (Mbps): 1 x 10/100/1000 Ethernet Ports  
Buttons: Reset  
Antennas: 2x External Dual-Band Omni Antennas (3 dBi, 4 dBi)  
Wi-Fi Standards: 802.11 a/b/g/n/ac  
Power Method: 24V Passive PoE (Pairs 4, 5+; 7, 8 Return); 802.3af Alternative A (Pairs 1, 2+; 3, 6 Return), (Supported Voltage Range- 44 to 57VDC)  
Power Supply: 24V, 0.5A Gigabit PoE Adapter  
Maximum Power Consumption: 8.5 W  
Maximum TX Power: 20 dBm  
BSSID: Up to 8 per Radio  
Dimensions: 353 x 46 x 34.4 mm  
Weight: 152 g with Antennas



#05352

Net Price:  
107.00 USD  
Unit: pcs

## Wireless Access Point UniFi UAP AC Lite (Ubiquiti UAP-AC-Lite)

Networking Interface (Mbps): 1 x 10/100/1000 Ethernet Ports  
Buttons: Reset  
Antennas: (1) Dual-Band Antenna, Tri-Polarity, 2.4 GHz- 3 dBi, 5 GHz- 3 dBi  
Wi-Fi Standards: 802.11 a/b/g/n/ac  
Power Method: Passive Power over Ethernet (24V), 802.3af Supported  
Power Supply: 24V, 0.5A PoE Adapter (Included)  
Maximum Power Consumption: 6.5 W  
Maximum TX Power: 2.4 GHz - 20 dBm, 5 GHz - 20 dBm  
BSSID: Up to 8 Per Radio  
Dimensions: 160 x 160 x 31.45 mm (6.30 x 6.30 x 1.24")  
Weight: 170 g (185 g with Mounting Kits)



#08871

Net Price:  
128.00 USD  
Unit: pcs

## Wireless Access Point UniFi UAP AC LR (Ubiquiti UAP-AC-LR)

Ideal for long-range deployments, the UniFi AC LR AP offers simultaneous, dual-band operation with 3x3 MIMO in the 2.4 GHz band and 2x2 MIMO in the 5 GHz band. The innovative antenna design provides a long-range, symmetrical-link coverage area, and the antenna gain of the UniFi AC LR AP performs better than one-way, high transmit power does for connecting distant clients.

Networking Interface (Mbps): 1 x 10/100/1000 Ethernet Ports  
Buttons: Reset  
Antennas: (1) Dual-Band Antenna, Tri-Polarity, 2.4 GHz- 3 dBi, 5 GHz- 3 dBi  
Wi-Fi Standards: 802.11 a/b/g/n/ac  
Power Method: Passive Power over Ethernet (24V), 802.3af Supported  
Power Supply: 24V, 0.5A PoE Adapter (Included)  
Maximum Power Consumption: 6.5 W  
Maximum TX Power: 2.4 GHz - 30 dBm, 5 GHz - 22 dBm  
BSSID: Up to Four Per Radio  
Dimensions: 175.7 x 175.7 x 43.2 mm (6.92 x 6.92 x 1.70")  
Weight: 240 g (315 g with Mounting Kits)



#08352

Net Price:  
177.00 USD  
Unit: pcs**Wireless Access Point UniFi UAP AC PRO  
(Ubiquiti UAP-AC-PRO)**

Ports: 2 x 10/100/1000 Ethernet Ports, 1x USB 2.0 Port  
Buttons: Reset  
Antennas: (3) Dual-Band Antennas, 2.4 GHz- 3 dBi, 5 GHz- 3 dBi  
Wi-Fi Standards: 802.11 a/b/g/n/ac  
Power Method: Passive Power over Ethernet (48V), 802.3af/at Supported  
Power Supply: 48V, 0.5A PoE Adapter (Included)  
Maximum Power Consumption: 9 W  
Maximum TX Power: 2.4 GHz - 22 dBm, 5 GHz - 22 dBm  
BSSID: Up to 8 Per Radio  
Dimensions: 196.7 x 196.7 x 35 mm (7.74 x 7.74 x 1.38")  
Weight: 350 g (450 g with Mounting Kits)



#05356

Net Price:  
330.00 USD  
Unit: pcs**Wireless Access Point UniFi UAP-AC-HD  
(Ubiquiti UAP-AC-HD)**

Dual-band, 802.11ac Wave 2 access point designed to support high-density networks and critical system applications.

The Access Point AC HD (UAP AC HD) is a high-performance, indoor/outdoor, 802.11 ac WiFi access point that utilizes Wave 2 technology to reach an impressive 2+ Gbps aggregate throughput rate with its 5 GHz (4x4 MU-MIMO) and 2.4 GHz (4x24MIMO) bands. The UAP AC HD also has a focused antenna pattern to enhance your network's capacity and reduce interference from neighboring access points. This access point is powered with 802.3at PoE+ and is equipped with (2) GbE RJ45 ports and (1) USB port to support multiple connection types. The UAP AC HD can be set up in minutes and fully managed with the UniFi Network web application or mobile app.

**Features:**

- 802.11ac Wave 2 WiFi technology
- 5 GHz (4x4 MU-MIMO) band with a 1.7 Gbps throughput rate
- 2.4 GHz (4x4 MIMO) band with a 800 Mbps throughput rate
- Powered with 802.3at PoE+\*
- (2) GbE RJ45 ports
- (1) USB port

Networking Interface (Mbps): 2 x 10/100/1000 Ethernet Ports  
Buttons: Reset  
Antennas: 2.4 GHz - (2) Dual-Port, Dual-Polarity Antennas, 3 dBi each (Supports 4x4 MIMO), 5 GHz - (2) Dual-Port, Dual-Polarity Antennas, 4 dBi each (Supports 4x4 MIMO)  
Wi-Fi Standards: 802.11 a/b/g/n/r/k/v/ac/ac-wave2  
Power Method: 802.3at PoE+, UniFi Switch (PoE), 44 to 57VDC  
Maximum Power Consumption: 17W  
Maximum TX Power: 2.4 GHz - 6-25 dBm, 5 GHz - 6-25 dBm  
BSSID: 8 per Radio  
Dimensions: 220 x 220 x 48.1 mm  
Weight: 700 g (830 g with Mounting Kits)



#05353

Net Price:  
186.00 USD  
Unit: pcs**Wireless Access Point UniFi UAP-nanoHD  
(Ubiquiti UAP-nanoHD)**

Dual-band, 802.11ac Wave 2 access point that can support over 200 clients with its 2+ Gbps aggregate throughput rate.

The Access Point nanoHD (UAP nanoHD) is a compact, dual-band access point that can reach a 2+ Gbps aggregate throughput rate with its 5 GHz (4x4 MU-MIMO) and 2.4 GHz (2x2 MIMO) bands. The UAP nanoHD can also support over 200 concurrently connected clients while maintaining an even, reliable wireless experience across your entire network. With its elegant, nano-sized design, this access point can be staged virtually anywhere indoors where you'd like to enhance your wireless speed and performance. Built for plug-and-play simplicity, the UAP nanoHD can be set up in minutes and fully managed with the UniFi Network web application or mobile app.

**Features:**

- Four-stream, 802.11ac Wave 2 WiFi technology
- 5 GHz (4x4 MU-MIMO) band with a 1.733 Gbps throughput rate
- 2.4 GHz (2x2 MIMO) band with a 300 Mbps throughput rate
- 200+ concurrent client capacity
- Powered by 802.3af PoE (PoE injector included with single pack)

Networking Interface (Mbps): 1 x 10/100/1000 Ethernet Ports  
Buttons: Reset  
Antennas: 2.4 GHz - (2) Single-Port, Single-Polarity Antennas, 2.8 dBi each (Supports 2x2 MIMO), 5 GHz - (2) Single-Port, Dual-Polarity Antennas, 3 dBi each (Supports 4x4 MIMO)  
Wi-Fi Standards: 802.11 a/b/g/n/r/k/v/ac/ac-wave2  
Power Method: 802.3af PoE, UniFi Switch (PoE)  
Maximum Power Consumption: 10.5W  
Maximum TX Power: 2.4 GHz - 23 dBm, 5 GHz - 26 dBm  
BSSID: 8 per Radio  
Dimensions: 160 x 160 x 32.65 mm  
Weight: 300 g (315 g with Mounting Kits)



#07001

Net Price:  
75.90 USD  
Unit: pcs**Wireless Base Station LiteBeam 5AC Gen2  
(Ubiquiti LBE-5AC-GEN2)**

Ports: 1x 10/100/1000 Mbps RJ-45  
Operating modes: Access Point, Bridge, Client, WDS  
Processor: MIPS 74Kc  
Operating memory: 64 MB DDR2  
Frequency range: 5150 MHz + 5875 MHz  
Gain: 23 dBi  
Antenna: detachable, 2x SMA-RP(F)  
Dimensions: 358 x 271.95 x 272.5 mm (14.09 x 10.71 x 10.73")  
Weight: 800 g (1.76 lb), With Mount 980 g (2.16 lb)  
Mounting: Pole-Mounting Kit (Included)  
Max. power consumption: 7 W  
Power: 24V, 0.3A Gigabit PoE Adapter (Included)  
Power Method: Passive PoE (Pairs 4, 5+; 7, 8 Return)



#09069

Net Price:  
47.10 USD  
Unit: pcs**Wireless N Access Point AC1200(TP-Link  
TL-WA1201)**

- AC1200 Dual-Band Wi-Fi - 867 Mbps at 5 GHz and 300 Mbps at 2.4 GHz band.
- Flexible Deployment - Supports Passive PoE to carry electrical power and data simultaneously.
- Multiple Modes - Supports Access Point, Range Extender, Multi-SSID, and Client modes to meet any network needs.
- MU-MIMO Technology - Simultaneously transfers data to multiple devices for 2x faster performance.
- Boosted Coverage - Four fixed antennas equipped with Beamforming technology extend and concentrate the Wi-Fi signals.
- Captive Portal - Offers a designed portal page for heightened security and marketing.

Standards: IEEE 802.11n, IEEE 802.11b/g 2.4 GHz, IEEE 802.11ac/n/a 5 GHz  
Ports: 1x 10/100/1000 Mbps RJ-45 PoE (LAN)  
Frequency range: 2.4 GHz and 5 GHz  
Modulation: DBPSK, DQPSK, CCK, OFDM, 16-QAM, 64-QAM  
Operating modes: AP Mode, Multi-SSID Mode, AP Client Mode, Repeater Mode (WDS / Universal), AP+ Bridge mode  
Max. speed: 1200 Mbps (867 Mbps at 5 GHz, 300 Mbps at 2.4 GHz)  
EIRP: CE <20 dBm (2.4 GHz), <23 dBm (5, 15 GHz~5, 25 GHz), FCC <30 dBm (2.4 GHz & 5 GHz)  
Antenna: 4 Fixed High Performance Antennas



#09104

Net Price:  
26.20 USD  
Unit: pcs**1200Mbps Wireless Gigabit Router Dual-band  
AC1200 (TP-Link Mercusys AC12G)**

- AC1200 dual band Wi-Fi - speeds of up to 300 Mbps on the 2.4 GHz band and 867 Mbps on the 5 GHz band
- Full gigabit ports - lightning-fast connections for wired devices, including game consoles, STBs, smart TVs and more
- Share with up to 60 devices - internet access for multiple streaming simultaneously
- 4 high gain external antennas - powerful wireless coverage throughout your house
- Easy installation - intuitive webpage guides you through the setup process in minutes

**HARDWARE FEATURES:**

Standards and Protocols: IEEE 802.11ac/n/a 5GHz, IEEE 802.11b/g/n 2.4GHz  
Interface: 3 10/100/1000Mbps LAN Ports, 1 10/100/1000Mbps WAN Port  
Button: WPS/Reset Button  
External Power Supply: 9V/0.85A  
Dimensions (W X D X H): 222 x 140 x 32 mm  
Antenna: 4x 5 dBi  
**WIRELESS FEATURES:**  
Frequency: 2.4GHz & 5GHz  
Signal Rate: 5GHz Up to 867Mbps, 2.4GHz Up to 300Mbps  
EIRP: < 20 dBm  
Reception Sensitivity: 5 GHz - 11a 6M -92 dBm, 11a 54M -75 dBm, 11ac 20M MCS8 -70 dBm, 11ac 40M MCS9 -64 dBm, 11ac 80M MCS9 -60 dBm, 2.4 GHz - 11g 6M -95 dBm, 11g 54M -77 dBm, 11n 20M MCS7 -74 dBm, 11n 40M MCS7 -71 dBm



#04610

Net Price:  
65.20 USD  
Unit: pcs

**1200Mbps Wireless Gigabit Router Dualband 1200AC, ADSL2+ (TP-Link Archer VR400)**

- Speedy Wi-Fi - Superb wireless experience with 300Mbps (2.4GHz) + 867Mbps (5GHz) dual band Wi-Fi connections
- Superior Range - Three detachable antennas provide stable wireless connections and optimal coverage
- Versatile Connectivity - Fully compatible with the VDSL2/ADSL2+/ADSL2/ADSL standards, as well as fiber, cable and 3G/4G Internet services
- Beamforming Technology - Improves wireless range and performance at 5GHz band
- USB Port - Supports storage and print service sharing, FTP and media servers as well as 3G/4G dongle
- Tether App - TP-LINK Tether provides the easiest way to access and manage the router on your iOS and Android devices

**HARDWARE FEATURES:**

Standards and Protocols: IEEE 802.11ac/n/a 5GHz, IEEE 802.11b/g/n 2.4GHz  
Interface: 1x10/100/1000Mbps RJ45 WAN/LAN Port, 3x10/100/1000Mbps RJ45 LAN Ports, 1xRJ11 Port, 1xUSB 2.0 Port  
Button: 1 Power On/Off Button, 1 Wi-Fi On/Off Button, 1 WPS Button, 1 RESET Button  
ADSL Standards: Full-rate ANSI T1.413 Issue 2, ITU-T G.992.1(G.DMT), ITU-T G.992.2(G.Lite), ITU-T G.994.1(G.hs), ITU-T G.995.1  
ADSL2 Standards: ITU-T G.992.3 (G.DMT.bis), ITU-T G.992.4 (G.lite.bis)  
ADSL2+ Standards: ITU-T G.992.5



#09084

Net Price:  
48.90 USD  
Unit: pcs

**1200Mbps Wireless Gigabit Router Dualband 1200AC, VDSL/ADSL+ (TP-Link Archer VR300)**

- Parental Controls: manage responsible internet access for your children
- Guest Network: provides separate access for guests while securing the home network
- Firewall Security: supports DoS, SPI Firewall, IP Addressing/Domain Filter, IP/MAC Address Binding
- Quality of Service: prioritizes network traffic by device or application
- IPTV IGMP Proxy/Snooping: supports Bridge and Tag VLAN for smooth IPTV application
- IPv6: compatible with IPv6 (Internet Protocol version 6)
- Multilingual Interface: provides hassle-free configuration in six languages (EN/DE/IT/TR/RU/PO)

**HARDWARE FEATURES:**

Standards and Protocols: IEEE 802.11ac/n/a 5GHz, IEEE 802.11b/g/n 2.4GHz  
Interface: 1x10/100Mbps RJ45 WAN/LAN Port, 3x10/100Mbps RJ45 LAN Ports, 1xRJ11 Port, Button: 1 Power On/Off Button, 1 Wi-Fi On/Off Button, 1 WPS Button, 1 RESET Button  
ADSL Standards: Full-rate ANSI T1.413 Issue 2, ITU-T G.992.1(G.DMT), ITU-T G.992.2(G.Lite), ITU-T G.994.1(G.hs), ITU-T G.995.1  
ADSL2 Standards: ITU-T G.992.3 (G.DMT.bis), ITU-T G.992.4 (G.lite.bis)  
ADSL2+ Standards: ITU-T G.992.5  
External Power Supply: 12VDC / 1A



#06238

Net Price:  
34.80 USD  
Unit: pcs

**1200Mbps Wireless Gigabit Router Dualband AC1200 (TP-Link Archer C6)**

- Supports 802.11ac standard
- Simultaneous 2.4GHz 300 Mbps and 5GHz 867 Mbps connections for 1200 Mbps of total available bandwidth
- 4 external antennas and one internal antenna provide stable wireless connections and optimal coverage
- Easy network management at your fingertips with TP-Link Tether
- MU-MIMO achieves 2X efficiency by communicating with up to 2 devices at once
- Supports Access Point mode to create a new Wi-Fi access point

**HARDWARE FEATURES:**

Standards and Protocols: IEEE 802.11ac/n/a 5GHz, IEEE 802.11b/g/n 2.4GHz  
Interface: 4 10/100/1000Mbps LAN Ports, 1 10/100/1000Mbps WAN Port  
Button: WPS Button, Wireless On/Off Button, Reset Button, On/Off Button  
External Power Supply: 12V/1A  
Dimensions (W X D X H): 230 x 144 x 35 mm (9.1 x 5.7 x 1.4 in.)  
Antenna: 3 external detachable dual band antennas (RP-SMA)  
WIRELESS FEATURES:  
Frequency: 2.4GHz & 5GHz  
Signal Rate: 5GHz Up to 867Mbps, 2.4GHz Up to 300Mbps  
EIRP: CE EIRP <20dBm(2.4GHz); <23dBm(5GHz)



#09080

Net Price:  
41.80 USD  
Unit: pcs

**1200Mbps Wireless Gigabit Router Dualband AC1200 (TP-Link Archer C6U)**

- Supports 802.11ac standard
- Simultaneous 2.4GHz 300 Mbps and 5GHz 867 Mbps connections for 1200 Mbps of total available bandwidth
- 4 external antennas and one internal antenna provide stable wireless connections and optimal coverage
- Easy network management at your fingertips with TP-Link Tether
- MU-MIMO achieves 2X efficiency by communicating with up to 2 devices at once
- Beamforming technology delivers wider wireless coverage
- Supports Access Point mode to create a new Wi-Fi access point

**HARDWARE FEATURES:**

Standards and Protocols: IEEE 802.11ac/n/a 5GHz, IEEE 802.11b/g/n 2.4GHz  
Interface: 4 10/100/1000Mbps LAN Ports, 1 10/100/1000Mbps WAN Port, 1 USB 2.0 Port  
Button: WPS Button, Wireless On/Off Button, Reset Button, On/Off Button  
External Power Supply: 12V/1A  
Dimensions (W X D X H): 8.5 x 4.6 x 1.2 in (215 x 117 x 32 mm)  
Antenna: 3 external detachable dual band antennas (RP-SMA)  
WIRELESS FEATURES:  
Frequency: 2.4GHz & 5GHz  
Signal Rate: 5GHz Up to 867Mbps, 2.4GHz Up to 300Mbps  
EIRP: CE EIRP <20dBm(2.4GHz); <23dBm(5GHz)



#09171

Net Price:  
34.80 USD  
Unit: pcs

**1200Mbps Wireless Gigabit Router Dualband AC1200, MU-MIMO (TP-Link Archer A6)**

- AC1200 Dual-Band Wi-Fi - 867 Mbps at 5 GHz and 300 Mbps at 2.4 GHz band
- MU-MIMO Technology - Simultaneously transfers data to multiple devices for 2x faster performance
- Boosted Coverage - Four external antennas equipped with Beamforming technology extend and concentrate the Wi-Fi signals
- Access Point Mode - Supports AP Mode to transform your wired connection into wireless network
- Easy Setup - Set up your Wi-Fi in minutes with TP-Link Tether app.

**HARDWARE FEATURES:**

Standards and Protocols: IEEE 802.11ac/n/a 5GHz, IEEE 802.11b/g/n 2.4GHz  
Interface: 4 10/100/1000Mbps LAN Ports, 1 10/100/1000Mbps WAN Port  
Button: WPS/Reset Button, Wireless On/Off Button, Power On/Off Button  
External Power Supply: 12VDC / 1A  
Dimensions (W X D X H): 9.1 x 5.7 x 1.4 in (230 x 144 x 35 mm)  
Antenna: 3 External Antennas + 1 Internal Antenna  
WIRELESS FEATURES:  
Frequency: 2.4GHz & 5GHz  
Signal Rate: 5GHz Up to 867Mbps, 2.4GHz Up to 300Mbps  
EIRP: <20dBm(EIRP)  
Reception Sensitivity: 5GHz - 11a 6Mbps-93dBm, 11a 54Mbps -76dBm, 11ac HT20 -68dBm, 11ac HT40 -64dBm, 11ac HT80 -61dBm, 2.4GHz - 11g 54M -77dBm, 11n HT20 -74dBm, 11n HT40 -72dBm



#04571

Net Price:  
25.50 USD  
Unit: pcs

**1200Mbps Wireless Router Dual-band AC1200 (TP-Link Archer C50)**

- Supports 802.11ac standard - the next generation of Wi-Fi
- Simultaneous 2.4GHz 300Mbps and 5GHz 867Mbps connections for 1.2Gbps of total available bandwidth
- 2 dual band external antennas provide stable wireless connections and optimal coverage
- USB Port - easily share a printer locally and files & media with networked devices or remotely via FTP server
- Easy network management at your fingertips with TP-LINK Tether

**HARDWARE FEATURES:**

Standards and Protocols: IEEE 802.11ac/n/a 5GHz, IEEE 802.11b/g/n 2.4GHz  
Interface: 4 10/100Mbps LAN Ports, 1 10/100Mbps WAN Port, 1 USB 2.0 Port  
Button: WPS/Reset Button, Wireless On/Off Button, Power On/off Button  
External Power Supply: 12VDC / 1.5A  
Dimensions (W X D X H): 182.95 x 123.5 x 32.1mm (7.2 x 4.9 x 1.3 in.)  
Antenna: 2 Detachable Antennas RP-SMA  
WIRELESS FEATURES:  
Frequency: 2.4GHz & 5GHz  
Signal Rate: 5GHz Up to 867Mbps, 2.4GHz Up to 300Mbps  
EIRP: <20dBm(EIRP)  
Reception Sensitivity: 5GHz - 11a 54Mbps -76dBm, 11ac HT20 -70dBm, 11ac HT40 -65.5dBm, 11ac HT80 -61.5dBm, 2.4GHz - 11g 54M -76dBm, 11n HT20 -74dBm, 11n HT40 -71dBm





#09079

Net Price:  
23.20 USD  
Unit: pcs

**1200Mbps Wireless Router Dual-band AC1200 (TP-Link Archer C54)**

- Faster AC Wi-Fi-AC1200 dual-band is ideal for 4K video streaming and high-speed downloading.
- Far-Reaching Coverage-4x antennas and Beamforming delivers extensive Wi-Fi coverage and reliable connections.
- Multi-Mode 3-in-1-Supports Router, Access Point, and Range Extender modes for added flexibility.
- Parental Controls-Manages when and how connected devices can access the internet.
- Guest Network-Provides separate access for guests in order to secure the host network.
- Smooth HD Streaming-Supports IGMP Proxy/Snooping, Bridge, and Tag VLAN to optimize IPTV streaming.
- IPv6 Supported-Compatible with the IPv6 (the latest Internet Protocol version 6).
- Compact and Mountable-Designed to conserve space and complement any décor.

**HARDWARE FEATURES:**

Standards and Protocols:IEEE 802.11ac/n/a 5GHz, IEEE 802.11b/g/n 2.4GHz  
Interface:4 10/100Mbps LAN Ports, 1 10/100Mbps WAN Port  
Button:WPS/Reset Button  
External Power Supply: 9VDC / 0.85A  
Dimensions (W X D X H): 4.5 x 4.2 x 1.0 in (115 x 106.7 x 24.3 mm)

Antenna: 4 Antennas

**WIRELESS FEATURES:**

Frequency:2.4GHz & 5GHz  
Signal Rate:5GHz Up to 867Mbps, 2.4GHz Up to 300Mbps  
EIRP: CE <20dBm(2.4GHz), <23dBm(5GHz), FCC <30dB  
Wireless Functions:Enable/Disable Wireless Radio, WMM, Wireless Statistics



#09102

Net Price:  
17.50 USD  
Unit: pcs

**1200Mbps Wireless Router Dual-band AC1200 (TP-Link Mercusys AC10)**

- High-Speed Wi-Fi - Stream with fast and stable connections, reaching speeds up to 1167 Mbps (300 Mbps on the 2.4 GHz band and 867 Mbps on the 5 GHz band)
- 4 High-Gain External Antennas - Receive strong Wi-Fi signals in every corner of your home
- Easy Installation - Set up in minutes guided by an intuitive web UI
- Active Parental Controls - Protect your family by setting appropriate access policies for responsible, safe internet use
- Multi-Mode - Access Point Mode, Range Extender Mode, and Router Mode supported to satisfy all application scenarios
- IPTV and IPv6 Supported

**HARDWARE FEATURES:**

Standards and Protocols:IEEE 802.11ac/n/a 5GHz, IEEE 802.11b/g/n 2.4GHz  
Interface:2 10/100Mbps LAN Ports, 1 10/100Mbps WAN Port  
Button:WPS/Reset Button  
External Power Supply:9V/0.85A  
Dimensions (W X D X H): 4.5 x 3.7 x 1.0 in (114 x 94 x 26 mm)

Antenna: 4 x 5 dBi Fixed Omni-Directional Antennas

**WIRELESS FEATURES:**

Frequency:2.4GHz & 5GHz  
Signal Rate:5GHz Up to 867Mbps, 2.4GHz Up to 300Mbps  
EIRP:2.4 GHz < 20 dBm (EIRP), 5 GHz < 23 dBm (EIRP)  
Reception Sensitivity:11g 6 Mb/s -96 dBm, 11g 54 Mb/s -78 dBm, 11n HT40 MCS7 -74 dBm, 11n HT20 MCS7 -71 dBm, 11a 6 Mb/s -97 dBm, 11a 54 Mb/s -79 dBm, 11ac VHT20 MCS8 -74 dBm, 11ac VHT40 MCS9 -70 dBm, 11ac VHT80 MCS9 -65 dBm



#09103

Net Price:  
19.70 USD  
Unit: pcs

**1200Mbps Wireless Router Dual-band AC1200 (TP-Link Mercusys AC12)**

- Supports 802.11ac standard - the next generation of Wi-Fi
- Enjoy smooth online gaming and video streaming with dual band 1200Mbps Wi-Fi
- 4 External Antennas Greatly Expand Wireless Coverage
- Guest Network Access provides secure Wi-Fi access for guests sharing your home or office network
- Easy installation - intuitive webpage guides you through the setup process in minutes
- IPTV and IPv6 Supported

**HARDWARE FEATURES:**

Standards and Protocols:IEEE 802.11ac/n/a 5GHz, IEEE 802.11b/g/n 2.4GHz  
Interface:3 10/100Mbps LAN Ports, 1 10/100Mbps WAN Port  
Button:WPS/Reset Button  
External Power Supply:9V/0.85A  
Dimensions (W X D X H): 222 x 140 x 32 mm  
Antenna: 4x 5 dBi

**WIRELESS FEATURES:**

Frequency:2.4GHz & 5GHz  
Signal Rate:5GHz Up to 867Mbps, 2.4GHz Up to 300Mbps  
EIRP:< 20 dBm  
Reception Sensitivity:5 GHz - 11a 6M -92 dBm, 11a 54M -75 dBm, 11ac 20M MCS8 -70 dBm, 11ac 40M MCS9 -64 dBm, 11ac 80M MCS9 -60 dBm, 2.4 GHz - 11g 6M -95 dBm, 11g 54M -77 dBm, 11n 20M MCS7 -74 dBm, 11n 40M MCS7 -71 dBm



#09192

Net Price:  
21.80 USD  
Unit: pcs

**1200Mbps Wireless Router Dual-band AC1200 (TP-Link Mercusys MR30G)**

- AC1200 Gigabit Wi-Fi - Enjoy home entertainment without any lag, reaching speeds up to 1.2 Gbps (867 Mbps on the 5 GHz band and 300 Mbps on the 2.4 GHz band)
- Broader Coverage - 4x high-gain antennas with Beamforming boost stable connections throughout your home for strong WiFi signals in every corner
- Full Gigabit Ports - Make full use of your internet access and transfer data at dizzying speeds for peak performance
- Higher Network Efficiency - MU-MIMO technology allows MR30G to communicate with multiple devices at the same time, increasing WiFi throughput for each device
- Easily Manage Your Home Network - Varied software functions such as Parental Controls, QoS, and Guest Network for safety and effectiveness
- IPTV Supported - Supports IGMP Proxy/Snooping, Bridge, and Tag VLAN to optimize IPTV streaming
- IPv6 Supported - Allows you to both enjoy the IPv6 services provided by your ISP and visit IPv6 websites

**HARDWARE FEATURES:**

Standards and Protocols:IEEE 802.11ac/n/a 5GHz, IEEE 802.11b/g/n 2.4GHz  
Interface:2 10/100/1000Mbps LAN Ports, 1 10/100/1000Mbps WAN Port  
Button:WPS/Reset Button  
Dimensions (W X D X H): 6.3 x 5.0 x 1.5 in (159.7 x 125.9 x 37.1 mm)

Antenna: 4 Fixed Omni Directional Antennas (5dBi)

**WIRELESS FEATURES:**

Frequency:2.4GHz & 5GHz  
Signal Rate:5GHz Up to 867Mbps, 2.4GHz Up to 300Mbps  
EIRP:<20dBm(EIRP)  
Wireless Functions:Enable/Disable Wireless Radio, Wireless Statistics  
Wireless Security:WPA-PSK / WPA2-PSK

NEW



#09398

Net Price:  
32.50 USD  
Unit: pcs

**1200Mbps Wireless Router Dual-band AC1200, MU-MIMO (TP-Link Archer A64)**

- 802.11ac Wave2 WiFi - 867 Mbps on the 5 GHz band and 400 Mbps on the 2.4 GHz band
- Boosted WiFi Coverage - 4 antennas provide stable wireless connections and optimal coverage
- MU-MIMO - Easy network management at your fingertips with TP-Link TetherMU-MIMO achieves 2X efficiency by communicating with up to 2 devices at once&#8225;
- Beamforming - Beamforming technology delivers a highly efficient wireless connection
- AP Mode - Supports Access Point mode to create a new WiFi access point
- Intelligent Connection - Smart Connect directs clients to the less congested band and Airtime Fairness optimizes the time usage
- Easy Setup - Easy network management at your fingertips with TP-Link Tether

**HARDWARE FEATURES:**

Standards and Protocols:IEEE 802.11ac/n/a 5GHz, IEEE 802.11b/g/n 2.4GHz  
Interface:4 10/100Mbps LAN Ports, 1 10/100Mbps WAN Port  
Button:WPS/Reset Button  
External Power Supply: 12VDC / 1A  
Dimensions (W X D X H): 4.7 x 4.7 x 1.1 in (120 x 120 x 27.9 mm)

Antenna: 4 Antennas

**WIRELESS FEATURES:**

Frequency:2.4GHz & 5GHz  
Signal Rate:5GHz Up to 867Mbps, 2.4GHz Up to 400Mbps  
EIRP: CE <20dBm(2.4GHz), <23dBm(5GHz), FCC <30dB  
Wireless Functions:Enable/Disable Wireless Radio, WMM, Wireless Statistics



#09185

Net Price:  
32.50 USD  
Unit: pcs

**1200Mbps Wireless Router Dual-band AC1200, MU-MIMO (TP-Link Archer C64)**

- 802.11ac Wave2 WiFi - 867 Mbps on the 5 GHz band and 400 Mbps on the 2.4 GHz band
- Boosted WiFi Coverage - 4 antennas provide stable wireless connections and optimal coverage
- MU-MIMO - Easy network management at your fingertips with TP-Link TetherMU-MIMO achieves 2X efficiency by communicating with up to 2 devices at once&#8225;
- Beamforming - Beamforming technology delivers a highly efficient wireless connection
- AP Mode - Supports Access Point mode to create a new WiFi access point
- Intelligent Connection - Smart Connect directs clients to the less congested band and Airtime Fairness optimizes the time usage
- Easy Setup - Easy network management at your fingertips with TP-Link Tether

**HARDWARE FEATURES:**

Standards and Protocols:IEEE 802.11ac/n/a 5GHz, IEEE 802.11b/g/n 2.4GHz  
Interface:4 10/100Mbps LAN Ports, 1 10/100Mbps WAN Port  
Button:WPS/Reset Button  
External Power Supply: 12VDC / 1A  
Dimensions (W X D X H): 4.7 x 4.7 x 1.1 in (120 x 120 x 27.9 mm)

Antenna: 4 Antennas

**WIRELESS FEATURES:**

Frequency:2.4GHz & 5GHz  
Signal Rate:5GHz Up to 867Mbps, 2.4GHz Up to 400Mbps  
EIRP: CE <20dBm(2.4GHz), <23dBm(5GHz), FCC <30dB  
Wireless Functions:Enable/Disable Wireless Radio, WMM, Wireless Statistics



#09254

Net Price:  
43.20 USD  
Unit: pcs

**1300Mbps Wireless Router Dual-band AC1300, MU-MIMO (TP-Link EC225-G5)**

- Faster WiFi for More Devices: 2.4 GHz and 5 GHz bands run at fast AC1300 Wi-Fi speeds to deliver more bandwidth and support more devices in your home.
- Full Gigabit Ports: Enjoy fast, reliable wired connections for gaming and streaming in the best quality.
- Extensive Coverage: Beamforming, and four antennas combine to deliver focused reception to devices far away.
- EasyMesh Compatible: Provides whole home Wi-Fi coverage with standard mesh technology.
- Enhanced Protection: Protect your network with firewalls, parental controls, and the latest WPA3 encryption.
- Easy Setup: Set up your router in minutes with the intuitive web interface or the powerful Aginet app.
- Remote Management: TR-181, TR-111, TR-104, and TR-143 are supported.

**HARDWARE FEATURES:**

Standards and Protocols: IEEE 802.11ac/n/a 5GHz, IEEE 802.11b/g/n 2.4GHz  
Interface: 3 10/100/1000Mbps LAN Ports, 1 10/100/1000Mbps WAN Port  
Button: WPS/Reset Button, Power On/Off Button  
External Power Supply: 12VDC / 1A  
Dimensions (W X D X H): 9.1 x 5.7 x 1.4 in (230 x 144 x 35 mm)

Antenna: 4 Antennas

**WIRELESS FEATURES:**

Frequency: 2.4GHz & 5GHz  
Signal Rate: 5GHz Up to 867Mbps, 2.4GHz Up to 400Mbps  
Wireless Functions: Enable/Disable Wireless Radio, WMM, Wireless Statistics  
Wireless Security: 64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK encryption



#09320

Net Price:  
58.80 USD  
Unit: pcs

**1500Mbps Wireless Gigabit Router Dual-band AX1500, MU-MIMO (TP-Link EX141)**

- 1.5 Gbps WiFi Speeds: Enjoy faster browsing, streaming, and downloading across two bands.
- Connect More, Stay Fast: Equipped with the latest WiFi 6 wireless technology for faster speeds, greater capacity, and reduced network congestion.
- Extensive Coverage: Beamforming and four antennas combine to deliver focused reception to devices far away.
- EasyMesh Compatible: Provides whole home WiFi coverage with standard mesh technology.
- Enhanced Security: Protect your network with firewalls and the latest WPA3 encryption.
- Easy Setup: Set up your network in minutes with the powerful Aginet app.
- Remote Management: TR-069, TR-098, TR-181, TR-111, and TR-143 protocols are supported.

**HARDWARE FEATURES:**

Standards and Protocols: IEEE 802.11ax/ac/n/a 5GHz, IEEE 802.11b/g/n 2.4GHz, Wi-Fi 6  
Interface: 3 10/100/1000Mbps LAN Ports, 1 1G/100Mbps WAN Port  
Button: WPS/Reset Button, Wireless On/Off Button, Power On/Off Button, LED On/Off  
Power Supply: 12V/1A  
Dimensions (W X D X H): 7.2 x 3.7 x 1.3 in (182.7 x 94 x 33.3 mm)

Antenna: 4 x External Antennas

**WIRELESS FEATURES:**

Frequency: 2.4GHz & 5GHz  
Signal Rate: 5 GHz@ 1201 Mbps (802.11ax), 2.4 GHz@ 300 Mbps (802.11n)  
Wireless Functions: Enable/Disable Wireless Radio, Guest Network, DFS, MU-MIMO, OFDMA



#09322

Net Price:  
28.40 USD  
Unit: pcs

**1500Mbps Wireless Gigabit Router Dual-band AX1500, MU-MIMO (TP-Link Marcusys MR60X)**

- Upgrade Your Network with Wi-Fi 6 - MR60X comes equipped with the latest Wi-Fi 6 standard, delivering more simultaneous connections, extend WiFi range, and maintain reliably fast data transmissions.
- Faster 1.5 Gbps Speeds - Optimal WiFi 6 speeds reaching up to 1.5 Gbps (1201 Mbps on the 5 GHz band and 300 Mbps on the 2.4 GHz band)
- Improved Network Capacity - OFDMA and MU-MIMO allow simultaneous data transmission to and from several devices, improving overall network efficiency
- Broader, Stronger Coverage - 4x multi-directional high-gain antennas with Beamforming boost stable connections throughout your home for strong WiFi signals in every corner
- Gigabit Wired Connections - Make full use of your internet access and transfer data at dizzying speeds for peak performance
- Overall Security Protection - The latest WPA3 provides improved WiFi security
- Less WiFi Interference - Minimizes the interference from neighboring signals to improve transmission efficiency with BSS color
- Smart Connect- Intelligently chooses the best available band for each device

**HARDWARE FEATURES:**

Standards and Protocols: IEEE 802.11ax/ac/n/a 5GHz, IEEE 802.11ax/b/g/n 2.4GHz, Wi-Fi 6  
Interface: 2 10/100/1000Mbps LAN Ports, 1 1G/100Mbps WAN Port  
Button: WPS/Reset Button  
Dimensions (W X D X H): 6.9 x 6.2 x 1.8 in (175.6 x 157.2 x 45 mm)  
Antenna: 4x 5 dBi Fixed Omni-Directional Antennas

**WIRELESS FEATURES:**  
Frequency: 2.4GHz & 5GHz  
Signal Rate: 5 GHz@ 1201 Mbps (802.11ax), 2.4 GHz@ 400 Mbps (802.11ax)  
Wireless Functions: Enable/Disable Wireless Radio, WMM  
Wireless Security: WPA-PSK / WPA2-PSK/ WPA3

NEW



#09397

Net Price:  
39.50 USD  
Unit: pcs

**1900Mbps Wireless Router Dual-band AC1900 (TP-Link Archer A8)**

- 802.11ac Wave2 Wi-Fi - 1300 Mbps on the 5 GHz band and 600 Mbps on the 2.4 GHz band.
- 3x3 MIMO Technology - Transmitting and receiving data on three streams to pair flawlessly with your 3x3 clients.
- Boosted Wi-Fi Coverage - Beamforming technology delivers a highly efficient wireless connection.
- MU-MIMO - To help your devices achieve optimal performance by making communication more efficient.
- Personalized Management - Advanced features like Parental Controls, Guest Network, and Access Control provide individualized tools for network management.
- Intelligent Connection - Smart Connect directs clients to the less congested band and Airtime Fairness optimizes the time usage.
- EasyMesh-Compatible - Flexibly creates a Mesh network by connecting to an EasyMesh-compatible router for seamless whole-home coverage.

**HARDWARE FEATURES:**

Standards and Protocols: IEEE 802.11ac/n/a 5GHz, IEEE 802.11b/g/n 2.4GHz  
Interface: 4 10/100/1000Mbps LAN Ports, 1 10/100/1000Mbps WAN Port  
Button: WPS/Reset Button, Wireless On/Off Button, Power On/Off Button  
External Power Supply: 12VDC / 1A  
Dimensions (W X D X H): 9.6 x 6.4 x 1.3 in (243 x 160.6 x 32.5 mm)

Antenna: 3 Omni Directional Antennas

**WIRELESS FEATURES:**

Frequency: 2.4GHz & 5GHz  
Signal Rate: 5GHz Up to 1300Mbps, 2.4GHz Up to 600Mbps  
EIRP: <20dBm(EIRP)  
Wireless Functions: Enable/Disable Wireless Radio, WMM, Wireless Statistics



#09042

Net Price:  
39.50 USD  
Unit: pcs

**1900Mbps Wireless Router Dual-band AC1900 (TP-Link Archer C80)**

- 802.11ac Wave2 Wi-Fi - 1300 Mbps on the 5 GHz band and 600 Mbps on the 2.4 GHz band.
- 3x3 MIMO Technology - Transmitting and receiving data on three streams to pair flawlessly with your 3x3 clients.
- Boosted Wi-Fi Coverage - Beamforming technology delivers a highly efficient wireless connection.
- MU-MIMO - To help your devices achieve optimal performance by making communication more efficient.
- Personalized Management - Advanced features like Parental Controls, Guest Network, and Access Control provide individualized tools for network management.
- Intelligent Connection - Smart Connect directs clients to the less congested band and Airtime Fairness optimizes the time usage.

**HARDWARE FEATURES:**

Standards and Protocols: IEEE 802.11ac/n/a 5GHz, IEEE 802.11b/g/n 2.4GHz  
Interface: 4 10/100/1000Mbps LAN Ports, 1 10/100/1000Mbps WAN Port  
Button: WPS/Reset Button, Wireless On/Off Button, Power On/Off Button  
External Power Supply: 12VDC / 1A  
Dimensions (W X D X H): 8.5 x 4.6 x 1.26 in (215 x 117 x 32 mm)

Antenna: 4 Fixed Omni Directional Antennas

**WIRELESS FEATURES:**

Frequency: 2.4GHz & 5GHz  
Signal Rate: 5GHz Up to 1300Mbps, 2.4GHz Up to 600Mbps  
EIRP: <20dBm(EIRP)  
Wireless Functions: Enable/Disable Wireless Radio, WMM, Wireless Statistics



#09108

Net Price:  
30.60 USD  
Unit: pcs

**1900Mbps Wireless Router Dual-band AC1900 (TP-Link Mercusys MR50G)**

- AC1900 Dual Band Speeds - Enjoy home entertainment without any lag, reaching speeds up to 1900 Mbps (1300 Mbps on the 5 GHz band and 600 Mbps on the 2.4 GHz band)
- Far-Reaching Coverage - 6x high-gain antennas with Beamforming boost stable connections throughout your home for strong WiFi signals in every corner
- Full Gigabit Ports - Make full use of your internet access and transfer data at dizzying speeds for peak performance
- Higher Network Efficiency - MU-MIMO technology allows MR50G to communicate with multiple devices at the same time, increasing the overall network throughput
- Smart Connect- Intelligently chooses the best available band for each device

**HARDWARE FEATURES:**

Standards and Protocols: IEEE 802.11ac/n/a 5GHz, IEEE 802.11b/g/n 2.4GHz  
Interface: 2 10/100/1000Mbps LAN Ports, 1 10/100/1000Mbps WAN Port  
Button: WPS/Reset Button  
External Power Supply: 12VDC / 1A  
Dimensions (W X D X H): 175.6 x 157.2 x 45 mm  
Antenna: 6 Fixed Omni Directional Antennas

**WIRELESS FEATURES:**  
Frequency: 2.4GHz & 5GHz  
Signal Rate: 5GHz Up to 1300Mbps, 2.4GHz Up to 600Mbps  
EIRP: <20dBm(EIRP)  
Wireless Functions: Enable/Disable Wireless Radio, Wireless Statistics



#09045

Net Price:  
86.40 USD  
Unit: pcs

**2100Mbps Wireless Gigabit Router Dualband  
2100AC, ADSL, MU-MIMO (TP-Link Archer  
VR2100)**

- Super VDSL - The Latest Super VDSL (VDSL2 Profile 35b) tech delivers internet speeds of up to 350 Mbps
- Ultra-Fast Speed - Surpasses the Wi-Fi speed limits of the previous generation, reaching up to 1733 Mbps on 5 GHz and 300 Mbps on 2.4 GHz
- 4x4 MU-MIMO - Simultaneously transfers data to multiple devices for 4x faster performance
- Whole-Home Coverage with OneMesh™ - Co-works with TP-Link OneMesh products to create a flexible and cost-efficient Mesh network
- Lightning-Fast Wired Connection - USB 3.0 port and four Gigabit Ethernet ports run up to 10x faster than the previous generation to unleash your home entertainment
- TP-Link Tether App - Easily access and manage your network, including remote control and automatic updates, using any iOS or Android mobile device.

**HARDWARE FEATURES:**

Standards and Protocols: IEEE 802.11ac/n/a 5GHz, IEEE 802.11b/g/n 2.4GHz  
Interface: 4x10/100/1000Mbps RJ45 LAN Ports, 1xRJ11 Port, 2xUSB 2.0 Ports  
Button: 1 Power On/Off Button, 1 Wi-Fi On/Off Button, 1 WPS Button, 1 RESET Button  
ADSL Standards: Full-rate ANSI T1.413 Issue 2, ITU-T G.992.1(G.DMT), ITU-T G.992.2(G.Lite),  
ADSL2 Standards: ITU-T G.992.3 (G.DMT.bis), ITU-T G.992.4 (G.lite.bis)  
ADSL2+ Standards: ITU-T G.992.5  
External Power Supply: 12VDC / 1.5A  
Dimensions (W x D x H): 8.5 x 6.5 x 1.4 in (216 x 164 x 36.8 mm)



#09522

Net Price:  
43.90 USD  
Unit: pcs

**3G/4G 1200Mbps Wireless Router Dual-band  
AC1200, MU-MIMO, 4G/LTE (TP-Link Marcusys  
MB130-4G)**

- 4G network - Enjoy the 4G download speeds up to 150 Mbps.
- Plug a SIM card and play - No configurations needed, compatibility of SIM cards are assured by years of field tests.
- Dual Band 1200 Mbps Wi-Fi - Fast Wi-Fi speeds up to 300 Mbps on the 2.4 GHz band and 867 Mbps on the 5 GHz band.
- Simultaneous Connection- Enjoy and share internet access with up to 64 Wi-Fi devices.
- Wi-Fi router mode - Plug an Ethernet cable into the LAN/WAN port for flexible access if you can't get a 4G connection.
- External Antennas Ports - Plug in your 4G/3G Antennas to enhance the Network Signal.

**HARDWARE FEATURES:**

Standards and Protocols: 802.11ac/a/b/g/n  
Interface: 1x 10/100Mbps LAN/WAN Port, 1x 10/100Mbps LAN Port, 2x 4G/3G External Antenna Ports, 1x Nano SIM Card Slot  
Button: WPS/Reset Button  
Dimensions (W x D x H): 95 x 61.05 x 165.97 mm  
**WIRELESS FEATURES:**  
Frequency: 2.4GHz & 5GHz  
Signal Rate: 5 GHz@ 867 Mb/s, 2.4 GHz@ 300 Mb/s  
Wireless Functions: Enable/Disable Wireless Radio, Wireless Schedule, WMM, Wireless, Statistics  
Wireless Security: WPA-PSK / WPA2-PSK  
Network Type: EU FDD-LTE B1/B3/B5/B7/B8/B20/B28 (2100/1800/850/2600/900/800/700 MHz), TDD-LTE B38/B40 (2600/2300 MHz), HSPA+/UMTS B1/B5/B8 (2100/850/900 MHz)



#04686

Net Price:  
74.60 USD  
Unit: pcs

**3G/4G Wireless AC1200 Router, 1200Mbps  
(TP-Link Archer MR400)**

- Shares your 4G LTE network with multiple Wi-Fi devices and enjoy download speeds of up to 150Mbps
- Powerful, integrated antennas provide stable wireless connections and better coverage
- Requires no configuration, just insert a SIM card and turn it on to enjoy a fast wireless connection
- Creates simultaneous dual band Wi-Fi networks, with maximum speeds of up to 300Mbps on the 2.4GHz band and 867Mbps on the 5GHz band
- Offers options and flexibility with the LAN/WAN port, allowing you to choose your connection type

**HARDWARE FEATURES:**

Interface: 1 10/100Mbps LAN/WAN Port, 3 10/100Mbps LAN Ports, 1 SIM Card Slot  
Button: WPS/Reset Button, Wireless On/Off Switch, Power On/Off Button  
External Power Supply: 12VDC/1A  
Dimensions (W x D x H): 7.95 x 5.71 x 1.34 in. (202 x 145 x 34 mm)  
Antenna Type: 3 Internal Wi-Fi Antennas, 2 Detachable External 4G LTE Antennas  
**WIRELESS FEATURES:**  
Wireless Standards: IEEE 802.11ac/n/a, IEEE 802.11g, IEEE 802.11b  
Frequency: 2.4GHz and 5GHz  
EIRP: <20dBm, <23dBm(5GHz)  
Signal Rate: 300Mbps at 2.4GHz, 867Mbps at 5GHz

NEW



#09543

Net Price:  
63.10 USD  
Unit: pcs

**3G/4G Wireless AC1200 Router, 1200Mbps  
(TP-Link Archer MR402)**

- Shares your 4G LTE network with multiple Wi-Fi devices and enjoy download speeds of up to 150Mbps
- Powerful, integrated antennas provide stable wireless connections and better coverage
- Requires no configuration, just insert a SIM card and turn it on to enjoy a fast wireless connection
- Creates simultaneous dual band Wi-Fi networks, with maximum speeds of up to 300Mbps on the 2.4GHz band and 867Mbps on the 5GHz band
- Offers options and flexibility with the LAN/WAN port, allowing you to choose your connection type

**HARDWARE FEATURES:**

Interface: 1 10/100Mbps LAN/WAN Port, 3 10/100Mbps LAN Ports, 1 SIM Card Slot, 2x External SMA-F Antenna Interface  
Button: WPS/Reset Button, Wireless On/Off Switch, Power On/Off Button  
External Power Supply: 12VDC/1A  
Dimensions (W x D x H): 7.95 x 5.71 x 1.34 in. (202 x 145 x 34 mm)  
Antenna Type: 3 Internal Wi-Fi Antennas, 2 Detachable External 4G LTE Antennas  
**WIRELESS FEATURES:**  
Wireless Standards: IEEE 802.11ac/n/a, IEEE 802.11g, IEEE 802.11b  
Frequency: 2.4GHz and 5GHz



#04604

Net Price:  
70.50 USD  
Unit: pcs

**3G/4G Wireless AC750 Router, 750Mbps (TP-Link  
Archer MR200)**

- Shares your 4G LTE network with multiple Wi-Fi devices and enjoy download speeds of up to 150Mbps
- Powerful, integrated antennas provide stable wireless connections and better coverage
- Requires no configuration, just insert a SIM card and turn it on to enjoy a fast wireless connection
- Creates simultaneous dual band Wi-Fi networks, with maximum speeds of up to 300Mbps on the 2.4GHz band and 433Mbps on the 5GHz band
- Offers options and flexibility with the LAN/WAN port, allowing you to choose your connection type

**HARDWARE FEATURES:**

Interface: 1 10/100Mbps LAN/WAN Port, 3 10/100Mbps LAN Ports, 1 SIM Card Slot  
Button: WPS/Reset Button, Wireless On/Off Switch, Power On/Off Button  
External Power Supply: 12VDC/1A  
Dimensions (W x D x H): 7.95 x 5.55 x 1.32 in. (202 x 141 x 33.6 mm)  
Antenna Type: 3 Internal Wi-Fi Antennas, 2 Detachable External 4G LTE Antennas  
**WIRELESS FEATURES:**  
Wireless Standards: IEEE 802.11ac/n/a, IEEE 802.11g, IEEE 802.11b  
Frequency: 2.4GHz and 5GHz  
EIRP: <20dBm, <23dBm(5GHz)  
Signal Rate: 300Mbps at 2.4GHz, 433Mbps at 5GHz

NEW



#09403

Net Price:  
55.90 USD  
Unit: pcs

**3G/4G Wireless AC750 Router, 750Mbps (TP-Link  
Archer MR202)**

- Shares your 4G LTE network with multiple Wi-Fi devices and enjoy download speeds of up to 150Mbps
- Powerful, integrated antennas provide stable wireless connections and better coverage
- Requires no configuration, just insert a SIM card and turn it on to enjoy a fast wireless connection
- Creates simultaneous dual band Wi-Fi networks, with maximum speeds of up to 300Mbps on the 2.4GHz band and 433Mbps on the 5GHz band
- Offers options and flexibility with the LAN/WAN port, allowing you to choose your connection type

**HARDWARE FEATURES:**

Interface: 1 10/100Mbps LAN/WAN Port, 3 10/100Mbps LAN Ports, 1 SIM Card Slot  
Button: WPS/Reset Button, Wireless On/Off Switch, Power On/Off Button  
External Power Supply: 12VDC/1A  
Dimensions (W x D x H): 7.95 x 5.55 x 1.32 in. (202 x 141 x 33.6 mm)  
Antenna Type: 3 Internal Wi-Fi Antennas, 2 Detachable External 4G LTE Antennas  
**WIRELESS FEATURES:**  
Wireless Standards: IEEE 802.11ac/n/a, IEEE 802.11g, IEEE 802.11b  
Frequency: 2.4GHz and 5GHz  
EIRP: <20dBm, <23dBm(5GHz)  
Signal Rate: 300Mbps at 2.4GHz, 433Mbps at 5GHz



#09521

Net Price:  
65.90 USD  
Unit: pcs

**3G/4G+ 1200Mbps Wireless Gigabit Router Dual-band AC1200, MU-MIMO, 4G/LTE (TP-Link Marcusys MB230-4G)**

- 4G+ network - Enjoy the 4G+ Cat 6 download speeds up to 300 Mbps.
- Plug a SIM card and play - No configurations needed, compatibility of SIM cards are assured by years of field tests.
- Dual Band 1200 Mbps WiFi - Fast WiFi speeds up to 300 Mbps on the 2.4 GHz band and 867 Mbps on the 5 GHz band.
- Simultaneous Connection- Enjoy and share internet access with up to 64 Wi-Fi devices.
- Wi-Fi router mode - Plug an Ethernet cable into the LAN/WAN port for flexible access if you can't get a 4G connection.

**HARDWARE FEATURES:**

Standards and Protocols:802.11ac/a/b/g/n  
Interface: 1x Gigabit LAN/WAN Port, 1x Gigabit LAN Port, 1x Nano SIM Card Slot  
Button:WPS/Reset Button  
Dimensions (W X D X H): 95 × 61,05 × 165,97 mm

**WIRELESS FEATURES:**

Frequency:2.4GHz & 5GHz  
Signal Rate: 5 GHz@ 867 Mb/s, 2.4 GHz@ 300 Mb/s  
Wireless Functions:Enable/Disable Wireless Radio, Wireless Schedule, WMM, Wireless, Statistics  
Wireless Security:WPA-PSK / WPA2-PSK / WPA3-SAE  
Network Type: EU FDD-LTE B1/B3/B5/B7/B8/B20/B28 (2100/1800/850/2600/900/800/700 MHz), TDD-LTE B38/B40 (2600/2300 MHz), HSPA+/UMTS B1/B5/B8 (2100/850/900 MHz)



#09212

Net Price:  
100.00 USD  
Unit: pcs

**3G/4G+ Cat6 Wireless AC1200 Router, 1200Mbps (TP-Link Archer MR500)**

- TP-Link's First 4G+ Router - supports 4G+ Cat6 to boost the data speeds of up to 300 Mbps
- Full Gigabit Ports - provides reliable wired connections for bandwidth-intensive devices such as game consoles and STB
- Plug a SIM card and play - no configurations needed, compatibility of SIM cards in 100+ countries are assured by years of field tests
- Better Signal for Connections Everywhere - enjoy stable and efficient connections to every device thanks to the two external LTE antennas
- Wi-Fi router mode - plug an Ethernet cable into the LAN/WAN port for flexible access as a backup option if you can't get a 4G connection
- Supports TP-Link OneMeshTM - co-works with TP-Link OneMesh products to create a flexible and cost-efficient Mesh network

**HARDWARE FEATURES:**

Interface: 1 10/100/1000Mbps LAN/WAN Port, 3 10/100/1000Mbps LAN Ports, 1 nano-SIM Card Slot  
Button:WPS/Reset Button, Wireless On/Off Switch, Power On/Off Button  
External Power Supply:12VDC/1.5A  
Dimensions ( W x D x H ):7.95 × 5.55 × 1.32 in (202 × 141 × 33.6 mm)

Antenna Type: 2 Detachable External 4G LTE Antennas

**WIRELESS FEATURES:**

Wireless Standards:IEEE 802.11ac/n/a, IEEE 802.11g, IEEE 802.11b  
Frequency:2.4GHz and 5GHz  
EIRP:<20dBm, <23dBm(5GHz)  
Signal Rate: 300Mbps at 2.4GHz, 867Mbps at 5GHz

NEW



#09402

Net Price:  
93.30 USD  
Unit: pcs

**3G/4G+ Cat6 Wireless AC1200 Router, 1200Mbps (TP-Link Archer MR505)**

- TP-Link's First 4G+ Router - supports 4G+ Cat6 to boost the data speeds of up to 300 Mbps
- Full Gigabit Ports - provides reliable wired connections for bandwidth-intensive devices such as game consoles and STB
- Plug a SIM card and play - no configurations needed, compatibility of SIM cards in 100+ countries are assured by years of field tests
- Wi-Fi router mode - plug an Ethernet cable into the LAN/WAN port for flexible access as a backup option if you can't get a 4G connection
- Supports TP-Link OneMeshTM - co-works with TP-Link OneMesh products to create a flexible and cost-efficient Mesh network

**HARDWARE FEATURES:**

Interface: 1 10/100/1000Mbps LAN/WAN Port, 2 10/100/1000Mbps LAN Ports, 1 nano-SIM Card Slot  
Button:WPS/Reset Button, Wireless On/Off Switch, Power On/Off Button  
External Power Supply:12VDC/1.5A  
Dimensions ( W x D x H ):212 × 157.5 × 57 mm (8.35 × 6.20 × 2.24 in)

Antenna Type: 2 × External SMA-F Antenna Interface

**WIRELESS FEATURES:**

Wireless Standards:IEEE 802.11ac/n/a, IEEE 802.11g, IEEE 802.11b  
Frequency:2.4GHz and 5GHz  
EIRP:<20dBm, <23dBm(5GHz)  
Signal Rate: 300Mbps at 2.4GHz, 867Mbps at 5GHz



#09005

Net Price:  
112.00 USD  
Unit: pcs

**3G/4G+ Cat6 Wireless AC1200 Router, 1200Mbps (TP-Link Archer MR600)**

- TP-Link's First 4G+ Router - supports 4G+ Cat6 to boost the data speeds of up to 300 Mbps
- Full Gigabit Ports - provides reliable wired connections for bandwidth-intensive devices such as game consoles and STB
- Plug a SIM card and play - no configurations needed, compatibility of SIM cards in 100+ countries are assured by years of field tests
- Better Signal for Connections Everywhere - enjoy stable and efficient connections to every device thanks to the two external LTE antennas
- Wi-Fi router mode - plug an Ethernet cable into the LAN/WAN port for flexible access as a backup option if you can't get a 4G connection
- Supports TP-Link OneMeshTM - co-works with TP-Link OneMesh products to create a flexible and cost-efficient Mesh network

**HARDWARE FEATURES:**

Interface: 1 10/100/1000Mbps LAN/WAN Port, 3 10/100/1000Mbps LAN Ports, 1 SIM Card Slot  
Button:WPS/Reset Button, Wireless On/Off Switch, Power On/Off Button

External Power Supply:12VDC/1.5A

Dimensions ( W x D x H ):9.0×6.3×1.5 in ( 229×160×37 mm)

Antenna Type: 3 Internal Wi-Fi Antennas, , 2 Detachable

External 4G LTE Antennas

**WIRELESS FEATURES:**

Wireless Standards:IEEE 802.11ac/n/a, IEEE 802.11g, IEEE 802.11b  
Frequency:2.4GHz and 5GHz  
EIRP:<20dBm, <23dBm(5GHz)  
Signal Rate: 300Mbps at 2.4GHz, 867Mbps at 5GHz



#06240

Net Price:  
30.30 USD  
Unit: pcs

**750Mbps Wireless AC Nano Router (TP-Link TL-WR902AC)**

- Travel-Sized Design - Conveniently small and light to pack and take on the road, creating Wi-Fi network via Ethernet or WISP
- Dual Band AC750 Wi-Fi - Strong, fast connection for HD streaming on all your devices
- One Switch for Multiple Modes - Perfect for Wi-Fi at home, your hotel room or on the road
- Flexible Power - Micro USB port to an adapter, portable charger or laptop
- Versatile USB - For file sharing or providing power supply to mobile devices

**HARDWARE FEATURES:**

Interface:1 10/100Mbps WAN/LAN Port, 1 USB Port, 1 Reset Button, 1 Mode Switch, 1 WPS Button  
Wireless Standards: IEEE 802.11ac/n/a 5GHz, IEEE 802.11b/g/n 2.4GHz  
Dimensions ( W x D x H ):74x67x22mm (2,91x2,64x0,87 in.)

External Power Supply: 5V/2A

Antenna Type:On-Board

**WIRELESS FEATURES:**

Frequency:2.4GHz and 5GHz  
Signal Rate:5GHz - Up to 433Mbps(Only with 11AC Wireless Adapter); Up to 150Mbps with 11N Wireless Adapter 2.4GHz  
- Up to 300Mbps  
EIRP:<20dBm(2,4GHz), <23dBm(5GHz)



#04572

Net Price:  
23.20 USD  
Unit: pcs

**750Mbps Wireless Router Dual-band AC750 (TP-Link Archer C20)**

- Supports 802.11ac standard - the next generation of Wi-Fi
- Simultaneous 2.4GHz 300Mbps and 5GHz 433Mbps connections for 733Mbps of total available bandwidth
- 3 external antennas provide stable omnidirectional signal and superior wireless coverage

**HARDWARE FEATURES:**

Standards and Protocols:IEEE 802.11ac/n/a 5GHz, IEEE 802.11b/g/n 2.4GHz  
Interface:4 10/100Mbps LAN Ports, 1 10/100Mbps WAN Port  
Button:WPS/Reset Button, Wireless On/Off Button, Power On/off Button  
External Power Supply: 9VDC / 0.6A  
Dimensions (W X D X H): 230 x 144 x 35mm (9,1 x 5,7 x 1,4 in.)

Antenna: 3 Antennas

**WIRELESS FEATURES:**

Frequency:2.4GHz & 5GHz  
Signal Rate:5GHz Up to 433Mbps, 2.4GHz Up to 300Mbps  
EIRP: CE <20dBm(2,4GHz), <23dBm(5GHz), FCC <30dB  
Wireless Functions:Enable/Disable Wireless Radio, WMM, Wireless Statistics





#09078

Net Price:  
20.80 USD  
Unit: pcs

#### 750Mbps Wireless Router Dual-band AC750 (TP-Link Archer C24)

- High-Speed Wi-Fi-AC750 dual-band is ideal for HD video streaming, high-speed downloading.
- Far-Reaching Coverage-4x antennas deliver far-reaching Wi-Fi and reliable connections.
- Multi-Mode 3 in 1-Supports Router, Access Point, and Range Extender to add flexibilities.
- Parental Controls-Manages when and how connected devices can access the internet.
- Guest Network-Provides separate access for guests while securing the host network.
- Smooth HD Streaming-Supports IGMP Proxy/Snooping, Bridge and Tag VLAN to optimize IPTV streaming.
- IPv6 Supported-Compatible with the IPv6 (the latest Internet Protocol version 6).
- Compact and Mountable-Designed to conserve space and complement any décor.

#### HARDWARE FEATURES:

Standards and Protocols: IEEE 802.11ac/n/a 5GHz, IEEE 802.11b/g/n 2.4GHz  
Interface: 4 10/100Mbps LAN Ports, 1 10/100Mbps WAN Port  
Button: WPS/Reset Button  
External Power Supply: 9VDC / 0.6A  
Dimensions (W X D X H): 4.5 x 4.2 x 1.0 in (115 x 106.7 x 24.3 mm)

Antenna: 4 Antennas

#### WIRELESS FEATURES:

Frequency: 2.4GHz & 5GHz  
Signal Rate: 5GHz Up to 433Mbps, 2.4GHz Up to 300Mbps  
EIRP: CE <20dBm(2.4GHz), <23dBm(5GHz), FCC <30dB  
Wireless Functions: Enable/Disable Wireless Radio, WMM, Wireless Statistics



#09012

Net Price:  
62.90 USD  
Unit: pcs

#### Router Mesh Deco E4 2-pack, AC1200 (TP-Link DECO E4(2-Pack))

- Deco uses a system of units to achieve seamless whole-home Wi-Fi coverage - eliminate weak signal areas once and for all!
- With advanced Deco Mesh Technology, units work together to form a unified network with a single network name. Devices automatically switch between - Decos as you move through your home for the fastest possible speeds.
- A Deco E4 three-pack delivers Wi-Fi to an area of up to 4,000 square feet (EU version). And if that's not enough, simply add more Decos to the network anytime to increase coverage.
- Deco E4 provides fast and stable connections with speeds of up to 1167 Mbps and works with the major internet service provider (ISP) and modem.
- Deco can handle traffic from even the busiest of networks, providing lag-free connections for up to 100 devices.
- Parental Controls limits online time and block inappropriate websites according to unique profiles created for each family member.
- Setup is easier than ever with the Deco app there to walk you through every step.

Standards: IEEE 802.11 ac/n/a 5 GHz, IEEE 802.11 b/g/n 2.4 GHz

Ports: 2 ports 10/100 Mb/s, 2 ports WAN/LAN, 1 Power Port  
Button: 1 Reset button  
Flash: 16 MB  
SDRAM: 128 MB

Frequency range: 2.4 GHz and 5 GHz

Signal Rate: 300 Mbps on 2.4 GHz, 867 Mbps on 5 GHz  
EIRP: FCC <30 dBm, CE <20 dBm (2.4 GHz) <23 dBm (5 GHz)

Advanced Functions: TP-Link Mesh Technology - MU-MIMO, Auto Path Selection, AP Steering, Band Steering, Beamforming

Wireless Security: WPA-PSK/WPA2-PSK  
Software Features: Quality of Service - WMM, IPv6 Support, WAN Type - Dynamic IP/Static IP/PPPoE, Local Management, Remote Management, DHCP - Server, Client, Port Forwarding Support, Access Control Blacklist, Firewall Security SPI Firewall, Protocols Supports IPv4 and IPv6, Homecare - Antivirus, Parental Controls, Quality of Service, Speedtest, Monthly Usage Reports, Auto FW Update, Expand for more deco, Guest Network 2.4 GHz guest network \* 1 - 5 GHz guest network \* 1, Beamformig, Easy setup by Deco App



#09014

Net Price:  
39.50 USD  
Unit: pcs

#### Router Mesh Deco M4 1-pack, AC1200 (TP-Link DECO M4(1-Pack))

- Deco uses a system of units to achieve seamless whole-home Wi-Fi coverage - eliminate weak signal areas once and for all!
- With advanced Deco Mesh Technology, units work together to form a unified network with a single network name. Devices automatically switch between - Decos as you move through your home for the fastest possible speeds.
- A Deco M4 delivers Wi-Fi to an area of up to 180 square metres. And if that's not enough, simply add more Decos to the network anytime to increase coverage.
- Deco M4 provides fast and stable connections with speeds of up to 1167 Mbps and works with the major internet service provider (ISP) and modem.
- Deco can handle traffic from even the busiest of networks, providing lag-free connections for up to 100 devices.
- Parental Controls limits online time and block inappropriate websites according to unique profiles created for each family member.
- Setup is easier than ever with the Deco app there to walk you through every step.

Standards: IEEE 802.11 ac/n/a 5 GHz, IEEE 802.11 b/g/n 2.4 GHz

Processor: Qualcomm CPU  
Ports: 2 ports 10/100/1000 Mb/s WAN/LAN  
Button: 1 Reset button  
Flash: 16 MB  
SDRAM: 128 MB

Frequency range: 2.4 GHz and 5 GHz

Signal Rate: 300 Mbps on 2.4 GHz, 867 Mbps on 5 GHz  
EIRP: FCC <30 dBm, CE <20 dBm (2.4 GHz) <23 dBm (5 GHz)

Advanced Functions: Router/ Access Point Mode, Optional Ethernet Backhaul, Guest network, TP-Link Mesh Technology MU-MIMO, Auto Path Selection, Self-Healing, AP Steering, Band Steering, Beamforming



#09015

Net Price:  
76.90 USD  
Unit: pcs

#### Router Mesh Deco M4 2-pack, AC1200 (TP-Link DECO M4(2-Pack))

- Deco uses a system of units to achieve seamless whole-home Wi-Fi coverage - eliminate weak signal areas once and for all!
- With advanced Deco Mesh Technology, units work together to form a unified network with a single network name. Devices automatically switch between - Decos as you move through your home for the fastest possible speeds.
- A Deco M4 delivers Wi-Fi to an area of up to 180 square metres. And if that's not enough, simply add more Decos to the network anytime to increase coverage.
- Deco M4 provides fast and stable connections with speeds of up to 1167 Mbps and works with the major internet service provider (ISP) and modem.
- Deco can handle traffic from even the busiest of networks, providing lag-free connections for up to 100 devices.
- Parental Controls limits online time and block inappropriate websites according to unique profiles created for each family member.
- Setup is easier than ever with the Deco app there to walk you through every step.

Standards: IEEE 802.11 ac/n/a 5 GHz, IEEE 802.11 b/g/n 2.4 GHz

Processor: Qualcomm CPU  
Ports: 2 ports 10/100/1000 Mb/s WAN/LAN  
Button: 1 Reset button  
Flash: 16 MB  
SDRAM: 128 MB

Frequency range: 2.4 GHz and 5 GHz

Signal Rate: 300 Mbps on 2.4 GHz, 867 Mbps on 5 GHz  
EIRP: FCC <30 dBm, CE <20 dBm (2.4 GHz) <23 dBm (5 GHz)

Advanced Functions: Router/ Access Point Mode, Optional Ethernet Backhaul, Guest network, TP-Link Mesh Technology MU-MIMO, Auto Path Selection, Self-Healing, AP Steering, Band Steering, Beamforming



#09016

Net Price:  
114.00 USD  
Unit: pcs

#### Router Mesh Deco M4 3-pack, AC1200 (TP-Link DECO M4(3-Pack))

- Deco uses a system of units to achieve seamless whole-home Wi-Fi coverage - eliminate weak signal areas once and for all!
- With advanced Deco Mesh Technology, units work together to form a unified network with a single network name. Devices automatically switch between - Decos as you move through your home for the fastest possible speeds.
- A Deco M4 delivers Wi-Fi to an area of up to 180 square metres. And if that's not enough, simply add more Decos to the network anytime to increase coverage.
- Deco M4 provides fast and stable connections with speeds of up to 1167 Mbps and works with the major internet service provider (ISP) and modem.
- Deco can handle traffic from even the busiest of networks, providing lag-free connections for up to 100 devices.
- Parental Controls limits online time and block inappropriate websites according to unique profiles created for each family member.
- Setup is easier than ever with the Deco app there to walk you through every step.

Standards: IEEE 802.11 ac/n/a 5 GHz, IEEE 802.11 b/g/n 2.4 GHz

Processor: Qualcomm CPU  
Ports: 2 ports 10/100/1000 Mb/s WAN/LAN  
Button: 1 Reset button  
Flash: 16 MB  
SDRAM: 128 MB

Frequency range: 2.4 GHz and 5 GHz

Signal Rate: 300 Mbps on 2.4 GHz, 867 Mbps on 5 GHz  
EIRP: FCC <30 dBm, CE <20 dBm (2.4 GHz) <23 dBm (5 GHz)

Advanced Functions: Router/ Access Point Mode, Optional Ethernet Backhaul, Guest network, TP-Link Mesh Technology MU-MIMO, Auto Path Selection, Self-Healing, AP Steering, Band Steering, Beamforming



#09387

Net Price:  
46.50 USD  
Unit: pcs

#### Router Mesh Deco P9 1-pack, AC1900 (TP-Link DECO S7(1-Pack))

- 1900 Mbps WiFi Speed - Enjoy binge watching your favorite series in 4K with combined speeds of up to 1900 Mbps (600 Mbps on 2.4 GHz and 1300 Mbps on 5 GHz ) with 3x3 MU-MIMO technology.
- Connect 100+ Devices - Deco handles traffic from even the busiest of networks, providing lag-free connections for over 100 devices.
- Boosted Seamless Coverage - With advanced Deco Mesh Technology, units work together to form a unified network with a single network name. Devices automatically switch between Decos as you move through your home for the fastest possible speeds.
- Full Gigabit Ethernet - 3x Gigabit WAN/LAN Ethernet ports provide solid internet access at high speeds.
- Robust Parental Controls - Limit online time and block inappropriate websites according to unique profiles you create for each family member.
- Two Modes in One - Works as a router or access point for a flexible home network.
- Easy Setup - Setup is easier than ever with the Deco app there to walk you through every step.

Standards: IEEE 802.11 ac/n/a 5 GHz, IEEE 802.11 b/g/n 2.4 GHz

Processor: Qualcomm CPU  
Ports: 3 ports 10/100/1000 Mb/s WAN/LAN  
Button: 1 Reset button  
Signal Rate: 1000 Mb/s

Standard: HomePlug AV2

Frequency range: 2.4 GHz and 5 GHz

Signal Rate: 600 Mbps on 2.4 GHz, 1300 Mbps on 5 GHz  
EIRP: FCC <30 dBm, CE <20 dBm (2.4 GHz) <23 dBm (5 GHz)

Advanced Functions: Router/ Access Point Mode, Optional Ethernet Backhaul, Guest network, TP-Link Mesh Technology MU-MIMO, Auto Path Selection, Self-Healing, AP Steering, Band Steering, Beamforming



**#09018**  
Net Price:  
147.00 USD  
Unit: pcs

**Router Mesh Deco P9 2-pack, AC1200 (TP-Link DECO P9(2-Pack))**

Standards: IEEE 802.11 ac/n/a 5 GHz, IEEE 802.11 b/g/n 2,4 GHz  
Processor: Qualcomm CPU  
Ports: 2 ports 10/100/1000 Mb/s WAN/LAN  
Button: 1 Reset button  
Signal Rate: 1000 Mb/s  
Standard: HomePlug AV2  
Frequency range: 2.4 GHz and 5 GHz  
Signal Rate: 300 Mbps on 2.4 GHz, 867 Mbps on 5 GHz  
EIRP: FCC <30 dBm, CE <20 dBm (2,4 GHz) <23 dBm (5 GHz)  
Advanced Functions: Router/ Access Point Mode, Optional Ethernet Backhaul, Guest network, TP-Link Mesh Technology MU-MIMO, Auto Path Selection, Self-Healing, AP Steering, Band Steering, Beamforming



**#09386**  
Net Price:  
86.30 USD  
Unit: pcs

**Router Mesh Deco P9 2-pack, AC1900 (TP-Link DECO S7(2-Pack))**

- 1900 Mbps WiFi Speed - Enjoy binge watching your favorite series in 4K with combined speeds of up to 1900 Mbps (600 Mbps on 2.4 GHz and 1300 Mbps on 5 GHz ) with 3x3 MU-MIMO technology.  
- Connect 100+ Devices - Deco handles traffic from even the busiest of networks, providing lag-free connections for over 100 devices.  
- Boosted Seamless Coverage - With advanced Deco Mesh Technology, units work together to form a unified network with a single network name. Devices automatically switch between Decos as you move through your home for the fastest possible speeds.  
- Full Gigabit Ethernet - 3x Gigabit WAN/LAN Ethernet ports provide solid internet access at high speeds.  
- Robust Parental Controls - Limit online time and block inappropriate websites according to unique profiles you create for each family member.  
- Two Modes in One - Works as a router or access point for a flexible home network.  
- Easy Setup - Setup is easier than ever with the Deco app there to walk you through every step.  
Standards: IEEE 802.11 ac/n/a 5 GHz, IEEE 802.11 b/g/n 2,4 GHz  
Processor: Qualcomm CPU  
Ports: 3 ports 10/100/1000 Mb/s WAN/LAN  
Button: 1 Reset button  
Signal Rate: 1000 Mb/s  
Standard: HomePlug AV2  
Frequency range: 2.4 GHz and 5 GHz  
Signal Rate: 600 Mbps on 2.4 GHz, 1300 Mbps on 5 GHz  
EIRP: FCC <30 dBm, CE <20 dBm (2,4 GHz) <23 dBm (5 GHz)  
Advanced Functions: Router/ Access Point Mode, Optional Ethernet Backhaul, Guest network, TP-Link Mesh Technology MU-MIMO, Auto Path Selection, Self-Healing, AP Steering, Band Steering, Beamforming



**#09019**  
Net Price:  
210.00 USD  
Unit: pcs

**Router Mesh Deco P9 3-pack, AC1200 (TP-Link DECO P9(3-Pack))**

Standards: IEEE 802.11 ac/n/a 5 GHz, IEEE 802.11 b/g/n 2,4 GHz  
Processor: Qualcomm CPU  
Ports: 2 ports 10/100/1000 Mb/s WAN/LAN  
Button: 1 Reset button  
Signal Rate: 1000 Mb/s  
Standard: HomePlug AV2  
Frequency range: 2.4 GHz and 5 GHz  
Signal Rate: 300 Mbps on 2.4 GHz, 867 Mbps on 5 GHz  
EIRP: FCC <30 dBm, CE <20 dBm (2,4 GHz) <23 dBm (5 GHz)  
Advanced Functions: Router/ Access Point Mode, Optional Ethernet Backhaul, Guest network, TP-Link Mesh Technology MU-MIMO, Auto Path Selection, Self-Healing, AP Steering, Band Steering, Beamforming



**#09385**  
Net Price:  
126.00 USD  
Unit: pcs

**Router Mesh Deco P9 3-pack, AC1900 (TP-Link DECO S7(3-Pack))**

- 1900 Mbps WiFi Speed - Enjoy binge watching your favorite series in 4K with combined speeds of up to 1900 Mbps (600 Mbps on 2.4 GHz and 1300 Mbps on 5 GHz ) with 3x3 MU-MIMO technology.  
- Connect 100+ Devices - Deco handles traffic from even the busiest of networks, providing lag-free connections for over 100 devices.  
- Boosted Seamless Coverage - With advanced Deco Mesh Technology, units work together to form a unified network with a single network name. Devices automatically switch between Decos as you move through your home for the fastest possible speeds.  
- Full Gigabit Ethernet - 3x Gigabit WAN/LAN Ethernet ports provide solid internet access at high speeds.  
- Robust Parental Controls - Limit online time and block inappropriate websites according to unique profiles you create for each family member.  
- Two Modes in One - Works as a router or access point for a flexible home network.  
- Easy Setup - Setup is easier than ever with the Deco app there to walk you through every step.  
Standards: IEEE 802.11 ac/n/a 5 GHz, IEEE 802.11 b/g/n 2,4 GHz  
Processor: Qualcomm CPU  
Ports: 3 ports 10/100/1000 Mb/s WAN/LAN  
Button: 1 Reset button  
Signal Rate: 1000 Mb/s  
Standard: HomePlug AV2  
Frequency range: 2.4 GHz and 5 GHz  
Signal Rate: 600 Mbps on 2.4 GHz, 1300 Mbps on 5 GHz  
EIRP: FCC <30 dBm, CE <20 dBm (2,4 GHz) <23 dBm (5 GHz)  
Advanced Functions: Router/ Access Point Mode, Optional Ethernet Backhaul, Guest network, TP-Link Mesh Technology MU-MIMO, Auto Path Selection, Self-Healing, AP Steering, Band Steering, Beamforming



**#09258**  
Net Price:  
50.50 USD  
Unit: pcs

**Router Mesh Halo H30G 2-pack, AC1300 (TP-Link Mercusys Halo H30G(2-pack))**

- One Unified Network - With advanced Mesh Technology, Halo units work together to form a single unified whole home network with one WiFi name and password.  
- Seamless Roaming - Automatically switch between Halos as you move around your home, always getting the best signal to enjoy the fastest connections for all your devices.  
- Whole Home Coverage - Blanket up to 2,800 ft<sup>2</sup> (260 m<sup>2</sup>) with high-speed WiFi, eliminating WiFi dead zones at your home.  
- 1.3 Gbps Dual Band WiFi - Halo H30G provides fast and stable connections for over 100 devices with speeds of up to 1,300 Mbps and works with major internet service providers (ISPs) and modems.  
- Easy App Control - Use the MERCUSYS App to quickly set up and manage your WiFi.  
- Full Gigabit Ports - 2x Gigabit ports per Halo unit for lightning-fast wired connections  
Standards: IEEE 802.11 ac/n/a 5 GHz, IEEE 802.11 b/g/n 2,4 GHz  
Ports: 2 x 10/100/1000 Mb/s ports per Halo unit (WAN/LAN auto-sensing)  
Button: 1 Reset button  
Frequency range: 2.4 GHz and 5 GHz  
Signal Rate: 400 Mbps on 2.4 GHz, 867 Mbps on 5 GHz  
EIRP: CE <20 dBm (2,4 GHz) <23 dBm (5 GHz)  
Wireless Security: WPA2-PSK + AES  
Wireless Functions: Enable/Disable Wireless Radio, Wireless Statistics  
Mesh protocol: 802.11k/v  
WAN Type: Dynamic IP/Static IP/PPPoE/PPTP/L2TP  
Management: Access Control, Local Management, Remote Management



**#09259**  
Net Price:  
74.80 USD  
Unit: pcs

**Router Mesh Halo H30G 3-pack, AC1300 (TP-Link Mercusys Halo H30G(3-pack))**

- One Unified Network - With advanced Mesh Technology, Halo units work together to form a single unified whole home network with one WiFi name and password.  
- Seamless Roaming - Automatically switch between Halos as you move around your home, always getting the best signal to enjoy the fastest connections for all your devices.  
- Whole Home Coverage - Blanket up to 2,800 ft<sup>2</sup> (260 m<sup>2</sup>) with high-speed WiFi, eliminating WiFi dead zones at your home.  
- 1.3 Gbps Dual Band WiFi - Halo H30G provides fast and stable connections for over 100 devices with speeds of up to 1,300 Mbps and works with major internet service providers (ISPs) and modems.  
- Easy App Control - Use the MERCUSYS App to quickly set up and manage your WiFi.  
- Full Gigabit Ports - 2x Gigabit ports per Halo unit for lightning-fast wired connections  
Standards: IEEE 802.11 ac/n/a 5 GHz, IEEE 802.11 b/g/n 2,4 GHz  
Ports: 2 x 10/100/1000 Mb/s ports per Halo unit (WAN/LAN auto-sensing)  
Button: 1 Reset button  
Frequency range: 2.4 GHz and 5 GHz  
Signal Rate: 400 Mbps on 2.4 GHz, 867 Mbps on 5 GHz  
EIRP: CE <20 dBm (2,4 GHz) <23 dBm (5 GHz)  
Wireless Security: WPA2-PSK + AES  
Wireless Functions: Enable/Disable Wireless Radio, Wireless Statistics  
Mesh protocol: 802.11k/v  
WAN Type: Dynamic IP/Static IP/PPPoE/PPTP/L2TP  
Management: Access Control, Local Management, Remote Management



#09191

Net Price:  
99.00 USD  
Unit: pcs

#### Router Mesh Halo H50G 3-pack, AC1900 (TP-Link Mercusys Halo H50G(3-pack))

- One Unified Network - With advanced Mesh Technology, Halo units work together to form a single unified whole home network with one WiFi name and password.
- Seamless Roaming - Automatically switch between Halos as you move around your home, always getting the best signal to enjoy the fastest connections for all your devices.
- Whole Home Coverage - Blanket up to 6,000 ft2 (550 m2) with high-speed WiFi, eliminating WiFi dead zones at your home.
- 1.9 Gbps Dual Band WiFi - Halo H50G provides fast and stable connections for over 100 devices with speeds of up to 1,900 Mbps and works with major internet service providers (ISPs) and modems.
- Easy App Control - Use the MERCUSYS App to quickly set up and manage your WiFi.
- Full Gigabit Ports - 3x Gigabit ports per Halo unit for lightning-fast wired connections

Standards: IEEE 802.11 ac/n/a 5 GHz, IEEE 802.11 b/g/n 2.4 GHz

Ports: 3 x 10/100/1000 Mb/s ports per Halo unit (WAN/LAN auto-sensing)

Button: 1 Reset button

Frequency range: 2.4 GHz and 5 GHz

Signal Rate: 600 Mbps on 2.4 GHz, 1300 Mbps on 5 GHz

EIRP: CE <20 dBm (2.4 GHz) <23 dBm (5 GHz)

Wireless Security: WPA2-PSK + AES

Wireless Functions: Enable/Disable Wireless Radio, Wireless Statistics

Mesh protocol: 802.11k/v

WAN Type: Dynamic IP/Static IP/PPPoE/PPTP/L2TP

Management: Access Control, Local Management, Remote Management



#09174

Net Price:  
34.80 USD  
Unit: pcs

#### 1200Mbps Wireless Range Extender AC (TP-Link RE365)

- Keep your whole home connected with strong Wi-Fi expansion at combined speed of up to 1.2Gbps
- Integrated power socket makes sure that no power outlet is waste
- Intelligent signal light helps to find the best location for optimal Wi-Fi coverage by showing the signal strength
- Works with any Wi-Fi router or wireless access point
- Unique design complements the aesthetic of daily life

##### HARDWARE FEATURES:

Interface:1x10/100/1000Mbps RJ45 Port

Plug Type: EU

Button:WPS, LED, Power, Reset

Power Consumption: About 6.5W

Wireless Standards:IEEE 802.11ac, IEEE 802.11n, IEEE 802.11g, IEEE 802.11a, IEEE 802.11b

Dimensions ( W x D x H ): 4.9 x 2.8 x 3.0 in. (125 x 70 x 77mm)

Antenna Type: 2 x external

##### WIRELESS FEATURES

Frequency:2.4GHz & 5GHz

Signal Rate:5GHz Up to 867Mbps, 2.4GHz Up to 300Mbps

EIRP:CE <18dBm, FCC <19dBm

Reception Sensitivity:5GHz- 11a 6Mbps -92dBm, 11a

54Mbps -74dBm, 11ac HT20 -72dBm, 11ac HT40 -63dBm,

11ac HT80 -59dBm, 2.4GHz- 11g 54Mbps -75dBm, 11n

HT20 -73dBm, 11n HT40 -70dBm



#09032

Net Price:  
30.20 USD  
Unit: pcs

#### 1200Mbps Wireless Range Extender Mesh, AC1200 (TP-Link RE300)

- Extends dual-band Wi-Fi across your home to eliminate Wi-Fi dead zones.
- Creates a Mesh network by connecting to a OneMesh router for seamless whole-home coverage.
- Operates over both the 2.4 GHz band (300 Mbps) and 5 GHz band (867 Mbps) for more stable wireless experience.
- Smart signal indicator helps to find the best location for optimal Wi-Fi coverage by showing the signal strength.
- Push the WPS button to easily set up a Mesh network you can uniformly manage from the Tether app or Web UI.
- Works with any Wi-Fi router or wireless access point.

##### HARDWARE FEATURES:

Plug Type: EU

Button:WPS Button, Reset Button

Power Consumption: About 7.3W

Wireless Standards:IEEE802.11ac,IEEE 802.11n, IEEE 802.11g, IEEE 802.11b, IEEE 802.11a

Dimensions ( W x D x H ): 4.9 x 2.7 x 2.0 in (124 x 69 x 52 mm)

##### WIRELESS FEATURES

Frequency:2.4GHz & 5GHz

Signal Rate: 5GHz Up to 867Mbps, 2.4GHz Up to 300Mbps

EIRP:<17dBm(2.4GHz) <17dBm(5GHz)

Reception Sensitivity:5GHz 11a 6Mbps -91dBm@10% PER, 11a 54Mbps -74dBm@10% PER, 11ac HT20 mcs8

-68dBm@10% PER, 11ac HT40 mcs9 -63dBm@10% PER, 11ac HT80 mcs9 -59dBm@10% PER, 2.4GHz 11g 54M

-79dBm@10% PER, 11n HT20 mcs7 -77dBm@10% PER, 11n HT40 mcs7 -74dBm@10% PER



#09107

Net Price:  
18.70 USD  
Unit: pcs

#### 1200Mbps Wireless Range Extender, AC1200 (TP-Link Mercusys ME30)

- Eliminate WiFi Dead Zones - Boosts WiFi signals to previously unreachable or hard-to-wire areas flawlessly
- AC1200 Dual Band WiFi - Keep your whole home connected with strong WiFi expansion at a combined speed of up to 1.2 Gbps
- Easy One-Touch Setup - Simply press the WPS button to expand your WiFi coverage in seconds
- Signal Indicator - Multicolor LED helps you find the right location for your range extender for the best WiFi extension
- Fast 10/100 Mbps Port - Provides speedy wired connections for PCs, IPTVs, and game consoles
- Works with Any Router or Wireless Access Point

##### HARDWARE FEATURES:

Ports:1 \* 10/100M Ethernet Port (RJ45)

Plug Type: EU

Button:WPS Button, Reset Button

Power Consumption: About 9.2W

Wireless Standards:IEEE802.11ac,IEEE 802.11n, IEEE 802.11g, IEEE 802.11b

Dimensions ( W x D x H ): 112 x 84,7 x 39 mm

Antenna Type: 2 x external

##### WIRELESS FEATURES

Frequency:2.4GHz & 5GHz

Signal Rate: 5GHz Up to 867Mbps, 2.4GHz Up to 300Mbps

EIRP:< 20 dBm

Wireless Security: WPA-PSK/WPA2-PSK

##### OTHERS

Certification:CE, RoHS

Package Contents:ME30, Quick Installation Guide



#04585

Net Price:  
32.50 USD  
Unit: pcs

#### 1200Mbps Wireless Range Extender, AC1200 (TP-Link RE305)

- Brings Wi-Fi dead zone to life with strong Wi-Fi expansion at combined speed of up to 1.2Gbps
- Operates over both the 2.4GHz band(300Mbps) and 5GHz band(867Mbps) for more stable wireless experience
- Intelligent signal light helps to find the best location for optimal Wi-Fi coverage by showing the signal strength
- Works with any Wi-Fi router or wireless access point

##### HARDWARE FEATURES:

Ports:1 \* 10/100M Ethernet Port (RJ45)

Plug Type: EU

Button:WPS Button, Reset Button

Power Consumption: About 7.3W

Wireless Standards:IEEE802.11ac,IEEE 802.11n, IEEE 802.11g, IEEE 802.11b

Dimensions ( W x D x H ): 3.1x3.0x3.0 in. (80x78x77mm)

Antenna Type: 2 x external

##### WIRELESS FEATURES

Frequency:2.4GHz & 5GHz

Signal Rate: 5GHz Up to 867Mbps, 2.4GHz Up to 300Mbps

EIRP:<17dBm(2.4GHz) <17dBm(5GHz)

Reception Sensitivity:5GHz 11a 6Mbps -91dBm@10% PER, 11a 54Mbps -74dBm@10% PER, 11ac HT20 mcs8

-68dBm@10% PER, 11ac HT40 mcs9 -63dBm@10% PER, 11ac HT80 mcs9 -59dBm@10% PER, 2.4GHz 11g 54M

-79dBm@10% PER, 11n HT20 mcs7 -77dBm@10% PER, 11n HT40 mcs7 -74dBm@10% PER

NEW



#09407

Net Price:  
27.80 USD  
Unit: pcs

#### 1200Mbps Wireless Range Extender, AC1200 (TP-Link RE315)

- Eliminate weak signal areas with whole home WiFi coverage.
- 2.4 GHz (300 Mbps) and 5 GHz (867 Mbps) dual-band WiFi connection ensures more stable wireless experience.
- EasyMesh-Compatible - Flexibly creates a Mesh network by connecting to an EasyMesh-compatible router for seamless whole-home coverage
- Adaptive Path Selection - connects to the fastest connection path to the router automatically and runs at top-speed.
- AP Mode - create a new Wi-Fi access point to enhance your wired network with Wi-Fi capability.
- Smart signal indicator helps to find the best location for optimal Wi-Fi coverage by showing the signal strength.
- Push the WPS button to easily connect to the router and you can uniformly manage from the Tether app or Web UI.
- Works with any Wi-Fi router or wireless access point.

##### HARDWARE FEATURES:

Ports:1 \* 10/100M Ethernet Port (RJ45)

Plug Type: EU

Button:WPS Button, Reset Button

Power Consumption: About 9.5W

Wireless Standards:IEEE802.11ac,IEEE 802.11n, IEEE 802.11g, IEEE 802.11b

Dimensions ( W x D x H ): 3.5x1.4x4.9 in. (89x35.0x124.1 mm)

Antenna Type: 2 x external

##### WIRELESS FEATURES

Frequency:2.4GHz & 5GHz

Signal Rate: 5GHz Up to 867Mbps, 2.4GHz Up to 300Mbps

EIRP:<17dBm(2.4GHz) <17dBm(5GHz)

Reception Sensitivity:5GHz 11a 6Mbps -91dBm@10% PER, 11a 54Mbps -74dBm@10% PER, 11ac HT20 mcs8

-68dBm@10% PER, 11ac HT40 mcs9 -63dBm@10% PER, 11ac HT80 mcs9 -59dBm@10% PER, 2.4GHz 11g 54M

-79dBm@10% PER, 11n HT20 mcs7 -77dBm@10% PER, 11n HT40 mcs7 -74dBm@10% PER





#04582

Net Price:  
46.50 USD  
Unit: pcs

**1750Mbps Wireless Range Extender, AC1750 (TP-Link RE450)**

- Expand Wi-Fi Network for Ultimate Performance
- Expanded 450Mbps on 2.4GHz + 1300Mbps on 5GHz totals 1750Mbps Wi-Fi speeds
- Three adjustable external antennas provide optimal Wi-Fi coverage and reliable connections
- Gigabit Ethernet port acts as a wireless adapter to connect a wired device to your network at gigabit speed
- Intelligent signal light helps to find the best location for optimal Wi-Fi coverage by showing the signal strength
- Works with any Wi-Fi router or wireless access point

**HARDWARE FEATURES:**

Ports:1 \* 10/100/1000M Ethernet Port (RJ45)

Plug Type: EU

Button:RE (Range Extender) Button, Reset Button, LED Button, Power Button

Power Consumption: About 9W

Wireless Standards:IEEE802.11ac,IEEE 802.11n, IEEE 802.11g, IEEE 802.11b

Dimensions ( W x D x H ): 6.4x 3.0 x 2.6 in. (163 x 76.4 x 66.5mm)

Antenna Type: 3 x external

**WIRELESS FEATURES**

Frequency:2.4GHz & 5GHz

Signal Rate: 5GHz Up to 1300Mbps, 2.4GHz Up to 450Mbps

EIRP:<20dBm(2.4GHz) <23dBm(5GHz)

Reception Sensitivity:5GHz 11a 6Mbps -93dBm@10% PER,

11a 54Mbps -76dBm@10% PER, 11ac HT20 mcs8

-68dBm@10% PER, 11ac HT40 mcs9 -64dBm@10% PER,

11ac HT80 mcs9 -61dBm@10% PER, 2.4GHz 11g 54M

-77dBm@10% PER, 11n HT20 mcs7 -73dBm@10% PER,

11n HT40 mcs7 -70dBm@10% PER



#09264

Net Price:  
37.30 USD  
Unit: pcs

**1900Mbps Wireless Range Extender, AC1900 (TP-Link Mercusys ME50G)**

- Dual Band Speeds up to 1900 Mbps - 1300 Mbps on 5 GHz and 600 Mbps on 2.4 GHz.
- Gigabit Wired Connection - Provides speedy wired connections for PCS, IPTVS.and game consoles.
- 3x3 MU-MIMO - Connect more devices simultaneously.
- Works with Any Routers - To Extend WiFi to Where You Need It Most.
- Easy One-Touch Setup - Press the WPS button to expand your Wi-Fi coverage in seconds.
- Built-In Access Point Mode - Works as RE mode and AP mode.
- Manage Your Network with App - Set up in minutes and manage your Wi-Fi at home or away through your iOS or Android devices.

**HARDWARE FEATURES:**

Ports:1 \* 10/100/1000M Ethernet Port (RJ45)

Plug Type: EU

Button:WPS Button, Reset Button

Power Consumption: About 12W

Wireless Standards:IEEE802.11ac,IEEE 802.11n, IEEE 802.11g, IEEE 802.11b

Dimensions ( W x D x H ): with plug - 84.7\*76.3\*112 mm,

without plug - 84.7\*39\*112 mm

Antenna Type: 4 x external

**WIRELESS FEATURES**

Frequency:2.4GHz & 5GHz

Signal Rate: 5GHz Up to 1300Mbps, 2.4GHz Up to 600Mbps

EIRP:<20 dBm

Wireless Security: WPA-PSK/WPA2-PSK

OTHERS

Certification:CE, RoHS



#09127

Net Price:  
51.20 USD  
Unit: pcs

**1900Mbps Wireless Range Extender, AC1900 (TP-Link RE550)**

- Maximum Coverage - Extend Wi-Fi coverage by up to 1,115 m2&#65288;12,000sq. ft&#65289;.
- AC1900 Dual Band Wi-Fi - Simultaneous 600Mbps on 2.4GHz + 1300Mbps on 5GHz
- Three Antennas - Three adjustable external antennas provide optimal Wi-Fi coverage and reliable connections
- Gigabit Ethernet port - Act as a wireless adapter to connect a wired device to your network at Gigabit speed
- Intelligent Signal Light - Help to find the best location for optimal Wi-Fi coverage by showing the signal strength
- AP Mode - Create a new Wi-Fi access point to enhance your wired network with Wi-Fi capability
- TP-Link Tether App - Easily access and manage your network using any iOS or Android mobile device
- Ultimate Compatibility - Extend the range of any Wi-Fi router or wireless access point

**HARDWARE FEATURES:**

Ports:1 \* 10/100/1000M Ethernet Port (RJ45)

Plug Type: EU

Button:RE (Range Extender) Button, Reset Button, LED Button, Power Button

Power Consumption: About 10W

Wireless Standards:IEEE802.11ac,IEEE 802.11n, IEEE 802.11g, IEEE 802.11b

Dimensions ( W x D x H ): 163 x 76.4 x 66.5 mm (6.4 x 3.0 x 2.6 in)

Antenna Type: 3 x external

**WIRELESS FEATURES**

Frequency:2.4GHz & 5GHz

Signal Rate: 5GHz Up to 1300Mbps, 2.4GHz Up to 600Mbps

EIRP:<20dBm(2.4GHz) <23dBm(5GHz)

Reception Sensitivity:5GHz 11a 6Mbps -93dBm@10% PER,

11a 54Mbps -76dBm@10% PER, 11ac HT20 mcs8

-68dBm@10% PER, 11ac HT40 mcs9 -64dBm@10% PER,

11ac HT80 mcs9 -61dBm@10% PER, 2.4GHz 11g 54M

-77dBm@10% PER, 11n HT20 mcs7 -73dBm@10% PER,

11n HT40 mcs7 -70dBm@10% PER



#04690

Net Price:  
76.90 USD  
Unit: pcs

**2533Mbps Wireless Range Extender, AC2600 (TP-Link RE650)**

- Superior Extended Range - Four fixed external antennas extend Wi-Fi coverage by up to 14,000 sq. ft.
- 4-Stream for AC2600 Dual Band Wi-Fi - Simultaneous 800Mbps on 2.4GHz + 1733Mbps on 5GHz
- 4x4 MU-MIMO - Simultaneously transfers data to multiple devices for 4x faster performance
- Beamforming Technology - Send targeted Wi-Fi signal to individual devices for stronger connections
- Gigabit Ethernet Port - Provide faster wired connections to smart TVs, computers and gaming consoles
- Intelligent Signal Light - Helps to determine the best location for optimal Wi-Fi coverage by indicating the signal strength in the current placement
- AP Mode - create a new Wi-Fi access point to enhance your wired network with Wi-Fi capability
- TP-LINK Tether App - Easily access and manage your network using any iOS or Android mobile device
- Ultimate Compatibility - Extend the range of any Wi-Fi router or wireless access point

**HARDWARE FEATURES:**

Ports:1 \* 10/100/1000M Ethernet Port (RJ45)

Plug Type: EU

Button:RE (Range Extender) Button, Reset Button, LED Button, Power Button

Power Consumption: About 12W

Wireless Standards:IEEE802.11ac,IEEE 802.11n, IEEE 802.11g, IEEE 802.11b

Dimensions ( W x D x H ): 6.4x 3.4 x 1.6 in. (163 x 86 x 40mm)

Antenna Type: 4 x external

**WIRELESS FEATURES**

Frequency:2.4GHz & 5GHz

Signal Rate: 5GHz Up to 1733Mbps, 2.4GHz Up to 800Mbps

EIRP:<20dBm(2.4GHz) <23dBm(5GHz)

Reception Sensitivity:5GHz 11a 6Mbps -96dBm@10% PER,

11a 54Mbps -78dBm@10% PER, 11ac HT20 mcs8

-69dBm@10% PER, 11ac HT40 mcs9 -66dBm@10% PER,

11ac HT80 mcs9 -63dBm@10% PER, 2.4GHz 11g 54M

-79dBm@10% PER, 11n HT20 mcs7 -77dBm@10% PER,

11n HT40 mcs7 -74dBm@10% PER



#09062

Net Price:  
23.90 USD  
Unit: pcs

**750Mbps Wireless Range Extender, AC750 (TP-Link RE190)**

- Boosts wireless signal to previously unreachable or hard-to-wire areas flawlessly
- Compatible with 802.11 b/g/n and 802.11ac WiFi devices
- Dual band speeds up to 750Mbps
- Miniature size and wall-mounted design make it easy to deploy and move flexibly

**HARDWARE FEATURES:**

Plug Type: EU

Button:Reset Button, WPS Button

Power Consumption: About 7.0W

Wireless Standards:IEEE802.11ac,IEEE 802.11n, IEEE 802.11g, IEEE 802.11b

Dimensions ( W x D x H ): 110.0 x 65.8 x 38.8 mm

Antenna Type: 3 x Omni-directional Antennas

**WIRELESS FEATURES**

Frequency:2.4GHz & 5GHz

Signal Rate:11n Up to 300Mbps(dynamic), 11g Up to

54Mbps(dynamic), 11b Up to 11Mbps(dynamic)

EIRP:<20dBm (EIRP)

Reception Sensitivity:270M -70dBm@10% PER, 130M

-70dBm@10% PER, 108M -73dBm@10% PER, 54M

-75dBm@10% PER, 11M -86dBm@8% PER, 6M

-92dBm@10% PER, 1M -94dBm@8% PER, 5G, 390M

-60dBm@10% PER, 29.3M -83dBm@10% PER, 180M

-64dBm@10% PER, 13.5M -87dBm@10% PER, 78M

-68dBm@10% PER, 6.5M -90dBm@10% PER, 54M

-75dBm@10% PER, 6M -90dBm@10% PER



#08935

Net Price:  
24.20 USD  
Unit: pcs

**750Mbps Wireless Range Extender, AC750 (TP-Link RE200)**

- Boosts wireless signal to previously unreachable or hard-to-wire areas flawlessly
- Compatible with 802.11 b/g/n and 802.11ac WiFi devices
- Dual band speeds up to 750Mbps
- Miniature size and wall-mounted design make it easy to deploy and move flexibly
- Ethernet port allows the Extender to function as a wireless adapter to connect wired devices

**HARDWARE FEATURES:**

Ports:1 \* 10/100M Ethernet Port (RJ45)

Plug Type: EU

Button:Reset Button, Range Extender Button

Power Consumption: About 6.5W

Wireless Standards:IEEE802.11ac,IEEE 802.11n, IEEE 802.11g, IEEE 802.11b

Dimensions ( W x D x H ): 4.3x 2.6 x 3.0in. (110.0 x 65.8 x 75.2mm)

Antenna Type: 3 x internal

**WIRELESS FEATURES**

Frequency:2.4GHz & 5GHz

Signal Rate:11n Up to 300Mbps(dynamic), 11g Up to

54Mbps(dynamic), 11b Up to 11Mbps(dynamic)

EIRP:<20dBm (EIRP)

Reception Sensitivity:270M -70dBm@10% PER, 130M

-70dBm@10% PER, 108M -73dBm@10% PER, 54M

-75dBm@10% PER, 11M -86dBm@8% PER, 6M

-92dBm@10% PER, 1M -94dBm@8% PER, 5G, 390M

-60dBm@10% PER, 29.3M -83dBm@10% PER, 180M

-64dBm@10% PER, 13.5M -87dBm@10% PER, 78M

-68dBm@10% PER, 6.5M -90dBm@10% PER, 54M

-75dBm@10% PER, 6M -90dBm@10% PER





#09173

Net Price:  
25.50 USD  
Unit: pcs

#### 750Mbps Wireless Range Extender, AC750 (TP-Link RE205)

- Brings Wi-Fi dead zone to life with strong Wi-Fi expansion at combined speed of up to 750Mbps
- Operates over both the 2.4GHz band(300Mbps) and 5GHz band(433Mbps) for more stable wireless experience
- Intelligent signal light helps to find the best location for optimal Wi-Fi coverage by showing the signal strength
- Works with any Wi-Fi router or wireless access point

##### HARDWARE FEATURES:

Ports: 1 \* 10/100M Ethernet Port (RJ45)

Plug Type: EU

Button: Reset Button, WPS Button

Power Consumption: About 7.3W

Wireless Standards: IEEE 802.11ac, IEEE 802.11n, IEEE 802.11g, IEEE 802.11b, IEEE 802.11a

Dimensions (W x D x H): 3.1 x 3.0 x 3.0 in. (80.0 x 78 x 77 mm)

Antenna Type: 2 x external

##### WIRELESS FEATURES

Frequency: 2.4GHz & 5GHz

Signal Rate: 11n Up to 300Mbps(dynamic), 11g Up to 54Mbps(dynamic), 11b Up to 11Mbps(dynamic)

EIRP: <20dBm (EIRP)

Reception Sensitivity: 5GHz - 11a 6 Mb/s -94 dBm@10% PER, 11a 54 Mb/s -77 dBm@10% PER, 11ac HT20 -69 dBm@10% PER, 11ac HT40 -66 dBm@10% PER, 11ac HT80 -63 dBm@10% PER, 2.4 GHz - 11g 54 Mb/s -79 dBm@10% PER, 11n HT20 -77 dBm@10% PER, 11n HT40 -74 dBm@10% PER



#09048

Net Price:  
32.70 USD  
Unit: pcs

#### Router Mesh Deco E4 1-pack, AC1200 (TP-Link DECO E4(1-Pack))

- Deco uses a system of units to achieve seamless whole-home Wi-Fi coverage - eliminate weak signal areas once and for all!
- With advanced Deco Mesh Technology, units work together to form a unified network with a single network name. Devices automatically switch between - Decos as you move through your home for the fastest possible speeds.
- A Deco E4 three-pack delivers Wi-Fi to an area of up to 4,000 square feet (EU version). And if that's not enough, simply add more Decos to the network anytime to increase coverage.
- Deco E4 provides fast and stable connections with speeds of up to 1167 Mbps and works with the major internet service provider (ISP) and modem.
- Deco can handle traffic from even the busiest of networks, providing lag-free connections for up to 100 devices.
- Parental Controls limits online time and block inappropriate websites according to unique profiles created for each family member.
- Setup is easier than ever with the Deco app there to walk you through every step.

Standards: IEEE 802.11 ac/n/a 5 GHz, IEEE 802.11 b/g/n 2.4 GHz

Ports: 2 ports 10/100 Mb/s, 2 ports WAN/LAN, 1 Power Port

Button: 1 Reset button

Flash: 16 MB

SDRAM: 128 MB

Frequency range: 2.4 GHz and 5 GHz

Signal Rate: 300 Mbps on 2.4 GHz, 867 Mbps on 5 GHz

EIRP: FCC <30 dBm, CE <20 dBm (2.4 GHz) <23 dBm (5 GHz)

Advanced Functions: TP-Link Mesh Technology - MU-MIMO, Auto Path Selection, AP Steering, Band Steering, Beamforming

Wireless Security: WPA-PSK/WPA2-PSK

Software Features: Quality of Service - WMM, IPv6 Support, WAN Type - Dynamic IP/Static IP/PPPoE, Local Management, Remote Management, DHCP - Server, Client, Port Forwarding Support, Access Control Blacklist, Firewall Security SPI Firewall, Protocols Supports IPv4 and IPv6, Homecare - Antivirus, Parental Controls, Quality of Service, Speedtest, Monthly Usage Reports, Auto FW Update, Expand for more deco, Guest Network 2.4 GHz guest network \* 1 - 5 GHz guest network \* 1, Beamformig, Easy setup by Deco App



#09049

Net Price:  
93.30 USD  
Unit: pcs

#### Router Mesh Deco E4 3-pack, AC1200 (TP-Link DECO E4(3-Pack))

- Deco uses a system of units to achieve seamless whole-home Wi-Fi coverage - eliminate weak signal areas once and for all!
- With advanced Deco Mesh Technology, units work together to form a unified network with a single network name. Devices automatically switch between - Decos as you move through your home for the fastest possible speeds.
- A Deco E4 three-pack delivers Wi-Fi to an area of up to 4,000 square feet (EU version). And if that's not enough, simply add more Decos to the network anytime to increase coverage.
- Deco E4 provides fast and stable connections with speeds of up to 1167 Mbps and works with the major internet service provider (ISP) and modem.
- Deco can handle traffic from even the busiest of networks, providing lag-free connections for up to 100 devices.
- Parental Controls limits online time and block inappropriate websites according to unique profiles created for each family member.
- Setup is easier than ever with the Deco app there to walk you through every step.

Standards: IEEE 802.11 ac/n/a 5 GHz, IEEE 802.11 b/g/n 2.4 GHz

Ports: 2 ports 10/100 Mb/s, 2 ports WAN/LAN, 1 Power Port

Button: 1 Reset button

Flash: 16 MB

SDRAM: 128 MB

Frequency range: 2.4 GHz and 5 GHz

Signal Rate: 300 Mbps on 2.4 GHz, 867 Mbps on 5 GHz

EIRP: FCC <30 dBm, CE <20 dBm (2.4 GHz) <23 dBm (5 GHz)

Advanced Functions: TP-Link Mesh Technology - MU-MIMO, Auto Path Selection, AP Steering, Band Steering, Beamforming

Wireless Security: WPA-PSK/WPA2-PSK

Software Features: Quality of Service - WMM, IPv6 Support, WAN Type - Dynamic IP/Static IP/PPPoE, Local Management, Remote Management, DHCP - Server, Client, Port Forwarding Support, Access Control Blacklist, Firewall Security SPI Firewall, Protocols Supports IPv4 and IPv6, Homecare - Antivirus, Parental Controls, Quality of Service, Speedtest, Monthly Usage Reports, Auto FW Update, Expand for more deco, Guest Network 2.4 GHz guest network \* 1 - 5 GHz guest network \* 1, Beamformig, Easy setup by Deco App



#09051

Net Price:  
135.00 USD  
Unit: pcs

#### Router Mesh Deco M5 2-pack (TP-Link DECO M5(2-Pack))

- Covers up to 5,500 sq. ft.
- Fast dual band WiFi
- One WiFi name for the entire home
- Connects 100-plus devices
- Works with Amazon Alexa Voice Assistant

Standards: IEEE 802.11 ac/n/a 5 GHz, IEEE 802.11 b/g/n 2.4 GHz

Ports: 2 LAN/WAN Gigabit Ethernet Ports

Processor: Quad-core CPU

Button: 1 Reset button on the underside

Flash: 32 MB

SDRAM: 256 MB

Bluetooth version: 4.2 and above

Frequency range: 2.4 GHz and 5 GHz

Signal Rate: 400 Mbps on 2.4 GHz, 867 Mbps on 5 GHz

EIRP: FCC <30 dBm, CE <20 dBm (2.4 GHz) <23 dBm (5 GHz)

Advanced Functions: TP-Link Mesh Technology - MU-MIMO, Auto Path Selection, AP Steering, Band Steering, Beamforming

Wireless Security: WPA-PSK/WPA2-PSK



#09052

Net Price:  
114.00 USD  
Unit: pcs

#### Router Mesh Deco S4 3-pack, AC1200 (TP-Link DECO S4(3-Pack))

- Deco uses a system of units to achieve seamless whole-home Wi-Fi coverage - eliminate weak signal areas once and for all!
- With advanced Deco Mesh Technology, units work together to form a unified network with a single network name. Devices automatically switch between Decos as you move through your home for the fastest possible speeds.
- A Deco S4 three-pack delivers Wi-Fi to an area of up to 4,000 sq.ft. (EU version)&#8224;. And if that's not enough, simply add more Decos to the network anytime to increase coverage.
- Deco S4 provides fast and stable connections with speeds of up to 1167 Mbps&#8224; and works with major internet service provider (ISP) and modem.
- Deco can handle traffic from even the busiest of networks, providing lag-free connections for up to 100 devices&#8224;.
- Parental Controls limits online time and block inappropriate websites according to unique profiles created for each family member.
- Setup is easier than ever with the Deco app there to walk you through every step.

Standards: IEEE 802.11 ac/n/a 5 GHz, IEEE 802.11 b/g/n 2.4 GHz

Processor: Qualcomm CPU

Ports: 2 ports 10/100/1000 Mb/s WAN/LAN

Button: 1 Reset button

Flash: 16 MB

SDRAM: 128 MB

Frequency range: 2.4 GHz and 5 GHz

Signal Rate: 300 Mbps on 2.4 GHz, 867 Mbps on 5 GHz

EIRP: FCC <30 dBm, CE <20 dBm (2.4 GHz) <23 dBm (5 GHz)

Advanced Functions: Router/ Access Point Mode, Optional Ethernet Backhaul, Guest network, TP-Link Mesh Technology MU-MIMO, Auto Path Selection, Self-Healing, AP Steering, Band Steering, Beamforming



<p>Standard N</p>  <p><b>#09316</b> Net Price: 31.10 USD Unit: pcs</p> <p><b>300Mbps Outdoor Wireless Access Point, N300 (TP-Link EAP113-Outdoor)</b></p> <ul style="list-style-type: none"><li>- Ideal for Outdoor Environment: IP65 weatherproof enclosure for outdoor Wi-Fi applications.</li><li>- Fast Wi-Fi: Up to 300Mbps Wi-Fi with 2x2 MIMO.</li><li>- Long-Range Coverage: Dedicated high-power amplifier and professional antennas.</li><li>- Integrated into Omada SDN: Centralized Cloud Management and Intelligent Monitoring.</li><li>- Centralized Management: Cloud access and Omada app for ultra convenience and easy management.</li><li>- PoE Support: Support both standard 802.3af and 48V Passive PoE for flexible installations.</li><li>- Secure Guest Network: Along with multiple authentication options (SMS/Voucher, etc.) and abundant wireless security technologies.</li></ul> <p>Standards: IEEE 802.11n, IEEE 802.11g, IEEE 802.11b Ports: Fast Ethernet (RJ-45) Port *1&amp;#65288;Support Passive PoE&amp;#65289; Frequency range: 2.4GHz Wireless Functions: Multiple SSIDs (Up to 8 SSIDs), Enable/Disable Wireless Radio, Automatic Channel Assignment, Transmit Power Control (Adjust Transmit Power on dBm), QoS(WMM), Load Balance, Wireless Schedule, Wireless Statistics based on SSID/AP/Client Wireless Security: Captive Portal Authentication, Wireless Mac Address Filtering, Wireless Isolation Between Clients, SSID to VLAN Mapping, Rogue AP Detection, 802.1X Support, 64/128/152-bit WEP / WPA / WPA2-Enterprise,WPA-PSK / WPA2-PSK</p>	 <p><b>#08563</b> Net Price: 22.50 USD Unit: pcs</p> <p><b>3G Mobile Hotspot Wi-Fi (TP-Link M5350)</b></p> <ul style="list-style-type: none"><li>- Equipped with a built-in 3G modem - No additional bulky devices required</li><li>- HSPA+ supported with up to 21.6Mbps download and 5.76Mbps upload speeds</li><li>- Powerful 2000mAh battery is ideal for extended hours of outdoor use</li><li>- Supports up to 10 users simultaneously</li></ul> <p><b>HARDWARE FEATURES</b> Interface: 1 micro USB port for power supply, SIM Card Slot, Micro SD card Slot Button: Power On/Off Button, Reset Button OLED Display: Singal strength, Network type, Wi-Fi status, Message, Internet connection status, Battery meter, connection mode and Traffic Statistics Wireless Standards: IEEE 802.11b, IEEE 802.11g, IEEE 802.11n Network Type: HSPA+/HSPA/UMTS/EDGE/GRPS/GSM Data Rates: DL- 21.6Mbps, UL- 5.76Mbps Antenna: Internal Antenna Power Supply: Internal 2000mAh Rechargeable Battery, 5VDC/1.0A</p>	 <p><b>#09101</b> Net Price: 48.90 USD Unit: pcs</p> <p><b>LTE Mobile Hotspot Wi-Fi (TP-Link M7000)</b></p> <ul style="list-style-type: none"><li>- Share with friends internet access for up to 10 devices simultaneously</li><li>- 2000mAh battery for 8 hours of usage</li><li>- Supports the latest generation 4G FDD/TDD-LTE, compatible with the network of most countries and regions</li><li>- Easy management with the tpMiFi App</li></ul> <p><b>HARDWARE FEATURES</b> Interface: 1 micro USB port for power supply, SIM Card Slot Button: Power On/Off Button, Reset Display: Wi-Fi status, Internet connection status, Battery status Wireless Standards: IEEE 802.11b, IEEE 802.11g, IEEE 802.11n Network Type: 4G FDD-LTE B1/B3/B7/B8/B20 (2100/1800/2600/900/800MHz), TDD-LTE B38/B40/B41 (2600/2300/2500MHz), 3G DC-HSPA+/HSPA+/HSPA/UMTS B1/B8 (2100/850/900MHz) Data Rates: DL- up to 150Mbps, UL- up to 50Mbps Antenna: Internal Antenna Power Supply: Internal 2000mAh Rechargeable Battery</p>
 <p><b>#06243</b> Net Price: 54.00 USD Unit: pcs</p> <p><b>LTE Mobile Hotspot Wi-Fi (TP-Link M7200)</b></p> <ul style="list-style-type: none"><li>- Share with friends internet access for up to 10 devices simultaneously</li><li>- 2000mAh battery for 8 hours of usage</li><li>- Supports the latest generation 4G FDD/TDD-LTE, compatible with the network of most countries and regions</li><li>- Easy management with the tpMiFi App</li></ul> <p><b>HARDWARE FEATURES</b> Interface: 1 micro USB port for power supply, SIM Card Slot Button: Power On/Off Button Display: Wi-Fi status, Internet connection status, Battery status Wireless Standards: IEEE 802.11b, IEEE 802.11g, IEEE 802.11n Network Type: 4G FDD-LTE B1/B3/B7/B8/B20 (2100/1800/2600/900/800MHz), TDD-LTE B38/B40/B41 (2600/2300/2500MHz), 3G DC-HSPA+/HSPA+/HSPA/UMTS B1/B8 (2100/900MHz) Data Rates: DL- up to 150Mbps, UL- up to 50Mbps Antenna: Internal Antenna Power Supply: Internal 2000mAh Rechargeable Battery</p>	 <p><b>#08942</b> Net Price: 67.60 USD Unit: pcs</p> <p><b>LTE Mobile Hotspot Wi-Fi (TP-Link M7350)</b></p> <ul style="list-style-type: none"><li>- 4G LTE supported with up to 150Mbps download and 50Mbps upload speeds</li><li>- Supports up to 15 devices simultaneously</li><li>- All useful information at a glance with screen display</li><li>- 2550mAh battery for up to 10 hours of working</li><li>- Selectable 2.4GHz or 5GHz dual band WiFi</li><li>- Equipped with a micro SD card slot for up to 32GB of optional storage</li></ul> <p><b>HARDWARE FEATURES</b> Interface: 1 micro USB port for power supply, SIM Card Slot, Micro SD card Slot Button: Power On/Off Button, Menu Button OLED Display: Traffic statistics, Wi-Fi status, user numbers, network type (2G/3G/4G), signal strength, Internet connection status, messages, battery meter Wireless Standards: IEEE 802.11a, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n Network Type: FDD-LTE Cat4 (800/900/1800/2100/2600MHz), DC-HSPA+/HSPA/UMTS (900/2100MHz), EDGE/GPRS/GSM (850/900/1800/1900MHz)</p>	 <p><b>#09524</b> Net Price: 32.90 USD Unit: pcs</p> <p><b>LTE Mobile Hotspot Wi-Fi (TP-Link Marcusys MT110)</b></p> <ul style="list-style-type: none"><li>- More Connections: Share with friends internet access for up to 10 devices simultaneously</li><li>- Long usage: 2200 mAh battery for 10 hours</li><li>- 4G Network: Supports the latest generation 4G FDD/TDD-LTE, compatible with the network of most countries and regions, and enjoy download speeds of up to 150 Mbps</li><li>- 150 Mbps WiFi: Fast WiFi speeds up to 150 Mbps to share your network</li><li>- SIM Card Plug and Play: Go anywhere and connect everywhere easily</li><li>- Easy App Control: Management with the MERCUSYS App</li></ul> <p><b>HARDWARE FEATURES:</b> Standards and Protocols:802.11a/b/g/n Interface: 1 micro USB port for power supply, 1 Nano SIM card slot Button:WPS/Reset Button External Power Supply: 5V/1A Antenna Type: Internal Antennas Data Rates: 4G LTE Speed DL 150 Mbps, UL 50 Mbps, WiFi Speed 150 Mbps on 2.4 GHz LED: Wi-Fi LED, Internet LED, Battery LED Dimensions (W X D X H): 111 x 70 x 23.8 mm <b>WIRELESS FEATURES:</b> Frequency:2.4GHz Wireless Functions:Enable/Disable Wireless Radio, Wireless Schedule, WMM, Wireless, Statistics</p>



#04687

Net Price:  
168.00 USD  
Unit: pcs

### LTE Mobile Hotspot Wi-Fi, 600Mbps (TP-Link M7650)

- LTE-Advanced cat11 supported with up to 600Mbps download and 50Mbps upload speeds
- Supports up to 32 devices simultaneously
- Selectable 300Mbps at 2.4GHz or 867Mbps at 5GHz dual band Wi-Fi
- All useful information at a glance with screen display
- 3000mAh battery for up to 15 hours of working
- Equipped with a micro SD card slot for up to 32GB of optional storage
- Easy management with the tpMiFi App

#### HARDWARE FEATURES

Interface: 1 micro USB port for power supply, SIM Card Slot, Micro SD card Slot  
Button: Power On/Off Button, Reset Button  
OLED Display: Traffic statistics, Wi-Fi status, user numbers, network type (2G/3G/4G), signal strength, Internet connection status, messages, battery meter  
Wireless Standards: IEEE 802.11a/b/g/n/ac 300Mbps at 2.4GHz or 867Mbps at 5GHz  
Network Type: FDD-LTE- B1/B3/B7/B8/B20(2100/1800/2600/900/800MHz), TDD-LTE- B38/B40/B41 (2600/2300/2500MHz), DC-HSPA+/HSPA/UMTS- B1/B8(2100/900MHz), EDGE/GPRS/GSM- 850/900/1800/1900MHz



#06242

Net Price:  
98.00 USD  
Unit: pcs

### LTE-Advanced Mobile Hotspot Wi-Fi (TP-Link M7450)

- LTE-Advanced cat6 supported with up to 300Mbps download and 50Mbps upload speeds
- Supports up to 32 devices simultaneously
- Selectable 300Mbps at 2.4GHz or 867Mbps at 5GHz dual band Wi-Fi
- All useful information at a glance with screen display
- 3000mAh battery for up to 15 hours of working
- Equipped with a micro SD card slot for up to 32GB of optional storage
- Easy management with the tpMiFi App

#### HARDWARE FEATURES

Interface: 1 micro USB port for power supply, SIM Card Slot, Micro SD card Slot  
Button: Power On/Off Button, Menu Button  
Display: 1.44", TFT  
Wireless Standards: IEEE 802.11a/b/g/n/ac 300Mbps at 2.4GHz or 867Mbps at 5GHz  
Network Type: FDD-LTE B1/B3/B7/B8/B20(2100/1800/2600/900/800MHz), TDD-LTE B38/B40/B41 (2600/2300/2500MHz), DC-HSPA+/HSPA/UMTS B1/B8(2100/900MHz), EDGE/GPRS/GSM 850/900/1800/1900MHz  
Data Rates: DL- 300Mbps, UL- 50Mbps  
Antenna: Internal Antenna  
Power Supply: Internal 3000mAh Rechargeable Battery



#09011

Net Price:  
43.80 USD  
Unit: pcs

### 150Mbps Wireless access point, 5GHz, PoE (TP-Link CPE605)

- Up to 150Mbps on 5GHz wireless data rates
- 23dBi high-gain directional antenna and a dedicated metal reflector, ideal for long-distance application
- Excellent beam directivity, improved latency and noise cancellation
- Innovative snap-lock parts make for fast assembly and a sturdy structural design keeps CPE605 stable even in strong winds
- Durable IP65 weatherproof enclosure along with 15 kV ESD and 6 kV lightning protection ensures all-weather suitability
- TP-Link Pharos MAXstream TDMA technology improves throughput, capacity and latency performance
- Pharos Control gives administrators a free, centralized management system
- Passive PoE supports to allow flexible deployment and convenient installation

Processor: Qualcomm 560MHz CPU, MIPS 74Kc  
Memory: 64MB DDR2 RAM, 8MB Flash  
Standards: IEEE 802.11a, IEEE 802.11n  
Ports: 1 10/100Mbps Shielded Ethernet Port (LAN0,Passive PoE in), 1 Reset Button  
Antenna Gain: 23dBi  
Antenna Beamwidth: 7°(Azimuth), 10°(Elevation)  
Wireless Configurations: Pharos MAXstream TDMA Technology, 802.11a/n Modes, Selectable Channel Width 5/10/20/40MHz, Automatic Channel Selection, Transmission Power Control, Dynamic Frequency Selection (DFS), WDS Enable/Disable, SSID Broadcast Enable/Disable, Multi-SSID with VLAN Tagging (AP mode only), Distance/ACK Timeout Setting, Wireless MAC Address Filter, Long Range PTP



#04680

Net Price:  
39.30 USD  
Unit: pcs

### 300Mbps Outdoor Wireless Access Point, N300 (TP-Link EAP110-Outdoor)

- Built for outdoor Wi-Fi applications
- Up to 300Mbps Wi-Fi with 2x2 MIMO technology
- High transmission power and high gain antennas provide a long-range coverage area
- Durable, weatherproof enclosure to withstand fair and foul weather
- Passive PoE(Power over Ethernet) support and simple mounting design allow for flexible deployment and convenient installation
- Free Auranet Controller Software lets administrators easily manage hundreds of EAPs
- Captive portal provides a convenient method for guest authentication

Standards: IEEE 802.11n, IEEE 802.11g, IEEE 802.11b  
Ports: Fast Ethernet (RJ-45) Port \*1&#65288;Support Passive PoE&#65289;  
Frequency range: 2.4GHz  
Wireless Functions: Multiple SSIDs (Up to 8 SSIDs), Enable/Disable Wireless Radio, Automatic Channel Assignment, Transmit Power Control (Adjust Transmit Power on dBm), QoS(WMM), Load Balance, Wireless Schedule, Wireless Statistics based on SSID/AP/Client  
Wireless Security: Captive Portal Authentication, Wireless Mac Address Filtering, Wireless Isolation Between Clients, SSID to VLAN Mapping, Rogue AP Detection, 802.1X Support, 64/128/152-bit WEP / WPA / WPA2-Enterprise,WPA-PSK / WPA2-PSK



#04679

Net Price:  
23.60 USD  
Unit: pcs

### 300Mbps Outdoor Wireless Access Point, N300 (TP-Link EAP115-Wall)

- Easy-mount construction allows installation into any standard EU-type data wall-box
- Compact, low-profile design fits discreetly with any existing interior style
- Free Auranet Controller Software enables administrators to easily manage hundreds of EAPs
- Support Power over Ethernet (802.3af) for convenient and affordable installation
- Enterprise class Wi-Fi security helps to decrease network security threats
- Captive portal provides one convenient method of authentication for Wi-Fi guests
- Supports management vlan for an enhanced network management

Standards: IEEE 802.11n, IEEE 802.11g, IEEE 802.11b  
Ports: Fast Ethernet (RJ-45) Port \*2  
Frequency range: 2.4GHz  
Wireless Functions: Multiple SSIDs (Up to 8 SSIDs), Enable/Disable Wireless Radio, Automatic Channel Assignment, Transmit Power Control (Adjust Transmit Power on dBm), QoS(WMM), Load Balance, Wireless Schedule, Wireless Statistics based on SSID/AP/Client  
Wireless Security: Captive Portal Authentication, Wireless Mac Address Filtering, Wireless Isolation Between Clients, SSID to VLAN Mapping, Rogue AP Detection, 802.1X Support, 64/128/152-bit WEP / WPA / WPA2-Enterprise,WPA-PSK / WPA2-PSK



#08941

Net Price:  
35.40 USD  
Unit: pcs

### 300Mbps Wireless access point, 2.4GHz (TP-LINK CPE210)

- Processor: Qualcomm Atheros 560MHz CPU, MIPS 74Kc
- Memory: 64MB DDR2 RAM, 8MB Flash
- Standards: IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
- Ports: 1 10/100Mbps Shielded Ethernet Port (LAN0,Passive PoE in), 1 10/100Mbps Shielded Ethernet Port (LAN1, Passive PoE
- Passthrough), 1 Grounding Terminal, 1 Reset Button
- Wireless Configurations: Pharos MAXstream TDMA Technology, 802.11b/g/n Modes, Selectable Channel Width 5/10/20/40MHz, Automatic Channel Selection, Transmission Power Control, Dynamic Frequency Selection (DFS), WDS Enable/Disable, SSID Broadcast Enable/Disable, Multi-SSID with VLAN Tagging (AP mode only), Distance/ACK Timeout Setting, Wireless MAC Address Filter



#08940

Net Price:  
48.30 USD  
Unit: pcs

**300Mbps Wireless access point, 5GHz (TP-LINK CPE510)**

Processor: Qualcomm Atheros Enterprise AR9350B 560MHz CPU, MIPS 74Kc  
Memory: 64MB DDR2 RAM, 8MB Flash  
Standards: IEEE 802.11a, IEEE 802.11n  
Ports: 1 10/100Mbps Shielded Ethernet Port (LAN0, Passive PoE in), 1 10/100Mbps Shielded Ethernet Port (LAN1, Passive PoE Passthrough), 1 Grounding Terminal, 1 Reset Button  
Wireless Configurations: Pharos MAXstream TDMA Technology, 802.11a/n Modes, Selectable Channel Width 5/10/20/40MHz, Automatic Channel Selection, Transmission Power Control, Dynamic Frequency Selection (DFS), WDS Enable/Disable, SSID Broadcast Enable/Disable, Multi-SSID with VLAN Tagging (AP mode only), Distance/ACK Timeout Setting, Wireless MAC Address Filter



#04661

Net Price:  
26.70 USD  
Unit: pcs

**300Mbps Wireless Access Point, N (TP-Link EAP110)**

- EAP Controller Software enables administrators to easily manage hundreds of EAPs
- Supports passive PoE for convenient installation up to 100meters
- Ceiling mounting design with chassis make it easy to deploy on a wall or ceiling
- Captive portal provides one convenient method of authentication for Wi-Fi guests
- Multi-SSID divides multiple wireless networks for different users
- Enterprise class Wi-Fi security help to decrease network security threats

Standards: IEEE 802.11n/g/b  
Ports: Fast Ethernet (RJ-45) Port \*1 (Support Passive PoE)  
Frequency range: 2.4-2.4835GHz  
Signal Rate: 11n Up to 300Mbps(dynamic), 11g Up to 54Mbps(dynamic), 11b Up to 11Mbps(dynamic)  
EIRP: FCC <26dBm(2.4GHz), CE <20dBm  
Wireless Functions: Multiple SSIDs (Up to 16 SSIDs, 8 for each band), Enable/Disable Wireless Radio, Automatic Channel Assignment, Transmit Power Control (Adjust Transmit Power on dBm), QoS(WMM), Airtime Fairness, Beamforming, Band Steering, Load Balance, Rate Limit, Link Aggregation, Reboot Schedule, Wireless Schedule, Wireless Statistics based on SSID/AP/Client



#04660

Net Price:  
28.10 USD  
Unit: pcs

**300Mbps Wireless Access Point, N (TP-Link EAP115)**

- Free Auranet Controller Software enables administrators to easily manage hundreds of EAPs
- The user-friendly Cluster Mode allows manage up to 24 (EAP115) without requiring any extra hardware or software
- Supports Power over Ethernet (802.3af) for convenient and affordable installation
- Simple mounting design for easy attachment to a wall or ceiling
- Captive portal provides one convenient method of authentication for Wi-Fi guests
- Enterprise class Wi-Fi security help to decrease network security threats
- Multi-SSID divides multiple wireless networks for different user types

Standards: IEEE 802.11n/g/b  
Ports: Fast Ethernet (RJ-45) Port \*1 (ETH1 Support IEEE802.3af PoE)  
Frequency range: 2.4-2.4835GHz  
Signal Rate: 11n Up to 300Mbps(dynamic), 11g Up to 54Mbps(dynamic), 11b Up to 11Mbps(dynamic)  
EIRP: FCC <26dBm(2.4GHz), CE <20dBm  
Wireless Functions: Multiple SSIDs (Up to 16 SSIDs, 8 for each band), Enable/Disable Wireless Radio, Automatic Channel Assignment, Transmit Power Control (Adjust Transmit Power on dBm), QoS(WMM), Airtime Fairness, Beamforming, Band Steering, Load Balance, Rate Limit, Link Aggregation, Reboot Schedule, Wireless Schedule, Wireless Statistics based on SSID/AP/Client



#08843

Net Price:  
82.80 USD  
Unit: pcs

**Wireless access point Ubiquiti NanoBeam M2 MIMO (Ubiquiti NBE-M2-13)**

Standards: IEEE 802.11n  
Ports: 1x 10/100 Mbps RJ-45  
Chipset: Atheros MIPS 74Kc, 560 MHz  
Operating memory: 64 MB DDR2  
Flash memory: 8 MB  
Antenna: build-in, 18 dBi  
VSWR: 1.5  
Diameter: 189mm  
Weight: 1.795 kg  
Mounting: mast or wall with the aid of antenna wall support  
Max. power consumption: 6 W  
Power: PoE 24V  
Operating temperatures: -40°C + 70°C  
Operating humidity: 5% + 95%, Non-condensing



#08141

Net Price:  
46.00 USD  
Unit: pcs

**Wireless access point Ubiquiti NanoStation Loco M2 (Ubiquiti Locom2)**

Standards: IEEE 802.11b/g/n, IEEE 802.3u  
Ports: 1x 10/100 Mbps RJ-45  
Operating modes: Access Point, Bridge, Client, WDS  
Chipset: Atheros MIPS 24Kc, 400MHz  
Operating memory: 32MB SDRAM  
Flash memory: 8MB  
Frequency range: 2400 MHz + 2483.5 MHz  
Max. output power: 20 dBm  
Antenna: build-in, 8 dBi, detachable RSMA  
Dimensions: 163x80x31 mm  
Weight: 0.18 kg  
Mounting: mast or wall with the aid of antenna wall support  
Max. power consumption: 5.5 W  
Power: PoE 24V  
Operating temperatures: -30°C + 80°C



#08928

Net Price:  
82.80 USD  
Unit: pcs

**Wireless access point Ubiquiti NanoStation M2 (Ubiquiti NSM2)**

Standards: IEEE 802.11b/g/n, IEEE 802.3u  
Ports: 2x 10/100 Mbps RJ-45  
Operating modes: Access Point, Bridge, Client, WDS  
Chipset: Atheros MIPS 24Kc, 400MHz  
Operating memory: 32MB SDRAM  
Flash memory: 8MB  
Frequency range: 2400 MHz + 2483.5 MHz  
Gain: 10.4-11.2 dBi  
Max. output power: 23 dBm  
Dimensions: 294 x 31 x 80 mm (11.57 x 1.22 x 3.15")  
Weight: 400 g  
Mounting: mast or wall with the aid of antenna wall support  
Max. power consumption: 5.5 W  
Power: PoE 24V, 0.5A  
Operating temperatures: -30°C + 75°C





#08394

Net Price:  
210.00 USD  
Unit: pcs

## Wireless Access Point UniFi UAP PRO (Ubiquiti UAP-PRO)

The UniFi Enterprise Wi-Fi System is a scalable enterprise access point solution designed to be easily deployed and managed. UniFi Access Point (AP) indoor models have a sleek design and can be easily mounted to a ceiling tile or wall using the included mounting hardware. UniFi AP (UAP) outdoor models have a form factor built to last outdoors.

The UniFi Enterprise Wi-Fi System includes the UniFi Controller software. The software installs on any PC, Mac, or Linux machine within the network and is easily accessible through any standard web browser. Using the UniFi Controller software, an Enterprise Wi-Fi network can be quickly configured and administered without any special training. Real-time status, automatic UAP device detection, map loading, and advanced security options are all seamlessly integrated.

Networking Interface (Mbps): 2 x 10/100/1000 Ethernet Ports  
Buttons: Reset  
Antennas: 2.4 GHz - 3 Integrated (Supports 3x3 MIMO with Spatial Diversity), 5 GHz - 2 Integrated (Supports 2x2 MIMO with Spatial Diversity)  
Wi-Fi Standards: 802.11 a/b/g/n  
Power Method: Passive Power over Ethernet (48V), 802.3af Supported  
Power Supply: 48V, 0.5A PoE Adapter (Included)  
Maximum Power Consumption: 12 W  
Maximum TX Power: 2.4 GHz - 30 dBm, 5 GHz - 22 dBm  
BSSID: Up to Four Per Radio  
Dimensions: 200 x 200 x 36.5 mm



#09118

Net Price:  
6.38 USD  
Unit: pcs

## Mini Wireless adapter N USB 2.0, 300Mbps (TP-Link Mercusys MW300UM)

- Provides fast 300Mbps Wi-Fi connections for wired devices
- Ideal for online gaming, HD streaming, web browsing, and more
- Supports Windows 10/8.1/8/7/XP (32/64bit)

Standards: IEEE 802.11 b/g, IEEE 802.11n  
Interface: USB 2.0 typ A  
Frequency range: 2400 MHz + 2483,5 MHz  
Max. speed: 300 Mbps when connected to 11n device  
Max. output power: 20 dBm  
WLAN security: WEP, WPA/WPA2, WPA-PSK/WPA2-PSK  
Drivers: Windows 10/8.1/8/7/XP (32/64bit)  
Dimensions: 42.9 x 17.2 x 8.5 mm  
Operating temperatures: 0°C + 40°C  
Operating humidity: 10% + 90%, non-condensing  
Manufacturer: TP-Link



#08549

Net Price:  
7.58 USD  
Unit: pcs

## Mini Wireless adapter N USB 2.0, 300Mbps (TP-Link TL-WN823N)

- 300Mbps wireless speed ideal for smooth HD video, voice streaming and online gaming
- Mini-sized design for convenient portability with a reliable high performance
- SoftAP Mode - Turn a wired internet connection to a PC or Laptop into a Wi-Fi hotspot
- Easily setup a secure wireless connection with one-touch WPS button

Standards: IEEE 802.11 b/g, IEEE 802.11n  
Interface: USB 2.0 typ A  
Frequency range: 2400 MHz + 2483,5 MHz  
Max. speed: 300 Mbps when connected to 11n device  
Max. output power: 20 dBm  
Modulation type: DBPSK, DQPSK, CCK, OFDM, 16-QAM, 64-QAM  
Operating modes: Soft AP Mode, Client Mode (support Ad-hoc/Infrastructure network)  
WLAN security: 64/128 bits WEP, WPA/WPA2, WPA-PSK/WPA2-PSK (TKIP/AES)  
Roaming support: yes  
WLAN features: MIMO, CCA  
Drivers: Windows Windows XP/Vista/7  
Dimmensions: 39 x 18.35 x 7.87mm



#09117

Net Price:  
8.59 USD  
Unit: pcs

## Wireless adapter Lite N USB 2.0 High Gain (TP-Link Mercusys MW300UH)

- Provides fast 300Mbps Wi-Fi connections for wired devices
- Two 5dBi high gain antennas deliver enhanced reception and transmission performance
- With 2x2 MIMO, users can easily access to high-speed wireless connection
- Supports Windows 10/8.1/8/7/XP (32/64bit)

Standards: IEEE 802.11 b/g, IEEE 802.11n  
Interface: micro USB 2.0  
Frequency range: 2400 MHz + 2483,5 MHz  
Max. speed: 300 Mbps when connected to 11n device  
Max. output power: 20 dBm  
WLAN security: WEP, WPA/WPA2, WPA-PSK/WPA2-PSK  
Drivers: Windows Windows 10/8.1/8/7/XP (32/64 bit)  
Dimensions: 113.2 x 63.8 x 21.7 mm (without antennas), 113.2 x 100.5 x 201.1 mm (with vertical antennas)  
Operating temperatures: 0°C + 40°C  
Operating humidity: 10% + 90%, non-condensing  
Certificates: CE, ROHS



#07054

Net Price:  
8.66 USD  
Unit: pcs

## Wireless adapter Lite N USB 2.0 High Gain (TP-Link TL-WN722N)

Standards: IEEE 802.11 b/g, IEEE 802.11n  
Interface: USB 2.0 typ A  
Frequency range: 2400 MHz + 2483,5 MHz  
Max. speed: 150 Mbps when connected to 11n device  
Max. output power: 20 dBm  
Modulation type: DBPSK, DQPSK, CCK, OFDM, 16-QAM, 64-QAM  
Operating modes: Ad-hoc, infrastructure  
Antenna: detachable, RP-SMA  
WLAN security: 64/128 bits WEP, WPA/WPA2, WPA-PSK/WPA2-PSK (TKIP/AES)  
Roaming support: yes  
Drivers: Windows Windows 2k/XP/Vista  
Dimensions: 93,5x26x11 mm  
Operating temperatures: 0°C + 40°C



#08424

Net Price:  
11.40 USD  
Unit: pcs

## Wireless adapter Lite N USB 2.0 High Gain (TP-Link TL-WN822N)

- 11N speed allows for the best HD video streaming and internet calling experience
- Dual external antennas deliver enhanced reception and transmission performance
- Easy one-touch wireless security encryption with the Quick Security Setup button
- 1.5 meter USB extension cable enables convenient, flexible deployment
- Supports Windows XP / Vista / 7

Standards: IEEE 802.11 b/g, IEEE 802.11n  
Interface: mini USB 2.0  
Frequency range: 2400 MHz + 2483,5 MHz  
Max. speed: 300 Mbps when connected to 11n device  
Max. output power: 20 dBm  
Modulation type: DBPSK, DQPSK, CCK, OFDM, 16-QAM, 64-QAM  
Operating modes: Ad-hoc, infrastructure  
Antenna: detachable, RP-SMA  
WLAN security: 64/128 bits WEP, WPA/WPA2, WPA-PSK/WPA2-PSK (TKIP/AES)  
Roaming support: yes  
Drivers: Windows Windows 2k/XP/Vista/7  
Dimensions: 90 x 68 x 16,8mm  
Operating temperatures: 0°C + 40°C



#06433

Net Price:  
8.20 USD  
Unit: pcs

## Wireless adapter N USB 2.0 (TP-Link TL-WN821N)

Standards: IEEE 802.11n (draft 2.0), IEEE 802.11 b/g  
Interface: USB 2.0 typ A  
Frequency range: 2400 MHz + 2483,5 MHz  
Max. speed: 300 Mbps  
Max. output power: 20 dBm  
Operating modes: Ad-hoc, infrastructure  
WLAN security: WEP 64/128/152-bit, WPA, WPA-PSK, TKIP, AES  
Roaming support: yes  
WLAN features: MIMO, CCA  
Drivers: Windows Windows 2k/XP/Vista  
Dimensions: 94x26x11 mm  
Operating temperatures: 0°C + 40°C  
Operating humidity: 10% + 90%, non-condensing  
Certificates: CE, FCC  
Warranty period: 24 months



#08463

Net Price:  
6.25 USD  
Unit: pcs

## Wireless adapter N USB NANO 2.0 (TP-Link TL-WN725N)

Standards: IEEE 802.11b/g/n  
Interface: USB 2.0 typ A  
Frequency range: 2400 MHz + 2483,5 MHz  
Max. speed: 150 Mbps  
Max. output power: 20 dBm  
Operating modes: Ad-hoc, infrastructure  
WLAN security: WEP 64/128-bit, WPA/WPA2, WPA-PSK/WPA2-PSK (TKIP/AES), IEEE 802.1X support  
Drivers: Windows Windows XP/Vista/7  
Dimensions: 18.6x15x7.1mm  
Operating temperatures: 0°C + 40°C  
Operating humidity: 10% + 90%, non-condensing  
Certificates: CE, FCC, IC, RoHS  
Warranty period: 24 months



#08464

Net Price:  
9.31 USD  
Unit: pcs

## Wireless PCI Express N adaptor (TP-Link TL-WN781ND)

Standards: IEEE 802.11b/g/n  
Interface: PCI Express  
Frequency range: 2400 MHz + 2483,5 MHz  
Max. speed: 150 Mbps  
Max. output power: 20 dBm  
Operating modes: Ad-Hoc, Infrastructure  
WLAN security: 64/128-bit WEP, WPA, WPA2, WPA-PSK/WPA2-PSK (TKIP/AES), Wireless MAC Filtering  
Antenna: detachable, SMA RP  
Roaming support: yes  
Drivers: Windows XP/Vista/7/8  
Dimensions: 120.8x78.5x21.5 mm  
Operating temperatures: 0°C + 40°C  
Operating humidity: 10% + 90%, non-condensing  
Certificates: CE, FCC, RoHS



#08552

Net Price:  
12.50 USD  
Unit: pcs

### Wireless PCI-Express N adaptor, 300Mbps (TP-Link TL-WN881ND)

- Wireless N speed up to 300Mbps makes it ideal for video streaming, online gaming and Internet calls
- MIMO technology with stronger signal penetration strength, wider wireless coverage, providing better performance and stability
- Easily setup a highly secured wireless link with WPSTN (Wi-Fi Protected Setup)

Standards: IEEE 802.11n, IEEE 802.11b/g  
Interface: PCI Express  
Frequency range: 2400 MHz ~ 2483.5 MHz  
Max. speed: 300 Mbps  
Max. output power: <20 dBm  
Operating modes: Ad-Hoc, Infrastructure  
WLAN security: Support 64/128 bit WEP, WPA-PSK/WPA2-PSK  
Antenna: Omni Directional, Detachable (RP-SMA)  
Antenna Gain: 2x2dBi  
Roaming support: yes  
Drivers: Windows XP/Vista/7  
Dimensions: 120.8 x 78.5 x 21.5mm  
Operating temperatures: 0°C ~ 40°C  
Operating humidity: 10% ~ 90%, non-condensing  
Certificates: CE, FCC, RoHS



#06257

Net Price:  
80.00 USD  
Unit: pcs

### Omada Cloud Controller (TP-Link OC200)

- Professional centralized management for Wi-Fi network
- Free cloud access to manage from anywhere, anytime
- PoE (802.3af/802.3at) supported for easy installation
- Industry leading hardware design with powerful chipset, durable metal casing, and USB port for auto backup
- Omada App for a convenient management
- Secure guest network with multiple login options(Facebook Wi-Fi, SMS login, Voucher)

Ports: 2\*10/100Mbps Ethernet Port, 1\*USB 2.0 Port, 1\*Micro USB Port  
Features:  
Wireless Function: L3 Management, Multi-SSID, Load Balance, Band Steering, Airtime Fairness, Beamforming, Rate Limit, Wireless Schedule, QoS  
Wireless Security: Captive Portal Authentication, Access Control, Wireless Mac Address Filtering, Wireless Isolation Between Clients, SSID to VLAN Mapping, Rogue AP Detection  
AP Management: Automatic Discovery, Unified Configuration, Reboot Schedule, Batch Firmware Upgrade, LED ON/OFF Authentication: Captive Portal  
Dimensions: 3.9x3.9x1.0in. (100x98x25mm)  
Operating temperature: 0°C ~ 40°C  
Operating humidity: 10% ~ 90%, non-condensing  
Power: 802.3af/at PoE or Micro USB&#65288;DC 5V/Minimum 1A&#65289;  
Certificates:CE, FCC, RoHS



#09124

Net Price:  
168.00 USD  
Unit: pcs

### Omada Cloud Controller (TP-Link OC300)

- Centralized management for up to 500 Omada access points, JetStream switches, and SafeStream routers.
- Cloud access to manage from anywhere, anytime.
- Locally monitor and manage devices with the ultimate security and stability.
- The Omada app for convenient management.
- Industry-leading hardware design with a powerful chipset, durable metal casing, and USB 3.0 port for auto backup.
- Batch management, multi-site management, and remote firmware updates benefit network maintenance.
- The easy-to-use dashboard makes it easy to see your real-time network status and check network usage and traffic distribution.
- Network topology helps IT admins quickly see and troubleshoot connections at a glance.

Ports: 2\*10/100/1000Mbps Ethernet Port, 1\*USB 3.0 Port  
Features:  
Omada App: Yes  
Centralized Management: Up to 500 Omada access points, JetStream switches, and SafeStream routers\*, Up to 15,000 clients  
\*Only some JetStream switches and Safestream gateways can be centrally managed by OC300, please refer to [www.tp-link.com/business-networking/all-omada/](http://www.tp-link.com/business-networking/all-omada/) to find all the models supported by OC300  
Cloud Access: Yes  
L3 Management: Yes  
Multi-site Management: Yes  
Management Features: Automatic Device Discovery, Batch Configuration, Batch Firmware Upgrading, Intelligent Network Monitoring, Abnormal Event Warnings, Unified Configuration, Reboot Schedule, Captive Portal Configuration

NEW



#09445

Net Price:  
561.00 USD  
Unit: pcs

### Omada Cloud Controller (TP-Link OC400)

- Centralized Management: for up to 1,000 Omada access points, 100 Omada routers, a maximum of 200 Omada switches, and a maximum of 10 certain - DeltaStream GPON OLTs&#8224;
- 2x 10GE SFP+ Slots, 4x GE RJ45 Ports, and 2x USB 3.0 Ports.
- Redundant power supplies offer a reliable networking architecture.
- Free cloud access with the Omada app or Web UI from anywhere, anytime.
- On-premises manages to locally monitor and manage devices.
- The easy-to-use dashboard and real-time network topology make network monitoring easy.
- Batch and multi-site management benefit network maintenance.

Ports: 2x 10G SFP+ Ports, 4x GE RJ45 Ports, 2x USB 3.0 Ports, 1x GE Console Port  
Features:  
Omada App: Yes  
Centralized Management: 1,000 Omada access points, 100 Omada routers  
Cloud Access: Yes  
L3 Management: Yes  
Multi-site Management: Yes  
Management Features: Automatic Device Discovery, Batch Configuration, Batch Firmware Upgrading, Intelligent Network Monitoring, Abnormal Event Warnings, Unified Configuration, Reboot Schedule, Captive Portal Configuration  
Dimensions: 17.3 x 7.1 x 1.7 in (440 x 180 x 44 mm)



#09116

Net Price:  
11.90 USD  
Unit: pcs

### 300Mbps Wireless Range Extender (TP-Link Mercusys MW300RE)

- Range Extender mode boosts wireless signal to previously unreachable or hard-to-wire areas flawlessly
- Three external antennas with MIMO technology help set the MW300RE apart from ordinary range extenders
- Easily expand wireless coverage at easy two-touch setup or a push of WPS button
- Miniature size and wall-mounted design make it easy to deploy and move flexibly
- The multicolor LED helps you to find the right location to deliver the best Wi-Fi extension

HARDWARE FEATURES:  
Interface:1x10/100Mbps Auto-Sensing RJ45 Port  
Plug Type: EU  
Button:Reset Button, WPS Button  
Wireless Standards:IEEE 802.11n, IEEE 802.11g, IEEE 802.11b  
Dimensions ( W x D x H ): 101 x 74.8 x 75.8 mm  
Antenna Type: 3 x external  
WIRELESS FEATURES  
Frequency:2.4-2.4835GHz  
EIRP:<20dBm (EIRP)  
Wireless Security: WPA-PSK/WPA2-PSK  
OTHERS  
Certification:CE, RoHS  
Package Contents:MW300RE, Quick Installation Guide  
Environment:Operating Temperature 0°~40° (32°~104°), Storage Temperature -40°~70° (-40°~158°), Operating Humidity 10%~90% non-condensing, Storage Humidity 5%~90% non-condensing



#08541

Net Price:  
15.20 USD  
Unit: pcs

### 300Mbps Wireless Range Extender (TP-Link TL-WA850RE)

- Range Extender mode boosts wireless signal to previously unreachable or hard-to-wire areas flawlessly
- Miniature size and wall-mounted design make it easy to deploy and move flexibly
- Easily expand wireless coverage at a push of Range Extender button
- Ethernet port allows the Extender to function as a wireless adapter to connect wired devices

HARDWARE FEATURES:  
Interface:1x10/100Mbps Auto-Sensing RJ45 Port  
Plug Type: EU  
Button:Reset Button, Range Extender Button  
Power Consumption: About 3W  
Wireless Standards:IEEE 802.11n, IEEE 802.11g, IEEE 802.11b  
Dimensions ( W x D x H ): 4.3x 2.6 x 3.0in. (110.0 x 65.8 x 75.2mm)  
Antenna Type: 2 x internal  
WIRELESS FEATURES  
Frequency:2.4-2.4835GHz  
Signal Rate:11n Up to 300Mbps(dynamic), 11g Up to 54Mbps(dynamic), 11b Up to 11Mbps(dynamic)  
EIRP:<20dBm (EIRP)  
Reception Sensitivity:270M -68dBm@10% PER, 130M -68dBm@10% PER, 108M -68dBm@10% PER, 54M -73dBm@10% PER, 11M -85dBm@8% PER, 6M -88dBm@10% PER, 1M -90dBm@8% PER



#08542

Net Price:  
12.90 USD  
Unit: pcs

### 300Mbps Wireless Range Extender (TP-Link TL-WA854RE)

- Range Extender mode boosts wireless signal to previously unreachable or hard-to-wire areas flawlessly
- Miniature size and wall-mounted design make it easy to deploy and move flexibly
- Easily expand wireless coverage at a push of Range Extender button

#### HARDWARE FEATURES:

Plug Type: EU  
Button: Reset Button, Range Extender Button  
Power Consumption: About 3W  
Wireless Standards: IEEE 802.11n, IEEE 802.11g, IEEE 802.11b  
Dimensions (W x D x H): 4.3x 2.6 x 3.0in. (110.0 x 65.8 x 75.2mm)

Antenna Type: 2 x internal

#### WIRELESS FEATURES:

Frequency: 2.4-2.4835GHz  
Signal Rate: 11n Up to 300Mbps(dynamic), 11g Up to 54Mbps(dynamic), 11b Up to 11Mbps(dynamic)  
EIRP: <20dBm (EIRP)  
Reception Sensitivity: 270M -68dBm@10% PER, 130M -68dBm@10% PER, 108M -68dBm@10% PER, 54M -73dBm@10% PER, 11M -85dBm@8% PER, 6M -88dBm@10% PER, 1M -90dBm@8% PER



#04587

Net Price:  
17.60 USD  
Unit: pcs

### 300Mbps Wireless Range Extender (TP-Link TL-WA855RE)

- Boosts your existing Wi-Fi coverage to deliver fast and reliable wired and wireless connectivity
- External antennas for faster and more reliable Wi-Fi
- Supports AP mode which creates a new Wi-Fi Access point
- Easily expand wireless coverage at a push of the Range Extender button
- Set the Power Schedule for the range extender for power-saving
- Tether App allows easy access and management with your mobile devices remotely
- Works with Any Wi-Fi Router

#### HARDWARE FEATURES:

Interface: 1x10/100Mbps Auto-Sensing RJ45 Port  
Plug Type: EU  
Button: Reset Button, Range Extender Button  
Power Consumption: About 3W  
Wireless Standards: IEEE 802.11n, IEEE 802.11g, IEEE 802.11b  
Dimensions (W x D x H): 2.0x 1.3 x 2.6in. (52 x 34 x 65mm)

Antenna Type: 2 x external

#### WIRELESS FEATURES:

Frequency: 2.4-2.4835GHz  
Signal Rate: 11n Up to 300Mbps(dynamic), 11g Up to 54Mbps(dynamic), 11b Up to 11Mbps(dynamic)  
EIRP: <20dBm (EIRP)  
Reception Sensitivity: 270M -68dBm@10% PER, 130M -68dBm@10% PER, 108M -68dBm@10% PER, 54M -68dBm@10% PER, 11M -68dBm@8% PER, 6M -68dBm@10% PER, 1M -68dBm@8% PER



#08936

Net Price:  
20.80 USD  
Unit: pcs

### 300Mbps Wireless Range Extender (TP-Link TL-WA860RE)

- Range Extender mode boosts wireless signal to previously unreachable or hard-to-wire areas flawlessly
- Miniature size and wall-mounted design make it easy to deploy and move flexibly
- Extra power socket making sure that no power outlet is going to waste
- 2 fixed external antennas provide excellent WiFi coverage and reliability
- Easily expand wireless coverage at a push of Range Extender button

#### HARDWARE FEATURES:

Interface: 1x10/100Mbps Auto-Sensing RJ45 Port  
Plug Type: EU  
Button: Reset Button, Range Extender Button  
Power Consumption: About 3W  
Wireless Standards: IEEE 802.11n, IEEE 802.11g, IEEE 802.11b  
Dimensions (W x D x H): 4.3x 2.6 x 3.0in. (110.0 x 65.8 x 75.2mm)

Antenna Type: 2 x external

#### WIRELESS FEATURES:

Frequency: 2.4-2.4835GHz  
Signal Rate: 11n Up to 300Mbps(dynamic), 11g Up to 54Mbps(dynamic), 11b Up to 11Mbps(dynamic)  
EIRP: <20dBm (EIRP)  
Reception Sensitivity: 270M -69dBm@10% PER, 130M -69dBm@10% PER, 108M -69dBm@10% PER, 54M -69dBm@10% PER, 11M -86dBm@8% PER, 6M -89dBm@10% PER, 1M -91dBm@8% PER



#04579

Net Price:  
20.80 USD  
Unit: pcs

### 300Mbps Wireless N Nano Router (TP-Link TL-WR802N)

- 300Mbps wireless data rates is ideal for video streaming, online gaming and Internet calling
- Pocket-size - Ideal for home and travel use
- Supports Router, Repeater, Client, AP and hotspot operation modes
- Powered through a micro USB port by an external power adapter or USB connection to a computer provides flexibility for any situation
- Easy installation in minutes

#### HARDWARE FEATURES:

Interface: 1 10/100Mbps WAN/LAN Port, 1 Micro USB Port, 1 Reset Button  
Wireless Standards: IEEE 802.11n, IEEE 802.11g, IEEE 802.11b

Dimensions (W x D x H): 2.2 x 2.2 x 0.7 in. (57 x 57 x 18 mm)

Antenna Type: On-Board

#### WIRELESS FEATURES:

Frequency: 2.4-2.4835GHz  
Signal Rate: 11n Up to 300Mbps(dynamic), 11g Up to 54Mbps(dynamic), 11b Up to 11Mbps(dynamic)  
EIRP: <20dBm (EIRP)  
Reception Sensitivity: 135M-70dBm@10%PER, 65M-73dBm@10%PER, 54M-76dBm@10%PER  
Wireless Modes: AP Mode, Router Mode, Client Mode, Repeater Mode, Bridge Mode



#09122

Net Price:  
53.50 USD  
Unit: pcs

### 3G/4G Wireless N Router, 300Mbps (TP-Link TL-MR100)

- Cutting-edge 4G network - Share internet access with up to 32 Wi-Fi devices and enjoy download speeds of up to 150 Mbps
- Plug a SIM card and play - No configurations needed, compatibility of SIM cards in 100+ countries are assured by years of field tests
- Two detachable advanced LTE antennas - Enjoy stable and efficient connections to every device thanks to the two external antennas
- Wi-Fi router mode - Plug an Ethernet cable into the LAN/WAN port for flexible access as a backup option if you can't get a 4G connection

#### HARDWARE FEATURES:

Interface: 1 10/100Mbps LAN/WAN Port, 1 10/100Mbps LAN Ports, 1 SIM Card Slot  
Button: WPS/Reset Button  
External Power Supply: 9VDC/0.85A  
Dimensions (W x D x H): 6.06x4.49x1.42 in (154x114x36 mm)

Antenna Type: 2 Detachable External 4G LTE Antennas

#### WIRELESS FEATURES:

Wireless Standards: IEEE 802.11n, IEEE 802.11g, IEEE 802.11b  
Frequency: 2.4GHz  
EIRP: <20dBm  
Signal Rate: 300Mbps at 2.4GHz  
Wireless Security: 64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK encryptions  
Network Type: 4G- FDD-LTE- B1/B3/B5/B7/B8/B20 (2100/1800/850/2600/900/800 MHz), TDD-LTE- B38/B40/B41 (2600/2300/2500 MHz), 3G- HSPA/UMTS- B1/B5/B8 (2100/850/900 MHz)

NEW



#09405

Net Price:  
44.40 USD  
Unit: pcs

### 3G/4G Wireless N Router, 300Mbps (TP-Link TL-MR105)

- Cutting-edge 4G network - Share internet access with up to 32 Wi-Fi devices and enjoy download speeds of up to 150 Mbps
- Plug a SIM card and play - No configurations needed, compatibility of SIM cards in 100+ countries are assured by years of field tests
- Wi-Fi router mode - Plug an Ethernet cable into the LAN/WAN port for flexible access if you can't get a 4G connection

#### HARDWARE FEATURES:

Interface: 1 10/100Mbps LAN/WAN Port, 1 10/100Mbps LAN Ports, 1 SIM Card Slot  
Button: WPS/Reset Button  
External Power Supply: 9VDC/0.85A  
Dimensions (W x D x H): 6.85x5.12x2.36 in (174x130x60 mm)

Antenna Type: 2x Internal 4G/3G Antennas, 2x Internal Wi-Fi Antennas

#### WIRELESS FEATURES:

Wireless Standards: IEEE 802.11n, IEEE 802.11g, IEEE 802.11b  
Frequency: 2.4GHz  
EIRP: <20dBm  
Signal Rate: 300Mbps at 2.4GHz  
Wireless Security: 64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK encryptions



NEW



#09404

Net Price:  
66.00 USD  
Unit: pcs

### 3G/4G Wireless N Router, 300Mbps (TP-Link TL-MR150)

- Cutting-edge 4G network - Share internet access with up to 32 Wi-Fi devices and enjoy download speeds of up to 150 Mbps
- Plug a SIM card and play - No configurations needed, compatibility of SIM cards in 100+ countries are assured by years of field tests
- Two detachable advanced LTE antennas - Enjoy stable and efficient connections to every device thanks to the two external antennas
- Wi-Fi router mode - Plug an Ethernet cable into the LAN/WAN port for flexible access as a backup option if you can't get a 4G connection

#### HARDWARE FEATURES:

Interface: 1 10/100Mbps LAN/WAN Port, 3 10/100Mbps LAN Ports, 1 SIM Card Slot  
Button:WPS/Reset Button  
External Power Supply:9VDC/0.85A  
Dimensions ( W x D x H ):6.85 × 4.9 × 1.32 in. (174 × 124.5 × 33.5 mm)

Antenna Type: 2 Detachable External 4G LTE Antennas

#### WIRELESS FEATURES:

Wireless Standards:IEEE 802.11n, IEEE 802.11g, IEEE 802.11b  
Frequency:2.4GHz  
EIRP:<20dBm  
Signal Rate: 300Mbps at 2.4GHz  
Wireless Security:64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK encryptions



#04605

Net Price:  
66.00 USD  
Unit: pcs

### 3G/4G Wireless N Router, 300Mbps (TP-Link TL-MR6400)

- Share your 4G LTE network with multiple Wi-Fi devices and enjoy download speeds of up to 150Mbps
- Wireless N speeds of up to 300Mbps
- Integrated antennas provide stable wireless connections
- Requires no configuration - just insert a SIM card and turn it on to enjoy high speed internet access
- LAN/WAN port provides options and flexibility, allowing you to choose your connection type

#### HARDWARE FEATURES:

Interface: 1 10/100Mbps LAN/WAN Port, 3 10/100Mbps LAN Ports, 1 SIM Card Slot  
Button:WPS/Reset Button, Wireless On/Off Switch, Power On/Off Button  
External Power Supply:12VDC/1A  
Dimensions ( W x D x H ):7.95 × 5.55 × 1.32 in. (202 × 141 × 33.6 mm)

Antenna Type: 2 Internal Wi-Fi Antennas, 2 Detachable External 4G LTE Antennas

#### WIRELESS FEATURES:

Wireless Standards:IEEE 802.11n, IEEE 802.11g, IEEE 802.11b  
Frequency:2.4GHz  
EIRP:<20dBm  
Signal Rate: 300Mbps at 2.4GHz  
Wireless Security:Support 64/128 bit WEP, WPA-PSK/WPA2-PSK, Wireless MAC Filtering



#09123

Net Price:  
93.30 USD  
Unit: pcs

### 3G/4G Wireless N Telephony Router, 300Mbps (TP-Link TL-MR6500v)

- Cutting-edge 4G network - share internet access with up to 32 Wi-Fi devices and enjoy download speeds of up to 150 Mbps\*
- Plug a SIM card and play - no configurations needed, compatibility for SIM cards in 100+ countries are assured by years of field tests
- Wi-Fi speeds up to 300 Mbps - enjoy uninterrupted HD movies, rapid file downloads, seamless video chats, and more at the same time\*
- Professional voice functions - supports VoLTE/CSFB/VoIP functions and provides 50 MB of internal storage for 100 minutes of voicemail
- Two detachable advanced LTE antennas - enjoy stable and efficient connections to every device thanks to the two external antennas
- Wi-Fi router mode - plug an Ethernet cable into the LAN/WAN port for flexible access as a backup option if you can't get a 4G connection

#### HARDWARE FEATURES:

Interface: 1 10/100Mbps LAN/WAN Port, 2 10/100Mbps LAN Ports, 1 SIM Card Slot, 1 Phone Port  
Button:WPS/Reset Button, Wi-Fi ON/OFF Button  
External Power Supply:12VDC/1A  
Dimensions ( W x D x H ):7.95 × 5.55 × 1.32 in (202 × 141 × 33.6 mm)

Antenna Type: 2 Detachable External 4G LTE Antennas

#### WIRELESS FEATURES:

Wireless Standards:IEEE 802.11n, IEEE 802.11g, IEEE 802.11b  
Frequency:2.4GHz  
EIRP:<20dBm  
Signal Rate: 300Mbps at 2.4GHz  
Wireless Security:64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK encryptions



#09523

Net Price:  
35.10 USD  
Unit: pcs

### 3G/4G Wireless Router (TP-Link Marcussys MB110-4G)

- 4G network - Share internet access with up to 32 Wi-Fi devices and enjoy download speeds of up to 150 Mbps
- Plug a SIM card and play - No configurations needed, compatibility of SIM cards are assured by years of field tests
- 300 Mbps WiFi - Fast WiFi speeds up to 300 Mbps to share your network
- Wi-Fi router mode - Plug an Ethernet cable into the LAN/WAN port for flexible access if you can't get a 4G connection

#### HARDWARE FEATURES:

Standards and Protocols:802.11b/g/n  
Interface: 1× 10/100Mbps LAN/WAN Port, 1× 10/100Mbps LAN Port, 2× 4G/3G External Antenna Ports, 1× Nano SIM Card Slot  
Button:WPS/Reset Button  
Dimensions (W X D X H): 90×92×150.5 mm

#### WIRELESS FEATURES:

Frequency:2.4GHz  
Signal Rate: 2.4 GHz@ 300 Mb/s  
Wireless Functions:Enable/Disable Wireless Radio, Wireless Schedule, WMM, Wireless, Statistics  
Wireless Security:WPA-PSK / WPA2-PSK  
Network Type: EU FDD-LTE B1/B3/B5/B7/B8/B20/B28 (2100/1800/850/2600/900/800/700 MHz), TDD-LTE B38/B40 (2600/2300 MHz), HSPA+/UMTS B1/B5/B8 (2100/850/900 MHz), UN FDD-LTE B1/B2/B3/B4/B5/B7/B8/B28/B66 (2100/1900/1800/1700/850/2600/900/700/1700 MHz), TDD-LTE B40 (2300 MHz), HSPA+/UMTS B1/B2/B4/B5/B8 (2100/1900/1700/850/900 MHz)



#08365

Net Price:  
20.20 USD  
Unit: pcs

### Portable 3G/4G Wireless N Router (TP-Link TL-MR3020)

Share a 3G/4G\* mobile connection, compatible with 120+ LTE/HSPA+/UMTS/EVDO 3G/4G USB modems, tested in the field

Travel-size Design, small and light enough to take on the road, enables users to share a 3G/4G\* mobile connection wherever 3G/4G\* coverage is available

Wireless speed is up to 150Mbps

Three modes available for different situations: 3G/4G\* Router, WISP Client Router and Travel Router Mode (AP Mode)

With 3G/4G\* and WAN failover back-up strategy, TL-MR3020 can provide a sustained internet connection.

#### HARDWARE FEATURES:

Interface:1 10/100Mbps WAN/LAN Port, USB 2.0 Port for 3G/4G modem, a mini USB Port for power supply.  
Button:Quick Setup Security Button, Reset Button, Mode Switch  
External Power Supply:5VDC/1.0A  
Dimensions ( W x D x H ):2.9 × 2.6 × 0.9 in. (74 × 67 × 22 mm)  
Antenna Type:Internal Antenna  
WIRELESS FEATURES:  
Wireless Standards:IEEE 802.11n, IEEE 802.11g, IEEE 802.11b  
Frequency:2.4-2.4835GHz  
EIRP:<20dBm  
Wireless Modes:3G Router, Travel Router (AP), WISP Client Router  
Wireless Security:Support 64/128 bit WEP, WPA-PSK/WPA2-PSK, Wireless MAC Filtering



#06236

Net Price:  
83.90 USD  
Unit: pcs

### Router Mesh Deco M5 1-pack (TP-Link DECO M5)

- Standalone coverage up to 2,000 sq. ft.
- Fast dual band WiFi
- Can be added to any TP-Link WiFi System
- Works with Amazon Alexa Voice Assistant

Standards: IEEE 802.11 ac/n/a 5 GHz, IEEE 802.11 b/g/n 2.4 GHz

Ports: 2 LAN/WAN Gigabit Ethernet Ports

Processor: Quad-core CPU

Button: 1 Reset button on the underside

Flash: 32 MB

SDRAM: 256 MB

Bluetooth version: 4.2 and above

Frequency range: 2.4 GHz and 5 GHz

Signal Rate: 400 Mbps on 2.4 GHz, 867 Mbps on 5 GHz  
EIRP: FCC <30 dBm, CE <20 dBm (2.4 GHz) <23 dBm (5 GHz)

Advanced Functions: TP-Link Mesh Technology - MU-MIMO, Auto Path Selection, AP Steering, Band Steering, Beamforming

Wireless Security: WPA-PSK/WPA2-PSK





#06235

Net Price:  
201.00 USD  
Unit: pcs**Router Mesh Deco M5 3-pack (TP-Link DECO M5)**

- Covers up to 5,500 sq. ft.
- Fast dual band WiFi
- One WiFi name for the entire home
- Connects 100-plus devices
- Works with Amazon Alexa Voice Assistant

Standards: IEEE 802.11 ac/n/a 5 GHz, IEEE 802.11 b/g/n 2.4 GHz  
Ports: 2 LAN/WAN Gigabit Ethernet Ports  
Processor: Quad-core CPU  
Button: 1 Reset button on the underside  
Flash: 32 MB  
SDRAM: 256 MB  
Bluetooth version: 4.2 and above  
Frequency range: 2.4 GHz and 5 GHz  
Signal Rate: 400 Mbps on 2.4 GHz, 867 Mbps on 5 GHz  
EIRP: FCC <30 dBm, CE <20 dBm (2.4 GHz) <23 dBm (5 GHz)  
Advanced Functions: TP-Link Mesh Technology - MU-MIMO, Auto Path Selection, AP Steering, Band Steering, Beamforming  
Wireless Security: WPA-PSK/WPA2-PSK



#09119

Net Price:  
10.80 USD  
Unit: pcs**Wireless N router (TP-Link Mercusys MW302R)**

- Fast Wi-Fi for Daily Life - MW302R provides fast and stable connections to meet all your network needs with speeds of up to 300 Mbps
  - Broader Coverage - Equipped with high gain external antennas to deliver strong Wi-Fi signals to every corner of your home
  - Multi-Mode - Four modes in one device to satisfy all application scenarios
  - Easy installation - Intuitive webpage guides you through the setup process in minutes
  - Active Parental Controls - Establish appropriate access policies to protect children with responsible, safe internet access
  - Compatible with IPv6 (Internet Protocol version 6)
- Standards: IEEE 802.11n, IEEE 802.11b/g  
Ports: 2x 10/100 Mbps RJ-45 (LAN), 1x 10/100 Mbps RJ-45 (WAN)  
Frequency range: 2400 MHz + 2483.5 MHz  
Max. speed: 300 Mbps  
Max. output power: 20 dBm  
Antenna: 2x Omni-Directional Antennas  
Wireless Functions: Enable/Disable Wireless Radio, WDS Bridging  
WLAN security: WPA-PSK / WPA2-PSK  
WAN Type: Dynamic IP, Static IP, PPPoE, PPTP, L2TP  
Management: Access Control, Local Management, Remote Management  
DHCP: Server  
Port Forwarding: Virtual Server, UPnP, DMZ



#09120

Net Price:  
12.30 USD  
Unit: pcs**Wireless N router (TP-Link Mercusys MW305R)**

- 300Mbps wireless speed is ideal for HD streaming, online gaming, and large file downloads
  - Three 5dBi antennas greatly increase wireless signal strength, size and stability
  - Intuitive webpage guides you through the setup process in minutes
- Standards: IEEE 802.11n, IEEE 802.11b/g  
Ports: 3x 10/100 Mbps RJ-45 (LAN), 1x 10/100 Mbps RJ-45 (WAN)  
Frequency range: 2400 MHz + 2483.5 MHz  
Max. speed: 300 Mbps  
Max. output power: 20 dBm  
Antenna: 3x Omni-Directional Antennas 5dBi  
Wireless Functions: Enable/Disable Wireless Radio, WDS Bridging  
WLAN security: WPA-PSK / WPA2-PSK  
WAN Type: Dynamic IP, Static IP, PPPoE, PPTP, L2TP  
Management: Access Control, Local Management, Remote Management  
DHCP: Server  
Port Forwarding: Virtual Server, UPnP, DMZ



#09121

Net Price:  
13.00 USD  
Unit: pcs**Wireless N router (TP-Link Mercusys MW325R)**

- Great Coverage - four 5dBi antennas provide wide wireless coverage
  - Enhanced Signal - high gain antennas dramatically increase wireless signal strength, size and stability
  - 300Mbps Wireless Speed - ideal for HD streaming, online gaming, and large file downloads
  - Easy Installation - intuitive webpage guides you through the setup process in minutes
- Standards: IEEE 802.11n, IEEE 802.11b/g  
Ports: 3x 10/100 Mbps RJ-45 (LAN), 1x 10/100 Mbps RJ-45 (WAN)  
Frequency range: 2400 MHz + 2483.5 MHz  
Max. speed: 300 Mbps  
Max. output power: 20 dBm  
Antenna: 4x Omni-Directional Antennas 5dBi  
Wireless Functions: Enable/Disable Wireless Radio, WDS Bridging  
WLAN security: WPA-PSK / WPA2-PSK  
WAN Type: Dynamic IP, Static IP, PPPoE, PPTP, L2TP  
Management: Access Control, Local Management, Remote Management  
DHCP: Server  
Port Forwarding: Virtual Server, UPnP, DMZ



#07114

Net Price:  
23.90 USD  
Unit: pcs**Wireless N router (TP-Link TL-MR3420)**

- Standards: IEEE 802.11n/g/b, IEEE 802.3/3u, USB 2.0  
Ports: 4x 10/100 Mbps RJ-45 (LAN), 1x 10/100 Mbps RJ-45 (WAN)  
Frequency range: 2400 MHz + 2483.5 MHz  
Modulation: DBPSK, DQPSK, CCK, OFDM, 16-QAM, 64-QAM  
Operating modes: AP Router  
Max. speed: 300 Mbps  
Max. output power: 20 dBm  
Antenna: 3x detachable SMA RP, 2 dBi  
WLAN security: WEP 64/128/152-bit, WPA, WPA-PSK, WPA2, WPA2-PSK, TKIP, AES  
LAN security: ACL, firewall, ICMP-FLOOD, UDP-FLOOD, TCP-SYN-FLOOD filtering, domain filtering, MAC address filtering, 802.1x, parental control



#09071

Net Price:  
12.90 USD  
Unit: pcs**Wireless N router (TP-Link TL-WR820N)**

- 300 Mbps Wi-Fi speed is ideal for daily tasks including browsing, emailing, and video streaming
  - IPTV supports IGMP Proxy/Snooping, Bridge and Tag VLAN to optimize IPTV streaming
  - Guest Network provides separate access for guests while securing the host network
  - Parental Controls manage when and how connected devices can access the internet
  - SPI firewall and wireless encryption protect your home network
  - Compatible with IPv6 (Internet Protocol version 6)
- Standards: IEEE 802.11n (draft 2.0), IEEE 802.11b/g, IEEE 802.3/u, 802.1x  
Ports: 2x 10/100 Mbps RJ-45 (LAN), 1x 10/100 Mbps RJ-45 (WAN)  
Frequency range: 2400 MHz + 2483.5 MHz  
Max. speed: 300 Mbps  
Max. output power: 20 dBm  
Antenna: 2x Omni-Directional Antennas  
Wireless Functions: Enable/Disable Wireless Radio, WMM, Wireless Statistics  
WLAN security: WEP, WPA / WPA2, WPA / WPA2-PSK  
WAN Type: Dynamic IP, Static IP, PPPoE, PPTP, L2TP  
Management: Access Control, Local Management, Remote Management



#06430

Net Price:  
16.10 USD  
Unit: pcs**Wireless N router (TP-Link TL-WR841N)**

- Standards: IEEE 802.11n (draft 2.0), IEEE 802.11b/g, IEEE 802.3/u, 802.1x  
Ports: 4x 10/100 Mbps RJ-45 (LAN), 1x 10/100 Mbps RJ-45 (WAN)  
Frequency range: 2400 MHz + 2483.5 MHz  
Modulation: DBPSK, DQPSK, CCK, OFDM, 16-QAM, 64-QAM  
Operating modes: AP Router  
Max. speed: 300 Mbps  
Max. output power: 20 dBm  
Antenna: 2x omni 3 dBi  
WLAN security: WEP 64/128/152-bit, WPA, WPA-PSK, WPA2, WPA2-PSK, TKIP, AES  
LAN security: ACL, firewall, ICMP-FLOOD, UDP-FLOOD, TCP-SYN-FLOOD filtering, domain filtering, MAC address filtering, 802.1x, parental control



#09072

Net Price:  
13.80 USD  
Unit: pcs**Wireless N router (TP-Link TL-WR844N)**

- High-Speed Wi-Fi - 300 Mbps wireless transmission rate is ideal for both bandwidth sensitive tasks and basic work.
- Boosted Coverage - Two omnidirectional antennas and 2x2 MIMO deliver strong Wi-Fi signal and reliable connections.
- Multi-Mode 4 in 1 - Supports Router, Access Point, Range Extender, and WISP modes to meet any network need.
- Parental Controls - Manages when and how connected devices can access the internet.
- Guest Network - Provides separate access for guests while securing the host network.
- Smooth HD Streaming - Supports IGMP Proxy/Snooping, Bridge and Tag VLAN to optimize IPTV streaming.
- IPv6 Supported - Compatible with the IPv6 (the latest Internet Protocol version 6).

Standards: IEEE 802.11n (draft 2.0), IEEE 802.11b/g, IEEE 802.3/u, 802.1x  
Ports: 4x 10/100 Mbps RJ-45 (LAN), 1x 10/100 Mbps RJ-45 (WAN)  
Frequency range: 2400 MHz  $\pm$  2483.5 MHz  
Max. speed: 300 Mbps  
Max. output power: 20 dBm  
Antenna: 2x Omni-Directional Antennas  
Wireless Functions: Enable/Disable Wireless Radio, WMM, Wireless Statistics  
WLAN security: WEP, WPA / WPA2, WPA / WPA2-PSK  
WAN Type: Dynamic IP, Static IP, PPPoE, PPTP, L2TP  
Management: Access Control, Local Management, Remote Management



#09073

Net Price:  
18.80 USD  
Unit: pcs**Wireless N router (TP-Link TL-WR850N)**

- 300Mbps wireless transmission rate ideal for both bandwidth sensitive tasks and basic work
- Supports Agile Config- Enable ISPs to customize default configurations by themselves
- Parental Controls manage when and how connected devices can access the internet
- IPTV supports IGMP Proxy/Snooping to optimize IPTV streaming
- Compatible with IPv6 (Internet Protocol version 6)
- Guest Network provides separate access for guests while securing the home network

Standards: IEEE 802.11n (draft 2.0), IEEE 802.11b/g, Ports: 4x 10/100 Mbps RJ-45 (LAN), 1x 10/100 Mbps RJ-45 (WAN)  
Frequency range: 2400 MHz  $\pm$  2483.5 MHz  
Modulation: DBPSK, DQPSK, CCK, OFDM, 16-QAM, 64-QAM  
Operating modes: AP Router  
Max. speed: 300 Mbps  
Max. output power: 20 dBm  
Antenna: 2x Omni-Directional Antennas  
Wireless Functions: Enable/Disable Wireless Radio, WDS Bridge, WMM, Wireless Statistics  
WLAN security: 64/128-bit WEP, WPA / WPA2, WPA-PSK / WPA2-PSK  
WAN Type: Dynamic IP, Static IP, PPPoE, PPTP, L2TP



#04576

Net Price:  
16.10 USD  
Unit: pcs**Wireless N Router, 300Mbps (TP-Link TL-WR840N)**

300Mbps wireless transmission rate with MIMO technology provides a smooth wireless N experience

Up to 4 SSIDs support multiple wireless networks with different SSIDs and passwords

Up to 5 VPN tunnels enable remote VPN connections

Multi-functional USB 2.0 port convenient for wireless printing and FTP server

Embedded media server allows users to share music, video and photos with Windows media player, PS3 or X-BOX 360

**HARDWARE FEATURES:**

Interface: 4 10/100Mbps LAN Ports, 1 10/100Mbps WAN Port  
Button: WPS Button, WiFi On/Off Button, Reset Button  
External Power Supply: 9VDC / 0.6A

Wireless Standards: IEEE 802.11n, IEEE 802.11g, IEEE 802.11b

Antenna: 2\* Antenna  
Dimensions (W x D x H): 7.2 x 5.0 x 1.4 in. (182 x 128 x 35 mm)

**WIRELESS FEATURES:**

Frequency: 2.4-2.4835GHz  
Signal Rate: Up to 300Mbps

EIRP: <20dBm

Reception Sensitivity: 270M -68dBm@10% PER, 130M -68dBm@10% PER, 108M -68dBm@10% PER, 54M -68dBm@10% PER, 11M -85dBm@8% PER, 6M -88dBm@10% PER, 1M -90dBm@8% PER

**Wireless active devices 2.4GHz**

#05375

Net Price:  
9.27 USD  
Unit: pcs**Wireless Access Point (AT8-4)**

Standard: IEEE 802.11a/b/g  
Chipset: Atheros AR5112 / AR2312  
Frequency band: 2400 MHz  $\pm$  2483.5 MHz, 5150 MHz  $\pm$  5350 MHz, 5470 MHz  $\pm$  5725 MHz  
Max. speed: 108 Mbps  
Radio modes: 11b/g, 11g, 11a, SuperA  
Max. TX power: 20 dBm  
Operational modes: Bridge, Access Point, Client Infrastructure, Client Ad-hoc  
Modulation: 802.11a - OFDM, 802.11b - DSSS, 802.11g - OFDM  
Antenna: detachable, SMA-RP  
WDS: 8x  
Access Control: SSID, MAC Address Control, max. clients  
WLAN Security: WEP 64/128/152-bit, WPA-PSK, WPA-TKIP/AES, RADIUS



#05327

Net Price:  
15.90 USD  
Unit: pcs**Wireless Access Point ADV (Interepoch IWE2100)**

Standards: IEEE 802.11a/b/g, IEEE 802.3u, IEEE 802.1Q/x  
Ports: 1x 10/100 Mbps RJ-45  
Frequency range: 2400 MHz  $\pm$  2483.5 MHz, 5150 MHz  $\pm$  5350 MHz, 5470 MHz  $\pm$  5825 MHz  
Operating modes: AP, Bridge, AP Client  
Max. speed: 11 Mbps  
Max. output power: 17 dBm  
Receiver sensitivity: > -85 dBm  
Antenna: detachable SMA-RP, 2 dBi  
WLAN security: WEP 64/128-bit, WPA, TKIP, 802.1x  
Addressing: DHCP client/server  
Additional features: Association control, packet filtering, VPN Pass Through, VLAN support, WLAN Client Isolation



#05425

Net Price:  
24.40 USD  
Unit: pcs**Wireless client device airClient Nexus PRO TOTAL (smartBridges sB3412)**

Standard: IEEE 802.11a/b/g, IEEE 802.3u  
Ports: 2x 10/100 Mbps RJ-45, 1x N(F) 2.4 GHz, 1x N(F) 5.x GHz  
Operating modes: AP Client, Router, Bridge  
Frequency range: 2.400 - 2.485 GHz, 5.150 - 5.350 GHz, 5.470 - 5.875 GHz  
Modulation: COFDM with BPSK, QPSK, 16 QAM, 64QAM, DSSS with CCK, BPSK, QPSK  
Max. output power: 26dBm @ 1Mbps (2.4 GHz), 23dBm @ 54 Mbps (2.4 GHz), 21dBm @ 6 Mbps (5.x GHz), 18dBm @ 54 Mbps (5.x GHz)  
Max. output power with build-in antenna: 39dBm @ 1 Mbps (2.4 GHz), 36dBm @ 54 Mbps (2.4 GHz), 38dBm @ 6 Mbps (5.x GHz), 35dBm @ 54 Mbps (5.x GHz)



#05344

Net Price:  
1.46 USD  
Unit: pcs**Wireless PCI card (VZA-81)**

Standard: IEEE 802.11a/b/g  
Interface: PCI ver. 2.2  
Frequency band: 2400 MHz  $\pm$  2483.5 MHz, 2412 MHz  $\pm$  2483.5 MHz, 5150 MHz  $\pm$  5350 MHz, 5470 MHz  $\pm$  5725 MHz  
Max. speed: 108 Mbps  
Max. TX power: 20 dBm  
Operational modes: Ad-hoc, infrastructure  
Modulation: 802.11a - OFDM, 802.11b/g - DSSS, OFDM  
Channels: 13 (802.11b/g), 19 non-overlapping (802.11a)  
WLAN Security: WEP 64/128/152-bit, AES, TKIP, RADIUS  
Antenna: SMA-RP connector  
Drivers: Windows 98SE/Me/2k/XP  
Operational temperature: 0°C  $\pm$  70°C



#05284

Net Price:  
9.76 USD  
Unit: pcs**Wireless router PRO (Interepoch IWE1100-R8S17P)**

Standard: IEEE 802.3/u, 802.11b  
Operational modes: AP/Bridge, Router w/PPPoE, Router w/DHCP, Router w/Static-IP, Router w/Dial-up  
WDS links: 6x  
Max. TX power [dBm]: 17  
Antenna / connector type: detachable, omnidirectional 3 dBi / SMA-RP(F)  
TX power control: yes  
Ports: 1x 10/100 Mbps RJ-45 LAN, 1x 10/100 Mbps RJ-45 WAN  
Access control: DHCP Server, MAC Address Filtering, Packet Type Filtering, TCP/UDP Port Filtering, NAT, Virtual Server, DMZ, UPnP, UPnP for NAT, SPI Firewall  
WLAN Security: WPA (802.1x/TKIP), WEP 64/128-bit, ESSID Disable, RADIUS



#07051

Net Price:  
1.00 USD  
Unit: pcs**Wireless PCI adaptor (TP-Link TL-WN350G)**

Standards: IEEE 802.11b/g  
Chipset: Atheros  
Interface: PCI 32-bit  
Frequency range: 2400 MHz  $\pm$  2483.5 MHz  
Max. speed: 54 Mbps  
Max. output power: 18 dBm  
Operating modes: Ad-Hoc, Infrastructure  
WLAN security: 64/128/152-bit WEP, WPA, WPA2, TKIP/AES  
Antenna: fixed  
Roaming support: yes  
Drivers: Windows 98SE/ME/2000/XP/Vista  
Dimensions: 133x121x22 mm  
Operating temperatures: 0°C  $\pm$  40°C  
Operating humidity: 10%  $\pm$  90%, non-condensing  
Certificates: CE, FCC  
Warranty period: 24 months



#05470

Net Price:  
1.00 USD  
Unit: pcs

## Wireless PCI adaptor (TP-Link TL-WN551G)

Standards: IEEE 802.11b/g  
Interface: PCI 32-bit  
Frequency range: 2400 MHz + 2483,5 MHz  
Max. speed: 54 Mbps  
Max. output power: 17 dBm  
Operating modes: Ad-Hoc, Infrastructure  
WLAN security: 64/128/152-bit WEP, WPA, WPA2, TKIP/AES  
Antenna: detachable, SMA  
WLAN features: Extended Range  
Roaming support: yes  
Drivers: Windows 98SE/ME/2000/XP  
Dimensions: 133x121x22 mm  
Operating temperatures: 0°C + 40°C  
Operating humidity: 10% + 90%, non-condensing  
Certificates: CE, FCC  
Warranty period: 24 months



#06019

Net Price:  
24.40 USD  
Unit: pcs

## Wireless client device airClient Nexus TOTAL 241 (smartBridges sB3415-03)

Standards: IEEE 802.11b/g, IEEE 802.3u  
Ports: 1x 10/100 Mbps RJ-45  
Operating modes: AP Client, Router, NAT, Bridge  
Frequency range: 2400 MHz - 2485 MHz  
Modulation: QPSK, 16QAM, 64QAM, DBPSK, DQPSK, CCK  
Max output power (inbuild antenna): 33dBm  
Max output power (external antenna): 18dBm  
Receiver sensitivity (inbuild antenna): -109dBm @ 1Mbps,  
-87dBm @ 54 Mbps  
Receiver sensitivity (external antenna): -94dBm @ 1Mbps,  
-71dBm @ 54 Mbps  
Typical useful throughput: 3 Mbps  
Management: WWW, SNMP

## Wireless active devices 5GHz



#07008

Net Price:  
66.00 USD  
Unit: pcs

## Wireless access point Airmax NanoStation Loco M5 TDMA (Ubiquiti LOCOM5)

Standards: IEEE 802.11a, IEEE 802.11n, IEEE 802.3u  
Ports: 1x 10/100 Mbps RJ-45  
Operating modes: Access Point, Bridge, Client, WDS  
Chipset: Atheros MIPS 24KC 400MHz  
Operating memory: 32 MB SDRAM  
Flash memory: 8 MB  
Frequency range: 5470 MHz + 5825 MHz  
Max. output power: 27 dBm @ 6-24 Mbps, 25 dBm @ 36 Mbps, 23 dBm @ 48 Mbps, 22 dBm @ 54 Mbps, 27 dBm @ MSC0, 27 dBm @ MSC1, 27 dBm @ MSC2, 27 dBm @ MSC3, 26 dBm @ MSC4, 24 dBm @ MSC5, 22 dBm @ MSC6, 21 dBm @ MSC7, 27 dBm @ MSC8, 27 dBm @ MSC9, 27 dBm @ MSC10, 27 dBm @ MSC11, 26 dBm @ MSC12, 24 dBm @ MSC13, 22 dBm @ MSC14, 21 dBm @ MSC15




#07006

Net Price:  
99.50 USD  
Unit: pcs

## Wireless access point Airmax NanoStation M5 TDMA (Ubiquiti NSM5)

Standards: IEEE 802.11a, IEEE 802.11n, IEEE 802.3u  
Ports: 2x 10/100 Mbps RJ-45  
Operating modes: Access Point, Bridge, Client, WDS  
Chipset: Atheros MIPS 24KC 400MHz  
Operating memory: 32 MB SDRAM  
Flash memory: 8 MB  
Frequency range: 5470 MHz + 5825 MHz  
Max. output power: 27 dBm @ 6-24 Mbps, 25 dBm @ 36 Mbps, 23 dBm @ 48 Mbps, 22 dBm @ 54 Mbps, 27 dBm @ MSC0, 27 dBm @ MSC1, 27 dBm @ MSC2, 27 dBm @ MSC3, 26 dBm @ MSC4, 24 dBm @ MSC5, 22 dBm @ MSC6, 21 dBm @ MSC7, 27 dBm @ MSC8, 27 dBm @ MSC9, 27 dBm @ MSC10, 27 dBm @ MSC11, 26 dBm @ MSC12, 24 dBm @ MSC13, 22 dBm @ MSC14, 21 dBm @ MSC15



#08180

Net Price:  
54.80 USD  
Unit: pcs

## Wireless access point Ubiquiti AirGrid M5 23dBi 1x1 MIMO HP (Ubiquiti AirGrid M5)

Utilizing InnerFeed technology, the new AirGrid M Series represents the evolution of outdoor broadband wireless devices. Complete antenna and radio system integration provides revolutionary cost/performance solutions to the Worldwide Broadband Industry.  
Standards: IEEE 802.11a, IEEE 802.3u  
Ports: 1x 10/100 Mbps RJ-45  
Operating modes: Access Point, Bridge, Client, WDS, Router  
Chipset: Atheros MIPS 24KC, 400MHz  
Operating memory: 32 MB SDRAM  
Flash memory: 8 MB  
Frequency range: 5475MHz - 5825MHz  
Antenna: build-in, 23 dBi  
Weight: 1.65 kg  
Grid dimensions: 279.4 x 355.6 mm  
Mounting: mast or wall with the aid of antenna wall support  
Max. power consumption: 3 W  
Power: PoE 24V  
Operating temperatures: -30°C + 75°C  
Operating humidity: 5% + 95%, condensing



#08181

Net Price:  
63.50 USD  
Unit: pcs

## Wireless access point Ubiquiti AirGrid M5 27dBi 1x1 MIMO HP (AirGrid M5)

Utilizing InnerFeed technology, the new AirGrid M Series represents the evolution of outdoor broadband wireless devices. Complete antenna and radio system integration provides revolutionary cost/performance solutions to the Worldwide Broadband Industry.  
Standards: IEEE 802.11a, IEEE 802.3u  
Ports: 1x 10/100 Mbps RJ-45  
Operating modes: Access Point, Bridge, Client, WDS, Router  
Chipset: Atheros MIPS 24KC, 400MHz  
Operating memory: 32 MB SDRAM  
Flash memory: 8 MB  
Frequency range: 5475MHz - 5825MHz  
Antenna: build-in, 27 dBi  
Weight: 2.75 kg  
Grid dimensions: 431.8 x 609.6 mm  
Mounting: mast or wall with the aid of antenna wall support  
Max. power consumption: 3 W  
Power: PoE 24V  
Operating temperatures: -30°C + 75°C  
Operating humidity: 5% + 95%, condensing



#08846

Net Price:  
62.50 USD  
Unit: pcs

## Wireless access point Ubiquiti NanoBeam M5 MIMO (Ubiquiti NBE-M5-16)

Standards: IEEE 802.11a/n  
Ports: 1x 10/100 Mbps RJ-45  
Chipset: Atheros MIPS 74KC, 560 MHz  
Operating memory: 64 MB DDR2  
Flash memory: 8 MB  
Antenna: build-in, 16 dBi  
VSWR: 1.5  
Diameter: 190mm  
Weight: 0.320 kg  
Mounting: mast or wall with the aid of antenna wall support  
Max. power consumption: 6 W  
Power: PoE 24V  
Operating temperatures: -40°C + 70°C  
Operating humidity: 5% + 95%, Non-condensing



#08874

Net Price:  
73.80 USD  
Unit: pcs

## Wireless access point Ubiquiti PowerBeam M5 MIMO 5GHz (Ubiquiti PBE-M5-300)

Standards: IEEE 802.11a/n  
Ports: 1x 10/100 Mbps RJ-45  
Chipset: Atheros MIPS 74KC, 560 MHz  
Operating memory: 64 MB DDR2  
Flash memory: 8 MB  
Antenna: build-in, 22 dBi  
Range: 20+ km  
VSWR: 1.5  
Diameter: 300mm  
Weight: 1.203 kg  
Mounting: mast or wall with the aid of antenna wall support  
Max. power consumption: 6 W  
Power: PoE 24V  
Operating temperatures: -40°C + 70°C  
Operating humidity: 5% + 95%, Non-condensing



#06285

Net Price:  
90.00 USD  
Unit: pcs**Wireless access point Ubiquiti PowerBeam M5 MIMO 5GHz (Ubiquiti PBE-M5-300-ISO-EU)**

Standards: IEEE 802.11a/n  
Ports: 1x 10/100 Mbps RJ-45  
Chipset: Atheros MIPS 74KC, 560 MHz  
Operating memory: 64 MB DDR2  
Flash memory: 8 MB  
Antenna: build-in, 22 dBi  
Range: 20+ km  
VSWR: 1.5  
Dimensions: 364 x 364 x 276 mm (14.33 x 14.33 x 10.87")  
Weight: 2.55 kg (5.62 lb)  
Mounting: mast or wall with the aid of antenna wall support  
Max. power consumption: 6 W  
Power: 24V, 0.5A PoE, Passive PoE (Pairs 4, 5+; 7, 8 Return)  
Operating temperatures: -40°C + 70°C  
Operating humidity: 5% + 95%, Non-condensing



#08875

Net Price:  
86.80 USD  
Unit: pcs**Wireless access point Ubiquiti PowerBeam M5 MIMO 5GHz (Ubiquiti PBE-M5-400)**

Standards: IEEE 802.11a/n  
Ports: 1x 10/100/1000 Mbps RJ-45  
Chipset: Atheros MIPS 74KC, 560 MHz  
Operating memory: 64 MB DDR2  
Flash memory: 8 MB  
Antenna: build-in, 25 dBi  
Range: 25+ km  
VSWR: 1.5  
Diameter: 400mm  
Weight: 1.753 kg  
Mounting: mast or wall with the aid of antenna wall support  
Max. power consumption: 8 W  
Power: PoE 24V  
Operating temperatures: -40°C + 70°C  
Operating humidity: 5% + 95%, Non-condensing



#06286

Net Price:  
104.00 USD  
Unit: pcs**Wireless access point Ubiquiti PowerBeam M5 MIMO 5GHz (Ubiquiti PBE-M5-400-ISO-EU)**

Standards: IEEE 802.11a/n  
Ports: 1x 10/100/1000 Mbps RJ-45  
Chipset: Atheros MIPS 74KC, 560 MHz  
Operating memory: 64 MB DDR2  
Flash memory: 8 MB  
Antenna: build-in, 25 dBi  
Range: 25+ km  
VSWR: 1.5  
Dimensions: 459 x 459 x 261 mm (18.07 x 18.07 x 10.28")  
Weight: 3.22 kg (7.10 lb)  
Mounting: mast or wall with the aid of antenna wall support  
Max. power consumption: 8 W  
Power: PoE 24V  
Operating temperatures: -40°C + 70°C  
Operating humidity: 5% + 95%, Non-condensing  
Salt Fog Test: IEC 68-2-11 (ASTM B117), Equivalent  
MIL-STD-810 G Method 509.5



#08876

Net Price:  
185.00 USD  
Unit: pcs**Wireless access point Ubiquiti PowerBeam M5 MIMO 5GHz (Ubiquiti PBE-M5-620)**

Standards: IEEE 802.11a/n  
Ports: 1x 10/100/1000 Mbps RJ-45  
Chipset: Atheros MIPS 74KC, 560 MHz  
Operating memory: 64 MB DDR2  
Flash memory: 8 MB  
Antenna: build-in, 29 dBi  
Range: 30+ km  
VSWR: 1.5  
Diameter: 600mm  
Weight: 6.4 kg  
Mounting: mast or wall with the aid of antenna wall support  
Max. power consumption: 8.5 W  
Power: PoE 24V  
Operating temperatures: -40°C + 70°C  
Operating humidity: 5% + 95%, Non-condensing



#07007

Net Price:  
82.80 USD  
Unit: pcs**Wireless Base Station Airmax TDMA (Ubiquiti Rocket M5)**

Standards: IEEE 802.11a, IEEE 802.11n, IEEE 802.3u  
Ports: 1x 10/100 Mbps RJ-45  
Operating modes: Access Point, Bridge, Client, WDS  
Chipset: Atheros MIPS 24KC 400MHz  
Operating memory: 64 MB SDRAM  
Flash memory: 8 MB  
Frequency range: 5470 MHz + 5825 MHz  
Max. output power: 27 dBm @ 6-24 Mbps, 25 dBm @ 36 Mbps, 23 dBm @ 48 Mbps, 22 dBm @ 54 Mbps, 27 dBm @ MSC0, 27 dBm @ MSC1, 27 dBm @ MSC2, 27 dBm @ MSC3, 26 dBm @ MSC4, 24 dBm @ MSC5, 22 dBm @ MSC6, 21 dBm @ MSC7, 27 dBm @ MSC8, 27 dBm @ MSC9, 27 dBm @ MSC10, 27 dBm @ MSC11, 26 dBm @ MSC12, 24 dBm @ MSC13, 22 dBm @ MSC14, 21 dBm @ MSC15

**Antennas 2.4 GHz**

#08203

Net Price:  
229.00 USD  
Unit: pcs**Omni-directional antenna AIRMAX MIMO 10dBi (Ubiquiti AMO-2G13)**

Directional gain: 13 dBi  
Frequency range: 2.35 - 2.55 GHz  
Vertical beam width: 7 degree  
Horizontal beam width: 360 degree  
VSWR: 1,7  
Connector: 2xRSMA  
Weight: 2.4 kg



#08961

Net Price:  
126.00 USD  
Unit: pcs**Omni-directional sector antenna AIRMAX 120 15dBi (Ubiquiti AM-2G15-120)**

Gain: 15.0 - 16.0 dBi  
Frequency: 2.3 - 2.7 GHz  
Vertical beam width: 118° (6 dB)  
Horizontal beam width: 123° (6 dB)  
Polarization: Dual Linear  
VSWR: 1.5  
Wind Survivability: 200 km/h (125 mph)  
Wind Loading: 169 N @ 200 km/h (38 lbf @ 125 mph)  
Height: 700 mm  
Width: 145 mm  
Thickness: 93 mm  
Weight: 4.0 kg  
Cross-Pol Isolation: 28 dB Min.  
ETSI Specification: EN 302 326 DN2












#08960










Net Price:  
126.00 USD  
Unit: pcs**Omni-directional sector antenna AIRMAX 90 16dBi (Ubiquiti AM-2G16-90)**

Gain: 16.0 - 17.0 dBi  
Frequency: 2.3 - 2.7 GHz  
Vertical beam width: 90° (6 dB)  
Horizontal beam width: 91° (6 dB)  
Polarization: Dual Linear  
VSWR: 1.5  
Wind Survivability: 200 km/h (125 mph)  
Wind Loading: 169 N @ 200 km/h (38 lbf @ 125 mph)  
Height: 700 mm  
Width: 145 mm  
Thickness: 79 mm  
Weight: 3.9 kg  
Cross-Pol Isolation: 28 dB Min.  
ETSI Specification: EN 302 326 DN2





<p>Antennas 5 GHz</p>  <p><b>#07016</b> Net Price: 126.00 USD Unit: pcs</p> <p><b>Airmax dish antenna 5 GHz, 30 dBi (Ubiquiti RocketDish 5G-30)</b> Directional gain: 30 dBi Frequency range: 5.1 - 5.9 GHz Vertical beam width: 5 degree Horizontal beam width: 5 degree Polarization: dual linear Cross-pol isolation: 35 db min. F/B Ratio: -34 dB VSWR: 1.4 Windloading: 120 mph Connector: SMA-RP(F) Diameter: Ø 648 mm Weight: 9.8 kg</p>	 <p><b>#07071</b> Net Price: 280.00 USD Unit: pcs</p> <p><b>Airmax dish antenna 5 GHz, 34 dBi (Ubiquiti RocketDish 5G-34)</b> Directional gain: 34 dBi Frequency range: 5.1 - 5.9 GHz Vertical beam width: 3 degree Horizontal beam width: 3 degree Polarization: dual linear Cross-pol isolation: 35 db min. F/B Ratio: -42 dB VSWR: 1.4 Wind Survivability: 125 mph Connector: SMA-RP(F) Diameter: Ø 1050 mm Weight: 13.5 kg</p>	 <p><b>#07013</b> Net Price: 73.80 USD Unit: pcs</p> <p><b>Airmax sector antenna 5 GHz, 16 dBi - 120 deg. (Ubiquiti 5G-120-16)</b> Patent-pending next-generation technology achieves gain, cross-pol isolation, and beamshaping characteristics rivaling the highest quality cellular carrier basestation antennas in the world. Instantly pair with Rocket M5 to create a powerful AirMax 2x2 MIMO PtMP BaseStation. Rocket mount and weatherproof RF jumpers included. Directional gain: 16 dBi Frequency range: 5.1 - 5.9 GHz Vertical beam width: 8 degree Horizontal beam width: 118 degree Polarization: dual linear Cross-pol isolation: 22 db min. Electrical downtilt: 4 degree VSWR: 1,5 Windloading: 120 mph Connector: SMA-RP(F) Height: 367 mm Width: 63 mm Thickness: 41 mm Weight: 1.1 kg</p>
 <p><b>#07012</b> Net Price: 37.50 USD Unit: pcs</p> <p><b>Airmax sector antenna 5 GHz, 17 dBi - 90 deg. (Ubiquiti 5G-90-17)</b> Patent-pending next-generation technology achieves gain, cross-pol isolation, and beamshaping characteristics rivaling the highest quality cellular carrier basestation antennas in the world. Instantly pair with Rocket M5 to create a powerful AirMax 2x2 MIMO PtMP BaseStation. Rocket mount and weatherproof RF jumpers included. Directional gain: 17 dBi Frequency range: 4.9 - 5.9 GHz Vertical beam width: 8 degree Horizontal beam width: 93 degree Polarization: dual linear Cross-pol isolation: 22 db min. Electrical downtilt: 4 degree VSWR: 1,5 Windloading: 120 mph Connector: SMA-RP(F) Height: 367 mm Width: 63 mm Thickness: 41 mm Weight: 1.1 kg</p>	 <p><b>#07011</b> Net Price: 126.00 USD Unit: pcs</p> <p><b>Airmax sector antenna 5 GHz, 19 dBi - 120 deg. (Ubiquiti 5G-120-19)</b> Patent-pending next-generation technology achieves gain, cross-pol isolation, and beamshaping characteristics rivaling the highest quality cellular carrier basestation antennas in the world. Instantly pair with Rocket M5 to create a powerful AirMax 2x2 MIMO PtMP BaseStation. Rocket mount and weatherproof RF jumpers included. Directional gain: 19 dBi Frequency range: 5.15 - 5.85 GHz Vertical beam width: 4 degree Horizontal beam width: 123 degree Polarization: dual linear Cross-pol isolation: 28 db min. Electrical downtilt: 2 degree VSWR: 1,5 Windloading: 160 mph Connector: SMA-RP(F) Height: 700 mm Width: 145 mm Thickness: 93 mm Weight: 5.9 kg</p>	 <p><b>#07010</b> Net Price: 126.00 USD Unit: pcs</p> <p><b>Airmax sector antenna 5 GHz, 20 dBi - 90 deg. (Ubiquiti 5G-90-20)</b> Patent-pending next-generation technology achieves gain, cross-pol isolation, and beamshaping characteristics rivaling the highest quality cellular carrier basestation antennas in the world. Instantly pair with Rocket M5 to create a powerful AirMax 2x2 MIMO PtMP BaseStation. Rocket mount and weatherproof RF jumpers included. Directional gain: 20 dBi Frequency range: 5.15 - 5.85 GHz Vertical beam width: 4 degree Horizontal beam width: 91 degree Polarization: dual linear Cross-pol isolation: 28 db min. Electrical downtilt: 2 degree VSWR: 1,5 Windloading: 160 mph Connector: SMA-RP(F) Height: 700 mm Width: 145 mm Thickness: 93 mm Weight: 5.9 kg</p>
 <p><b>#08200</b> Net Price: 214.00 USD Unit: pcs</p> <p><b>Omni-directional antenna AIRMAX MIMO 10dBi (Ubiquiti AMO-5G10)</b> Directional gain: 10 dBi Frequency range: 5.15 - 5.875 GHz Vertical beam width: 12 degree Horizontal beam width: 360 degree VSWR: 1,6 Connector: 2xRSMA Weight: 0,68 kg</p>	 <p><b>#06921</b> Net Price: 21.50 USD Unit: pcs</p> <p><b>Panel antenna RooTenna 19 dBi 5GHz</b> Antenna type: panel Frequency range: 4940-5850 MHz Gain: 19 dBi Beam width: 15° Polarization: H or V VSWR: 1.5 Impedance: 50 Ω Connector: SMA Diam of holder: 38 - 51 mm Dimensions: 267 x 267 x 89 mm Weight: 0.8 kg</p>	
<p>Antennas LTE, 3G, GSM</p>  <p><b>#08957</b> Net Price: 18.00 USD Unit: pcs</p> <p><b>Mini omni-directional antenna AS1-LTE</b> Frequency range: 790-960 MHz, 1710-2700MHz Gain: up to 5 dBi Impedance: 50 Ohm Connector: interchangeable TS9 / CRC9 Standard: LTE To use with: Huawei B593s; B593u; E5373; E398</p>		

Wireless accessories		
 <p><b>#09530</b> Net Price: 5.01 USD Unit: pcs</p> <p><b>Nano adapter Bluetooth 5.3 (TP-Link Mercusys MA530)</b></p> <ul style="list-style-type: none"> <li>- Bluetooth 5.3 - Speed, coverage, security and reliability improvement than last-gen Bluetooth</li> <li>- Wireless Connectivity - Provides stable and convenient communication between Bluetooth devices and your PC or laptop</li> <li>- Nano-Size - Ultra-small for convenient portability with reliable high performance</li> <li>- Backward Compatibility - Work with devices supported the earlier Bluetooth version</li> <li>- Supported Operating System - Windows 11/10/8.1/7</li> </ul> <p><b>HARDWARE FEATURES</b> Standards and Protocols: Bluetooth 5.3 Interface: USB 2.0 Dimensions ( W x D x H ): 19,15 * 14,94 * 7,19 mm <b>OTHERS</b> Package Contents: Bluetooth 5.3 Nano USB Adapter (MA530), Quick Installation Guide System Requirements: Windows 11/10/8.1/7 Environment Operating Temperature: 0°C~40°C (32°F ~104°F) Storage Temperature: -40°C~70°C (-40°F ~158°F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing</p>	 <p><b>#05381</b> Net Price: 9.49 USD Unit: pcs</p> <p><b>(E8533) Wall bracket, 0 MM-50L13</b></p> <p>Distance from a wall: 130 mm Mount holes diameter: 12 mm</p>	 <p><b>#05382</b> Net Price: 3.82 USD Unit: pcs</p> <p><b>(E8681) Antenna wall support, UML-38L10</b></p> <p>Diameter: 38 mm Distance from a wall: 130 mm Height: 100 mm Mount holes diameter: 9 mm</p>
 <p><b>#05383</b> Net Price: 5.72 USD Unit: pcs</p> <p><b>(E8682) Wall bracket, UML-38L30</b></p> <p>Diameter: 38 mm Distance from a wall: 300 mm Height: 300 mm Mount holes diameter: 9 mm Weight: 0.97 kg</p>	 <p><b>#06729</b> Net Price: 9.25 USD Unit: pcs</p> <p><b>(E8686) Wall bracket, UML-38L30x60</b></p> <p>Diameter: 38 mm Distance from a wall: 340 mm Height: 580 mm Mount holes diameter: 10 mm Weight: 1.44 kg colour: white or silver</p>	 <p><b>#05385</b> Net Price: 4.62 USD Unit: pcs</p> <p><b>(E8728) Antenna mount, TV-SAT, US-32*200, painted</b></p> <p>Diameter: 32 mm Distance from a wall: 200 mm</p>
 <p><b>#05394</b> Net Price: 6.42 USD Unit: pcs</p> <p><b>(E9228) Antenna support, WG-25/800</b></p> <p>Diameter: 25 mm Width: 800 mm</p>	 <p><b>#09040</b> Net Price: 4.61 USD Unit: pcs</p> <p><b>Nano adapter Bluetooth 4.0 (TP-Link UB400)</b></p> <ul style="list-style-type: none"> <li>- Bluetooth 4.0 - Applies the latest Bluetooth 4.0 with low energy (BLE) technology and it is backward compatible with Bluetooth V3.0/2.1/2.0/1.1</li> <li>- Driver Free - Plug and Play for Win 8, Win 8.1, and Win 10</li> <li>- Nano-Sized - Ultra-small for convenient portability with reliable high performance</li> <li>- Supported Operating System - Supports Windows 10/8.1/8/7/XP</li> </ul> <p><b>HARDWARE FEATURES</b> Standards and Protocols: Bluetooth 4.0 Interface: USB 2.0 Dimensions ( W x D x H ): 0.58 x 0.27 x 0.74 in (14.8 x 6.8 x 18.9 mm) <b>OTHERS</b> Certification: FCC, CE, RoHS Package Contents: Bluetooth 4.0 Nano USB Adapter UB400, Quick Installation Guide System Requirements: Windows 10/8.1/8/7/XP Environment Operating Temperature: 0°C~40°C (32°F ~104°F) Storage Temperature: -40°C~70°C (-40°F ~158°F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing</p>	 <p><b>#09196</b> Net Price: 6.77 USD Unit: pcs</p> <p><b>Nano adapter Bluetooth 5.0 (TP-Link UB500)</b></p> <ul style="list-style-type: none"> <li>- Bluetooth 5.0 - Applies the latest Bluetooth 5.0 technology, backward compatible with Bluetooth V4.0/3.0/2.1/2.0/1.1</li> <li>- Wireless Connectivity - Provides stable and convenient communication between Bluetooth devices and your PC or laptop</li> <li>- Nano-Sized - Ultra-small for convenient portability with reliable high performance</li> <li>- Supported Operating System - Windows 10/8.1/8/7/XP</li> </ul> <p><b>HARDWARE FEATURES</b> Standards and Protocols: Bluetooth 5.0 Interface: USB 2.0 Dimensions ( W x D x H ): 0.58 x 0.27 x 0.74 in (14.8 x 6.8 x 18.9 mm) <b>OTHERS</b> Package Contents: Bluetooth 5.0 Nano USB Adapter UB500, Quick Installation Guide System Requirements: Windows 10/8.1/8/7/XP Environment Operating Temperature: 0°C~40°C (32°F ~104°F) Storage Temperature: -40°C~70°C (-40°F ~158°F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing</p>



NEW



#09417

Net Price:  
9.22 USD  
Unit: pcs

**Nano adapter Bluetooth 5.3 (TP-Link UB500 Plus)**

- Bluetooth 5.3 - Security and reliability improvement than last-gen Bluetooth
- Wireless Connectivity - Provides stable and convenient communication between Bluetooth devices and your PC or laptop
- Adjustable, Multi-Directional Antenna - Rotate and adjust the multi-directional antenna to improve user experience and performance in different environments.
- Supported Operating System - Windows 11/10/8.1/7

**HARDWARE FEATURES**

Standards and Protocols: Bluetooth 5.3  
Dimensions ( W x D x H ): 3.19 × 1.65 × 0.66 in (81 × 42 × 16.8 mm)

**OTHERS**

Package Contents: Bluetooth 5.3 USB Adapter UB500 Plus, Quick Installation Guide  
System Requirements: Windows 11/10/8.1/7  
Environment  
Operating Temperature: 0°C~40°C (32°F ~104°F)  
Operating Humidity: 10%~90% non-condensing  
Storage Humidity: 5%~90% non-condensing  
Manufacturer: TP-Link



#06380

Net Price:  
4.00 USD  
Unit: pcs

**Pigtail U.FL-SMA RP(F), 20cm, RG316**

# Index

802.11bx (WiFi 7) .....	1
Mikrotik Routerboard .....	5
802.11ax (WiFi 6) .....	6
Standard AC .....	22
Standard N .....	38
Wireless active devices 2.4GHz .....	46
Wireless active devices 5GHz .....	47
Antennas 2.4 GHz .....	48
Antennas 5 GHz .....	49
Antennas LTE, 3G, GSM .....	49
Wireless accessories .....	50